



HCT CO., LTD.

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8525

CERTIFICATE OF COMPLIANCE
FCC Certification

Applicant Name:

Nokia, Inc.

Address:

12278 Scripps Summit Drive, San Diego,
CA 92131

Date of Issue:

April 30, 2009

Location:

HCT CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,
Kyungki-do, Korea

Test Report No.: HCT-RF09-0413-3

HCT FRN: 0005866421

IC Recognition No.: IC 5944A

FCC ID : QMNRN-526
IC ID : 661X-RM526
APPLICANT : Nokia, Inc.

Model(s): RM-526

EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth

Tx Frequency: 824.70 — 848.31 MHz (CDMA)

1 851.25 — 1 908.75 MHz (PCS CDMA)

Rx Frequency: 869.70 — 893.31 MHz (CDMA)

1 931.25 — 1 988.75 MHz (PCS CDMA)

Max. RF Output Power: 0.540 W ERP CDMA (27.32 dBm) / 0.592 W EIRP PCS CDMA (27.72 dBm)
0.668 W ERP CDMA EVDO (28.25 dBm) / 0.807 W EIRP PCS EVDO (29.07 dBm)

Emission Designator(s): 1M28F9W (CDMA), 1M28F9W (PCS CDMA)
1M27F9W (CDMA EVDO), 1M27F9W (PCS EVDO)

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §22, §24, §2

IC Rule: RSS-129 Issue 2_September 25, 1999, RSS-133 Issue 5_February 2009,
RSS-GEN Issue 2_June 2007

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Jong Seok Lee

Report prepared by

: Jong Seok Lee

Test engineer of RF Part

Sang Jun Lee

Approved by

: Sang Jun Lee

Manager of RF Part

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526	



Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF09-0413-1	April 21, 2009	<ul style="list-style-type: none">■ IC information update
HCT-RF09-0413-2	April 23, 2009	<ul style="list-style-type: none">■ Version control update■ Update the IC Rule■ Update the information for Minimum Controlled Output Power
HCT-RF09-0413-3	April 30, 2009	<ul style="list-style-type: none">■ Change from "IC ID" to "IC"■ The uncertainty update■ Revised the name and pate of test plot■ Add the version for IC rule

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION.....	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power.....	6
3.2 Peak- to- Average Ratio	7
3.3 Occupied bandwidth.....	8
3.4 Spurious and Harmonic Emissions at Antenna Terminal.	9
3.5 Radiated Spurious and Harmonic Emissions	10
3.6 Frequency stability / variation of ambient temperature.....	11
4. LIST OF TEST EQUIPMENT	14
5. SUMMARY OF TEST RESULTS	15
6. SAMPLE CALCULATION	16
7. TEST DATA	17
7.1 Conducted Output Power.....	17
7.1.1 Minimum Controlled Output Power	17
7.1.2 Standby Output Power	18
7.2 Peak-to-Average Ratio	18
7.3 Occupied Bandwidth.....	19
7.4 Conducted Spurious Emissions.....	19
7.4.1 Band Edge	20
7.5 Effective Radiated Power Output(CDMA)	21
7.6 Equivalent Isotropic Radiated Power (E.I.R.P.) (PCS CDMA).....	22
7.7 Radiated Spurious Emissions	23
7.7.1 Radiated Spurious Emissions (CDMA Mode).....	23
7.7.2 Radiated Spurious Emissions (Extended Battery - CDMA Mode).....	24
7.7.3 Radiated Spurious Emissions (PCS CDMA Mode)	25
7.7.4 Radiated Spurious Emissions (Extended Battery - PCS CDMA Mode).....	26
7.8 Frequency stability / variation of ambient temperature.....	27
7.8.1 FREQUENCY STABILITY (CDMA).....	27
7.8.2 FREQUENCY STABILITY (PCS CDMA).....	28
8. TEST PLOTS	29

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	Nokia, Inc.				
Address:	12278 Scripps Summit Drive, San Diego, CA 92131				
Contact:	TEL : + 858-831-5000 / FAX : + 858-831-6500				
FCC ID:	QMNRN-526				
IC ID:	661X-RM526				
Application Type:	Certification				
FCC Classification:	Licensed Portable Transmitter Held to Ear (PCE)				
FCC Rule Part(s):	§22, §24, §2				
EUT Type:	Dual-Band CDMA/ EV-DO Phone with Bluetooth				
Model(s):	RM-526				
S/N :	A00000016703A5				
HW Version :	3000				
SW Version :	VN_2040T13_VZW_108				
Battery	Model Name:	BL-4C(Standard)			
	Power Rating:	3.7 V, 860mAh			
	Type:	Li-ion			
	Model Name:	BL-10C(Extended)			
	Power Rating:	3.7 V, 1760mAh			
	Type:	Li-ion			
Tx Frequency:	824.70 — 848.31 MHz (CDMA) 1 851.25 — 1 908.75 MHz (PCS CDMA)				
Rx Frequency:	869.70 — 893.31 MHz (CDMA) 1 931.25 — 1 988.75 MHz (PCS CDMA)				
Max. RF Output Power:	0.540 W ERP CDMA (27.32 dBm) / 0.592 W EIRP PCS CDMA (27.72 dBm) 0.668 W ERP CDMA EVDO (28.25 dBm) / 0.807 W EIRP PCS EVDO (29.07 dBm)				
Max. RF Output Power (Extended Battery):	0.361 W ERP CDMA (25.58 dBm) / 0.518 W EIRP PCS CDMA (27.14 dBm) 0.466 W ERP CDMA EVDO (26.68 dBm) / 0.635 W EIRP PCS EVDO (28.03 dBm)				
Emission Designator(s):	1M28F9W (CDMA), 1M28F9W (PCS CDMA) 1M27F9W (CDMA EVDO), 1M27F9W (PCS EVDO)				
Antenna Specification	Manufacturer: ACE ANTENNA CORP. Antenna type: Built in Antenna Peak Gain: -1.6 dBi				
Date(s) of Tests:	March 23, 2009 ~ April 20, 2009				

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



2. INTRODUCTION

2.1. EUT DESCRIPTION

The RM-526 Dual-Band CDMA/ EV-DO Phone with Bluetooth consists of Cellular CDMA, PCS CDMA and 1xEvDO Rev.0

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY


The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated July 6, 2006(Registration Number: 90661)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526	

3. DESCRIPTION OF TESTS

3.1 Effective Radiated Power/Equivalent Isotropic Radiated Power

Test Set-up



Test Procedure

Radiated emission measurements were performed at an open Site.

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty

For a 95 % confidence level, the measurement uncertainties for defined system.

30 MHz ~ 1 GHz ± 5.6 dB (k = 2)

Above 1 GHz ± 5.8 dB (k = 2)

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



3.2 Peak- to- Average Ratio

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. Plots of the EUT's Peak- to- Average Ratio are shown herein.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.


Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute error	Rectangular	0.61
Frequency response	Rectangular	0.58
Error of the input attenuator	Rectangular	0.40
Error of bandwidth switching	Rectangular	0.03
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependancy for DUT	Rectangular	0.08
Mismatch: Spectrum : Divider	U-Shaped	0.25
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty		0.99
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)		1.99

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

3.3 Occupied bandwidth.

Test set-up



(Configuration of conducted Emission measurement)

Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (Hz)
Year aging of oscillator	Rectangular	577.35
Drift of temperature	Rectangular	11.55
Readout uncertainty	normal	290.00
Marker count accuracy	Rectangular	1039.81
DUT drift of temperature	Rectangular	115.47
Combined standard uncertainty		1229.67
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of k = 2)		2459.35

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



3.4 Spurious and Harmonic Emissions at Antenna Terminal.

Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the – 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 30 MHz to 10 GHz. (PCS CDMA Mode: 30 MHz to 20 GHz). A display line was placed at – 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.


Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute error	Rectangular	0.61
Frequency response	Rectangular	0.58
Error of the input attenuator	Rectangular	0.40
Error of bandwidth switching	Rectangular	0.03
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependency for DUT	Rectangular	0.08
Mismatch: Spectrum : Divider	U-Shaped	0.25
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty	0.99	
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)	1.99	

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

3.5 Radiated Spurious and Harmonic Emissions

Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable wooden platform mounted at three from the antenna mast.

- 1) The unit mounted on a wooden table 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10th harmonic of the fundamental frequency.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



Test Procedure

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.

The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty


For a 95 % confidence level, the measurement uncertainties for defined system.

30 MHz ~ 1 GHz	±5.6 dB (k = 2)
Above 1 GHz	±5.8 dB (k = 2)

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

3.6 Frequency stability / variation of ambient temperature

Test Set-up



Test Procedure

The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.000\ 25\% (\pm 2.5\ ppm)$ of the center frequency.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526	



2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with 'All Up' power control bits.

Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (Hz)
Year aging of oscillator	Rectangular	415.69
Drift of temperature	Rectangular	51.96
Frequency Error	Rectangular	8.66
DUT drift of temperature	Rectangular	115.47
Combined standard uncertainty		434.64
Expanded uncertainty (Confidence interval of 95.45 %, Coverage Factor of $k = 2$)		869.27

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	ESI40/ Spectrum Analyzer	831564/003	Annual	10/31/2009
Agilent	E4416A/ Power Meter	GB41291412	Annual	01/21/2010
Agilent	E9327A/ Power Sensor	MY4442009	Annual	07/28/2009
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2010
MITEQ	AMF-60-0010 1800-35-20P / AMP	1200937	Annual	05/20/2009
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	06/28/2009
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	06/28/2009
Agilent	775D/ Dual Directional Coupler	12922	Annual	12/24/2009
Agilent	11636B/ Power Divider	11377	Annual	12/24/2009
Digital	EP-3010/ Power Supply	3110117	Annual	01/07/2010
Schwarzbeck	UHAP/ Dipole Antenna	585	Annual	02/13/2011
Schwarzbeck	UHAP/ Dipole Antenna	558	Annual	02/13/2011
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	Annual	12/31/2009
Schwarzbeck	VULB9160/ TRILOG Antenna	3150	Biennial	12/18/2010
Schwarzbeck	VULB9160/ TRILOG Antenna	3125	Biennial	05/16/2009
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	Biennial	03/26/2010
Schwarzbeck	BBHA 9120D/ Horn Antenna	1201	Biennial	05/02/2009
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	12/23/2009

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	IC Rule	Test Description	Test Limit	Test Condition	Test Result
2.1049, 22.917(a), 24.238(a)	RSS-129, Section 6.3 RSS-GEN, Section 4.6.1	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 22.917(a), 24.238(a)	RSS-129, Section 8.1.1 (Cell) RSS-133, Section 6.5 (PCS) RSS-GEN, Section 4.9	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	< 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS
2.1046	-	Conducted Output Power	-		PASS
24.232(d)	-	Peak- to- Average Ratio	< 13 dB		PASS
2.1055, 22.355, 24.235	RSS-129, Section 9.2.1 RSS-133, Section 6.3 RSS-GEN, Section 4.7	Frequency stability / variation of ambient temperature	< 2.5 ppm		PASS
-	RSS-129, Section 9.3	Standby Output Power	< -61 dBm/MHz		PASS
-	RSS-129, Section 9.4	Minimum Controlled Output Power	< -51 dBm/MHz		PASS
22.913(a)(2) 24.232(c)	RSS-GEN, Section 4.8 RSS-129, Section 9.1 (ERP, Cell) RSS-133, Section 6.4 (EIRP, PCS) RSS-139, Section	Effective Radiated Power Equivalent Isotropic Radiated Power	< 7 Watts max. ERP < 6.3 Watts max. ERP (IC) < 2 Watts max. EIRP		PASS PASS
2.1053, 22.917(a), 24.238(a)	RSS-129, Section 8.1.1 (Cell) RSS-133, Section 6.5 (PCS) RSS-GEN, Section 4.9	Radiated Spurious and Harmonic Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of band emissions		PASS

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



6. SAMPLE CALCULATION

A. ERP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	384	836.52	-10.96	24.81	2.50	1.19	H	0.41	26.12

ERP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (**ERP**).

B. Emission Designator

CDMA Emission Designator

Emission Designator = 1M27F9W

CDMA BW = 1.27 MHz (Measured at the 99% power bandwidth)

F = Frequency Modulation

9 = Composite Digital Info


W = Combination (Audio/Data)

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	

7. TEST DATA

7.1 Conducted Output Power

A base station simulator was used to establish communication with The EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Band	Channel	SO2	SO2	SO55	SO55	TDSO SO32	1xEvDO Rev.0	1xEvDO Rev.0
		RC1/1 (dBm)	RC3/3 (dBm)	RC1/1 (dBm)	RC3/3 (dBm)	RC3/3 (dBm)	(FTAP) (dBm)	(RTAP) (dBm)
CDMA	1013	24.29	24.36	24.33	24.30	24.30	24.36	24.39
	384	24.37	24.31	24.32	24.34	24.28	24.40	24.42
	777	24.20	24.23	24.22	24.28	24.21	24.13	24.17
PCS	25	24.26	24.19	24.25	24.20	24.35	24.41	24.36
	600	24.21	24.27	24.20	24.18	24.29	24.20	24.21
	1175	24.19	24.24	24.21	24.24	24.20	24.28	24.21

(Maximum Conducted Output Powers)

7.1.1 Minimum Controlled Output Power

Open Loop mode

Band	Channel	Data(dBm)
CDMA	1013	-58.34
	384	-57.96
	777	-57.55

The output power of a mobile transmitter was tested with both closed loop and open loop power control functions set to minimum. Open loop is worst case.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

Measurement Uncertainty

Contributions	Probability Distribution	Standard Uncertainty (dB)
Absolute Accuracy	Rectangular	0.02
Power sensor linearity	Rectangular	0.11
Power range	Rectangular	0.02
Drift of temperature for DUT	Rectangular	0.15
Time-duty cycle error for DUT	Rectangular	0.05
Supply voltage dependancy for DUT	Rectangular	0.08
Mismatch: Sensor : Divider	U-Shaped	0.05
Mismatch: Power meter : sensor	U-Shaped	0.01
Mismatch: Divider : DUT	U-Shaped	0.16
Combined standard uncertainty	0.26	
Expanded uncertainty (confidence interval of 95.45 %, Coverage Factor of $k = 2$)	0.53	

7.1.2 Standby Output Power

- Plots of the EUT's Peak- to- Average Ratio are shown Page 48 ~ 49.

7.2 Peak-to-Average Ratio

- Plots of the EUT's Peak- to- Average Ratio are shown Page 34.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



7.3 Occupied Bandwidth

Band	Channel	Frequency(MHz)	Data (MHz)
CDMA	1013	824.7	1.2753
	384	836.5	1.2732
	777	848.3	1.2761
PCS	25	1.851	1.2766
	600	1.880	1.2731
	1175	1.908	1.2818

- Plots of the EUT's Occupied Bandwidth are shown Page 30 ~ 33.

7.4 Conducted Spurious Emissions

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
CDMA	1013	1.648	-34.20
	384	2.512	-42.23
	777	1.697	-34.60
PCS	25	3.920	-37.86
	600	3.762	-33.17
	1175	3.815	-31.63

- Plots of the EUT's Conducted Spurious Emissions are shown Page 42 ~ 48.

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526



7.4.1 Band Edge

- Plots of the EUT's Band Edge are shown Page 34 ~ 42.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526	



7.5 Effective Radiated Power Output(CDMA)

(CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	1013	824.70	-11.94	33.89	-8.31	1.17	V	0.28	24.41
	384	836.52	-11.56	34.93	-8.22	1.19	V	0.36	25.52
	777	848.31	-10.48	36.65	-8.13	1.20	V	0.54	27.32
EVDO	777	848.31	-9.55	37.58	-8.13	1.20	V	0.67	28.25

(Extended Battery - CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	1013	824.70	-13.17	32.66	-8.31	1.17	V	0.21	23.18
	384	836.52	-13.18	33.31	-8.22	1.19	V	0.25	23.90
	777	848.31	-12.22	34.91	-8.13	1.20	V	0.36	25.58
EVDO	777	848.31	-11.12	36.01	-8.13	1.20	V	0.47	26.68

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRM-526	661X-RM526	



7.6 Equivalent Isotropic Radiated Power (E.I.R.P.) (PCS CDMA)

(PCS CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
PCS	25	1,851.25	-12.71	18.90	10.05	1.91	H	0.50	27.03
	600	1,880.00	-12.40	19.42	10.05	1.95	H	0.56	27.52
	1175	1,908.75	-12.27	19.63	10.06	1.97	H	0.59	27.72
EVDO	1175	1,908.75	-10.92	20.98	10.06	1.97	H	0.81	29.07

(Extended Battery - PCS CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol.	EIRP	
	channel	Freq.(MHz)						W	dBm
PCS	25	1,851.25	-13.30	18.31	10.05	1.91	H	0.44	26.44
	600	1,880.00	-12.78	19.04	10.05	1.95	H	0.52	27.14
	1175	1,908.75	-13.09	18.81	10.06	1.97	H	0.49	26.90
EVDO	600	1,880.00	-11.89	19.93	10.05	1.95	H	0.64	28.03

Note: Standard batteries are the only options for this phone

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	



7.7 Radiated Spurious Emissions

7.7.1 Radiated Spurious Emissions (CDMA Mode)

MEASURED OUTPUT POWER: 27.32 dBm = 0.540 W

MODULATION SIGNAL: CDMA

DISTANCE: 3 meters

LIMIT: $-(43 + 10 \log_{10}(W))$ = - 40.32 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
1013	1,649.40	-39.23	7.09	-49.76	1.73	H	-44.40	-71.72
	2,474.10	-38.16	8.12	-45.27	2.28	H	-39.43	-66.75
	3,298.80	-55.12	9.72	-62.70	2.57	V	-55.55	-82.87
384	1,673.04	-51.09	7.23	-61.85	1.79	H	-56.41	-83.73
	2,509.56	-45.46	8.14	-52.59	2.33	H	-46.78	-74.10
	3,346.08	-54.98	9.99	-63.01	2.66	V	-55.68	-83.00
777	1,696.62	-47.35	7.41	-57.96	1.83	H	-52.38	-79.70
	2,544.93	-44.03	8.21	-51.31	2.34	H	-45.44	-72.76
	3,393.24	-54.88	9.91	-62.51	2.85	V	-55.45	-82.77

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004;

2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	



7.7.2 Radiated Spurious Emissions (Extended Battery - CDMA Mode)

MEASURED OUTPUT POWER: 25.58 dBm = 0.361 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: - (43 + 10 log₁₀(W)) = - 38.58 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
1013	1,649.40	-42.58	7.09	-53.11	1.73	H	-47.75	-73.33
	2,474.10	-36.30	8.12	-43.41	2.28	H	-37.57	-63.15
	3,298.80	-55.81	9.72	-63.39	2.57	V	-56.24	-81.82
384	1,673.04	-53.56	7.23	-64.32	1.79	H	-58.88	-84.46
	2,509.56	-37.09	8.14	-44.22	2.33	H	-38.41	-63.99
	3,346.08	-55.01	9.99	-63.04	2.66	V	-55.71	-81.29
777	1,696.62	-46.69	7.41	-57.30	1.83	H	-51.72	-77.30
	2,544.93	-36.53	8.21	-43.81	2.34	H	-37.94	-63.52
	3,393.24	-54.77	9.91	-62.40	2.85	V	-55.34	-80.92

NOTES: 1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004;
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	



7.7.3 Radiated Spurious Emissions (PCS CDMA Mode)

MEASURED OUTPUT POWER: 27.72 dBm = 0.592 W
 MODULATION SIGNAL: PCS CDMA
 DISTANCE: 3 meters
 LIMIT: - (43 + 10 \log_{10} (W)) = - 40.72 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
25	3,702.50	-37.52	12.46	-43.79	2.73	H	-34.06	-61.78
	5,553.75	-51.51	12.70	-53.09	3.60	H	-43.99	-71.71
	7,405.00	-55.44	11.36	-46.56	3.88	H	-39.08	-66.80
600	3,760.00	-32.96	12.47	-38.93	2.73	H	-29.19	-56.91
	5,640.00	-51.67	12.75	-53.32	3.60	H	-44.17	-71.89
	7,520.00	-55.84	11.33	-46.74	3.88	V	-39.29	-67.01
1175	3,817.50	-35.05	12.49	-40.93	2.73	H	-31.17	-58.89
	5,726.25	-50.96	12.80	-52.27	3.60	H	-43.07	-70.79
	7,635.00	-55.96	11.30	-46.63	3.88	H	-39.21	-66.93

NOTES:

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	



7.7.4 Radiated Spurious Emissions (Extended Battery - PCS CDMA Mode)

MEASURED OUTPUT POWER: 27.14 dBm = 0.518 W

MODULATION SIGNAL: PCS CDMA

DISTANCE: 3 meters

LIMIT: - (43 + 10 log₁₀ (W)) = - 40.14 dBc

Ch.	Freq.(MHz)	Measured Level [dBm]	Ant. Gain	Substitute Level [dBm]	C.L	Pol.	ERP (dBm)	dBc
25	3,702.50	-36.67	12.46	-42.94	2.73	H	-33.21	-60.35
	5,553.75	-55.69	12.70	-57.27	3.60	H	-48.17	-75.31
	7,405.00	-56.11	11.36	-47.23	3.88	V	-39.75	-66.89
600	3,760.00	-34.84	12.47	-40.81	2.73	H	-31.07	-58.21
	5,640.00	-56.02	12.75	-57.67	3.60	H	-48.52	-75.66
	7,520.00	-55.17	11.33	-46.07	3.88	V	-38.62	-65.76
1175	3,817.50	-35.98	12.49	-41.86	2.73	H	-32.10	-59.24
	5,726.25	-55.90	12.80	-57.21	3.60	H	-48.01	-75.15
	7,635.00	-56.66	11.30	-47.33	3.88	H	-39.91	-67.05

NOTES:

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5th Harmonic for all channel.


FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No.	Date of Issue:	EUT Type:	FCC ID:	IC ID:	
HCT-RF09-0413-3	April 30, 2009	Dual-Band CDMA/ EV-DO Phone with Bluetooth	QMNRN-526	661X-RM526	

7.8 Frequency stability / variation of ambient temperature

7.8.1 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	836 520 002	1.79	0.000 000	0.002
100%		-30	836 520 004	3.58	0.000 000	0.004
100%		-20	836 519 998	-2.39	0.000 000	-0.003
100%		-10	836 520 001	1.15	0.000 000	0.001
100%		0	836 519 999	-1.06	0.000 000	-0.001
100%		+10	836 520 002	1.74	0.000 000	0.002
100%		+20	836 519 997	-2.87	0.000 000	-0.003
100%		+30	836 520 004	3.63	0.000 000	0.004
100%		+40	836 520 001	0.81	0.000 000	0.001
100%		+50	836 520 004	4.07	0.000 000	0.005
115%	4.255	+20	836 519 996	-3.69	0.000 000	-0.004
Batt. Endpoint	3.400	+20	836 520 002	1.77	0.000 000	0.002




FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

7.8.2 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1880,000,000 Hz
 CHANNEL: 600
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 997	-3.36	0.000 000	-0.002
100%		-30	1879 999 997	-2.92	0.000 000	-0.002
100%		-20	1880 000 002	1.50	0.000 000	0.001
100%		-10	1879 999 997	-3.28	0.000 000	-0.002
100%		0	1880 000 004	4.16	0.000 000	0.002
100%		+10	1879 999 992	-7.78	0.000 000	-0.004
100%		+20	1879 999 997	-2.81	0.000 000	-0.001
100%		+30	1879 999 995	-5.45	0.000 000	-0.003
100%		+40	1880 000 009	8.86	0.000 000	0.005
100%		+50	1879 999 997	-3.12	0.000 000	-0.002
115%	4.255	+20	1880 000 002	1.91	0.000 000	0.001
Batt. Endpoint	3.400	+20	1879 999 996	-4.17	0.000 000	-0.002




FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526




8. TEST PLOTS

FCC CERTIFICATION REPORT					www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526	

■ CDMA MODE (1013 CH.) Occupied Bandwidth




■ CDMA MODE (384 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA MODE (777 CH.) Occupied Bandwidth




■ CDMA EVDO (777 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (25 CH.) Occupied Bandwidth




■ PCS CDMA MODE (600 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (1175 CH.) Occupied Bandwidth




■ PCS EVDO MODE (1175CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (600 CH.) Peak-to-Average Ratio




■ CDMA MODE (1013 CH.) Band Edge




FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

■ CDMA MODE (777 CH.) Band Edge




■ CDMA EVDO MODE (1013 CH.) Band Edge




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA EVDO MODE (777 CH.) Band Edge




■ PCS CDMA MODE (25 CH.) Band Edge




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (1175 CH.) Band Edge




■ PCS CDMA EVDO MODE (25 CH.) Band Edge




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA EVDO MODE (1175 CH.) Band Edge




■ CDMA MODE (1013 CH.) 4 MHz Span




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA EVDO MODE (1013 CH.) 4 MHz Span




■ CDMA MODE (777 CH.) 4 MHz Span



FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA EVDO MODE (777 CH.) 4 MHz Span




■ PCS CDMA MODE (25 CH.) 4 MHz Span




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA EVDO MODE (25 CH.) 4 MHz Span




■ PCS CDMA MODE (1175 CH.) 4 MHz Span




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA EVDO MODE (1175 CH.) 4 MHz Span




■ CDMA MODE (1013 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA MODE (1013 CH.) Conducted Spurious Emissions - 2




■ CDMA MODE (384 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA MODE (384 CH.) Conducted Spurious Emissions - 2




■ CDMA MODE (777 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ CDMA MODE (777 CH.) Conducted Spurious Emissions - 2




■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions - 2




■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions - 2




■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------

■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions - 2




■ CDMA MODE (1013 CH.) Standby Output Power




FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526

■ CDMA MODE (384 CH.) Standby Output Power



■ CDMA MODE (777 CH.) Standby Output Power



FCC CERTIFICATION REPORT

Test Report No. HCT-RF09-0413-3	Date of Issue: April 30, 2009	EUT Type: Dual-Band CDMA/ EV-DO Phone with Bluetooth	FCC ID: QMNRN-526	IC ID: 661X-RM526
------------------------------------	----------------------------------	---	----------------------	----------------------