



## FCC HAC Test Report

### Test Report Number: WR-599.001

**Terminal device:** Type Nokia RM-66, HW: 3000, SW: HL100\_05wk19.nbr (Detailed information is listed in section 5).

Originator: Anu Balijepalli  
Function: TCC – Dallas  
Version/Status: 1.0 Approved  
Location: TCC Directories  
Date: 12 September 2005

#### Change History:

Version	Date	Status	Handled By	Comments
0.1	12 September 05	Draft	Anu Balijepalli	Initial Draft
0.2	12 September 05	Review	Anu Balijepalli	Submit for Approval
1.0	12 September 05	Approved	Nerina Walton	Approved

**Testing laboratory:**

Test & Certification Center (TCC)  
Dallas  
Nokia Inc  
6021 Connection Drive  
Irving, Texas 75039  
U.S.A.  
Tel. 972-894-5000  
Fax. 972-894-4988

**Client:**

Nokia SanDeigo  
12278 Scripps Summit Drive  
San Deigo, California, 92131  
U.S.A.  
Tel. 858-831-5000  
Fax. 858-831-6500

**Date and signatures:**

12 September 2005

For the Contents:

Anu Balijepalli,  
Technical Review

Nerina Walton,  
Manager Review



## TABLE OF CONTENTS

<b>1. GENERAL .....</b>	<b>3</b>
1.1    OBJECTIVE .....	3
1.2    TEST SUMMARY .....	3
<b>2. LIST OF ABBREVIATIONS, ACRONYMS AND TERMS .....</b>	<b>4</b>
2.1    ABBREVIATIONS .....	4
2.2    ACRONYMS.....	4
2.3    TERMS .....	4
<b>3. STANDARDS BASIS .....</b>	<b>5</b>
<b>4. TEST EQUIPMENT LIST .....</b>	<b>5</b>
<b>5. EQUIPMENT-UNDER-TEST (EUT) .....</b>	<b>6</b>
5.1    DESCRIPTION OF TESTED DEVICE(S):.....	6
5.2    PHOTOGRAPH OF TESTED DEVICE(S):.....	6
<b>6. TEST METHOD(S) AND SETUP(S) .....</b>	<b>7</b>
6.1    PROBE DESCRIPTION .....	7
6.2    SPEAG ROBOTIC SYSTEM.....	12
6.3    TEST SETUP .....	14
<b>7. PASS/FAIL CRITERIA.....</b>	<b>14</b>
<b>8. TEST PROCEDURE.....</b>	<b>15</b>
<b>9. SYSTEM VALIDATION.....</b>	<b>16</b>
<b>10. DETAILED TEST RESULTS.....</b>	<b>25</b>
10.1    NEAR FIELD E AND H RF EMISSIONS MEASUREMENTS .....	25
10.1.1    Test Results .....	25
<b>11. MEASUREMENT UNCERTAINTY.....</b>	<b>29</b>
<b>APPENDIX A: VALIDATIONS SCANS .....</b>	<b>30</b>
<b>APPENDIX B: MEASUREMENT SCANS .....</b>	<b>35</b>
<b>APPENDIX C: PROBE CALIBRATION REPORTS AND DIPOLE CALIBRATION REPORTS .....</b>	<b>60</b>

© No part of this report shall be reproduced out of the context of the report without the written approval of Nokia Mobile Phones, Inc., Dallas Product Creation, TCC – Dallas.



## 1. GENERAL

### 1.1 Objective

This test is performed to ensure that the EUT meets the requirements required by the FCC Method of Measurement for near field E and H emissions. Please note that this report is only for near field emissions, not for the T-coil HAC testing.

### 1.2 Test Summary

**Test Results:** *The test result relates only to those tested devices mentioned in Section 5 of this test report.*

Sample #	Test Performed	Reference	Category
1	Near Field Emissions- E field Near Field Emissions- H field	ANSI C63.19	M3



## 2. LIST OF ABBREVIATIONS, ACRONYMS AND TERMS

### 2.1 Abbreviations

dB - decibel  
dBm - decibels per milliwatt (absolute measurement)  
MHz - megahertz or 1000000 Hertz  
V/m – Volts per meter  
A/m – Amps per meter

### 2.2 Acronyms

AMPS - Advanced Mobile Phone System  
BSS - Base Station Simulator  
CDMA - Code Division Multiple Access  
ESN - Electronic Serial Number  
EUT - Equipment under Test  
GSM - Global System for Mobile communications  
IMEI - International Mobile Equipment Identity  
PCS - Personal Communication System  
RF- Radio Frequency  
TDMA - Time Division Multiple Access

### 2.3 Terms

Base Station Simulator (BSS) - simulates all the necessary signals that a phone would experience while on a live network. There are many types of base station simulators catering for all current protocols, i.e., GSM, AMPS, TDMA, and CDMA.

Cellular - refers to a frequency in the 800MHz band.

PCS - refers to a frequency in the 1900MHz band.

Crest Factor - is the relation between the peak power and the average power in a signal.



### 3. STANDARDS BASIS

*Testing has been carried out in accordance with:*

REF.	Code of the standard	Name of the standard
1	-	ANSI C63.19

Note: Unless otherwise stated, (by reference to a version number and a publication date), the latest version of the above documents applies.

*Deviations:*

Not Applicable.

### 4. TEST EQUIPMENT LIST

The listing below indicates the test equipment utilized for the test (s). Calibration interval on all items listed can be obtained from the Engineering Services Group within NMP, Product Creation - Dallas. Where relevant, measuring equipment is subjected to in-service checks between testing. TCC - Dallas shall notify clients promptly, in writing, of identification of defective measuring equipment that casts doubt on the validity of results given in this report.

Test Equipment	NMP #	Calibration Interval	Calibration Expiry
SPEAG DASY4 Robot System	2056	NA	NA
SPEAG Data Acquisition Electronics (DAE)	2292	12 months	Jan - 2006
SPEAG E-field Probe ER3DV6	4036	12 months	Jan - 2006
SPEAG H-field Probe H3DV6	4037	12 months	Feb-2006
SPEAG 835MHz Dipole CD835V3	4050	12 months	Apr-2006
SPEAG 1880MHz Dipole CD1880V3	4049	12 months	Jun-2006
Signal Generator HP8648C	0409	12 months	Sep-2005
Boonton Powermeter 4232A	0147	12 months	Sep-2005
AR Power Amplifier 5S1G4	0188	NA	NA
R&S CMU 200	2625	12 months	Nov-2005
R&S FSP	3459	12 months	Jan-2006



## 5. EQUIPMENT-UNDER-TEST (EUT)

*The results in this report relate only to the items listed below:*

### 5.1 Description of Tested Device(s):

Sample #	Mode of Operation	Date of Receipt	Condition of Sample	Item	Identifying Information
1	CDMA 800/1900 RC2, SO9	20 July 2005	Good	Phone	Type: RM-66 Model: 6265 ESN: 044/12052363 HW: 3000 SW: HL100_05wk19.nbr Code: 0521741DM21EZ FCC ID: QMNRN-66

### 5.2 Photograph of Tested Device(s):





## 6. TEST METHOD(S) AND SETUP(S)

Testing was performed in accordance with ANSI C63.19.

### 6.1 Probe Description

#### E field Probe Description

##### Construction

One dipole parallel, two dipoles normal to probe axis

Built-in shielding against static charges

##### Calibration

In air from 100 MHz to 3.0 GHz (absolute accuracy  $\pm 6.0\%$ , k=2)

##### Frequency

100 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (100 MHz to 3 GHz)

##### Directivity

$\pm 0.2$  dB in air (rotation around probe axis)

$\pm 0.4$  dB in air (rotation normal to probe axis)

##### Dynamic Range

2 V/m to > 1000 V/m; Linearity:  $\pm 0.2$  dB

##### Dimensions

Overall length: 330 mm (Tip: 16 mm)

Tip diameter: 8 mm (Body: 12 mm)

Distance from probe tip to dipole centers: 2.5 mm

##### Application

General near-field measurements up to 6 GHz

Field component measurements

Fast automatic scanning in phantoms



#### H field Probe Description

##### Construction

Three concentric loop sensors with 3.8 mm loop diameters

Resistively loaded detector diodes for linear response

Built-in shielding against static charges

##### Frequency

200 MHz to 3 GHz (absolute accuracy  $\pm 6.0\%$ , k=2); Output linearized

##### Directivity

$\pm 0.25$  dB (spherical isotropy error)

##### Dynamic Range

10 mA/m to 2 A/m at 1 GHz

##### E-Field Interference

< 10% at 3 GHz (for plane wave)

##### Dimensions

Overall length: 330 mm (Tip: 40 mm)

Tip diameter: 6 mm (Body: 12 mm)

Distance from probe tip to dipole centers: 3 mm

##### Application

General magnetic near-field measurements up to 3 GHz






Field component measurements  
Surface current measurements  
Measurements in air or liquids  
Low interaction with the measured field

### Probe Tip Description

HAC field measurements take place in the close near field with high gradients. Increasing the measuring distance from the source will generally decrease the measured field values. Magnetic field sensors are measuring the integral of the H-field across their sensor area surrounded by the loop. They are calibrated in precise, homogenous field. When measuring a gradient field, the result will be very close to the field in the center of the loop, which is equivalent to the center value. But it will be different from the field at the border of the loop.

Consequently, two sensors with different loop diameters – both calibrated ideally – would give different results when measuring from the edge of the probe sensor elements. The behaviour for electrically small E-field sensors is equivalent. See below for distance plots from a WD, which show the conservative nature of field readings at the probe element center vs. measurements at the sensor end.






The magnetic field loops of the H3D probes are concentric, with the center 3mm from the tip for H3DV6. Their radius is 1.9mm.

The electric field probes have a more irregular internal geometry because it is physically not possible to have the 3 orthogonal sensors situated with the same center. The effect of the different sensor centers is accounted for in the HAC uncertainty budget. Their geometric center is at 2.5mm from the tip, and the element ends are 1.1mm closer to the tip.



## Connector Plan



The antistatic shielding inside the probe is connected to the probe connector case. It is recommended to connect the probes with the amplifier using a short and well-shielded cable and to connect the cable shielding with the connector case.

### Instrumentation Chain:

Conversion of Connector Voltage to E field

$$E_i = \sqrt{\frac{u_i + (u_i^2 \cdot CF)}{(DCP)}} / Norm_i \cdot ConvF$$

whereby

$E_i$  = Electric field in V/m

$u_i$  = Voltage of channel i at the connector in  $\mu$  V

$Norm_i$  = Sensitivity of channel in  $\mu$ V / (V / m)<sup>2</sup>

ConvF = enhancement factor in liquid (ConvF = 1 for Air)

DCP = Diode compression point in  $\mu$  V

CF = Signal Crest Factor (peak power/average power)

## Probe Response to Frequency

The E-field sensors have inherently a very flat frequency response. They are calibrated with a number of frequencies resulting in a common calibration factor, with the frequency behaviour documented in the calibration certificate.



WR-599.001


12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide R22)

Uncertainty of Frequency Response of E-field:  $\pm 6.3\% (k=2)$ 

H-field sensors have frequency dependant sensitivity, which is evaluated for a series of frequencies also visible in the probe calibration certificate. The calibration factors result from a fitting algorithm. The proper conversion is calculated by the DASY4 software depending on the frequency setting in the procedure.

## Frequency Response of H-Field

(TEM-Cell:ifi110, Waveguide R22)

Uncertainty of Frequency Response of E-field:  $\pm 6.3\% (k=2)$



## Conversion to Peak

Peak is defined as Peak Envelope Power. All raw measurements from the HAC measurement system are RMS values. The DASY4 system incorporates the crest factor of the signal in the computation of the RMS values. Although the software also has capability to estimate the peak field by applying a square root of crest factor value to the readings, the probe modulation factor was applied manually instead per PC63.19 in the measurement tables in this report. The equation to convert the raw measurements in the data tables are:

$$\text{Peak Field} = 20 \log (\text{Raw} \times \text{PMF})$$

Where:

Peak Field = Peak field (in dBV/m or dBA/m)


Raw = Raw field measurement from the measurement system (in V/m or A/m).

PMF = Probe Modulation Factor (in linear units).

## 6.2 Speag Robotic System

E-field and H-field measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) and consists of high precision robotics system (Staubli), robot controller, Pentium 4 computer, near- field probe, probe alignment sensor, and the HAC phantom. The robot is a six- axis industrial robot performing precise movements to the position the probe to the location of maximum EMF.

## System Hardware



A cell controller system contains the power supply, robot controller; teach pendant, and a remote control used to drive the robot motors. The PC consists of RF measurement system DASY4 V4.5 with HAC extension, A/D interface card, monitor, mouse and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD conversion, offset measurements, mechanical surface detection, collision detection, etc is connected to the Electro – optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

The DAE consists of a highly sensitive electrometer – grade preamplifier with auto-zeroing, a channel and gain switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built- in VME-bus computer.



## Data Evaluation

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_2 * (cf/dcpi)$$

with  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{Norm_i \times ConvF}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \times \frac{a_{io} + a_{il}f + a_{i2}f^2}{f}$$

with  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$Norm_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )  
 $\mu\text{V}/(\text{V}/\text{m})_2$  for E-field Probes

$ConvF$  = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel  $i$  in  $\text{V}/\text{m}$

$H_i$  = magnetic field strength of channel  $i$  in  $\text{A}/\text{m}$

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The signal response time is evaluated as the time required by the system to reach 90% of the expected final value after an on/off switch of the power source with an integration time of 500 ms and a probe response time of <5ms. In the current implementation, DASY4 waits longer than 100 ms after having reached the grid point before starting a measurement, i.e., the response time uncertainty is negligible.

If the device under test does not emit a CW signal, the integration time applied to measure the electric field at a specific point may introduce additional uncertainties due to the discretization. The tolerances for the different systems had the worst-case of 2.6%.



## 6.3 Test Setup

The test setup is shown in the picture below.



## 7. PASS/FAIL CRITERIA


The EUT must meet the following M3 category standards –

Category	Wireless Device Parameters		
Near field	AWF	E-field Emissions Peak – V/m	H-field Emissions Peak – A/m
Category M3	AWF = 0 (TDMA, CDMA)	63.1 to 112.2	0.19 to 0.34
	AWF = -5 (GSM)	47.3 to 84.1	0.15 to 0.25
Category M4	AWF = 0 (TDMA, CDMA)	< 63.1	< 0.19
	AWF = -5 (GSM)	< 47.3	< 0.15

## 8. TEST PROCEDURE

The following illustrates a typical RF emissions test scan over a wireless communication device:

- Proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed.
- WD is positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.
- The WD operation for maximum rated RF output power was configured and confirmed with the base station simulator, at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test.
- The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The WD audio outout was positioned tangent (as physically possible) to the measurement plane.
- The measurement system measured the field strength at the reference location.
- Measurements at 2mm increments in the 5x5 cm region were performed and recorded. A 360 deg rotation about the azimuth axis at the maximum interpolated position was measured. For the worst case condition, the peak reading from this rotation was used in re-evaluating the HAC category.
- The system performed a drift evaluation by measuring the field at the reference location.
- Same steps were done for both the E and H field measurements.






## 9. SYSTEM VALIDATION

The input signal was an unmodulated continuous wave. The following points were taken into consideration in performing the system validation:

Average Input Power = 100mW (20dBm RMS) after adjustment for return loss.

The test fixture must meet the 2-wavelength separation criterion.


The proper measurement of the 1cm probe to dipole separation, which is measured from the top surface of the dipole to the calibration reference point of the sensor, defined by the probe manufacturer is shown in the following picture:



To assure proper operation of the near-field measurement probe the input power to the dipole shall be commensurate to with the full rated output power of the wireless device (eg. – for a cellular phone wireless device the average peak antenna input power will be on the order of 100mW (ie, 20dBm) RMS after adjustment for any mismatch.

A dipole antenna meeting the requirements in PC63.19 was placed in the position normally occupied by the WD. The length of the dipole was scanned with both E-field and H-field probes and the maximum values for each were recorded.

Using the near-field measurement system, scan the antenna over the radiating dipole and record the greatest field reading observed. Due to the nature of E-fields about freespace dipoles, the two E-field peaks measured over the dipole are averaged to compensate for non-parallelism of the setup. See manufacturer method on dipole calibration certificates, page 2. Field strength measurements shall be made only when the probe is stationary.



Setup for Desired Output Power to Dipole


Setup to Dipole

Using this setup configuration, the signal generator was adjusted for the desired output power (100mW) at a specified frequency. The reference power from the coupled port of the directional coupler is recorded. Next, the output cable is connected to the reference dipole, as shown in the figure above.

The input signal was adjusted until the reference power from the coupled port of the directional coupler was the same as previously recorded, to compensate for the impedance mismatch between the output cable and the reference dipole.

To assure proper operation of the near-field measurement probe the input power to the reference dipole was verified to the full rated output power of the wireless device. The dipole was secured in a holder in a manner to meet the 20dB reflection. The near-field measurement probe was positioned over the dipole.

The antenna was scanned over the appropriate sized area to cover the dipole from end to end. SPEAG uses 2D interpolation algorithms between the measured points. Please see below two-dimensional plots showing that the interpolated values interpolate smoothly between 5mm steps for a free space RF dipole:





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

Validations were performed for CW at 20dBm peak power.

		Recorded	Target Value	% deviation
835 MHz	E field	154.0	162.1	5.00%
	H field	0.422	0.451	6.43%
1880 MHz	E field	129.1	137.6	6.18%
	H field	0.424	0.452	6.19%

Note: Please see Appendix A for the Validation Scans



## MODULATION FACTOR

A calibration was made of the modulation response of the probe and its instrumentation chain. This calibration was performed with the field probe, attached to its instrumentation. The response of the probe system to a CW field at the frequency of interest is compared to its response to a modulated signal with equal peak amplitude to that of a CW signal. The field level of the test signals are ensured to be more than 10dB above the ambient level and the noise floor of the instrumentation being used. The ratio of the CW reading to that taken with a modulated reading was applied to the DUT measurements.

This was done using the following procedure:

- The probe was illuminated with a CW signal at the intended measurement frequency.
- The probe was positioned at the field maxima over the dipole antenna (determined after an area scan over the dipole).
- The reading of the probe measurement system of the CW signal at the maximum point was recorded.
- Using a Spectrum Analyzer, the modulated signal adjusted with the same peak level of the CW signal was determined.
- The probe measurement system reading was recorded with the modulated signal.
- The ratio of the CW reading to the modulated signal reading is the probe modulation factor (PMF) for the modulation and field probe combination.
- Same steps are repeated at all frequency bands and for both E and H field probes.

The modulation factors obtained were applied to readings taken of the actual wireless device, in order to obtain an accurate peak field reading using the formula:

$$\text{Peak} = 20\log(\text{Raw} \times \text{PMF})$$

This method correlates well with the modulation using the DUT in the alternative substitution method. See below for correlation of signal:



Test &amp; Certification Center (TCC) - Dallas


WR-599.001

12 September 2005


Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

## Signal Generator Modulated Signal:



## Wireless Device Modulated Signal:





Test &amp; Certification Center (TCC) - Dallas


WR-599.001

12 September 2005


Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

Modulation Factors were performed for CW, 80%AM and the modulated signal at 20dBm peak power, See below for the picture as well as the Spectrum Analyzer Plots.



Determining Modulation Factor Probe Setup



CW Signal for 850MHz band




Test &amp; Certification Center (TCC) - Dallas

WR-599.001


12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0



CDMA Signal for 850MHz band



80%AM Signal for 850MHz band




Test &amp; Certification Center (TCC) - Dallas


WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

CW Signal for 1900MHz band



CDMA Signal for 1900MHz band




Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0



80%AM Signal for 1900MHz band

835 MHz	E-Field (V/m)	H-Field (A/m)	Modulation Factor (MF) for E-field	Modulation Factor (MF) for H-field
CDMA	152.2	0.43	1.0	1.0
CW	152.0	0.41		
80%AM	90.3	0.25		

1880 MHz	E-Field (V/m)	H-Field (A/m)	Modulation Factor (MF) for E-field	Modulation Factor (MF) for H-field
CDMA	118.3	0.57	1.0	0.7
CW	115.0	0.38		
80%AM	71.5	0.24		



## 10. DETAILED TEST RESULTS

<b>Test Technician / Engineer</b>	Anu Balijepalli		
<b>Date of Measurement</b>	August 31-September 2, 2005		
<b>Temperature / Humidity / Pressure</b>	20-25°C	45-60%RH	29-31 in
<b>Test Result</b>	Complies		

### 10.1 Near Field E and H RF emissions measurements

#### 10.1.1 Test Results

Note: Testing was done at the antenna extended position. See Appendix B for the grids and plots of these cases.

#### CDMA CELLULAR E – FIELD

##### Slide Closed

CDMA Cellular	Conducted Power (dBm)	Power Drift (dB)	E (V/m)	Modulation Factor	Peak Field (V/m)	Excluded Blocks
Ch 1013	25.2	-0.144	65.9	1.0	65.9	6,8,9
Ch 384	24.7	-0.0927	68.9	1.0	68.9	3,6,9
Ch 777	24.7	-0.0754	72.4	1.0	72.4	6,8,9

##### Slide Open

CDMA Cellular	Conducted Power (dBm)	Power Drift (dB)	E (V/m)	Modulation Factor	Peak Field (V/m)	Excluded Blocks
Ch 1013	25.2	-0.00505	82.8	1.0	82.8	2,3,6
Ch 384	24.7	-0.31	84.9	1.0	84.9	2,3,6
Ch 777	24.7	-0.119	97.4	1.0	97.4	2,3,6



Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

**CDMA CELLULAR H- FIELD****Slide Closed**

CDMA Cellular	Conducted Power (dBm)	Power Drift (dB)	H (A/m)	Modulation Factor	Peak Field (A/m)	Excluded Blocks
Ch 1013	25.2	-0.133	0.237	1.0	0.237	4,7,8
Ch 384	24.7	-0.209	0.234	1.0	0.234	4,7,8
Ch 777	24.7	-0.128	0.248	1.0	0.248	4,7,8

**Slide Open**

CDMA Cellular	Conducted Power (dBm)	Power Drift (dB)	H (A/m)	Modulation Factor	Peak Field (A/m)	Excluded Blocks
Ch 1013	25.2	-0.103	0.138	1.0	0.138	1,4,7
Ch 384	24.7	0.0842	0.133	1.0	0.133	1,4,7
Ch 777	24.7	-0.382	0.154	1.0	0.154	1,4,7

**CDMA PCS E – FIELD****Slide Closed**

CDMA PCS	Conducted Power (dBm)	Power Drift (dB)	E (V/m)	Modulation Factor	Peak Field (V/m)	Excluded Blocks
Ch 25	22.8	0.19	44.4	1.0	44.4	7,8,9
Ch 600	23.3	0.221	46.5	1.0	46.5	7,8,9
Ch 1175	23.2	0.00476	45.7	1.0	45.7	7,8,9



Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

**Slide Open**

CDMA PCS	Conducted Power (dBm)	Power Drift (dB)	E (V/m)	Modulation Factor	Peak Field (V/m)	Excluded Blocks
Ch 25	22.8	0.00112	35.9	1.0	35.9	7,8,9
Ch 600	23.3	0.142	40.0	1.0	40.0	7,8,9
Ch 1175	23.2	-0.319	43.9	1.0	43.9	7,8,9

**CDMA PCS H – FIELD****Slide Closed**

CDMA PCS	Conducted Power (dBm)	Power Drift (dB)	H (A/m)	Modulation Factor	Peak Field (A/m)	Excluded Blocks
Ch 25	22.8	-0.0557	0.136	0.7	0.0952	6,8,9
Ch 600	23.3	-0.0955	0.183	0.7	0.1281	6,8,9
Ch 1175	23.2	0.15	0.160	0.7	0.112	6,8,9

**Slide Open**

CDMA PCS	Conducted Power (dBm)	Power Drift (dB)	H (A/m)	Modulation Factor	Peak Field (A/m)	Excluded Blocks
Ch 25	22.8	0.139	0.098	0.7	0.0686	4,7,8
Ch 600	23.3	0.0688	0.122	0.7	0.0854	4,7,8
Ch 1175	23.2	-0.158	0.112	0.7	0.0784	4,7,8



Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005


Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

**WORST CASE CONFIGURATION**

CDMA Cellular	E (V/m)	Modulation Factor	Peak Field (V/m)	FCC M3 Limits (V/m)	Category
Ch 777	102.3	1.0	102.3	63.1 to 112.2	M3

The probe rotation was done at the sub grid 5 for Channel 777, E field in the Slide Open Position.



**11. MEASUREMENT UNCERTAINTY**

HAC Uncertainty Budget									
Error Description	Uncertainty value	Prob. Dist.	Div.	(ci) E	(ci) H	Std. Unc. E	Std. Unc. H	Squared E	Squared H
Measurement System									
Probe Calibration	5.1	N	1	1	1	5.1	5.1	26.0	26.0
Axial Isotropy	4.7	R	1.7321	1	1	2.7	2.7	7.4	7.4
Sensor Displacement	16.5	R	1.7321	1	0.145	9.5	1.4	90.7	1.9
Boundary Effects	2.4	R	1.7321	1	1	1.4	1.4	1.9	1.9
Linearity	4.7	R	1.7321	1	1	2.7	2.7	7.4	7.4
Scaling to Peak Envelope Power	2	R	1.7321	1	1		1.2	1.2	1.3
System Detection Limit	1	R	1.7321	1	1	0.6	0.6	0.3	0.3
Readout Electronics	0.3	N	1	1	1	0.3	0.3	0.1	0.1
Response Time	0.8	R	1.7321	1	1	0.5	0.5	0.2	0.2
Integration Time	2.6	R	1.7321	1	1	1.5	1.5	2.3	2.3
RF Ambient Conditions	3	R	1.7321	1	1		1.7	1.7	3.0
RF Reflections	12	R	1.7321	1	1	6.9	6.9	48.0	48.0
Probe Positioner	1.2	R	1.7321	1	0.67	0.7	0.5	0.5	0.2
Probe Positioning	4.7	R	1.7321	1	0.67	2.7	1.8	7.4	3.3
Extrap. And Interpolation	1	R	1.7321	1	1	0.6	0.6	0.3	0.3
Test Sample Related								0.0	0.0
Device Positioning Vertical	10	R	1.7321	1	0.67		2.7	1.8	7.4
Device Positioning Lateral	10	R	1.7321	1	1	0.6	0.6	0.3	0.3
Device Holder	2.4	R	1.7321	1	1	1.4	1.4	1.9	1.9
Power Drift	5	R	1.7321	1	1	2.9	2.9	8.3	8.3
Phantom and Setup Related								0.0	0.0
Phantom Thickness	2.4	R	1.7321	1	0.67	1.4	0.9	1.9	0.9
Combined Std. Uncertainty								16.6	12.8
Expanded Std. Uncertainty on Field (k=2)								33.2%	21.8%

# TCC

Test & Certification Center (TCC) - Dallas

Company Confidential

WR-599.001

12 September 2005



30 (60)

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

## APPENDIX A: VALIDATIONS SCANS



Date/Time: 8/30/2005 1:36:40 PM

Test Laboratory: TCC Dallas

**835MHz, E field, CW Validation**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1


DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.00461 dB

**HAC Procedure/Hearing Aid Compatibility Test 0 deg (81x401x1):** Measurement grid: dx=5mm, dy=5mm  
Maximum value of Total field (slot averaged) = 158.1 V/m**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

E in V/m (Time averaged)			E in V/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>152.9</b>	<b>158.1</b>	<b>129.1</b>	<b>152.9</b>	<b>158.1</b>	<b>129.1</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>75.2</b>	<b>87.6</b>	<b>83.9</b>	<b>75.2</b>	<b>87.6</b>	<b>83.9</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>122.6</b>	<b>149.8</b>	<b>145.6</b>	<b>122.6</b>	<b>149.8</b>	<b>145.6</b>





Date/Time: 8/30/2005 2:09:37 PM

Test Laboratory: TCC Dallas

**835MHz, H field, CW Validation**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1


DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.0274 dB

**HAC Procedure/Hearing Aid Compatibility Test 0 deg (81x401x1):** Measurement grid: dx=5mm, dy=5mm  
Maximum value of Total field (slot averaged) = 0.422 A/m**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.299</b>	<b>0.362</b>	<b>0.335</b>	<b>0.299</b>	<b>0.362</b>	<b>0.335</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.353</b>	<b>0.422</b>	<b>0.388</b>	<b>0.353</b>	<b>0.422</b>	<b>0.388</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.307</b>	<b>0.364</b>	<b>0.334</b>	<b>0.307</b>	<b>0.364</b>	<b>0.334</b>





Date/Time: 8/30/2005 2:57:52 PM

Test Laboratory: TCC Dallas

**1880MHz, E field, CW Validation**

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1


DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.0302 dB

**HAC Procedure/Hearing Aid Compatibility Test 0 deg (81x181x1):** Measurement grid: dx=5mm, dy=5mm  
Maximum value of Total field (slot averaged) = 130.4 V/m**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

E in V/m (Time averaged)			E in V/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>108.8</b>	<b>127.8</b>	<b>116.5</b>	<b>108.8</b>	<b>127.8</b>	<b>116.5</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>74.6</b>	<b>87.0</b>	<b>83.8</b>	<b>74.6</b>	<b>87.0</b>	<b>83.8</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>107.5</b>	<b>130.4</b>	<b>123.3</b>	<b>107.5</b>	<b>130.4</b>	<b>123.3</b>





Date/Time: 8/30/2005 2:43:21 PM

Test Laboratory: TCC Dallas

**1880MHz, H field, CW Validation**

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1


DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.0182 dB

**HAC Procedure/Hearing Aid Compatibility Test 0 deg (81x181x1):** Measurement grid: dx=5mm, dy=5mm  
Maximum value of Total field (slot averaged) = 0.424 A/m**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.320</b>	<b>0.388</b>	<b>0.356</b>	<b>0.320</b>	<b>0.388</b>	<b>0.356</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.351</b>	<b>0.424</b>	<b>0.395</b>	<b>0.351</b>	<b>0.424</b>	<b>0.395</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.315</b>	<b>0.384</b>	<b>0.362</b>	<b>0.315</b>	<b>0.384</b>	<b>0.362</b>



# TCC

Test & Certification Center (TCC) - Dallas

Company Confidential

WR-599.001

12 September 2005



35 (60)

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

## APPENDIX B: MEASUREMENT SCANS



Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

Date/Time: 9/2/2005 10:54:58 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch1013, E field, Slide Closed**

Communication System: CDMA800; Frequency: 824.7 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.144 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 65.9 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>42.9</b>	<b>62.5</b>	<b>64.6</b>	<b>42.9</b>	<b>62.5</b>	<b>64.6</b>
<b>39.0</b>	<b>65.9</b>	<b>69.1</b>	<b>39.0</b>	<b>65.9</b>	<b>69.1</b>
<b>41.0</b>	<b>66.4</b>	<b>69.4</b>	<b>41.0</b>	<b>66.4</b>	<b>69.4</b>





Date/Time: 9/2/2005 11:17:25 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch384, E field, Slide Closed**

Communication System: CDMA800; Frequency: 836.52 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.0927 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 68.9 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>50.3</b>	<b>67.8</b>	<b>69.9</b>	<b>50.3</b>	<b>67.8</b>	<b>69.9</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>43.5</b>	<b>68.9</b>	<b>70.6</b>	<b>43.5</b>	<b>68.9</b>	<b>70.6</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>45.5</b>	<b>68.7</b>	<b>70.6</b>	<b>45.5</b>	<b>68.7</b>	<b>70.6</b>





Date/Time: 9/2/2005 11:38:28 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch777, E field, Slide Closed**

Communication System: CDMA800; Frequency: 848.31 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.0754 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm


Maximum value of Total field (slot averaged) = 72.4 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3
<b>51.1</b>	<b>70.1</b>	<b>71.3</b>
Grid 4	Grid 5	Grid 6
<b>44.9</b>	<b>72.4</b>	<b>75.3</b>

Grid 1	Grid 2	Grid 3
<b>51.1</b>	<b>70.1</b>	<b>71.3</b>
Grid 4	Grid 5	Grid 6
<b>44.9</b>	<b>72.4</b>	<b>75.3</b>





Date/Time: 9/2/2005 10:32:03 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch1013, E field, Slide Open**

Communication System: CDMA800; Frequency: 824.7 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.00505 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 82.8 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>69.7</b>	<b>83.1</b>	<b>83.1</b>	<b>69.7</b>	<b>83.1</b>	<b>83.1</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>64.5</b>	<b>82.8</b>	<b>82.9</b>	<b>64.5</b>	<b>82.8</b>	<b>82.9</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>61.2</b>	<b>78.5</b>	<b>78.5</b>	<b>61.2</b>	<b>78.5</b>	<b>78.5</b>





Date/Time: 9/2/2005 10:10:13 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch384, E field, Slide Open**

Communication System: CDMA800; Frequency: 836.52 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.31 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 84.9 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)			E in V/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
71.9	85.4	85.3	71.9	85.4	85.3
65.0	84.9	85.1	65.0	84.9	85.1
61.5	79.4	79.5	61.5	79.4	79.5





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

Date/Time: 9/2/2005 9:47:55 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch777, E field, Slide Open**

Communication System: CDMA800; Frequency: 848.31 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.119 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 97.4 V/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>80.4</b>	<b>97.4</b>	<b>97.5</b>	<b>80.4</b>	<b>97.4</b>	<b>97.5</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>74.4</b>	<b>97.4</b>	<b>97.5</b>	<b>74.4</b>	<b>97.4</b>	<b>97.5</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>71.5</b>	<b>92.1</b>	<b>92.1</b>	<b>71.5</b>	<b>92.1</b>	<b>92.1</b>





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

Date/Time: 9/1/2005 12:26:22 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch1013, H field, Slide Closed**

Communication System: CDMA800; Frequency: 824.7 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.133 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.237 A/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.237</b>	<b>0.214</b>	<b>0.186</b>	<b>0.237</b>	<b>0.214</b>	<b>0.186</b>
0.226	0.223	0.204	0.226	0.223	0.204
0.267	0.255	0.202	0.267	0.255	0.202





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

Date/Time: 9/1/2005 11:08:23 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch384, H field, Slide Closed**

Communication System: CDMA800; Frequency: 836.52 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.209 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.234 A/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.234</b>	<b>0.212</b>	<b>0.188</b>	<b>0.234</b>	<b>0.212</b>	<b>0.188</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.221</b>	<b>0.218</b>	<b>0.203</b>	<b>0.221</b>	<b>0.218</b>	<b>0.203</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.265</b>	<b>0.254</b>	<b>0.203</b>	<b>0.265</b>	<b>0.254</b>	<b>0.203</b>





Date/Time: 9/1/2005 1:07:22 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch777, H field, Slide Closed**

Communication System: CDMA800; Frequency: 848.31 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.128 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.248 A/m

**Hearing Aid Near-Field Category: M3 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.248</b>	<b>0.226</b>	<b>0.200</b>	<b>0.248</b>	<b>0.226</b>	<b>0.200</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.236</b>	<b>0.232</b>	<b>0.216</b>	<b>0.236</b>	<b>0.232</b>	<b>0.216</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.274</b>	<b>0.263</b>	<b>0.216</b>	<b>0.274</b>	<b>0.263</b>	<b>0.216</b>





Date/Time: 9/2/2005 3:26:17 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch1013, H field, Slide Open**

Communication System: CDMA800; Frequency: 824.7 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.103 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.119 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
0.162	0.119	0.070	0.162	0.119	0.070
0.138	0.103	0.064	0.138	0.103	0.064
0.162	0.118	0.071	0.162	0.118	0.071





Date/Time: 9/1/2005 3:52:31 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch384, H field, Slide Open**

Communication System: CDMA800; Frequency: 836.52 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = 0.0842 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.116 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
0.158	0.116	0.068	0.158	0.116	0.068
0.133	0.098	0.059	0.133	0.098	0.059
0.153	0.109	0.065	0.153	0.109	0.065





Date/Time: 9/2/2005 9:20:37 AM

Test Laboratory: TCC Dallas

**RM-66, CDMA800, Ch777, H field, Slide Open**

Communication System: CDMA800; Frequency: 848.31 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.382 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.132 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
0.183	0.132	0.076	0.183	0.132	0.076
0.154	0.112	0.068	0.154	0.112	0.068
0.183	0.131	0.075	0.183	0.131	0.075





Date/Time: 9/2/2005 12:25:35 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch25, E field, Slide Closed**

Communication System: CDMA1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.19 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 44.4 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>41.8</b>	<b>41.8</b>	<b>37.9</b>	<b>41.8</b>	<b>41.8</b>	<b>37.9</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>41.1</b>	<b>44.4</b>	<b>44.0</b>	<b>41.1</b>	<b>44.4</b>	<b>44.0</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>51.0</b>	<b>53.9</b>	<b>52.6</b>	<b>51.0</b>	<b>53.9</b>	<b>52.6</b>





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Accredited Laboratory Certificate  
Number: 1819-01

Ver 1.0

Date/Time: 9/2/2005 12:03:07 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch600, E field, Slide Closed**

Communication System: CDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.221 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 46.5 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>46.5</b>	<b>46.4</b>	<b>40.8</b>	<b>46.5</b>	<b>46.4</b>	<b>40.8</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>45.3</b>	<b>44.6</b>	<b>44.6</b>	<b>45.3</b>	<b>44.6</b>	<b>44.6</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>54.2</b>	<b>54.3</b>	<b>53.4</b>	<b>54.2</b>	<b>54.3</b>	<b>53.4</b>





Date/Time: 9/2/2005 12:47:45 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch1175, E field, Slide Closed**

Communication System: CDMA1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.00476 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 45.7 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>45.7</b>	<b>45.3</b>	<b>38.3</b>	<b>45.7</b>	<b>45.3</b>	<b>38.3</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>42.0</b>	<b>42.0</b>	<b>42.7</b>	<b>42.0</b>	<b>42.0</b>	<b>42.7</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>50.4</b>	<b>52.0</b>	<b>51.9</b>	<b>50.4</b>	<b>52.0</b>	<b>51.9</b>





Date/Time: 9/2/2005 1:56:07 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch25, E field, Slide Open**

Communication System: CDMA1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.000112 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 36.7 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>35.9</b>	<b>36.7</b>	<b>35.9</b>	<b>35.9</b>	<b>36.7</b>	<b>35.9</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>32.9</b>	<b>35.8</b>	<b>35.8</b>	<b>32.9</b>	<b>35.8</b>	<b>35.8</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>39.6</b>	<b>41.4</b>	<b>39.9</b>	<b>39.6</b>	<b>41.4</b>	<b>39.9</b>





Date/Time: 9/2/2005 1:34:39 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch600, E field, Slide Open**

Communication System: CDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = 0.142 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 40.0 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>39.2</b>	<b>40.0</b>	<b>39.4</b>	<b>39.2</b>	<b>40.0</b>	<b>39.4</b>
35.8	38.5	38.4	35.8	38.5	38.4
41.3	41.9	39.0	41.3	41.9	39.0





Date/Time: 9/2/2005 1:13:09 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch1175, E field, Slide Open**

Communication System: CDMA1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: ER3DV6 - SN2337; ConvF(1, 1, 1); Calibrated: 1/31/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Power Drift = -0.319 dB


**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 43.9 V/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

E in V/m (Time averaged)    E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>43.9</b>	<b>43.9</b>	<b>41.5</b>	<b>43.9</b>	<b>43.9</b>	<b>41.5</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>38.0</b>	<b>40.6</b>	<b>40.5</b>	<b>38.0</b>	<b>40.6</b>	<b>40.5</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>43.4</b>	<b>44.7</b>	<b>41.9</b>	<b>43.4</b>	<b>44.7</b>	<b>41.9</b>





Date/Time: 9/1/2005 1:55:17 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch25, H field, Slide Closed**

Communication System: CDMA1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.0557 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.148 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.099</b>	<b>0.125</b>	<b>0.125</b>	<b>0.099</b>	<b>0.125</b>	<b>0.125</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.123</b>	<b>0.148</b>	<b>0.146</b>	<b>0.123</b>	<b>0.148</b>	<b>0.146</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.136</b>	<b>0.148</b>	<b>0.147</b>	<b>0.136</b>	<b>0.148</b>	<b>0.147</b>





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

Date/Time: 9/1/2005 1:31:42 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch600, H field, Slide Closed**

Communication System: CDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.0955 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.183 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.125</b>	<b>0.154</b>	<b>0.155</b>	<b>0.125</b>	<b>0.154</b>	<b>0.155</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.153</b>	<b>0.183</b>	<b>0.182</b>	<b>0.153</b>	<b>0.183</b>	<b>0.182</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.166</b>	<b>0.185</b>	<b>0.184</b>	<b>0.166</b>	<b>0.185</b>	<b>0.184</b>





Date/Time: 9/1/2005 2:17:47 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch1175, H field, Slide Closed**

Communication System: CDMA1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = 0.15 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.160 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.108</b>	<b>0.134</b>	<b>0.133</b>	<b>0.108</b>	<b>0.134</b>	<b>0.133</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.131</b>	<b>0.160</b>	<b>0.159</b>	<b>0.131</b>	<b>0.160</b>	<b>0.159</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.143</b>	<b>0.160</b>	<b>0.160</b>	<b>0.143</b>	<b>0.160</b>	<b>0.160</b>





Date/Time: 9/1/2005 3:28:51 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch25, H field, Slide Open**

Communication System: CDMA1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = 0.139 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.098 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.074</b>	<b>0.075</b>	<b>0.071</b>	<b>0.074</b>	<b>0.075</b>	<b>0.071</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.099</b>	<b>0.098</b>	<b>0.088</b>	<b>0.099</b>	<b>0.098</b>	<b>0.088</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.114</b>	<b>0.106</b>	<b>0.092</b>	<b>0.114</b>	<b>0.106</b>	<b>0.092</b>





Test &amp; Certification Center (TCC) - Dallas

WR-599.001

12 September 2005

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

Date/Time: 9/1/2005 3:07:20 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch600, H field, Slide Open**

Communication System: CDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = 0.0688 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.122 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.095</b>	<b>0.094</b>	<b>0.088</b>	<b>0.095</b>	<b>0.094</b>	<b>0.088</b>
0.124	0.122	0.110	0.124	0.122	0.110
0.143	0.132	0.112	0.143	0.132	0.112





Date/Time: 9/1/2005 2:40:50 PM

Test Laboratory: TCC Dallas

**RM-66, CDMA1900, Ch1175, H field, Slide Open**

Communication System: CDMA1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

DASY4 Configuration:

- Probe: H3DV6 - SN6155; ; Calibrated: 2/16/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn389; Calibrated: 1/12/2005
- Phantom: SAM3 Cover FreeSpace Only; Phantom section: Table Section
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146


Power Drift = -0.158 dB

**HAC Procedure/Hearing Aid Compatibility Test (251x251x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of Total field (slot averaged) = 0.112 A/m

**Hearing Aid Near-Field Category: M4 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.090</b>	<b>0.092</b>	<b>0.087</b>	<b>0.090</b>	<b>0.092</b>	<b>0.087</b>
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
<b>0.113</b>	<b>0.112</b>	<b>0.100</b>	<b>0.113</b>	<b>0.112</b>	<b>0.100</b>
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
<b>0.125</b>	<b>0.116</b>	<b>0.102</b>	<b>0.125</b>	<b>0.116</b>	<b>0.102</b>



# TCC

Test & Certification Center (TCC) - Dallas

Company Confidential

WR-599.001

12 September 2005



60 (60)

Ver 1.0

Accredited Laboratory Certificate  
Number: 1819-01

## APPENDIX C: PROBE CALIBRATION REPORTS AND DIPOLE CALIBRATION REPORTS

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
**Zeughausstrasse 43, 8004 Zurich, Switzerland**



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**Client **Nokia TX**Certificate No: **ER3-2337\_Jan05**

## CALIBRATION CERTIFICATE

Object **ER3DV6 - SN:2337**

Calibration procedure(s) **QA CAL-02.v4**  
**Calibration procedure for E-field probes optimized for close near field evaluations in air**

Calibration date: **January 31, 2005**Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&amp;TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	5-May-04 (METAS, No. 251-00388)	May-05
Power sensor E4412A	MY41495277	5-May-04 (METAS, No. 251-00388)	May-05
Reference 3 dB Attenuator	SN: S5054 (3c)	10-Aug-04 (METAS, No. 251-00403)	Aug-05
Reference 20 dB Attenuator	SN: S5086 (20b)	3-May-04 (METAS, No. 251-00389)	May-05
Reference 30 dB Attenuator	SN: S5129 (30b)	10-Aug-04 (METAS, No. 251-00404)	Aug-05
Reference Probe ER3DV6	SN: 2328	6-Oct-04 (SPEAG, No. ER3-2328_Oct04)	Oct-05
DAE4	SN: 617	19-Jan-05 (SPEAG, No. DAE4-617_Jan05)	Jan-06
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092180	18-Sep-02 (SPEAG, in house check Oct-03)	In house check: Oct 05
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Dec-03)	In house check: Dec-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov 05

Calibrated by:	Name	Function	Signature
	Katja Pokovic	Technical Manager	

Approved by:	Name	Function	Signature
	Niels Kuster	Quality Manager	

Issued: February 19, 2005

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### **Glossary:**

NORM $x,y,z$	sensitivity in free space
DCP	diode compression point
Polarization $\phi$	$\phi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

### **Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1309-1996, " IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", 1996.

### **Methods Applied and Interpretation of Parameters:**

- NORM $x,y,z$ : Assessed for E-field polarization  $\vartheta = 0$  for XY sensors and  $\vartheta = 90$  for Z sensor ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide).
- $NORM(f)x,y,z = NORMx,y,z * frequency\_response$  (see Frequency Response Chart).
- DCP $x,y,z$ : DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency.
- *Spherical isotropy (3D deviation from isotropy)*: in a locally homogeneous field realized using an open waveguide setup.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the NORM $x$  (no uncertainty required).

**ER3DV6 SN:2337**

**January 31, 2005**

# **Probe ER3DV6**

**SN:2337**

**Manufactured:** September 9, 2003  
**Calibrated:** January 31, 2005

**Calibrated for DASY Systems**

(Note: non-compatible with DASY2 system!)

**DASY - Parameters of Probe: ER3DV6 SN:2337**

Sensitivity in Free Space [ $\mu\text{V}/(\text{V}/\text{m})^2$ ]      Diode Compression<sup>A</sup>

NormX	<b>1.51</b> $\pm$ 10.1 % (k=2)	DCP X	<b>95</b> mV
NormY	<b>1.43</b> $\pm$ 10.1 % (k=2)	DCP Y	<b>95</b> mV
NormZ	<b>1.58</b> $\pm$ 10.1 % (k=2)	DCP Z	<b>97</b> mV

**Frequency Correction**

X	<b>0.0</b>
Y	<b>0.0</b>
Z	<b>0.0</b>

**Sensor Offset**      (Probe Tip to Sensor Center)

X	<b>2.5</b> mm
Y	<b>2.5</b> mm
Z	<b>2.5</b> mm


**Connector Angle**      **-25** °

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



<sup>A</sup> numerical linearization parameter: uncertainty not required

## Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )


Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$ Receiving Pattern ( $\phi$ ),  $\theta = 90^\circ$ 

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)


### Receiving Pattern ( $\phi$ ), $\theta = 90^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)


### Dynamic Range f(E-field)

(Waveguide R22, f = 1800 MHz)



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

**Deviation from Isotropy in Air**  
**Error ( $\phi, \theta$ ), f = 900 MHz**



**Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)**

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
**Zeughausstrasse 43, 8004 Zurich, Switzerland**



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Nokia TX**

Certificate No: **H3-6155\_Feb05**

## CALIBRATION CERTIFICATE

Object **H3DV6 - SN:6155**

Calibration procedure(s) **QA CAL-03.v4**  
 Calibration procedure for H-field probes optimized for close near field evaluations in air

Calibration date: **February 16, 2005**

Condition of the calibrated item **In Tolerance**


This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	5-May-04 (METAS, No. 251-00388)	May-05
Power sensor E4412A	MY41495277	5-May-04 (METAS, No. 251-00388)	May-05
Reference 3 dB Attenuator	SN: S5054 (3c)	10-Aug-04 (METAS, No. 251-00403)	Aug-05
Reference 20 dB Attenuator	SN: S5086 (20b)	3-May-04 (METAS, No. 251-00389)	May-05
Reference 30 dB Attenuator	SN: S5129 (30b)	10-Aug-04 (METAS, No. 251-00404)	Aug-05
Reference Probe H3DV6	SN: 6182	6-Oct-04 (SPEAG, No. H3-6182_Oct04)	Oct-05
DAE4	SN: 617	19-Jan-05 (SPEAG, No. DAE4-617_Jan05)	Jan-06
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092180	18-Sep-02 (SPEAG, in house check Oct-03)	In house check: Oct 05
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Dec-03)	In house check: Dec-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov 05

Calibrated by:	Name	Function	Signature
	Katja Pokovic	Technical Manager	

Approved by:	Name	Function	Signature
	Niels Kuster	Quality Manager	

Issued: February 19, 2005

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### **Glossary:**

NORM <sub>x,y,z</sub>	sensitivity in free space
DCP	diode compression point
Polarization $\phi$	$\phi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

### **Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1309-1996, " IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", 1996.

### **Methods Applied and Interpretation of Parameters:**

- $X, Y, Z_a0a1a2$ : Assessed for E-field polarization  $\vartheta = 90$  for XY sensors and  $\vartheta = 0$  for Z sensor ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide).
- $X, Y, Z(f)_a0a1a2 = X, Y, Z_a0a1a2 * \text{frequency\_response}$  (see Frequency Response Chart).
- $DCPx, y, z$ : DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency.
- *Spherical isotropy (3D deviation from isotropy)*: in a locally homogeneous field realized using an open waveguide setup.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the  $X_a0a1a2$  (no uncertainty required).

H3DV6 SN:6155

February 16, 2005

# Probe H3DV6

SN:6155

Manufactured: June 22, 2004  
Calibrated: February 16, 2005

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

**DASY - Parameters of Probe: H3DV6 SN:6155**Sensitivity in Free Space [A/m /  $\sqrt{\mu\text{V}}$ ]

	a0	a1	a2
X	2.719E-03	-7.681E-5	3.643E-5 $\pm$ 5.1 % (k=2)
Y	2.743E-03	1.819E-5	-1.877E-5 $\pm$ 5.1 % (k=2)
Z	2.974E-03	-4.287E-5	-1.156E-5 $\pm$ 5.1 % (k=2)

Diode Compression<sup>1</sup>

DCP X	86 mV
DCP Y	86 mV
DCP Z	85 mV

Sensor Offset (Probe Tip to Sensor Center)

X	3.0 mm
Y	3.0 mm
Z	3.0 mm


Connector Angle 319 °

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



<sup>1</sup> numerical linearization parameter: uncertainty not required


## Frequency Response of H-Field

(TEM-Cell:ifi110, Waveguide R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )



**Receiving Pattern ( $\phi$ ),  $\theta = 90^\circ$** **Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$** 

**Receiving Pattern ( $\phi$ ),  $\theta = 90^\circ$** 

Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

**Receiving Pattern ( $\phi$ ),  $\theta = 0^\circ$** 

Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

**Dynamic Range f(H-field)**(Waveguide R22,  $f = 1800$  MHz)Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
**Zeughausstrasse 43, 8004 Zurich, Switzerland**

Client **Nokia TX**Certificate No: **CD835V3-1032\_Apr05**

## **CALIBRATION CERTIFICATE**

Object **CD835V3 - SN: 1032**

Calibration procedure(s) **QA CAL-20.v3**  
**Calibration procedure for dipoles in air**


Calibration date: **April 27, 2005**Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 All calibrations have been conducted at an environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&amp;TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	12-Oct-04 (METAS, No. 251-00412)	Oct-05
Power sensor HP 8481A	US37292783	12-Oct-04 (METAS, No. 251-00412)	Oct-05
20 dB Attenuator	SN: 5086 (20g)	10-Aug-04 (METAS, No 251-00402)	Aug-05
10 dB Attenuator	SN: 5047.2 (10r)	10-Aug-04 (METAS, No 251-00402)	Aug-05
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-4419B	GB43310788	10-Aug-03 (SPEAG, in house check Jan-04)	In house check: Oct-05
Power sensor HP 8481A	MY41092312	10-Aug-03 (SPEAG, in house check Jan-04)	In house check: Oct-05
Power sensor HP 8481A	MY41093315	10-Aug-03 (SPEAG, in house check Jan-04)	In house check: Oct-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov-05
RF generator R&S SMT06	1039.2000.06	26-Jul-04 (SPEAG, in house check Jul-04)	In house check: Jan-06
DAE4	SN: 901	29-Jun-04 (SPEAG, No. DAE4-901_Jun04)	Calibration, Jun-05
Probe ER3DV6	SN: 2336	20-Jan-05 (SPEAG, No. ER3-2336_Jan05)	Calibration, Jan-06
Probe H3DV6	SN: 6065	10-Dec-04 (SPEAG, No. H3-6065-Dec04)	Calibration, Dec-05

Calibrated by: Name **Mike Meili** Function **Laboratory Technician**



Approved by: Name **Fin Bornholt** Function **Technical Director**



Issued: June 13, 2005

## References

[1] ANSI-PC63.19-2001 (Draft 3.x, 2005)  
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.

## Methods Applied and Interpretation of Parameters:

- **Coordinate System:** y-axis is in the direction of the dipole arms. z-axis is from the basis of the antenna (mounted on the table) towards its feed point between the two dipole arms. x-axis is normal to the other axes. In coincidence with standard [1], the measurement planes (probe sensor center) are selected to be at a distance of 10 mm above the the top edge of the dipole arms.
- **Measurement Conditions:** Further details are available from the hardcopies at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated. The forward power to the dipole connector is set with a calibrated power meter connected and monitored with an auxiliary power meter connected to a directional coupler. While the dipole under test is connected, the forward power is adjusted to the same level.
- **Antenna Positioning:** The dipole is mounted on a HAC Test Arch phantom using the matching dipole positioner with the arms horizontal and the feeding cable coming from the floor. The measurements are performed in a shielded room with absorbers around the setup to reduce the reflections.  
It is verified before the mounting of the dipole under the Test Arch phantom, that its arms are perfectly in a line. It is installed on the HAC dipole positioner with its arms parallel below the dielectric reference wire and able to move elastically in vertical direction without changing its relative position to the top center of the Test Arch phantom. The vertical distance to the probe is adjusted after dipole mounting with a DASY4 Surface Check job. Before the measurement, the distance between phantom surface and probe tip is verified. The proper measurement distance is selected by choosing the matching section of the HAC Test Arch phantom with the proper device reference point (upper surface of the dipole) and the matching grid reference point (tip of the probe) considering the probe sensor offset. The vertical distance to the probe is essential for the accuracy.
- **Feed Point Impedance and Return Loss:** These parameters are measured using a HP 8753E Vector Network Analyzer. The impedance is specified at the SMA connector of the dipole. The influence of reflections was eliminating by applying the averaging function while moving the dipole in the air, at least 70cm away from any obstacles.
- **E- field distribution:** E field is measured in the x-y-plane with an isotropic ER3D-field probe with 100 mW forward power to the antenna feed point. In accordance with [1], the scan area is 20mm wide, its length exceeds the dipole arm length (180 or 90mm). The sensor center is 10 mm (in z) above the top of the dipole arms. Two 3D maxima are available near the end of the dipole arms. Assuming the dipole arms are perfectly in one line, the average of these two maxima (in subgrid 2 and subgrid 8) is determined to compensate for any non-parallelity to the measurement plane as well as the sensor displacement. The E-field value stated as calibration value represents the maximum of the interpolated 3D-E-field, 10mm above the dipole surface.
- **H-field distribution:** H-field is measured with an isotropic H-field probe with 100mW forward power to the antenna feed point, in the x-y-plane. The scan area and sensor distance is equivalent to the E-field scan. The maximum of the field is available at the center (subgrid 5) above the feed point. The H-field value stated as calibration value represents the maximum of the interpolated H-field, 10mm above the dipole surface at the feed point.

## 1 Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY4	V4.5 B19
<b>DASY PP Version</b>	SEMCAD	V1.8 B149
<b>Phantom</b>	HAC Test Arch	SD HAC P01 BA, #1002
<b>Distance Dipole Top - Probe Center</b>	10 mm	
<b>Scan resolution</b>	$dx, dy = 5 \text{ mm}$	area = $20 \times 180 \text{ mm}$
<b>Frequency</b>	$835 \text{ MHz} \pm 1 \text{ MHz}$	
<b>Forward power at dipole connector</b>	$20.0 \text{ dBm} = 100 \text{ mW}$	
<b>Input power drift</b>	< 0.05 dB	

## 2 Maximum Field values

<b>H-field 10 mm above dipole surface</b>	condition	<b>interpolated maximum</b>
Maximum measured	100 mW forward power	<b>0.451 A/m</b>

Uncertainty for H-field measurement: 8.2% (k=2)

<b>E-field 10 mm above dipole surface</b>	condition	<b>Interpolated maximum</b>
Maximum measured above high end	100 mW forward power	163.8 V/m
Maximum measured above low end	100 mW forward power	160.4 V/m
Averaged maximum above arm	100 mW forward power	<b>162.1 V/m</b>

Uncertainty for E-field measurement: 12.8% (k=2)

## 3 Appendix

### 3.1 Antenna Parameters

<b>Frequency</b>	<b>Return Loss</b>	<b>Impedance</b>
800 MHz	17.1 dB	( 40.6. - j8.5 ) Ohm
<b>835 MHz</b>	<b>27.5 dB</b>	<b>( 51.1 + j4.1 ) Ohm</b>
900 MHz	17.2 dB	( 49.5 - j13.9 ) Ohm
950 MHz	18.7 dB	( 55.2 + j11.1 ) Ohm
960 MHz	14.0 dB	( 67.6 + j15.6 ) Ohm

### 3.2 Antenna Design and Handling

The calibration dipole has a symmetric geometry with a built-in two stub matching network, which leads to the enhanced bandwidth.


The dipole is built of standard semirigid coaxial cable. The internal matching line is open ended. The antenna is therefore open for DC signals.

Do not apply force to dipole arms, as they are liable to bend. The soldered connections near the feedpoint may be damaged. After excessive mechanical stress or overheating, check the impedance characteristics to ensure that the internal matching network is not affected.

After long term use with 40W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

### 3.3 Measurement Sheets

#### 3.3.1 Return Loss and Smith Chart



### 3.3.2 DASY4 H-field result

Date/Time: 27.04.2005 14:21:13

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: HAC-Dipole 835 MHz; Type: D835V3; Serial: 1032**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Air

Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>

Phantom section: H Dipole Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: H3DV6 - SN6065; ; Calibrated: 10.12.2004
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn901; Calibrated: 29.06.2004
- Phantom: HAC Phantom; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 149

### **H Scan 10mm above CD 835 MHz/Hearing Aid Compatibility Test (41x361x1):**

Measurement grid: dx=5mm, dy=5mm

Maximum value of Total field (slot averaged) = 0.451 A/m


Reference Value = 0.473 A/m; Power Drift = -0.01 dB

**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

H in A/m (Time averaged)      H in A/m (Slot averaged)

Grid 1	Grid 2	Grid 3
<b>0.365</b>	<b>0.397</b>	<b>0.380</b>
Grid 4	Grid 5	Grid 6
<b>0.415</b>	<b>0.451</b>	<b>0.433</b>

Grid 1	Grid 2	Grid 3
<b>0.365</b>	<b>0.397</b>	<b>0.380</b>
Grid 4	Grid 5	Grid 6
<b>0.415</b>	<b>0.451</b>	<b>0.433</b>



### 3.3.3 DASY4 E-Field result

Date/Time: 27.04.2005 14:55:54

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: HAC-Dipole 835 MHz; Type: D835V3; Serial: 1032**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Air

Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: E Dipole Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ER3DV6 - SN2336; ConvF(1, 1, 1); Calibrated: 20.01.2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn901; Calibrated: 29.06.2004
- Phantom: HAC Phantom; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 149

### **E Scan 10mm above CD 835 MHz/Hearing Aid Compatibility Test (41x361x1):**


Measurement grid: dx=5mm, dy=5mm

Maximum value of Total field (slot averaged) = 163.8 V/m

Reference Value = 102.7 V/m; Power Drift = -0.017 dB

**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

E in V/m (Time averaged)			E in V/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>156.6</b>	<b>160.4</b>	<b>153.8</b>	<b>156.6</b>	<b>160.4</b>	<b>153.8</b>
85.9	88.0	84.1	85.9	88.0	84.1
157.9	163.8	159.6	157.9	163.8	159.6



**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
**Zeughausstrasse 43, 8004 Zurich, Switzerland**

Client **Nokia TX**Certificate No: **CD1880V3-1025\_Jun05**

## **CALIBRATION CERTIFICATE**


Object **CD1880V3 - SN: 1025**Calibration procedure(s) **QA CAL-20.v3**  
**Calibration procedure for dipoles in air**Calibration date: **June 2, 2005**Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). All calibrations have been conducted at an environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&amp;TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	12-Oct-04 (METAS, No. 251-00412)	Oct-05
Power sensor HP 8481A	US37292783	12-Oct-04 (METAS, No. 251-00412)	Oct-05
20 dB Attenuator	SN: 5086 (20g)	10-Aug-04 (METAS, No 251-00402)	Aug-05
10 dB Attenuator	SN: 5047.2 (10r)	10-Aug-04 (METAS, No 251-00402)	Aug-05
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov-05
RF generator R&S SML-03	100698	27-Mar-02 (SPEAG, in house check Dec-03)	In house check: Dec-05
DAE4	SN: 901	29-Jun-04 (SPEAG, No. DAE4-901_Jun04)	Calibration, Jun-05
Probe ER3DV6	SN: 2336	20-Jan-05 (SPEAG, No. ER3-2336_Jan05)	Calibration, Jan-06
Probe H3DV6	SN: 6065	10-Dec-04 (SPEAG, No. H3-6065-Dec04)	Calibration, Dec-05

Calibrated by: Name **Mike Mell** Function **Laboratory Technician**

Signature 

Approved by: Name **Fin Bomholt** Function **Technical Director**

Signature 

Issued: June 13, 2005

## References

[1] ANSI-PC63.19-2001 (Draft 3.x, 2005)  
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.

## Methods Applied and Interpretation of Parameters:

- **Coordinate System:** y-axis is in the direction of the dipole arms. z-axis is from the basis of the antenna (mounted on the table) towards its feed point between the two dipole arms. x-axis is normal to the other axes. In coincidence with standard [1], the measurement planes (probe sensor center) are selected to be at a distance of 10 mm above the the top edge of the dipole arms.
- **Measurement Conditions:** Further details are available from the hardcopies at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated. The forward power to the dipole connector is set with a calibrated power meter connected and monitored with an auxiliary power meter connected to a directional coupler. While the dipole under test is connected, the forward power is adjusted to the same level.
- **Antenna Positioning:** The dipole is mounted on a HAC Test Arch phantom using the matching dipole positioner with the arms horizontal and the feeding cable coming from the floor. The measurements are performed in a shielded room with absorbers around the setup to reduce the reflections.  
It is verified before the mounting of the dipole under the Test Arch phantom, that its arms are perfectly in a line. It is installed on the HAC dipole positioner with its arms parallel below the dielectric reference wire and able to move elastically in vertical direction without changing its relative position to the top center of the Test Arch phantom. The vertical distance to the probe is adjusted after dipole mounting with a DASY4 Surface Check job. Before the measurement, the distance between phantom surface and probe tip is verified. The proper measurement distance is selected by choosing the matching section of the HAC Test Arch phantom with the proper device reference point (upper surface of the dipole) and the matching grid reference point (tip of the probe) considering the probe sensor offset. The vertical distance to the probe is essential for the accuracy.
- **Feed Point Impedance and Return Loss:** These parameters are measured using a HP 8753E Vector Network Analyzer. The impedance is specified at the SMA connector of the dipole. The influence of reflections was eliminating by applying the averaging function while moving the dipole in the air, at least 70cm away from any obstacles.
- **E-field distribution:** E field is measured in the x-y-plane with an isotropic ER3D-field probe with 100 mW forward power to the antenna feed point. In accordance with [1], the scan area is 20mm wide, its length exceeds the dipole arm length (180 or 90mm). The sensor center is 10 mm (in z) above the top of the dipole arms. Two 3D maxima are available near the end of the dipole arms. Assuming the dipole arms are perfectly in one line, the average of these two maxima (in subgrid 2 and subgrid 8) is determined to compensate for any non-parallelity to the measurement plane as well as the sensor displacement. The E-field value stated as calibration value represents the maximum of the interpolated 3D-E-field, 10mm above the dipole surface.
- **H-field distribution:** H-field is measured with an isotropic H-field probe with 100mW forward power to the antenna feed point, in the x-y-plane. The scan area and sensor distance is equivalent to the E-field scan. The maximum of the field is available at the center (subgrid 5) above the feed point. The H-field value stated as calibration value represents the maximum of the interpolated H-field, 10mm above the dipole surface at the feed point.

## 1 Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY4	V4.5 B31
<b>DASY PP Version</b>	SEMCAD	V1.8 B149
<b>Phantom</b>	HAC Test Arch	SD HAC P01 BA, #1002
<b>Distance Dipole Top - Probe Center</b>	10 mm	
<b>Scan resolution</b>	$dx, dy = 5 \text{ mm}$	area = 20 x 90 mm
<b>Frequency</b>	<b>1880 MHz <math>\pm 1 \text{ MHz}</math></b>	
<b>Forward power at dipole connector</b>	20.0 dBm = 100mW	
<b>Input power drift</b>	< 0.05 dB	

## 2 Maximum Field values

<b>H-field 10 mm above dipole surface</b>	condition	<b>interpolated maximum</b>
Maximum measured	100 mW forward power	<b>0.452 A/m</b>

Uncertainty for H-field measurement: 8.2% (k=2)

<b>E-field 10 mm above dipole surface</b>	condition	<b>interpolated maximum</b>
Maximum measured above high end	100 mW forward power	139.4 V/m
Maximum measured above low end	100 mW forward power	135.8 V/m
Averaged maximum above arm	100 mW forward power	<b>137.6 V/m</b>

Uncertainty for E-field measurement: 12.8% (k=2)

## 3 Appendix

### 3.1 Antenna Parameters

<b>Frequency</b>	<b>Return Loss</b>	<b>Impedance</b>
1710 MHz	19.9 dB	( 61.2 - j0.7 ) Ohm
<b>1880 MHz</b>	<b>20.9 dB</b>	<b>( 58.6 - j4.7 ) Ohm</b>
1900 MHz	21.7 dB	( 55.5 - j6.7 ) Ohm
1950 MHz	30.4 dB	( 49.0 - j2.8 ) Ohm
2000 MHz	21.0 dB	( 54.0 + j8.4 ) Ohm

### 3.2 Antenna Design and Handling

The calibration dipole has a symmetric geometry with a built-in two stub matching network, which leads to the enhanced bandwidth.


The dipole is built of standard semirigid coaxial cable. The internal matching line is open ended. The antenna is therefore open for DC signals.

Do not apply force to dipole arms, as they are liable to bend. The soldered connections near the feedpoint may be damaged. After excessive mechanical stress or overheating, check the impedance characteristics to ensure that the internal matching network is not affected.

After long term use with 40W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

### 3.3 Measurement Sheets

#### 3.3.1 Return Loss and Smith Chart



### 3.3.2 DASY4 H-field result

Date/Time: 6/2/2005 6:15:52 PM

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: HAC Dipole 1880 MHz; Type: CD1880V3; Serial: 1025**

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Air

Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>

Phantom section: H Dipole Section

DASY4 Configuration:

- Probe: H3DV6 - SN6065; Calibrated: 12/10/2004
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn901; Calibrated: 6/29/2004
- Phantom: HAC Test Arch; Type: SD HAC P01 BA; Serial: 1002
- Measurement SW: DASY4, V4.5 Build 31; Postprocessing SW: SEMCAD, V1.8 Build 149

### **H Scan 10mm above CD1880V3/Hearing Aid Compatibility Test (41x181x1):**


Measurement grid: dx=5mm, dy=5mm

Maximum value of Total field (slot averaged) = 0.452 A/m

Reference Value = 0.478 A/m; Power Drift = -0.034 dB

**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

H in A/m (Time averaged)			H in A/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
<b>0.391</b>	<b>0.425</b>	<b>0.408</b>	<b>0.391</b>	<b>0.425</b>	<b>0.408</b>
<b>0.419</b>	<b>0.452</b>	<b>0.437</b>	<b>0.419</b>	<b>0.452</b>	<b>0.437</b>
<b>0.372</b>	<b>0.401</b>	<b>0.389</b>	<b>0.372</b>	<b>0.401</b>	<b>0.389</b>



### 3.3.3 DASY4 E-Field result

Date/Time: 6/2/2005 2:45:27 PM

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: HAC Dipole 1880 MHz; Type: CD1880V3; Serial: 1025**

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Air

Medium parameters used:  $\sigma = 0 \text{ mho/m}$ ,  $\epsilon_r = 1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: E Dipole Section

DASY4 Configuration:

- Probe: ER3DV6 - SN2336; ConvF(1, 1, 1); Calibrated: 1/20/2005
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn901; Calibrated: 6/29/2004
- Phantom: HAC Test Arch; Type: SD HAC P01 BA; Serial: 1002
- Measurement SW: DASY4, V4.5 Build 31; Postprocessing SW: SEMCAD, V1.8 Build 149

### **E Scan 10mm above CD1880V3/Hearing Aid Compatibility Test (41x181x1):**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of Total field (slot averaged) = 139.4 V/m

Reference Value = 157.2 V/m; Power Drift = 0.013 dB

**Hearing Aid Near-Field Category: M2 (AWF 0 dB)**

E in V/m (Time averaged)			E in V/m (Slot averaged)		
Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
131.9	135.8	130.9	131.9	135.8	130.9
90.0	91.6	87.1	90.0	91.6	87.1
131.8	139.4	135.3	131.8	139.4	135.3

