

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-707_08.docx	Date of Report:	28-Feb-2011
Number of pages:	14	Customer's Contact person:	Bill Griffin
Testing laboratory:	TCC Nokia Salo Laboratory P.O.Box(86) Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Customer:	Nokia Corporation 12278 Scripps Summit Drive SAN DIEGO CA. 92131 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-707 / AC-Charger AC-10U / USB-Cable CA-101 / Headset WH-701		
FCC ID:	QMNRM-707	IC:	661X-RM707
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 3, December 2010) and RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			
	Sami Lehtonen, System Specialist, EMC		

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	20-Jan-2011
Testing completed	04-Feb-2011
The customer's contact person	Bill Griffin
Test Plan referred to	T:\Projects\RM-707\TestPlan\RS_testplan_RM-707.xls
Notes	-
Document name	T:\Projects\RM-707\EMC\FCC15C_RM-707_08.docx

1.1. EUT and Accessory Information

The EUT is a 9-band (GSM850/900/1800/1900) and WCDMA Band (I/II(1900)/IV(1700)/V(850)/VIII/) mobile phone with GPRS, EGPRS, HSDPA, HSUPA and WLAN and Bluetooth. Bluetooth and WLAN are tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-707	004402134050628	0100	-	020.027 PERF	15473
AC-Charger	AC-10U	3997910023090100784;0675474	-	-	-	15474
USB-Cable	CA-101	07306348391T1249270	-	-	-	15475
Headset	WH-701	14	0.2	0.4	0.1	14713

1.2. Summary of Test Results

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (4)	Conducted peak output power	NP
15.247(d)	A8.5	Band edge compliance of RF emissions	PASSED
15.247(d)	A8.5	Spurious RF conducted emissions	NP
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	NP
15.247(a)(2)	A8.2 (a)	6dB(bandwidth)	NP
15.247(e)	A8.2 (b)	Power spectral density	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.

CONTENTS

1. Summary for FCC Part 15C Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5)	4
2.2. Test method and limit	4
2.3. WLAN Test results	5
3. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)	8
3.1. Test method and limit	8
3.2. WLAN Test results	9
4. Test Equipment	13
4.1. Conducted measurements	13
4.2. Radiated measurements	13

2.3. WLAN Test results


Average (RBW: 1 MHz, VBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	Result
11 / 2462 (802.11n HT20 MCS 0)	41.79	PASSED
1 / 2412 (802.11n HT20 MCS 0)	42.38	PASSED
1 / 2412 (OFDM,PBSK,6)	40.2	PASSED
11 / 2462 (OFDM, PBSK,6)	40.44	PASSED
11 / 2462 (DSSS,QPSK,11)	35.52	PASSED
1 / 2412 (DSSS,QPSK,11)	37.24	PASSED


Peak (RBW: 1 MHz, VBW: 1 MHz)

Channel / f_c [MHz]	E [dB μ V/m]	Result
11 / 2462 (802.11n HT20 MCS 0)	60.83	PASSED
1 / 2412 (802.11n HT20 MCS 0)	59.38	PASSED
1 / 2412 (OFDM,PBSK,6)	56.37	PASSED
11 / 2462 (OFDM, PBSK,6)	54.89	PASSED
11 / 2462 (DSSS,QPSK,11)	47.41	PASSED
1 / 2412 (DSSS,QPSK,11)	48.19	PASSED


802.11n HT20 MCS 0 mode, modulation, Mbps data rate. Channel 11 / 2462 MHz




802.11n HT20 MCS 0 mode, modulation, Mbps data rate. Channel 1 / 2412 MHz




OFDM mode, PBSK modulation, 6 Mbps data rate. Channel 1 / 2412 MHz




OFDM mode, PBSK modulation, 6 Mbps data rate. Channel 11 / 2462 MHz



DSSS mode, QPSK modulation, 11 Mbps data rate. Channel 11 / 2462 MHz



DSSS mode, QPSK modulation, 11 Mbps data rate. Channel 1 / 2412 MHz



3. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-707, DUT 15473
Accessories with DUT numbers	AC-10U, DUT 15474 ; CA-101, DUT 15475 ; WH-701, DUT 14713
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 35 / 98.8
Date of measurements	04-Feb-2011
Measured by	Sami Lehtonen

3.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

3.2. WLAN Test results

3.2.1 WLAN DSSS mode and QPSK modulation, 11Mbit/s data rate

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4824.1	40.34	104.028	44.75	-4.41	VERTICAL	PASSED
7237.7	45.24	182.726	44.75	0.49	HORIZONTAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
4824.1	26.76	21.775	31.17	-4.41	VERTICAL	PASSED
7237.7	32.56	42.452	32.07	0.49	HORIZONTAL	PASSED

Channel 7 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
30.09	22.32	13.06	31.08	-8.76	HORIZONTAL	PASSED
30.15	22.29	13.011	31.09	-8.8	HORIZONTAL	PASSED
30.24	22.24	12.937	31.09	-8.85	HORIZONTAL	PASSED
30.27	22.18	12.853	31.04	-8.86	HORIZONTAL	PASSED
30.3	22.16	12.829	31.04	-8.88	HORIZONTAL	PASSED
30.41	22.1	12.741	31.04	-8.94	HORIZONTAL	PASSED
32.014	20.98	11.192	30.8	-9.82	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
10602.704	52.33	413.619	43.44	8.89	HORIZONTAL	PASSED
11276.955	52.06	400.913	43.18	8.88	HORIZONTAL	PASSED
17965.03	62.3	1303.317	41.82	20.48	HORIZONTAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB $\mu\text{V/m}$]	E [$\mu\text{V/m}$]	U _{RX} [dB μV]	A _{TOT} [dB]	Polarisation	Result
-----------------	-------------------------	-----------------------	-------------------------------------	-----------------------	--------------	--------

10602.704	38.85	87.609	29.96	8.89	HORIZONTAL	PASSED
11276.955	39.2	91.191	30.32	8.88	HORIZONTAL	PASSED
17965.03	49.41	295.325	28.93	20.48	HORIZONTAL	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4924.6	40.57	106.746	44.62	-4.05	HORIZONTAL	PASSED
7385.7	45.92	197.651	44.75	1.17	HORIZONTAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4924.6	27.69	24.233	31.74	-4.05	HORIZONTAL	PASSED
7385.7	32.99	44.627	31.82	1.17	HORIZONTAL	PASSED

3.2.2 WLAN OFDM mode and BPSK modulation, 6Mbit/s data rate

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4822.5	39.43	93.648	43.83	-4.4	VERTICAL	PASSED
7234.7	45.5	188.408	45.01	0.49	VERTICAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4822.5	26.83	21.958	31.23	-4.4	VERTICAL	PASSED
7234.7	32.6	42.633	32.11	0.49	VERTICAL	PASSED

Channel 7 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
30.12	22.22	12.915	31	-8.78	HORIZONTAL	PASSED
30.3	22.08	12.709	30.96	-8.88	HORIZONTAL	PASSED
30.32	22.11	12.753	31	-8.89	HORIZONTAL	PASSED
30.78	21.74	12.214	30.88	-9.14	HORIZONTAL	PASSED
31.05	21.51	11.893	30.8	-9.29	HORIZONTAL	PASSED
32.293	20.78	10.943	30.75	-9.97	HORIZONTAL	PASSED
32.919	20.44	10.521	30.75	-10.31	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
10994.088	51.71	384.99	42.44	9.27	VERTICAL	PASSED
11059.122	51.8	389.224	42.8	9	HORIZONTAL	PASSED
17988.174	62.99	1411.237	41.57	21.42	VERTICAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
10994.088	39.05	89.65	29.78	9.27	VERTICAL	PASSED
11059.122	39.15	90.646	30.15	9	HORIZONTAL	PASSED
17988.174	50.33	328.284	28.91	21.42	VERTICAL	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4922.5	40.43	105.015	44.49	-4.06	HORIZONTAL	PASSED
7385.6	46.05	200.655	44.88	1.17	HORIZONTAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4922.5	27.73	24.353	31.79	-4.06	HORIZONTAL	PASSED
7385.6	33.07	45.03	31.9	1.17	HORIZONTAL	PASSED

3.2.3 WLAN 802.11n HT20 MCS 0 mode

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4826	39.2	91.18	43.58	-4.38	HORIZONTAL	PASSED
7236.4	45.76	193.999	45.28	0.48	HORIZONTAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4826	26.87	22.042	31.25	-4.38	HORIZONTAL	PASSED
7236.4	32.64	42.835	32.16	0.48	HORIZONTAL	PASSED

Channel 7 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
30.09	22.28	13	31.04	-8.76	HORIZONTAL	PASSED
30.24	22.16	12.817	31.01	-8.85	HORIZONTAL	PASSED
30.35	22.06	12.669	30.97	-8.91	HORIZONTAL	PASSED
30.63	21.82	12.33	30.88	-9.06	HORIZONTAL	PASSED
30.63	21.86	12.388	30.92	-9.06	HORIZONTAL	PASSED
30.87	21.69	12.145	30.88	-9.19	HORIZONTAL	PASSED
30.884	21.64	12.077	30.84	-9.2	HORIZONTAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
10957.818	52.34	413.857	43.06	9.28	VERTICAL	PASSED
11160.223	51.38	370.595	42.44	8.94	HORIZONTAL	PASSED
17982.564	62.97	1406.857	41.7	21.27	VERTICAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
10957.818	39.33	92.534	30.05	9.28	VERTICAL	PASSED
11160.223	39.11	90.251	30.17	8.94	HORIZONTAL	PASSED
17982.564	50.17	322.626	28.9	21.27	VERTICAL	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4922.9	40.69	108.256	44.75	-4.06	VERTICAL	PASSED
7386.1	45.79	194.693	44.62	1.17	VERTICAL	PASSED

Average(RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4922.9	27.73	24.344	31.79	-4.06	VERTICAL	PASSED
7386.1	33.1	45.201	31.93	1.17	VERTICAL	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1759	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
1916	Communication Tester	CMTA84	R&S	15B
1986	GPS Antenna	AMHP10-15R/390	European Antenna	15C, 15B
1992	Signal Generator	83630B	Agilent	15C, 15B
2039	Power Supply	PL330QMD	Thurlby	15C, 15B
2060	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
2068	CDN	S1	NMP	15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
2156	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2206	Signal Generator	SMX	R&S	15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2352	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C
2359	Temperature Test Chamber	VT4002	Vötsch	22/24/27
2360	Serial Bus Converter	Serial 488A	IO Tech	22/24/27
2362	Power Supply	NGPX 70/5	R&S	22/24/27
2388	Bluetooth Tester	CBT	R&S	15B
2389	Signal Generator	SMJ 100A	R&S	15B
2390	Directional Coupler	DC2600	AR	-
6009	GPS Antenna	SA-700	Chronos	15C
6010	GPS Network amplifier	NLA20FPDC	GPS Networking, Inc	15C
6011	GPS signal Splitter	LDCBS1x4	GPS Networking, Inc	15C
6012	CDN	CDN USB/c	Teseq	-
6015	Receiver	ESI	R&S	22/24, 15C, 15B
6016	ESD gun	PESD 1610	HAEFELY	-
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B
6036	Data Logger	175-H2	Testo	22/24/27, 15C, 15B
6038	Data Logger	Testo 580	Testo	23/24/27, 15C, 15B
6039	USB Interface	5541765	Testo	23/24/27, 15C, 15B
2059	V-network	ESH3-Z6	R&S	-
6044	V-network	ESH3-Z6	R&S	-
6045	Power splitter	11667B	Agilent	23/24/27, 15C
6046	Attenuator 10dB	8493C	Agilent	23/24/27, 15C
6047	Attenuator 20dB	8493C	Agilent	23/24/27, 15C

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1917	Communication Tester	CMTA84	R&S	15B
1984	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C, 15B
1986	GPS Antenna	AMHP10-15R/390	European Antenna	15C, 15B
1988	Antenna	HL562	R&S	22/24/27, 15C, 15B
1989	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2009	Signal Generator	SMP 22	R&S	22/24/27, 15C, 15B
2027	CDN	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	CDN	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2029	Power Supply	PL330	Thurlby	22/24/27, 15C
2043	Band Reject Filter	WRCA824/849-0,2-6SS	Wainwright	22
2047	Band Reject Filter	WRCC1800/2000-0.2-10SS	Wainwright	24
2051	High Pass Filter	4HC1700-1-KK	R&S	22

Eq. No	Equipment	Type	Manufacturer	Used in
2109	Power Supply	PL330QMD	Thurlby	22/24/27, 15C, 15B
2116	Controller	EMCO 2090	ETS	22/24/27, 15C, 15B
2135	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2140	Antenna	EMCO93110B	EMCO	22/24/27, 15C
2142	Antenna	3146	EMCO	22/24/27, 15C
2150	High Pass Filter	F-15041	RLC	22/24/27, 15C
2156	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2176	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2188	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2348	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
2349	Computer Controller	GS-232B	Yaesu	22/24/27, 15C, 15B
2350	Preamplifier	AMF-6D-020180-29-20P	Miteq	22/24/27, 15C, 15B
2353	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
2357	Band Reject Filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	15C
2361	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	Euroshield	22/24/27, 15C, 15B
2364	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	24
2366	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2384	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	22
2388	Bluetooth Tester	CBT	R&S	15B
2389	Signal Generator	SMJ 100A	R&S	15B
2391	Band Reject Filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
6009	GPS Antenna	SA-700	Chronos	15C
6010	GPS Network amplifier	NLA20FPDC	GPS Networking, Inc	15C
6011	GPS signal Splitter	LDCBS1x4	GPS Networking, Inc	15C
6014	Substitute Calibration Cable	Sucoflex 104PB	Suhner	-
6017	Antenna	SBA 9113	Schwarzbeck	22 / 24 / 27
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B
-	RF immunity / Emission Software	EMC32	R&S	22/24/27, 15C, 15B
6037	Data Logger	175-H2	Testo	23/24/27, 15C, 15B
6038	Data Logger	Testo 580	Testo	23/24/27, 15C, 15B
6039	USB Interface	5541765	Testo	23/24/27, 15C, 15B