

TEST REPORT

Ref. Report No.

02-341-035-01

This test report only responds to the tested sample and shall not be reproduced except

Name and address of the applicant

Felio Group(M) Sdn. Bhd.
Lot 5, Jalan Gudang 16/9 Seksyen 16,
Shah Alam, 40200 Malaysia

Standard / Test regulation

FCC Part 15, Subpart C

Test result

Pass

Incoming date : October 01, 2002

Test date : October 07, 2002

Test item(s)

Security/Remote Control Transmitter
(Tire Pressure Monitoring System)

Model/type ref.

TPMS

Manufacturer

Felio Group(M) Sdn. Bhd.

Additional information

-Required Authorization : Certification
-FCC ID. : QN5XT400-T

-Note : Test report(Certification) of Receiver
portion of this System is issued on Ref.
Report No. 02-341-035-02.

Issue date : October 16, 2002

in full without written approval of the Korea Testing Laboratory.

Tested and reported by



Jeong-Min Kim , Senior Engineer

Reviewed by



Hee-Soo Kim , Telecommunication
Team Manager

**KOREA TESTING
LABORATORY**

TABLE OF CONTENTS

I. GENERAL INFORMATION.....	3
1. Grantee's Name and Mailing Address	
2. Manufacturer's Name and Mailing Address	
3. Equipment Descriptions	
4. Rules and Regulations	
5. Measuring Procedure	
6. Place of Measurement	
7. Date of Measurement	
□. GENERAL REQUIREMENTS OF THE EUT.....	4
1. Labeling Requirement (Section 15.19)	
2. Information to User (Sections 15.21)	
3. Special Accessories (Section 15.27)	
4. Compliant Conditions (Section 15.231)	
□. RADIATED EMISSION MEASUREMENT (Section 15.231(e)).....	6
1. Test Procedure	
2. Photograph of the test configuration	
3. Sample Calculation	
4. Measurement Data	
□. OCCUPIED BANDWIDTH MEASUREMENT (Section 15.231).....	10
□. TEST EQUIPMENTS USED FOR MEASUREMENT.....	11

□. GENERAL INFORMATION

1. Grantee's Name and
Mailing Address : Felio Group(M) Sdn. Bhd.
Lot 5, Jalan Gudang 16/9 Seksyen 16,
Shah Alam, 40200 Malaysia

2. Manufacturer's Name and
Mailing Address : Felio Group(M) Sdn. Bhd.
Lot 5, Jalan Gudang 16/9 Seksyen 16,
Shah Alam, 40200 Malaysia

3. Equipment Descriptions

3.1 Operating Frequency : 433.92 MHz
3.2 Type of Emission : Pulse Code Signal
3.3 Power Supply : DC 3.0 V(Lithium Cell Battery)

4. Rules and Regulations : FCC Part 15, Subpart C

5. Measuring Procedure : ANSI C63.4-1992

6. Place of Measurement : Absorber-lined Room (KTL)

7. Date of Measurement

7.1 Conducted Emission : Not Applicable
7.2 Radiated Emission : October 07, 2002

□. GENERAL REQUIREMENTS OF THE EUT**1. Labeling Requirement (Section 15.19)**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

1.1 Location of Label : User's Guide Manual

1.2 How Applied : Printed

2. Information to User (Section 15.21)

The following or similar statements were provided in the manual for user instruction.

Please refer page 2 of the attached manual for details.

CAUTION : Any changes or modifications in construction of this device which are not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. Special Accessories (Section 15.27)

3.1 Were the special Accessories provided? [] yes, [] no

3.2 If yes, details for the special accessories are as follows :

3.3 If yes, were the appropriate instructions provided on the first page of the text concerned with the installation of the device?

[] yes, [] no

3.4 Are these accessories provided of the type which can be readily obtained from multiple retail outlets ?

[] yes, [] no

And therefore does the manual specify what additional components or accessories are required to be used in order to comply with the Rules?

[] yes, [] no

4. Compliant Conditions (Section 15.231)

4.1 Was the EUT used for continuous transmissions, such as voice or video, and data transmission ?

[] yes, [] no

4.2 Was the EUT manually operated ?

[] yes, [] no

If yes, did the EUT employ a switch that would automatically deactivate the transmitter within not more than 5 seconds of being released ?

[] yes, [] no

4.3 Was the EUT automatically activated ?

[] yes, [] no

If yes, did the EUT cease transmission within 5 seconds after activation ?

[] yes, [] no

4.4 Was the EUT used for periodic transmissions at regular predetermined intervals ?

[] yes, [] no

4.5 The duration of each transmission : 38 ~ 45 ms

4.6 The silent period between transmission : 50 ~ 58 seconds

□. RADIATED EMISSION MEASUREMENT (Section 15.231(e))**1. Test Procedure****1.1 Preliminary Testing for Reference**

Preliminary testing was performed in a KTL absorber-lined room to determine the emission characteristics of the EUT. The EUT was placed on the wooden table which has dimensions of 0.8 meters in height, 1 meter in length and 1.5 meters in width. Receiving antenna (Biconical antenna : 30 to 300 MHz, Log-periodic antenna : 200 to 1000 MHz or Horn Antenna : 1 to 18 GHz) was placed at the distance of 1 meter from the EUT.

An attempt was made to maximize the emission level with the various configurations of the EUT. Emission levels from the EUT with various configurations were examined on a spectrum analyzer connected with a RF amplifier and graphed by a plotter.

1.2 Final Radiated Emission Test at an Absorber-Lined Room

The final measurement of radiated field strength was carried out in a KTL absorber-lined Room that was listed up at FCC according to the "Radiated Emissions Testing" procedure specified by ANSI C63.4.

Based on the test results in preliminary test, measurement was made in same test set up and configuration with 3 orthogonal planes which produced maximum emission level. Receiving antenna was installed at 3-meter distance from the EUT, and was connected to an EMI receiver or spectrum analyzer with a RF amplifier.

Turntable was rotated through 360 degrees and receiving antenna height was varied from 1 to 4 meters above the ground plane with horizontal and vertical polarization to read maximum emission level.

If necessary, the radiated emission measurements could be performed at a closer distance than specified distance to ensure higher accuracy and their results were extrapolated to the specified distance using an inverse linear distance extrapolation factor(20dB/decade) as per Section 15.31(f).

The maximum emission level from the EUT occurred in such configuration as shown in the following photograph.

2. Photograph of the test configuration



3. Sample Calculation

The emission level measured in decibels above one microvolt ($\text{dB } \square$) was converted into microvolt per meter (\square/m) as shown in following sample calculation.

For example :

Measured Value at	<u>433.99 MHz</u>	48.2 $\text{dB } \square$
+ Antenna Factor		16.1 dB/m
+ Cable Loss		4.1 dB
- Preamplifier		0.0 dB
- Distance Correction Factor *		0.0 dB
<hr/>		
= Radiated Emission		68.4 $\text{dB } \square/\text{m}$
		(= 2630.3 \square/m)

* Extrapolated from the measured distance to the specified distance by an inverse linear distance extrapolation.

4. Measurement Data

- Detect Mode and Resolution Bandwidth :

CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz for ranges below 1 GHz)

Average & Peak (6 dB Bandwidth: 1 MHz for ranges over 1 GHz)

- Measurement Distance : 3 Meter

Frequency (MHz)	* D.M.	* A.P.	Measured Value (dB□)	* A.F. + C.L. (dB/m)	* A.G. (dB)	* D.C.F. (dB)	Emission Level		Limit (dB□/m)	** Margin (dB)
							(dB□/m)	(□/m)		
433.99	Q	H	48.2	20.2	-	-	68.4	2630.3	72.9	- 4.5
867.98	Q	H	15.8	28.2	-	-	44.0	158.5	52.9	- 8.9
1301.97	A	H	20.5	27.0	-	-	47.5	237.1	52.9	- 5.4
1301.97	P	H	31.0	27.0	-	-	58.0	794.3	72.9	- 14.9
1735.88	A	H	< 10.0	28.9	-	-	<38.9	< 88.1	52.9	< - 14.0
1735.88	P	H	< 20.0	28.9	-	-	<48.9	< 278.6	72.9	< - 24.0
-	-	-	-	-	-	-	-	-	-	-

Note

The upper frequency range of this test was 5 GHz. The observed EMI Test Receiver's noise floor level was 10.0 dB□ and 20.0 dB□ with respect to average and peak mode respectively. And all other emissions not reported on data were more than 20 dB below the permitted level.

* D.M. : Detect Mode (P : Peak, Q : Quasi-Peak, A : Average)

A.P. : Antenna Polarization (H : Horizontal, V : Vertical)

A.F. : Antenna Factor

C.L. : Cable Loss

A.G. : Amplifier Gain

D.C.F. : Distance Correction Factor

< : Less than

** Margin (dB) = Emission Level (dB) - Limit (dB)


Note ;

(1) Fundamental emissions from the intentional radiators were not located within any of frequency bands described in section 15.205(a) listed below ;

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.1775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-
23.12			
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	
13.36-13.41			

The field strength of emissions appearing within above frequency bands did not exceed the limits shown in section 15.209. At frequency equal to or less than 1000 MHz, compliance with the limits section 15.209 was demonstrated using measurement employing a CISPR quasi-peak detector. Above 1000 MHz, demonstrated based on the average value of the measured emissions.

- (2) If the intentional radiator was operated under the radiated emission limits of the general requirements of section 15.209, it's fundamental emissions were not located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz, 470-860 MHz.
- (3) The level of any unwanted emissions from an intentional radiator did not exceed the level of the fundamental emission.
- (4) Radiated and spurious emissions were checked from 30 MHz to 5 GHz. And all other emissions not reported on data were more than 20 dB below the permitted level.



□. TEST EQUIPMENT USED FOR MEASUREMENTS

<u>Equipment</u>	<u>Model No.</u>	<u>Manufacturer</u>	<u>Serial No.</u>	<u>Effective Cal. Duration</u>
[x] EMI Receiver (20 MHz-1 GHz)	ESVS30	R & S	830516/002	06/13/02-06/13/03
[x] EMI Receiver (20 Hz-7 GHz)	ESI	R & S	835571/004	09/05/02-09/05/03
[x] Spectrum Analyzer (9 kHz-26.5 GHz)	8563A	H. P.	3222A02069	03/27/02-03/27/03
[x] Spectrum Analyzer (100 Hz-22 GHz)	8566B	H. P.	3014A07057	05/26/02-05/26/03
[x] Quasi-Peak Adapter (10 kHz-1 GHz)	85650A	H. P.	3107A01511	05/26/02-05/26/03
[x] RF-Preselector (20 Hz-2 GHz)	85685A	H. P.	3010A01181	05/26/02-05/26/03
[] Test Receiver (9 kHz-30 MHz)	ESH3	R & S	860905/001	06/13/02-06/13/03
[x] Pre-Amplifier (0.1-3000 MHz, 30 dB)	8347A	H. P.	2834A00543	05/26/02-05/26/03
[x] Pre-Amplifier (1-26.5 GHz, 35 dB)	8449B	H. P.	3008A00302	05/26/02-05/26/03
[] LISN(50 Ω, 50 μH) (10 kHz-100 MHz)	3825/2	EMCO	9010-1710	05/26/02-05/26/03
[x] Plotter	7470A	H. P.	3104A21292	-
[] Tuned Dipole Ant. (30 MHz-300 MHz)	VHA 9103	Schwarzbeck	-	*
[] Tuned Dipole Ant. (300 MHz-1 GHz)	UHA 9105	Schwarzbeck	-	*
[x] Biconical Ant. (30 MHz-300 MHz)	BBA 9106	Schwarzbeck	-	*
[x] Log Periodic Ant. (200 MHz-1 GHz)	3146	EMCO	-	*
[x] Horn Ant. (1 GHz-18 GHz)	3115	EMCO	-	*
[] Active Loop Ant. (9 kHz-30 MHz)	6502	EMCO	2532	*
[] DC Power Supply	6260B	H.P.	1145A04822	-
[] Shielded Room (5.0 m x 4.5 m)	-	SIN-MYUNG	-	-

* Each set of antennas has been calibrated to ensure correlation with ANSI C63.5 standard. The calibration of antennas is traceable to Korea Standard Research Institute(KSRI).