

产品编码(Product code)	名称(Name)	规格说明 (Specification)	物料号 (Material code)	客户名称 (Client name)		
001-100101	发射成品咪 Transmitter	STVD-1001USA (TX)	19-27S100100020	雅士 Arts		
物料编号(Material Number)	物料名称(Material Name)	规格说明 (Specification)	单位(Unit)	需求量 (Quantity)	生产车间 (Workshop)	备注说明 (Remark)
101-08050D1121	三极管, Audion	8050D	PCS	1000	2F	Q2
101-0KSP102121	三极管, Audion	KSP10	PCS	1000	2F	Q5
101-S9014C4211	三极管, Audion	S9014C	PCS	1000	2F	Q1
101-S9018H2111	三极管, Audion	S9018H	PCS	2000	2F	Q3,Q4
102-1091110121	稳压二极管, Stable voltage Diode	9.1 V	PCS	1000	2F	D4
102-3IN4148121	二极管, Diode	IN4148	PCS	2000	2F	D2,D3
102-3IN5819121	二极管, Diode	IN5819	PCS	1000	2F	D5
103-0103201122	灯仔 (红色), LED(red)	3 mm	PCS	1000	2F	D1
104-SC88030021	IC/集成块	SC8803(SMD)	PCS	1000	2F	IC1
106-0001040110	咪芯, MIC	T-104	PCS	1000	2F	
107-1524707121	电阻, Resistance	47欧 1/8W $\pm$ 10%	PCS	1000	2F	R25
107-1535607121	电阻, Resistance	560欧 1/8W $\pm$ 10%	PCS	2000	2F	R18,R24
107-1541007121	电阻, Resistance	1K 1/8W $\pm$ 10%	PCS	1000	2F	R16
107-1544707121	电阻, Resistance	4.7 K 1/8W $\pm$ 10%	PCS	4000	2F	R7,R13,R19,R21
107-1546807121	电阻, Resistance	6.8 K 1/8W $\pm$ 10%	PCS	1000	2F	R23

107-1551207121	电阻, Resistance	12 K 1/8W $\pm$ 10%	PCS	1000	2F	R22
107-1551507121	电阻, Resistance	15 K 1/8W $\pm$ 10%	PCS	1000	2F	R14
107-1551807121	电阻, Resistance	18 K 1/8W $\pm$ 10%	PCS	1000	2F	R17
107-1552207121	电阻, Resistance	22 K 1/8W $\pm$ 10%	PCS	1000	2F	R10
107-1552707121	电阻, Resistance	27 K 1/8W $\pm$ 10%	PCS	1000	2F	R15
107-1553307121	电阻, Resistance	33 K 1/8W $\pm$ 10%	PCS	1000	2F	R9
107-1553907121	电阻, Resistance	39 K 1/8W $\pm$ 10%	PCS	1000	2F	R12
107-1554707121	电阻, Resistance	47 K 1/8W $\pm$ 10%	PCS	1000	2F	R20
107-1563907121	电阻, Resistance	390 K 1/8W $\pm$ 10%	PCS	1000	2F	R8
109-1230930121	瓷片电容NPO, Ceramic Capacitance	3 PF $\pm$ 5%	PCS	1000	2F	C28
109-1310930121	瓷片电容NPO, Ceramic Capacitance	10 PF $\pm$ 5%	PCS	1000	2F	C27
109-1315930121	瓷片电容NPO, Ceramic Capacitance	15 PF $\pm$ 5%	PCS	4000	2F	C12,C25,C 29,C32
109-1320930121	瓷片电容NPO, Ceramic Capacitance	20 PF $\pm$ 5%	PCS	2000	2F	C5,C6
109-1322930121	瓷片电容NPO, Ceramic Capacitance	22 PF $\pm$ 5%	PCS	1000	2F	C13
109-1330930121	瓷片电容NPO, Ceramic Capacitance	30 PF $\pm$ 5%	PCS	1000	2F	C17
109-1339930121	瓷片电容NPO, Ceramic Capacitance	39 PF $\pm$ 5%	PCS	1000	2F	C21
109-1347930121	瓷片电容NPO, Ceramic Capacitance	47 PF $\pm$ 5%	PCS	1000	2F	C30
109-1350930121	瓷片电容NPO, Ceramic Capacitance	50 PF $\pm$ 5%	PCS	2000	2F	C14,C23

109-2510950121	瓷片电容NPO, Ceramic Capacitance	1000 PF (简 称102P) ±20%	PCS	7000	2F	C18,C22,C 24,C26,C3 1,C33,C34,
109-2522950121	瓷片电容NPO, Ceramic Capacitance	2200 PF (简 称222P) ±20%	PCS	1000	2F	C2
109-2610950121	瓷片电容NPO, Ceramic Capacitance	10000 PF (简 称103P) ±20%	PCS	5000	2F	C10,C11,C 19,C36,C3 7
109-2710950121	瓷片电容NPO, Ceramic Capacitance	100000 PF (简 称104) 0.1uF ±20%	PCS	2000	2F	C15,C16
110-1410A50321	电解电容, electrolytic Capacitance	1 uF 50V 4 X 7 mm ±20%	PCS	1000	2F	C7
110-1447A50321	电解电容, electrolytic Capacitance	4.7 uF 50V 4 X 7 mm ±20%	PCS	3000	2F	C1,C3,C9
110-1610650421	电解电容, electrolytic Capacitance	100 uF 10V 5 X 7 mm ±20%	PCS	1000	2F	C8
112-01C1711711	晶体, Oscillator	T171.105M 49/T	PCS	1000	2F	X1
114-1222052432	色环电感, Color Code Inductor	2.2 uH 4 X 3 mm ±5%	PCS	2000	2F	L7,L8
114-2130335201	空心电感/顺绕 Hollow Inductor	SLRO-3.5T X 3.0 X 0.65	PCS	3000	2F	L3,L5,L6
115-7140120031	中周 107&112, Tr.Transistor	7 mm -IFT- 2Ts: 4Ts (TX)	PCS	1000	2F	L1
115-9025002132	可调电感, Variable Inductor	2T5 (磁芯: 3.2 X 5mm)	PCS	2000	2F	L2,L4
116-B020332061	垂直柄滑动开关, Switch	#988 (TX)	PCS	1000	2F	STVG988A (TX)
118-1102540006	线仔 (黑色), Cable(Black)	UL1007 AWG28 (3+48+3mm)	PCS	1000	2F	MIC"-TO PCB
118-1102540026	线仔 (红色), Cable(Red)	UL1007 AWG28 (3+48+3mm)	PCS	1000	2F	MIC"+TO PCB
119-2999011021	PCB (机板)	G999 TX	PCS	1000	2F	STVG999(TX)

Tune Up procedure

1. When adjusting the RF power at manufacturing, just turn L2, L4

2. Adjust oscillator X1 and Tr. Transistor L1 for proper Transmitter frequency