

2. Photograph for the test configuration



3. Sample Calculation


The emission level measured in decibels above one microvolt (dB μ) was converted into microvolt (μ) as shown in following sample calculation.

For example :

| | | | |
|----------------------|----------|---------|----------------|
| Measured Value at | 0.16 MHz | 47.6 dB | @ average mode |
| + Cable Losses * | | 0.0 dB | |
| <hr/> | | | |
| = Conducted Emission | | 47.6 dB | |

* In case of RG214/ RF cable 15 Ft, the loss is about 0.17 dB at the frequency of 30 MHz which is negligible.

2. Photograph for the test configuration



3. Sample Calculation

The emission level measured in decibels above one microvolt (dB μ V) was converted into microvolt per meter (μ V/m) as shown in following sample calculation.

For example :

| | | |
|-------------------|------------------------------|----------------------|
| Measured Value at | <u>436.6MHz</u> | 20.9dB μ V/m |
| + | Antenna Factor | 16.1 dB |
| + | Cable Loss | 4.0 dB |
| | Preamplifier | 0.0 dB |
| | Distance Correction Factor * | 0.0 dB |
| = | Radiated Emission | 41.0 dB μ V/m |
| | | (= 112.2 μ V/m) |

* Extrapolated from the measured distance to the specified distance by an inverse linear distance extrapolation.