

Nemko Test Report: 4L0041RUS1

Applicant: Sychip, Inc.
2805 North Dallas Tollway
Suite 400
Plano, TX 75093

Equipment Under Test: WLAN6090SD
(E.U.T.)

In Accordance With: **FCC Part 15, Subpart C, 15.247**
Direct Sequence Spread Spectrum Transmitters

Tested By: Nemko Dallas Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

Authorized By: 

Tom Tidwell, Frontline Manager

Date: 4/27/04

Table of Contents

Section 1. Summary of Test Results	3
Section 2. Equipment Under Test (E.U.T.).....	5
Section 3. Powerline Conducted Emissions	8
Section 4. Minimum 6 dB Bandwidth	11
Section 5. Maximum Peak Output Power	15
Section 6. RF Exposure	16
Section 7. Spurious Emissions (conducted).....	17
Section 8. Spurious Emissions (radiated)	22
Section 9. Peak Power Spectral Density.....	28
Section 10. Test Equipment List.....	32
ANNEX A - TEST DETAILS.....	33
ANNEX B - TEST DIAGRAMS.....	40

Section 1. Summary of Test Results

Manufacturer: Sychip, Inc.

Model No.: WLAN6090SD

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C, Paragraph 15.247 for Direct Sequence Spread Spectrum devices. Radiated tests were conducted in accordance with ANSI C63.4-1992. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

<input checked="" type="checkbox"/>	New Submission	<input type="checkbox"/>	Production Unit
<input type="checkbox"/>	Class II Permissive Change	<input checked="" type="checkbox"/>	Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE. NONE
See "Summary of Test Data".



NVLAP LAB CODE: 100426-0

Nemko Dallas Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Dallas Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Summary Of Test Data

NAME OF TEST	PARA. NO.	SPEC.	RESULT
Powerline Conducted Emissions	15.207(a)	48 dB?V	Complies
Minimum 6 dB Bandwidth	15.247(a)(2)	>500 kHz	Complies
Maximum Peak Power Output	15.247(b)(1)	<1 Watt	Complies
Spurious Emissions (Antenna Conducted)	15.247(c)	-20 dBc/100kHz	Complies
Spurious Emissions (Restricted Bands)	15.247(c)	< 74 dBuV/m Peak < 54 dBuV/m Avg	Complies
Peak Power Spectral Density	15.247(d)	+8 dBm/3kHz	Complies

Footnotes:

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 2. Equipment Under Test (E.U.T.)

General Equipment Information

Frequency Band: 902 – 928 MHz
 2400 – 2483.5 MHz
 5725 – 5850 MHz

Channel Spacing: 5 MHz

User Frequency Adjustment: Software controlled


Description of EUT

The WLAN6090SD is an SDIO card with an 802.11b radio integrated for wireless LAN communication. It is designed for use in PDA type devices. The radio has an integral antenna.

All testing was performed at 11 Mbps as this was found to be the worst-case emission configuration. Emission levels were checked at 1 Mbps, 2 Mbps, and 5.5 Mbps as well and found to be the same or less than emission levels in 11 Mbps mode. A software test mode was used to operate the equipment in the required channels and at the required power levels.

EMC testing was performed with the device installed in a PDA (Compaq iPAQ 3955, s/n. 4G29KUL190MX)

Testing was performed with fully charged batteries in the host device.

System Diagram

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)

REPORT NO.: [4L0041RUS1](#)

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 3. Powerline Conducted Emissions

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
TESTED BY: Arturo Ruvalcaba	DATE: 2/12/04

Test Results: Complies.

Measurement Data: See attached plots.

Measurement Uncertainty: +/- 1.7 dB

Test Data – Powerline Conducted Emissions



NEMKO Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Conducted Emissions
Powerline Voltage Measurement

Complete X Job # : 4L0041E Test # : CEPV-01
Preliminary _____ Page 1 of 1

Client Name : SyChip, Inc.
EUT Name : SDIO 802.11b Radio
EUT Model # : WLAN6090SD
EUT Part # : N/A
EUT Serial # : N/A
EUT Config. : Installed in PDA
Tx Full Power
Specification : CFR 47 Part 15 Subpart C, 15.207 Reference : 15.247
Transducer # : 1258 Temp. (deg. C) : 21 Date : 02/12/04
HP Filter # : 1433 Humidity (%) : 38 Time : 13:10
Cable 1 # : 1988 EUT Voltage : 115VAC Staff : Art Ruvalcaba
Cable 2 # : 1998 EUT Frequency : 60Hz Location : Lab 2
Detector 1 # : 785 Peak Bandwidth: 10kHz Photo ID: 4L0041E CEPV-01
Detector 2 # : NA QP Bandwidth 10kHz
Limiter # : NA Avg. Bandwidth 10kHz

Meas. Freq. (MHz)	EUT Test Point	Detector Type (P, QP, A)	Limit Type (QP, A)	Meter Reading (dBuV)	Path Loss (dB)	Transducer Factor (dB)	Corrected Reading (dBuV)	Spec.limit (dBuV)		CR/SL Diff. (dB)	Pass Fail Unc.	Comment
								Q.P.	Avg.			
0.161	N	P	A	45.0	0	0	45.0	65.41	55.412	-10.4	Pass	
0.321	N	P	A	34.2	0	0	34.2	59.68	49.681	-15.5	Pass	
0.48	N	P	A	28.9	0	0	28.9	56.34	46.339	-17.4	Pass	
0.669	N	P	A	36.6	0	0	36.6	56	46	-9.4	Pass	
1.14	N	P	A	36.7	0	0	36.7	56	46	-9.3	Pass	
5	N	P	A	36.0	0	0	36.0	60	50	-14.0	Pass	
0.189	H	P	A	43.0	0	0	43.0	64.08	54.081	-11.1	Pass	
0.384	H	P	A	37.8	0	0	37.8	58.19	48.193	-10.4	Pass	
0.492	H	P	A	31.8	0	0	31.8	56.13	46.134	-14.4	Pass	
0.658	H	P	A	35.8	0	0	35.8	56	46	-10.2	Pass	
2.3	H	P	A	33.5	0	0	33.5	56	46	-12.5	Pass	
5	H	P	A	36.1	0	0	36.1	60	50	-13.9	Pass	
												Scanned .150-30MHz

..\EMCShare\AUTOMATE\DATASHTS\CEP_Voltage Rev C.xls Document Control #EMC DS EM COND VOLT

Photos – Powerline Conducted Emissions

Front



Side



Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 4. Minimum 6 dB Bandwidth

NAME OF TEST: Minimum 6 dB Bandwidth	PARA. NO.: 15.247(a)(2)
TESTED BY: David Light	DATE: 2/19/04

Test Results: Complies.

Measurement Data: See 6 dB BW plot

Measured 6 dB bandwidth: 10.17 MHz
Channel Separation: 5 MHz

Equipment Used: 1464-1463-1621

Measurement Uncertainty: +/- 1×10^{-7} ppm

Temperature: 22 °C

Relative Humidity: 40 %

EQUIPMENT: [WLAN6090SD](#)REPORT NO.: [4L0041RUS1](#)


Test Data – Occupied Bandwidth



Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667


Data Plot		Occupied Bandwidth			
Page 1 of 6					
Job No.:	4L0041R	Date:	2/19/2004	Complete	<input checked="" type="checkbox"/>
Specification:	15.247	Temperature(°C):	22	Preliminary:	<input type="checkbox"/>
Tested By:	David Light	Relative Humidity(%)	40		
E.U.T.:	WLAN6090SD				
Configuration:	TX FULL POWER				
Sample Number:	1	RBW:	Refer to plots		
Location:	Lab 2	VBW:	Refer to plots	Measurement	
Detector Type:	Peak			Distance:	NA m
Test Equipment Used					
Antenna:	Directional Coupler:				
Pre-Amp:	Cable #1: 1621				
Filter:	Cable #2:				
Receiver:	Cable #3:				
Attenuator #1	Cable #4:				
Attenuator #2:	Mixer:				
Additional equipment used:					
Measurement Uncertainty: +/-1.7 dB					
<p>ATTEN 20dB ΔMKR - .67dB</p> <p>RL 20.8dBm 10dB/ 10.17MHz</p> <p>CENTER 2.41200GHz SPAN 50.00MHz</p> <p>*RBW 100kHz VBW 100kHz SWP 50.0ms</p>					
Notes:	6 dB BW Channel 1				

EQUIPMENT: [WLAN6090SD](#)**REPORT NO.:** [4L0041RUS1](#)**Test Data – Occupied Bandwidth****Nemko Dallas, Inc.****Dallas Headquarters:**
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

EQUIPMENT: WLAN6090SDREPORT NO.: 4L0041RUS1**Test Data – Occupied Bandwidth**

Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



Section 5. Maximum Peak Output Power

NAME OF TEST: Maximum Peak Output power PARA. NO.: 15.247(b)(1)

TESTED BY: David Light DATE: 2/19/04

Test Results: Complies.**Measurement Data:****Antennas:** Integral (3dBi max gain)

Frequency MHz	Type	Conducted Power (dBm)	Gain (dBi)	E.I.R.P. (dBm)
2412	Integral	15	3	18
2437	Integral	15	3	18
2462	Integral	15	3	18

Peak power output at antenna port(dBm): 18 dBm / 63.1 mW

All measurements made with fully charged batteries.

Equipment Used: 1029-1030Measurement Uncertainty: +/- 0.7 dB

Temperature: 22 °C

Relative Humidity: 40 %

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 6. RF Exposure

NAME OF TEST: RF Exposure	PARA. NO.: 15.247(b)(4)
TESTED BY:	DATE:

Test Results: Complies.

Measurement Data:

Please refer to SAR report.

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 7. Spurious Emissions (conducted)

NAME OF TEST: Spurious Emissions (conducted)	PARA. NO.: 15.247(c)
--	----------------------

TESTED BY: David Light	DATE: 2/19/04
------------------------	---------------

Test Results: Complies.

Measurement Data: See attached plots.

EQUIPMENT: [WLAN6090SD](#)REPORT NO.: [4L0041RUS1](#)

Test Data – Spurious Emissions at Antenna Port



Nemko Dallas, Inc.


Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Data Plot		Spurious Emissions at Antenna Terminals	
Page 1 of 6		Complete <input checked="" type="checkbox"/>	Preliminary <input type="checkbox"/>
Job No.:	4L0041R	Date:	2/19/2004
Specification:	15.247	Temperature(°C):	22
Tested By:	David Light	Relative Humidity(%):	40
E.U.T.:	WLAN6090SD		
Configuration:	TX FULL POWER		
Sample Number:	1	RBW:	Refer to plots
Location:	Lab 2	VBW:	Refer to plots
Detector Type:	Peak	Measurement	Distance: NA m
Test Equipment Used			
Antenna:	Directional Coupler:		
Pre-Amp:	Cable #1: 1621		
Filter:	Cable #2:		
Receiver:	Cable #3: 1464		
Attenuator #1	Cable #4: 1469		
Attenuator #2:	Mixer:		
Additional equipment used:			
Measurement Uncertainty: +/-1.7 dB			
Notes:	Channel 1 Display line = -20 dBc		

Test Data – Spurious Emissions at Antenna Port

Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Test Data – Spurious Emissions at Antenna Port



Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Data Plot **Spurious Emissions at Antenna Terminals**

Page 3 of 6

Job No.: 41.0041R Date: 2/19/2004

Specification: 15.247 Temperature(°C): 22

Tested By: David Light Relative Humidity(%): 40

E.U.T.: WLAN6090SD

Configuration: TX FULL POWER

ATTEN 20dB
RL 20.8dBm 10dB/
MKR 4.30dBm
2.40GHz

DISPLAY LINE
-15.7 dBm

D
R

START 30MHz STOP 25.00GHz
*RBW 100kHz VBW 100kHz SWP 6.30sec

Notes: Channel 6

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)


REPORT NO.: [4L0041RUS1](#)

Test Data – Spurious Emissions at Antenna Port



Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 8. Spurious Emissions (radiated)

NAME OF TEST: Radiated Spurious Emissions	PARA. NO.: 15.247 (c)
TESTED BY: David Light	DATE: 2/19/04

Test Results: Complies.

Measurement Data: See attached table.

Note – The unit was tested on three orthogonal axis'.

Test Data – Radiated Spurious Emissions (Restricted Bands of Operation)



Nemko Dallas, Inc.

Dallas Headquarters:

 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

<u>Radiated Emissions</u>								
Page 1 of 2								
Job No.:	4L0041R	Date: 2/19/2004						
Specification:	15.15.247/15.205	Temperature(°C): 22						
Tested By:	David Light	Relative Humidity(%) 40						
E.U.T.:	WLAN6090SD							
Configuration:	TX FULL POWER - LYING ON SIDE (WORST CASE)							
Sample Number:	1							
Location:	AC 3	RBW: 1 MHz						
Detector Type:	Peak	VBW: 1 MHz						
<u>Test Equipment Used</u>								
Antenna:	1304	Directional Coupler: #N/A						
Pre-Amp:	1016	Cable #1: 1484						
Filter:	1482	Cable #2: 1485						
Receiver:	1464	Cable #3: #N/A						
Attenuator #1	#N/A	Cable #4: #N/A						
Attenuator #2:	#N/A	Mixer: #N/A						
Measurement Uncertainty:	+/-3.7 dB							
The device was tested on 3 axis' with the worst case being reported.								
Frequency (GHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Comment
								Channel 11
2483.5	29.5	28.2	3.1	0.0	60.8	74	-13.2	V - Peak
2483.5	20.5	28.2	3.1	0.0	51.8	54	-2.2	V - Avg
4924.0	46.8	33.9	4.3	32.7	52.3	54	-1.7	V - Peak
7386.0	42	36.3	5.3	32.8	50.8	54	-3.2	V - Peak
12310.0	45	39.9	7.3	34.4	57.8	74	-16.2	V - Peak
12310.0	33.7	39.9	7.3	34.4	46.5	54	-7.5	V - Avg
2483.5	31.5	28.2	3.1	0.0	62.8	74	-11.2	H - Peak
2483.5	21	28.2	3.1	0.0	52.3	54	-1.7	H - Avg
4924.0	46.2	33.9	4.3	32.7	51.7	54	-2.3	H - Peak
7386.0	42	36.3	5.3	32.8	50.8	54	-3.2	H - Peak
12310.0	43.5	39.9	7.3	34.4	56.3	74	-17.7	H - Peak
12310.0	33.3	39.9	7.3	34.4	46.1	54	-7.9	H - AHg
								Channel 6
Notes:								

EQUIPMENT: [WLAN6090SD](#)REPORT NO.: [4L0041RUS1](#)

Test Data – Radiated Spurious Emissions (Restricted Bands of Operation)



Nemko Dallas, Inc.

Dallas Headquarters:

 802 N. Kealy
 Lewisville, TX 75057
 Tel: (972) 436-9600
 Fax: (972) 436-2667

Radiated Spurious Emissions								
Page <u>2</u> of <u>2</u>		Continuation Page						
Job No.:	4L0041R	Date: 2/20/2004						
Specification:	15.247/15.205	Temperature(°F): <u>22</u>						
Tested By:	#N/A	Relative Humidity(%) <u>40</u>						
E.U.T.:	WLAN6090SD							
Configuration:	TX FULL POWER - LYING ON SIDE (WORST CASE)							
Frequency (GHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Comment
								Channel 1
4824.0	44.2	33.9	4.3	32.7	49.7	54	-4.3	H - Peak
7236.0	42	36.3	5.3	32.8	50.8	54	-3.2	H - Peak
12060.0	44.2	39.9	7.3	34.4	57.0	74	-17.0	H - Peak
12060.0	33.7	39.9	7.3	34.4	46.5	54	-7.5	H - AHg
4824.0	44.7	33.9	4.3	32.7	50.2	54	-3.8	V - Peak
7236.0	41.7	36.3	5.3	32.8	50.5	54	-3.5	V - Peak
12060.0	44.2	39.9	7.3	34.4	57.0	74	-17.0	V - Peak
12060.0	33.7	39.9	7.3	34.4	46.5	54	-7.5	V - Avg
								Channel 6
4874.0	43.8	33.9	4.3	32.7	49.3	54	-4.7	H - Peak
7311.0	42.7	36.3	5.3	32.8	51.5	54	-2.5	H - Peak
12185.0	44.2	39.9	7.3	34.4	57.0	74	-17.0	H - Peak
12185.0	33.3	39.9	7.3	34.4	46.1	54	-7.9	H - AHg
4874.0	45.5	33.9	4.3	32.7	51.0	54	-3.0	V - Peak
7311.0	42.2	36.3	5.3	32.8	51.0	54	-3.0	V - Peak
12185.0	44.8	39.9	7.3	34.4	57.6	74	-16.4	V - Peak
12185.0	33.5	39.9	7.3	34.4	46.3	54	-7.7	V - Avg
Notes:								


Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)

REPORT NO.: [4L0041RUS1](#)

Setup Photos



Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)

REPORT NO.: [4L0041RUS1](#)

Setup Photos




Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Setup Photos (Worst Case)



Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

Section 9. Peak Power Spectral Density

NAME OF TEST: Peak Power Spectral Density	PARA. NO.: 15.247(d)
TESTED BY: David Light	DATE: 2/19/04

Test Results: Complies.

Measurement Data: See attached plots.

EQUIPMENT: [WLAN6090SD](#)REPORT NO.: [4L0041RUS1](#)

Test Data – Peak Power Spectral Density



Nemko Dallas, Inc.


Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Data Plot		Peak Power Spectral Density			
Page 1 of 6				Complete <input checked="" type="checkbox"/>	
Job No.:	4L0041R	Date:	2/19/2004	Preliminary:	<input type="checkbox"/>
Specification:	15.247	Temperature(°C):	22		
Tested By:	David Light	Relative Humidity(%):	40		
E.U.T.:	WLAN6090SD				
Configuration:	TX FULL POWER				
Sample Number:	1				
Location:	Lab 2	RBW:	Refer to plots	Measurement	
Detector Type:	Peak	VBW:	Refer to plots	Distance: <u>NA</u> m	
Test Equipment Used					
Antenna:			Directional Coupler:		
Pre-Amp:			Cable #1:	1621	
Filter:			Cable #2:		
Receiver:	1464		Cable #3:		
Attenuator #1	1469		Cable #4:		
Attenuator #2:			Mixer:		
Additional equipment used:					
Measurement Uncertainty: <u>+/-1.7 dB</u>					
ATTEN 20dB RL 20.8dBm		10dB/	MKR -10.03dBm 2.411217GHz		
CENTER 2.412000GHz SPAN 5.000MHz *RBW 3.0kHz VBW 3.0kHz *SWP 1.7ksec					
Notes:	<u>Channel 1</u>				

Test Data – Peak Power Spectral Density

Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



Test Data – Peak Power Spectral Density


Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy

Lewisville, TX 75057

Tel: (972) 436-9600

Fax: (972) 436-2667



Section 10. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date	Calibration Due
1464	Spectrum analyzer	Hewlett Packard 8563E	3551A04428	02/11/03	02/11/05
1484	Cable 2.0-18.0 Ghz	Storm PR90-010-072	N/A	07/24/03	07/23/04
1485	Cable 2.0-18.0 Ghz	Storm PR90-010-216	N/A	07/24/03	07/23/04
1029	PEAK POWER METER	HP 8900D	3303U0012	12/23/03	12/22/04
1030	PEAK POWER SENSOR	HP 84811A	2539A03573	12/23/03	12/22/04
1469	10 db Attenuator DC 18 Ghz	MCL Inc. BW-S10W2 10db-2WDC	NONE	CBU	N/A
1628	CABLE, 6 ft	MEGAPHASE TM26 S1S5 72	N/A	03/05/03	03/04/04
1304	HORN ANTENNA	ELECTRO METRICS RGA-60	6151	09/22/03	09/22/05
1304	HORN ANTENNA	ELECTRO METRICS RGA-60	6151	09/22/03	09/22/05
1482	Band Pass Filter	K & L 11SH10-4000/T12000-0/0	2	Cal B4 Use	N/A
1258	LISN .15mhz-30mhz	EMCO 0	1305	09/15/03	09/14/04
1433	High pass filter	Solar 7930-5.0	933142	02/04/04	02/03/05
1988	CABLE, 6.8m	KTL RG223	N/A	07/02/03	07/01/04
785	ANALYZER, SPECTRUM	HP 8591E	3412A02996	04/09/03	04/08/04
480	Bilog Antenna, 30 MHz – 1 GHz	Schaffner CBL6111C	2572	5/10/03	5/10/04
791	Preamplifier	None	None	10/27/03	10/27/04

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)

REPORT NO.: [4L0041RUS1](#)

ANNEX A - TEST DETAILS

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
---	----------------------

Minimum Standard: The R.F. that is conducted back onto the AC power line on any frequency within the band 0.45 to 30 MHz shall not exceed:

Frequency of Emission (MHz)	Emission Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 – 56*	56 – 46
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

NAME OF TEST: Minimum 6 dB bandwidth	PARA. NO.: 15.247(a)(2)
--------------------------------------	-------------------------

Minimum Standard: The minimum 6 dB bandwidth shall be at least 500 kHz

NAME OF TEST: Maximum Peak Output Power**PARA. NO.: 15.247(b)(1)****Minimum Standard:** The maximum peak output power shall not exceed 1 watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point to point operation may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceed 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operation may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Direct Measurement Method For Detachable Antennas:

If the antenna is detachable, a peak power meter is used to measure the power output with the transmitter operating into a 50 ohm load. The dBi gain of the antenna(s) employed shall be reported.

EIRP Measurement for Non-Detachable Antennas:**Test Method:** TIA/EIA-603-1992, Section 2.2.12

The antenna substitution method was used to determine the equivalent radiated power at spurious frequencies. The spurious emissions were measured at a distance of 3 meters. The EUT was then replaced with a reference substitution antenna with a known gain referenced to a dipole. This antenna was fed with a signal at the spurious frequency. The level of the signal was adjusted to repeat the previously measured level. The resulting erp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator if required.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom

Nemko Dallas

FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: WLAN6090SD

REPORT NO.: 4L0041RUS1

more than 10 MHz	3	top, middle, bottom
------------------	---	---------------------

NAME OF TEST: RF Exposure	PARA. NO.: 15.247(b)(4)
---------------------------	-------------------------

Minimum Standard: Systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines stipulated in 1.1307(b)(1) of CFR 47.

NAME OF TEST: Spurious Emissions(conducted)	PARA. NO.: 15.247(c)
---	----------------------

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits. Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (? V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM IS SEARCHED TO THE 10th HARMONIC OF THE HIGHEST FREQUENCY GENERATED IN THE EUT.

Method Of Measurement:

30 MHz - 10th harmonic plot

RBW: 100 kHz

VBW: 300 kHz

Sweep: Auto

Display line: -20 dBc

Lower Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 902 MHz, 2400 MHz, or 5725 MHz

Marker: Peak of fundamental emission

Marker ?: Peak of highest spurious level below center frequency.

Upper Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 928 MHz, 2483.5 MHz, or 5850 MHz

Marker: Peak of fundamental emission

Marker ?: Peak of highest spurious level above center frequency.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Radiated Spurious Emissions PARA. NO.: 15.247(c)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits:

Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (? V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM WAS SEARCHED TO THE 10th HARMONIC

15.205 Restricted Bands

MHz	MHz	MHz	GHz
0.09-0.11	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.125-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41	1718		

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Transmitter Power Density	PARA. NO.: 15.247(d)
---	----------------------

Minimum Standard: The transmitted power density averaged over any 1 second interval shall not be greater than +8 dBm in any 3 kHz bandwidth.

Method Of Measurement: The spectrum analyzer is set as follows:

RBW: 3 kHz
VBW: >3 kHz
Sweep: Span (kHz)/3 (i.e. for a span of 1.5 MHz the sweep rate is
 $1500/3 = 500$ sec.)

Note: For devices with spectrum line spacing =< 3 kHz, the RBW of the analyzer is reduced until the spectral lines are resolved. The measurement data is normalized to 3 kHz by summing the power of all the individual spectral lines within a 3 kHz band in linear power units.

For Devices With Integral Antenna:

For devices with non-detachable antennas, the received field strength is peaked and the spectrum analyzer is set as above. The peak emission level is then measured and converted to a field strength by adding the appropriate antenna factor and cable loss. This field strength is then converted to an equivalent isotropic radiated power using the same method as described for Peak Power output.

Number of channels tested:

Tuning Range	Number Of Channels Tested	Channel Location In Band
1 MHz or Less	1	Middle
1 to 10 MHz	2	Top And Bottom
More Than 10 MHz	3	Top, Middle, Bottom



Nemko Dallas


FCC PART 15, SUBPART C
DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: [WLAN6090SD](#)

REPORT NO.: [4L0041RUS1](#)

ANNEX B - TEST DIAGRAMS

Test Site For Radiated Emissions**Conducted Emissions**

Peak Power At Antenna Terminals

Minimum 6 dB Bandwidth
Peak Power Spectral Density
Spurious Emissions (conducted)

