

EMC Test Data

7-	VE ENGINEER SOCCESS		
Client:	Flextronics	Job Number:	J89632
Model:	WS-AP3710i	T-Log Number:	T89871
	W5-AF3/101	Account Manager:	Christine Krebill
Contact:	Georges Fares		
Standard:	15.407, RSS-210	Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 2/14/2013 Test Engineer: David Bare

General Test Configuration

Calculation uses the free space transmission formula:

 $S = (PG)/(4 \pi d^2)$

Where: S is power density (W/m²), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	VAC
If not, required separation distance (in cm):	

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

WE ENGINEER SOCCESS								
Client:	Flextronics	Job Number:	J89632					
Model:	WS-AP3710i	T-Log Number:	T89871					
	W3-AF37 101	Account Manager:	Christine Krebill					
Contact:	Georges Fares							
Standard:	15.407, RSS-210	Class:	N/A					

Use: General Antenna: 2 dBi internal

Band	Mode	Output Power		Antenna EIRP		Channels	Channels	Total EIRP		
		Peak	Average	gain (Max)	dBm	W	Available	Used	W	dBm
2400 - 2483.5	OFDM	22.6	-	6.8	29.4	0.872	11	1	0.982	29.4
2400 - 2483.5	CCK	1	23.1	6.8	29.9	0.982	11	l	0.902	29.4
5725 - 5850	OFDM	21.9	1	6.8	28.7	0.733	5	1	0.733	28.7
Totals:									1.715	32.3

Band	Mode	Output Power		Antenna	EIRP		Channels	Channels	Total	EIRP
		Peak	Average	gain (Max)	dBm	W	Available	Used	W	dBm
2400 -	OFDM	22.6		6.8	29.4	0.872				
2483.5	OFDIVI	22.0	-	0.0	23.4	0.072	11	1	0.982	29.4
2400 -	CCK		23.1	6.8	29.9	0.982	11			
2483.5	COR	_	23.1	0.0	23.3	0.302				
5150 -										
5350, 5470-	OFDM	_	20.0	6.8	26.8	0.479	4	1	0.479	26.8
5725	0. 2			0.0	_0.0		•		• • • • • • • • • • • • • • • • • • • •	
0.20								2		
Totals:									1.460	31.6

Maximum eirp is calculated as follows:

Uses the average power for each channel (where given), otherwise uses the peak power

Worst case Total EIRP

Total EIRP	Power Density(S)	MPE Limit	Distance where
	at 20 cm	at 20 cm	
mW	mW/cm ²	mW/cm ²	S <= MPE Limit
1715	0.341	1.000	11.7cm