

RF Exposure Evaluation
FCCID: QRF-24QGFKT3
2.4 GHz Wireless Network Adapter
Tranzeo Wireless Technologies Inc.


Date: March 18, 2009

Report No.: 031709.1

Labs: 19473 Fraser Way, Pitt Meadows, BC, Canada V3Y 2V4



Andrew Marles
EMC Manager



Andrei Moldavanov
EMC Engineer

RF Exposure Evaluation

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Section 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Section 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation".

Frequency Range (MHZ)	Electric Field Strength (V/m)	Magnetic Field Strength (A/M)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

EUT Operating Condition

The maximum antenna gain is 19 dBi.

RF exposure evaluation distance calculation FCC 1.304

2.4 GHz radio with 19 dBi antenna

Freq (MHz)	Max Output Power to Antenna (dBm)	Antenna Gain (dBi)	r (cm)
2412	19.49	19	23.7
2437	19.60	19	24.0
2462	19.67	19	24.2

As shown above, the minimum distance where the MPE limit is reached is 24.2 cm for the EUT.