

Operational Description

FCCID: QRF- BNYKH900A

900 MHz Wireless Network Adapter

Tranzeo Wireless Technologies Inc.

Date: 02 February, 2009

Report No.: 020209.1

Labs: 19473 Fraser Way, Pitt Meadows, BC, Canada V3Y 2V4



Andrew Marles
EMC Manager



Bruce Balston
EMC Engineer

Operational Description

The device is a wireless network bridge designed specifically for outdoor applications. The device provides a bridge between IEEE802.3 wired Ethernet LANs and IEEE 802.11b/g compliant wireless networks. It uses an external antenna coupled with an 802.11b/g transceiver to connect to remote wireless clients. The transceiver operates in the frequency band 902-928 MHz. The device transmits digital network data. The unit is mounted externally in fixed point-to-point installations. It is mounted on the exterior of a building typically for broadband internet access.

The type of RF modulation is DSSS and OFDM both used at 900 MHz. The device can transmit data at a bit rate of 11 Mbps in DSSS mode and 54 Mbps in OFDM mode or a real-world data rate of approximately 14 and 27 Mbps respectively. The WEP/WPA/WPA2 algorithms are used for secure communications. The device's standard compliance ensures that it can communicate with any 802.11b/g network.

The firmware used with the device prevents the use of channels outside the specified frequency bands.

The product is used exclusively in a professionally installed, fixed point-to-point environment.