

**RF-EXPOSURE REPORT****FCC 47 CFR Part 2.1091****ISED RSS-102****Maximum permissible exposure**

<b>Report Reference No</b>	G0M-2206-1512-TFC091MP-V01
<b>Testing Laboratory</b>	Eurofins Product Service GmbH
<b>Address</b>	Storkower Str. 38c 15526 Reichenwalde Germany
<b>Accreditation</b>	  A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Test Firm Designation Number: DE0008 ISED Testing Laboratory site: 3470A-2
<b>Applicant</b>	BIOTRONIK SE & Co. KG
<b>Address</b>	Woermannkehre 1 12359 Berlin GERMANY
<b>Test Specification</b>	According to FCC/ISED rules
<b>Standard</b>	FCC 47 CFR 2.1091 ISED RSS-102
<b>Non-Standard Test Method</b>	None
<b>Equipment under Test (EUT):</b>	
<b>Product Description</b>	Data Gateway for Electrophysiology Lab
<b>Model(s)</b>	Qubic Connect
<b>Additional Model(s)</b>	None
<b>Brand Name(s)</b>	BIOTRONIK
<b>Hardware Version(s)</b>	A.A
<b>Software Version(s)</b>	Wi-Fi Driver Version: 22.70.0.6, LTE Modem Firmware: 24.01.514
<b>FCC ID</b>	QRI-QCONNECT
<b>IC</b>	4708A-QCONNECT
<b>Test Result</b>	<b>PASSED</b>

<b>Possible test case verdicts:</b>	
required by standard but not tested	N/T
not required by standard	N/R
test object does meet the requirement	P(PASS)
test object does not meet the requirement	F(FAIL)
<b>Testing:</b>	
Test Lab Temperature	20 °C - 30 °C
Test Lab Humidity	25 % - 55 %
Date of receipt of test item	2022-06-15
<b>Report:</b>	
Compiled by	Odai Qawasmeh
Tested by (+ signature) (Responsible for Test)	Odai Qawasmeh 
Approved by (+ signature) (Test Lab Engineer)	Burkhard Pudell 
Date of Issue	2022-11-30
Total number of pages	27
<b>General Remarks:</b>	
<p>The test results presented in this report relate only to the object tested.</p> <p>The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.</p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p>	
<b>Additional Comments:</b>	

## VERSION HISTORY

<b>Version History</b>			
Version	Issue Date	Remarks	Revised By
01	2022-11-30	Initial Release	

**ABBREVIATIONS AND ACRONYMS**

Acronyms	
Acronym	Description
EIRP	Equivalent Isotropic Radiated Power
EUT	Equipment Under Test
MPE	Maximum Permissible Exposure

**REPORT INDEX**

<b>1</b>	<b>Equipment (Test Item) Under Test.....</b>	<b>6</b>
1.1	Reference Documents.....	7
1.2	Power density radiation sources.....	8
1.3	Field strength radiation sources .....	8
1.4	Concurrent Sources .....	8
<b>2</b>	<b>Result Summary.....</b>	<b>9</b>
<b>3</b>	<b>RF-Exposure classification .....</b>	<b>11</b>
<b>4</b>	<b>RF-Exposure limits .....</b>	<b>12</b>
<b>5</b>	<b>RF-Exposure Evaluation .....</b>	<b>13</b>
<b>6</b>	<b>Single Source Evaluation Results - FCC .....</b>	<b>14</b>
<b>7</b>	<b>Single Source Evaluation Results - ISED .....</b>	<b>21</b>

## 1 Equipment (Test Item) Under Test

Description	Data Gateway for Electrophysiology Lab
Model	Qubic Connect
Additional Model(s)	None
Brand Name(s)	BIOTRONIK
Serial Number(s)	(44) 00298859
Hardware Version(s)	A.A
Software Version(s)	Wi-Fi Driver Version: 22.70.0.6, LTE Modem Firmware: 24.01.514
PMN	Qubic Connect
HVIN	Qubic Connect
FVIN	n/a
HMN	n/a
FCC ID	QRI-QCONNECT
IC	4708A-QCONNECT
Equipment type	End Product
Environment	General public

## 1.1 Reference Documents

Document Type	Document No.	Issued by	Date
Radio Test Report FCC CFR Title 47 Part 15 C RSS-247 issue 2, RSS-Gen issue 5 A1	200611-03.TR04	Intel Corporation S.A.S – WRF Lab	2020-10-14
Radio Test Report FCC CFR Title 47 Part 15 E (U-NII-1 & 2A)	200611-03.TR01	Intel Corporation S.A.S – WRF Lab	2020-10-14
Radio Test Report FCC CFR Title 47 Part 15 E RSS-247 issue 2, RSS-Gen issue 5 A1 (U-NII-2C)	200611-03.TR02	Intel Corporation S.A.S – WRF Lab	2020-10-26
Radio Test Report FCC CFR Title 47 Part 15 E RSS-247 issue 2, RSS-Gen issue 5 - A1 (U-NII-3)	200611-03.TR03	Intel Corporation S.A.S – WRF Lab	2020-10-14

## 1.2 Power density radiation sources

Power density radiation						
Mode	Operating Frequency [MHz]	Maximum conducted power [dBm]	Maximum radiated power [dBm EIRP]	Maximum duty cycle [%]	Maximum antenna gain [dBi]	Maximum antenna diameter [cm]
IEEE 802.11 (2.4 GHz)	2442	28.99	31.49	100	2.5	N/A
IEEE 802.11 (U-NII-1)	5230	22.99	27.59	100	4.6	N/A
IEEE 802.11 (U-NII-2A)	5280	22.18	26.78	100	4.6	N/A
IEEE 802.11 (U-NII-2C)	5590	23.88	28.48	100	4.6	N/A
IEEE 802.11 (U-NII-3)	5755	24.22	28.82	100	4.6	N/A
LTE FDD2	1880.0	25.7*	27.2	100	1.5	N/A
LTE FDD4	1732.5	25.7*	27.2	100	1.5	N/A
LTE FDD5	836.5	25.7*	25.7	100	0	N/A
LTE FDD12	707.5	25.7*	27.2	100	1.5	N/A
LTE FDD17	710.0	25.7*	27.2	100	1.5	N/A
LTE FDD25	1882.5	25.7*	27.2	100	1.5	N/A
LTE FDD26	831.5	25.7*	25.7	100	0	N/A
LTE FDD66	1745	25.7*	27.2	100	1.5	N/A

Comment: \* Maximum power permitted by specific radio technology standard.

## 1.3 Field strength radiation sources

None

## 1.4 Concurrent Sources

No concurrent radiation sources

## 2 Result Summary

FCC MPE Evaluation - Single radiation sources					
Product Standard Reference	Requirement	Reference Method	Mode	Distance [m]	Verdict
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-1)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-2A)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-2C)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-3)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD2	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD4	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD5	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD12	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD17	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD25	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD26	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	LTE FDD66	0.20	PASS
Comment:					

ISED MPE Evaluation - Single radiation sources					
Product Standard Reference	Requirement	Reference Method	Mode	Distance [m]	Verdict
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	IEEE 802.11 (2.4 GHz)	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	IEEE 802.11 (U-NII-1)	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	IEEE 802.11 (U-NII-2A)	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	IEEE 802.11 (U-NII-2C)	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	IEEE 802.11 (U-NII-3)	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD2	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD4	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD5	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD12	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD17	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD25	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD26	0.20	PASS
ISED RSS-102	Maximum permissible exposure	ISED RSS-102	LTE FDD66	0.20	PASS
Comment:					

### 3 RF-Exposure classification

RF-Exposure Categories	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

RF-Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / Uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

#### 4 RF-Exposure limits

FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.3 – 1.34	614	1.63	1000	30
1.34 – 30	824/f	2.19/f	1800/f <sup>2</sup>	30
30 – 300	27.5	0.073	2	30
300 – 1500	-	-	f/150	30
1500 – 100000	-	-	10.0	30

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.3 – 3.0	614	1.63	1000	6
3.0 – 30	1842/f	4.89/f	9000/f <sup>2</sup>	6
30 – 300	61.4	0.163	10.0	6
300 – 1500	-	-	f/30	6
1500 – 100000	-	-	50	6

ISED Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003 – 10	83	90	-	Instantaneous
0.1 – 10	-	0.73/f	-	6
1.1 – 10	87/f <sup>0.5</sup>	-	-	6
10 – 20	27.46	0.0728	2	6
20 – 48	58.07/f <sup>0.5</sup>	0.1540/f <sup>0.25</sup>	8.944/f <sup>0.5</sup>	6
48 – 300	22.06	0.05852	1.291	6
300 – 6000	3.142·f <sup>0.3417</sup>	0.008335·f <sup>0.3417</sup>	0.02619·f <sup>0.6834</sup>	6
6000 – 15000	61.4	0.163	10	6
15000 – 150000	61.4	0.163	10	616000/f <sup>1.2</sup>
150000 – 300000	0.158·f <sup>0.5</sup>	4.21·10 <sup>-4</sup> ·f <sup>0.5</sup>	6.67·10 <sup>-5</sup> ·f	616000/f <sup>1.2</sup>

ISED Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.003 – 10	170	180	-	Instantaneous
0.1 – 10	-	1.6/f	-	6
1.1 – 10	193/f <sup>0.5</sup>	-	-	6
10 – 20	61.4	0.163	10	6
20 – 48	129.8/f <sup>0.5</sup>	0.3444/f <sup>0.25</sup>	44.72/f <sup>0.5</sup>	6
48 – 300	49.33	0.1309	6.455	6
300 – 6000	15.60·f <sup>0.25</sup>	0.04138·f <sup>0.25</sup>	0.6455·f <sup>0.5</sup>	6
6000 – 15000	137	0.364	50	6
15000 – 150000	137	0.364	50	616000/f <sup>1.2</sup>
150000 – 300000	0.354·f <sup>0.5</sup>	9.40·10 <sup>-4</sup> ·f <sup>0.5</sup>	3.33·10 <sup>-5</sup> ·f	616000/f <sup>1.2</sup>

## 5 RF-Exposure Evaluation

Evaluation Relations
$\lambda[m] = \frac{c \left[ \frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$
$S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2} ; R[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$
$DCC [dB] = 10 \cdot \log_{10} \left( \frac{DC[\%]}{100} \right)$
$\sum_{i=1}^N \frac{S_i \left[ \frac{W}{m^2} \right]}{S_{Li} \left[ \frac{W}{m^2} \right]} + \sum_{j=1}^M \left( \frac{E_j \left[ \frac{V}{m} \right]}{E_{Lj} \left[ \frac{V}{m} \right]} \right)^2 + \sum_{k=1}^o \left( \frac{H_k \left[ \frac{A}{m} \right]}{H_{Lk} \left[ \frac{A}{m} \right]} \right)^2 < 1$

Evaluation Procedure
<u>Standalone operation evaluation:</u>
For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance is calculated. The distance from the radiation source for compliance power density is calculated. If the separation distance is lower than the far-field distance, the far-field distance is given as compliance separation distance because the plane wave power density assessment is only valid in the far-field of the radiation source.
For radiation sources for which the average electric and magnetic fields are measured using field probes, the measured field strength values are compared to the reference limits. For those sources no calculations are performed. Compliance with the reference values is determined with the near field measurements.
<u>Concurrent operation evaluation:</u>
First the evaluation distance is set to an appropriate value. For all radiation sources for which power densities are calculated, the power densities at the evaluation distance are calculated and for all other sources the electric or magnetic field strengths are measured using field probes. Finally the ratios of the power densities and/or field strength values and the corresponding limits are calculated and summed and the sum is compared to the maximum of 1.

## 6 Single Source Evaluation Results - FCC

IEEE 802.11 (2.4 GHz)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2442
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	31.49
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	31.49
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	2.804
Power density ratio @ 0.20 m	0.28
Distance for compliance power density (S=SL) [m]	0.106
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-1)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5230
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.59
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.59
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.142
Power density ratio @ 0.20 m	0.11
Distance for compliance power density (S=SL) [m]	0.068
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-2A)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5280
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	26.78
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	26.78
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.948
Power density ratio @ 0.20 m	0.09
Distance for compliance power density (S=SL) [m]	0.062
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-2C)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5590
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	28.48
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	28.48
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.402
Power density ratio @ 0.20 m	0.14
Distance for compliance power density (S=SL) [m]	0.075
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-3)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5755
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	28.82
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	28.82
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.516
Power density ratio @ 0.20 m	0.15
Distance for compliance power density (S=SL) [m]	0.078
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD2	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1880.0
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.10
Distance for compliance power density (S=SL) [m]	0.065
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD4</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1732.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.10
Distance for compliance power density (S=SL) [m]	0.065
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD5</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	836.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	25.7
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	25.70
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	5.577
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.739
Power density ratio @ 0.20 m	0.13
Distance for compliance power density (S=SL) [m]	0.073
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD12</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	707.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.717
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.22
Distance for compliance power density (S=SL) [m]	0.094
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD17</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	710.0
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.733
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.22
Distance for compliance power density (S=SL) [m]	0.094
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD25	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1882.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.10
Distance for compliance power density (S=SL) [m]	0.065
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD26	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	831.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	25.7
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	25.70
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	5.543
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.739
Power density ratio @ 0.20 m	0.13
Distance for compliance power density (S=SL) [m]	0.073
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD66	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1745
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.10
Distance for compliance power density (S=SL) [m]	0.065
<b>Compliance</b>	
Verdict	PASS
Comment:	

## 7 Single Source Evaluation Results - ISED

IEEE 802.11 (2.4 GHz)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2442
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	31.49
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	31.49
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	5.412
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	2.804
Power density ratio @ 0.20 m	0.52
Distance for compliance power density (S=SL) [m]	0.144
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-1)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5230
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.59
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.59
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	9.107
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.142
Power density ratio @ 0.20 m	0.13
Distance for compliance power density (S=SL) [m]	0.071
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-2A)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5280
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	26.78
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	26.78
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	9.166
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.948
Power density ratio @ 0.20 m	0.10
Distance for compliance power density (S=SL) [m]	0.064
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-2C)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5590
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	28.48
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	28.48
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	9.531
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.402
Power density ratio @ 0.20 m	0.15
Distance for compliance power density (S=SL) [m]	0.077
<b>Compliance</b>	
Verdict	PASS
Comment:	

IEEE 802.11 (U-NII-3)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5755
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	28.82
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	28.82
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	9.722
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.516
Power density ratio @ 0.20 m	0.16
Distance for compliance power density (S=SL) [m]	0.079
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD2	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1880.0
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.526
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.23
Distance for compliance power density (S=SL) [m]	0.096
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD4</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1732.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.280
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.24
Distance for compliance power density (S=SL) [m]	0.099
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD5</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	836.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	25.7
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	25.70
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	2.602
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.739
Power density ratio @ 0.20 m	0.28
Distance for compliance power density (S=SL) [m]	0.107
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD12</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	707.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	2.321
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.45
Distance for compliance power density (S=SL) [m]	0.134
<b>Compliance</b>	
Verdict	PASS
Comment:	

<b>LTE FDD17</b>	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	710.0
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	2.326
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.45
Distance for compliance power density (S=SL) [m]	0.134
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD25	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1882.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.530
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.23
Distance for compliance power density (S=SL) [m]	0.096
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD26	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	831.5
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	25.7
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	25.70
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	2.592
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.739
Power density ratio @ 0.20 m	0.29
Distance for compliance power density (S=SL) [m]	0.107
<b>Compliance</b>	
Verdict	PASS
Comment:	

LTE FDD66	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	1745
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	27.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	27.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	4.301
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	1.044
Power density ratio @ 0.20 m	0.24
Distance for compliance power density (S=SL) [m]	0.099
<b>Compliance</b>	
Verdict	PASS
Comment:	

==== END OF TEST REPORT ====