



TEST REPORT

Report Reference No..... : TRE18050064 R/C.....: 77022

FCC ID..... : QRP-AZUMIK5QL

Applicant's name..... : AZUMI S.A

Address.....: Avenida Aquilino de la Guardia con Calle 47, PH Ocean Plaza,
Piso 16 of. 16-01, Marbella, Ciudad de Panama, Panama

Manufacturer.....: AZUMI HK LTD

Address.....: FLAT/RM 18 BLK 1 14/F GOLDEN INDUSTRIAL BUILDING 16-
26 KWAI TAK STREET KWAI CHUNG,HK

Test item description : Mobile Phone

Trade Mark: AZUMI

Model/Type reference.....: K5QL

Listed Model(s): -

Standard : FCC 47 CFR Part2.1093
IEEE 1528: 2013 ANSI/IEEE C95.1: 1999

Date of receipt of test sample.....: May.08,2018

Date of testing.....: May.09,2018- May.18,2018

Date of issue.....: May.22,2018

Result.....: PASS

Compiled by
(position+printedname+signature)....: File administrators:Xiaodong Zhao *Xiaodong Zhao*

Supervised by
(position+printedname+signature)....: Test Engineer: Xiaodong Zhao *Xiaodong Zhao*

Approved by
(position+printedname+signature)....: Manager: Hans Hu *Hans Hu*

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd

Address.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao,
Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>Test Standards and Report version</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>Summary</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
<u>3.</u>	<u>Test Environment</u>	<u>6</u>
3.1.	Test laboratory	6
3.2.	Test Facility	6
<u>4.</u>	<u>Equipments Used during the Test</u>	<u>7</u>
<u>5.</u>	<u>Measurement Uncertainty</u>	<u>8</u>
<u>6.</u>	<u>SAR Measurements System Configuration</u>	<u>10</u>
6.1.	SAR Measurement Set-up	10
6.2.	DASY5 E-field Probe System	11
6.3.	Phantoms	12
6.4.	Device Holder	12
<u>7.</u>	<u>SAR Test Procedure</u>	<u>13</u>
7.1.	Scanning Procedure	13
7.2.	Data Storage and Evaluation	15
<u>8.</u>	<u>Position of the wireless device in relation to the phantom</u>	<u>17</u>
8.1.	Head Position	17
8.2.	Body Position	18
8.3.	Hotspot Mode Exposure conditions	18
<u>9.</u>	<u>System Check</u>	<u>19</u>
9.1.	Tissue Dielectric Parameters	19
9.2.	SAR System Check	20
<u>10.</u>	<u>SAR Exposure Limits</u>	<u>32</u>
<u>11.</u>	<u>Conducted Power Measurement Results</u>	<u>33</u>
<u>12.</u>	<u>Maximum Tune-up Limit</u>	<u>49</u>
<u>13.</u>	<u>Antenna Location</u>	<u>55</u>
<u>14.</u>	<u>SAR Measurement Results</u>	<u>56</u>
<u>15.</u>	<u>Simultaneous Transmission analysis</u>	<u>96</u>
<u>16.</u>	<u>TestSetup Photos</u>	<u>106</u>
<u>17.</u>	<u>External and Internal Photos of the EUT</u>	<u>108</u>

1. Test Standards and Report version

1.1. Test Standards

The tests were performed according to following standards:

[FCC 47 Part 2.1093](#) Radiofrequency Radiation Exposure Evaluation:Portable Devices

[IEEE Std C95.1, 1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 KHz to 300 GHz.

[IEEE Std 1528™-2013](#): IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

[KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04](#): SAR Measurement Requirements for 100 MHz to 6 GHz

[KDB 865664 D02 RF Exposure Reporting v01r02](#): RF Exposure Compliance Reporting and Documentation Considerations

[KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

[KDB 248227 D01 802.11 Wi-Fi SAR v02r02](#): SAR Measurement Proceduresfor802.11 a/b/g Transmitters

[KDB 648474 D04 Handset SAR v01r03](#): SAR Evaluation Considerations for Wireless Handsets

[KDB 941225 D01 3G SAR Procedures v03r01](#): SAR Measurement Procedures for 3G Devices

[KDB 941225 D06 Hotspot Mode v02r01](#): SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

[KDB 941225 D05 SAR for LTE Devices v02r05](#): SAR Evaluation Considerations for LTE Devices

1.2. Report version

Revision No.	Date of issue	Description
N/A	May.22,2018	Original

2. Summary

2.1. Client Information

Applicant:	AZUMI S.A
Address:	Avenida Aquilino de la Guardia con Calle 47, PH Ocean Plaza, Piso 16 of. 16-01, Marbella, Ciudad de Panama, Panama
Manufacturer:	AZUMI HK LTD
Address:	FLAT/RM 18 BLK 1 14/F GOLDEN INDUSTRIAL BUILDING 16-26 KWAI TAK STREET KWAI CHUNG,HK

2.2. Product Description

Name of EUT:	Mobile Phone			
Trade Mark:	AZUMI			
Model No.:	K5QL			
Listed Model(s):	-			
Power supply:	DC 3.7V			
Device Category:	Portable			
Product stage:	Production unit			
RF Exposure Environment:	General Population / Uncontrolled			
IMEI:	354779090000267			
Hardware version:	W4G01_MB_V3.0			
Software version:	AZUMI-k5_QL_SINGLESIM_V01_20171205			
Maximum SAR Value				
Separation Distance:	Head: 0mm			
	Body: 10mm			
Max Report SAR Value (1g):	Test location:	PCE	DTS	Simultaneous TX
	Head:	0.358 W/Kg	0.408 W/Kg	0.766 W/Kg
	Body:	0.769 W/Kg	0.220 W/Kg	0.989 W/Kg
	Hotspot:	0.769 W/Kg	0.220 W/Kg	0.989 W/Kg
GSM				
Support Network:	GSM, GPRS, EGPRS			
Support Band:	GSM850, PCS1900			
Modulation:	GSM/GPRS/EGPRS: GMSK EGPRS: 8PSK			
GPRS Class:	12			
EGPRS Class:	12			
Antenna type:	Integral Antenna			
WCDMA				
Operation Band:	WCDMA Band II, WCDMA Band IV, WCDMA Band V			
Power Class:	Power Class 3			
Modilation Type:	QPSK/16QAM/64QAM/HSUPA/HSDPA			
DC-HSUPA Release Version:	Not Supported			
Antenna type:	Integral Antenna			

LTE	
Operation Band:	FDD Band 2,FDD Band 4, FDD Band 5, FDD Band 7
Modulation Type:	QPSK,16QAM
Antenna type:	Integral Antenna
WIFI	
Supported type:	802.11b/802.11g/802.11n(HT20)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20)
Channel separation:	5MHz
Antenna type:	Integral Antenna
Bluetooth	
Version:	Supported BT4.0+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Integral Antenna
Bluetooth-BLE	
Version:	Supported BT4.0+BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Integral Antenna
<i>Remark:</i> 1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power	

3. Test Environment

3.1. Test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

3.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025:2005 General Requirements) for the Competence of Testing and Calibration Laboratories

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4. Equipments Used during the Test

Test Equipment	Manufacturer	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
Data Acquisition Electronics DAEx	SPEAG	DAE4	1549	2018/04/25	2019/04/24
E-field Probe	SPEAG	EX3DV4	7494	2018/02/26	2019/02/25
System Validation Dipole	SPEAG	D835V2	4d238	2018/02/19	2021/02/18
System Validation Dipole	SPEAG	D1750V2	1164	2018/02/06	2021/02/05
System Validation Dipole	SPEAG	D1900V2	5d226	2018/02/22	2021/02/21
System Validation Dipole	SPEAG	D2450V2	1009	2018/02/05	2021/02/04
System Validation Dipole	SPEAG	D2600V2	1150	2018/02/05	2021/02/04
Dielectric Assessment Kit	SPEAG	DAK-3.5	1267	2018/03/01	2019/02/28
Network analyzer	Agilent	N9923A	MY51491493	2017/09/05	2018/09/04
Power meter	Agilent	N1914A	MY52090010	2018/03/22	2019/03/21
Power sensor	Agilent	E9304A	MY52140008	2018/03/22	2019/03/21
Power sensor	Agilent	E9301H	MY54470001	2017/06/02	2018/06/01
Signal Generator	ROHDE & SCHWARZ	SMB100A	175248	2017/09/02	2018/09/01
Universal Radio Communication Tester	ROHDE & SCHWARZ	CMU200	112012	2017/11/11	2018/11/10
Universal Radio Communication Tester	ROHDE & SCHWARZ	CMW500	137668	2017/10/26	2018/10/25
Dual Directional Coupler	Agilent	772D	MY46151257	2018/03/22	2019/03/21
Dual Directional Coupler	Agilent	778D	MY48220612	2018/03/22	2019/03/21
Power Amplifier	Mini-Circuits	ZHL-42W	QA1202003	2017/11/27	2018/11/26

Note:

1. The Probe, Dipole and DAE calibration reference to the Appendix A and Appendix B.
2. Referring to KDB865664 D01, the dipole calibration interval can be extended to 3 years with justification. The dipole are also not physically damaged or repaired during the interval.

5. Measurement Uncertainty

Measurement Uncertainty										
No.	Error Description	Type	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement System										
1	Probe calibration	B	6.0%	N	1	1	1	6.0%	6.0%	∞
2	Axial isotropy	B	4.70%	R	$\sqrt{3}$	0.7	0.7	1.90%	1.90%	∞
3	Hemispherical isotropy	B	9.60%	R	$\sqrt{3}$	0.7	0.7	3.90%	3.90%	∞
4	Boundary Effects	B	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
5	Probe Linearity	B	4.70%	R	$\sqrt{3}$	1	1	2.70%	2.70%	∞
6	Detection limit	B	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
7	RF ambient conditions-noise	B	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
8	RF ambient conditions-reflection	B	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
9	Response time	B	0.80%	R	$\sqrt{3}$	1	1	0.50%	0.50%	∞
10	Integration time	B	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	∞
11	RF ambient	B	3.00%	R	$\sqrt{3}$	1	1	1.70%	1.70%	∞
12	Probe positioned mech. restrictions	B	0.40%	R	$\sqrt{3}$	1	1	0.20%	0.20%	∞
13	Probe positioning with respect to phantom shell	B	2.90%	R	$\sqrt{3}$	1	1	1.70%	1.70%	∞
14	Max.SAR evaluation	B	3.90%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
Test Sample Related										
15	Test sample positioning	A	1.86%	N	1	1	1	1.86%	1.86%	∞
16	Device holder uncertainty	A	1.70%	N	1	1	1	1.70%	1.70%	∞
17	Drift of output power	B	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	∞
Phantom and Set-up										
18	Phantom uncertainty	B	4.00%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
19	Liquid conductivity (target)	B	5.00%	R	$\sqrt{3}$	0.64	0.43	1.80%	1.20%	∞
20	Liquid conductivity (meas.)	A	0.50%	N	1	0.64	0.43	0.32%	0.26%	∞
21	Liquid permittivity (target)	B	5.00%	R	$\sqrt{3}$	0.64	0.43	1.80%	1.20%	∞
22	Liquid permittivity (meas.)	A	0.16%	N	1	0.64	0.43	0.10%	0.07%	∞
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$		/	/	/	/	9.79%	9.67%	∞
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$		R	K=2	/	/	19.57%	19.34%	∞

System Check Uncertainty										
No.	Error Description	Type	Uncertainty Value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement System										
1	Probe calibration	B	6.0%	N	1	1	1	6.0%	6.0%	∞
2	Axial isotropy	B	4.70%	R	$\sqrt{3}$	0.7	0.7	1.90%	1.90%	∞
3	Hemispherical isotropy	B	9.60%	R	$\sqrt{3}$	0.7	0.7	3.90%	3.90%	∞
4	Boundary Effects	B	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
5	Probe Linearity	B	4.70%	R	$\sqrt{3}$	1	1	2.70%	2.70%	∞
6	Detection limit	B	1.00%	R	$\sqrt{3}$	1	1	0.60%	0.60%	∞
7	RF ambient conditions-noise	B	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
8	RF ambient conditions-reflection	B	0.00%	R	$\sqrt{3}$	1	1	0.00%	0.00%	∞
9	Response time	B	0.80%	R	$\sqrt{3}$	1	1	0.50%	0.50%	∞
10	Integration time	B	5.00%	R	$\sqrt{3}$	1	1	2.90%	2.90%	∞
11	RF ambient	B	3.00%	R	$\sqrt{3}$	1	1	1.70%	1.70%	∞
12	Probe positioned mech. restrictions	B	0.40%	R	$\sqrt{3}$	1	1	0.20%	0.20%	∞
13	Probe positioning with respect to phantom shell	B	2.90%	R	$\sqrt{3}$	1	1	1.70%	1.70%	∞
14	Max.SAR evalation	B	3.90%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
System validation source-dipole										
15	Deviation of experimental dipole from numerical dipole	A	1.58%	N	1	1	1	1.58%	1.58%	∞
16	Dipole axis to liquid distance	A	1.35%	N	1	1	1	1.35%	1.35%	∞
17	Input power and SAR drift	B	4.00%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
Phantom and Set-up										
18	Phantom uncertainty	B	4.00%	R	$\sqrt{3}$	1	1	2.30%	2.30%	∞
20	Liquid conductivity (meas.)	A	0.50%	N	1	0.64	0.43	0.32%	0.26%	∞
22	Liquid cpermittivity (meas.)	A	0.16%	N	1	0.64	0.43	0.10%	0.07%	∞
Combined standard uncertainty		$u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$		/	/	/	/	8.80%	8.79%	∞
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$		R	K=2	/	/	17.59%	17.58%	∞

6. SAR Measurements System Configuration

6.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.


Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



6.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

● Probe Specification


Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 W/kg; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI



● Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



6.3. Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6mm).

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.



SAM Twin Phantom

6.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.



Device holder supplied by SPEAG

7. SAR Test Procedure

7.1. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5\%$.

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space.

They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

Table 1: Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v04

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^{\circ} \pm 1^{\circ}$	$20^{\circ} \pm 1^{\circ}$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.2. Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors),s together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension “.DA4”. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [W/kg], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity:	Normi, ai0, ai1, ai2
	Conversion factor:	ConvFi
	Diode compression point:	Dcpi
Device parameters:	Frequency:	f
	Crest factor:	cf
Media parameters:	Conductivity:	σ
	Density:	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Vi:	compensated signal of channel (i = x, y, z)
Ui:	input signal of channel (i = x, y, z)
cf:	crest factor of exciting field (DASY parameter)
dcp _i :	diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes : } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$H - \text{fieldprobes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

Vi:	compensated signal of channel (i = x, y, z)
Normi:	sensor sensitivity of channel (i = x, y, z), [mV/(V/m)²] for E-field Probes
ConvF:	sensitivity enhancement in solution
aij:	sensor sensitivity factors for H-field probes
f:	carrier frequency [GHz]
Ei:	electric field strength of channel i in V/m
Hi:	magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

SAR: local specific absorption rate in W/kg
Etot: total field strength in V/m
 σ : conductivity in [mho/m] or [Siemens/m]
 ρ : equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

8. Position of the wireless device in relation to the phantom


8.1. Head Position

The wireless device define two imaginary lines on the handset, the vertical centreline and the horizontal line, for the handset in vertical orientation as shown in Figures 5a and 5b.


The vertical centreline passes through two points on the front side of the handset: the midpoint of the width W_t of the handset at the level of the acoustic output (point A in Figures 5a and 5b), and the midpoint of the width W_b of the bottom of the handset (point B).

The horizontal line is perpendicular to the vertical centreline and passes through the centre of the acoustic output (see Figures 5a and 5b). The two lines intersect at point A.

Note that for many handsets, point A coincides with the centre of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the handset (see Figure 5b), especially for clam-shell handsets, handsets with flip cover pieces, and other irregularly shaped handsets.




Figures 5a



Figures 5b


W_t	Width of the handset at the level of the acoustic
W_b	Width of the bottom of the handset
A	Midpoint of the width w_t of the handset at the level of the acoustic output
B	Midpoint of the width w_b of the bottom of the handset

Cheek position



Picture 2 Cheek position of the wireless device on the left side of SAM

Tilt position




Picture 3 Tilt position of the wireless device on the left side of SAM

8.2. Body Position

Devices that support transmission while used with body-worn accessories must be tested for body-worn accessory SAR compliance, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics.


Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance $\leq 10 \text{ mm}$ to support compliance.



Picture 4 Test positions for body-worn devices

8.3. Hotspot Mode Exposure conditions

The hotspot mode and body-worn accessory SAR test configurations may overlap for handsets. When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations. This typically applies to the Rear and front surfaces of a handset when SAR is required for both hotspot mode and body-worn accessory exposure conditions. Depending on the form factor and dimensions of a device, the test separation distance used for hotspot mode SAR measurement is either **10 mm** or that used in the body-worn accessory configuration, whichever is less for devices with dimension $> 9 \text{ cm} \times 5 \text{ cm}$. For smaller devices with dimensions $\leq 9 \text{ cm} \times 5 \text{ cm}$ because of a greater potential for next to body use a test separation of $\leq 5 \text{ mm}$ must be used.



Picture 5 Test positions for Hotspot Mode

9. System Check

9.1. Tissue Dielectric Parameters

It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB865664.

Tissue dielectric parameters for head and body phantoms				
Target Frequency	Head		Body	
(MHz)	ϵ_r	σ (s/m)	ϵ_r	σ (s/m)
835	41.5	0.90	55.2	0.97
1750	40.1	1.37	53.4	1.49
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16

Check Result:

Dielectric performance of Head tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
835	41.50	43.90	0.90	0.93	5.78%	3.56%	±10%	22	2018-05-09
1750	40.10	41.93	1.37	1.38	4.56%	0.36%	±10%	22	2018-05-11
1900	40.00	41.67	1.40	1.47	4.16%	4.71%	±10%	22	2018-05-14
2450	39.20	40.96	1.80	1.84	4.48%	2.11%	±10%	22	2018-05-16
2600	39.00	40.63	1.96	1.97	4.18%	0.51%	±10%	22	2018-05-16


Dielectric performance of Body tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
835	55.20	55.40	0.97	0.97	0.36%	-0.41%	±10%	22	2018-05-10
1750	53.40	53.91	1.49	1.44	0.96%	-3.36%	±10%	22	2018-05-11
1900	53.30	53.72	1.52	1.55	0.79%	1.97%	±10%	22	2018-05-15
2450	52.70	53.03	1.95	2.00	0.63%	2.56%	±10%	22	2018-05-16
2600	52.50	52.78	2.16	2.15	0.53%	-0.46%	±10%	22	2018-05-16

9.2. SAR System Check

The purpose of the system check is to verify that the system operates within its specifications at the device test frequency. The system check is a simple check of repeatability to make sure that the system works correctly at the time of the compliance test.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.



System Performance Check Setup




Photo of Dipole Setup

Check Result:

Head									
Frequency (MHz)	1g SAR		10g SAR		Delta (1g)	Delta (10g)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
835	9.51	9.92	6.15	6.52	4.31%	6.02%	±10%	22	2018-05-09
1750	36.60	36.24	19.40	19.44	-0.98%	0.21%	±10%	22	2018-05-11
1900	40.30	41.60	21.10	21.68	3.23%	2.75%	±10%	22	2018-05-14
2450	51.50	50.40	24.10	23.44	-2.14%	-2.74%	±10%	22	2018-05-16
2600	55.60	57.60	25.00	26.04	3.60%	4.16%	±10%	22	2018-05-16

Body									
Frequency (MHz)	1g SAR		10g SAR		Delta (1g)	Delta (10g)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
835	9.64	10.08	6.32	6.64	4.56%	5.06%	±10%	22	2018-05-10
1750	36.70	37.56	19.50	20.16	2.34%	3.38%	±10%	22	2018-05-11
1900	39.80	41.60	20.90	21.68	4.52%	3.73%	±10%	22	2018-05-15
2450	49.40	50.00	23.30	23.32	1.21%	0.09%	±10%	22	2018-05-16
2600	54.60	58.80	24.40	26.36	7.69%	8.03%	±10%	22	2018-05-16

Plots of System Performance Check

System Performance Check-Head 835MHz

DUT: D835V2; Type: D835V2; Serial: 4d238

Date: 2018-05-09

Communication System: UID 0, CW (0); Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.932$ S/m; $\epsilon_r = 43.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.73, 10.73, 10.73); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Head/d=15mm, Pin=250mW/Area Scan (41x101x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 3.51 W/kg


Head/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 66.38 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 3.78 W/kg

SAR(1 g) = 2.48 W/kg; SAR(10 g) = 1.63 W/kg

Maximum value of SAR (measured) = 3.34 W/kg



0 dB = 3.34 W/kg = 5.24 dBW/kg

System Performance Check-Body 835MHz

DUT: D835V2; Type: D835V2; Serial: 4d238

Date: 2018-05-10


Communication System: UID 0, CW (0); Frequency: 835 MHz

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.966 \text{ S/m}$; $\epsilon_r = 55.403$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.5, 10.5, 10.5); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Body/d=15mm,Pin=250mW/Area Scan (41x101x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 3.40 W/kg **Body/d=15mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 61.67 V/m ; Power Drift = -0.04 dB Peak SAR (extrapolated) = 3.97 W/kg **SAR(1 g) = 2.52 W/kg ; SAR(10 g) = 1.66 W/kg** Maximum value of SAR (measured) = 3.44 W/kg 

Plots of System Performance Check

System Performance Check-Head 1750MHz

DUT: D1750V2; Type: D1750V2; Serial: 1164

Date: 2018-05-11

Communication System: UID 0, CW (0); Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.375$ S/m; $\epsilon_r = 41.933$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(9.23, 9.23, 9.23); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 14.1 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 103.5 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 9.06 W/kg; SAR(10 g) = 4.86 W/kg

Maximum value of SAR (measured) = 13.8 W/kg



0 dB = 13.8 W/kg = 11.40 dBW/kg

System Performance Check-Body 1750MHz

DUT: D1750V2; Type: D1750V2; Serial: 1164

Date: 2018-05-11

Communication System: UID 0, CW (0); Frequency: 1750 MHz

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.441$ S/m; $\epsilon_r = 53.908$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.77, 8.77, 8.77); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Body/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 14.7 W/kg


Body/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 102.2 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 9.39 W/kg; SAR(10 g) = 5.04 W/kg

Maximum value of SAR (measured) = 14.1 W/kg



System Performance Check-Head 1900MHz

DUT: D1900V2; Type: D1900V2; Serial: 5d226

Date:2018-05-14

Communication System: UID 0, CW (0); Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.466$ S/m; $\epsilon_r = 41.665$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.83, 8.83, 8.83); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 17.1 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 112.4 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.4 W/kg; SAR(10 g) = 5.42 W/kg

Maximum value of SAR (measured) = 16.1 W/kg



0 dB = 16.1 W/kg = 12.07 dBW/kg

System Performance Check-Body 1900MHz

DUT: D1900V2; Type: D1900V2; Serial: 5d226

Date:2018-05-15

Communication System: UID 0, CW (0); Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.553$ S/m; $\epsilon_r = 53.719$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.42, 8.42, 8.42); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Body/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 16.4 W/kg


Body/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 105.9 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.4 W/kg; SAR(10 g) = 5.42 W/kg

Maximum value of SAR (measured) = 15.7 W/kg



0 dB = 15.7 W/kg = 11.96 dBW/kg

SystemPerformanceCheck-Head 2450MHz

DUT: D2450V2; Type: D2450V2; Serial: 1009

Date:2018-05-16

Communication System: UID 0, CW (0); Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.838$ S/m; $\epsilon_r = 40.956$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.27, 8.27, 8.27); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 21.1 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 110.0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 26.2 W/kg

SAR(1 g) = 12.6 W/kg; SAR(10 g) = 5.86 W/kg

Maximum value of SAR (measured) = 20.8 W/kg



0 dB = 20.8 W/kg = 13.18 dBW/kg

SystemPerformanceCheck-Body 2450MHz

DUT: D2450V2; Type: D2450V2; Serial: 1009

Date:2018-05-16

Communication System: UID 0, CW (0); Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.001$ S/m; $\epsilon_r = 53.03$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.08, 8.08, 8.08); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Body/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 21.1 W/kg


Body/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 105.6 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 25.7 W/kg

SAR(1 g) = 12.5 W/kg; SAR(10 g) = 5.83 W/kg

Maximum value of SAR (measured) = 20.7 W/kg



0 dB = 20.7 W/kg = 13.16 dBW/kg

SystemPerformanceCheck-Head 2600MHz

DUT: D2600V2; Type: D2600V2; Serial: 1150

Date:2018-05-16

Communication System: UID 0, CW (0); Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.97$ S/m; $\epsilon_r = 40.632$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.92, 7.92, 7.92); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Head/d=10mm,Pin=250mW/Area Scan (41x51x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 25.4 W/kg


Head/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 115.2 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 31.2 W/kg

SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.51 W/kg

Maximum value of SAR (measured) = 24.9 W/kg



0 dB = 24.9 W/kg = 13.96 dBW/kg

SystemPerformanceCheck-Body 2600MHz

DUT: D2600V2; Type: D2600V2; Serial: 1150

Date:2018-05-16

Communication System: UID 0, CW (0); Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.15$ S/m; $\epsilon_r = 52.78$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.51, 7.51, 7.51); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0; Type: QD 000 P41 AA; Serial: 1947
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Body/d=10mm,Pin=250mW/Area Scan (41x51x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 26.6 W/kg


Body/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 110.2 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 31.6 W/kg

SAR(1 g) = 14.7 W/kg; SAR(10 g) = 6.59 W/kg

Maximum value of SAR (measured) = 25.1 W/kg



0 dB = 25.1 W/kg = 14.00 dBW/kg

10. SAR Exposure Limits

SAR assessments have been made in line with the requirements of ANSI/IEEE C95.1-1992

Type Exposure	Limit (W/kg)	
	General Population / Uncontrolled Exposure Environment	Occupational / Controlled Exposure Environment
Spatial Average SAR (whole body)	0.08	0.4
Spatial Peak SAR (1g cube tissue for head and trunk)	1.60	8.0
Spatial Peak SAR (10g for limb)	4.0	20.0

Population/Uncontrolled Environments: are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

11. Conducted Power Measurement Results

GSM Conducted Power

1. Per KDB 447498 D01, the maximum output power channel is used for SAR testing and further SAR test reduction
2. Per KDB 941225 D01, considering the possibility of e.g. 3rd party VoIP operation for Head and Body-worn SAR test reduction for GSM and GPRS modes is determined by the source-base time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (3Tx slots) for GSM850 and GPRS (2Tx slots) for PCS1900.
3. Per KDB941225 D01, for hotspot SAR test reduction for GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance, For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (3Tx slots) for GSM850 and GPRS (2Tx slots) for PCS1900.

Mode: GSM850		Conducted Power (dBm)			Division Factors	Averager Power (dBm)		
		CH128	CH190	CH251		CH128	CH190	CH251
		824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM		32.64	32.77	32.80	-9.03	23.61	23.74	23.77
GPRS (GMSK)	1TXslot	32.57	32.71	32.74	-9.03	23.54	23.68	23.71
	2TXslots	31.98	32.07	31.91	-6.02	25.96	26.05	25.89
	3TXslots	30.51	30.29	30.24	-4.26	26.25	26.03	25.98
	4TXslots	28.04	28.06	28.01	-3.01	25.03	25.05	25.00
EGPRS (8PSK)	1TXslot	27.26	27.50	27.66	-9.03	18.23	18.47	18.63
	2TXslots	26.78	26.71	27.12	-6.02	20.76	20.69	21.10
	3TXslots	25.32	25.83	25.93	-4.26	21.06	21.57	21.67
	4TXslots	24.57	24.67	24.74	-3.01	21.56	21.66	21.73
Mode: PCS1900		Conducted Power (dBm)			Division Factors	Averager Power (dBm)		
		CH512	CH661	CH810		CH512	CH661	CH810
		1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GSM		29.11	29.15	29.02	-9.03	20.08	20.12	19.99
GPRS (GMSK)	1TXslot	29.18	29.19	29.04	-9.03	20.15	20.16	20.01
	2TXslots	28.14	28.32	27.67	-6.02	22.12	22.30	21.65
	3TXslots	26.50	26.51	26.15	-4.26	22.24	22.25	21.89
	4TXslots	24.28	24.29	23.99	-3.01	21.27	21.28	20.98
EGPRS (8PSK)	1TXslot	25.32	25.38	25.29	-9.03	16.29	16.35	16.26
	2TXslots	24.84	24.65	24.35	-6.02	18.82	18.63	18.33
	3TXslots	24.14	24.02	23.67	-4.26	19.88	19.76	19.41
	4TXslots	22.39	22.49	22.44	-3.01	19.38	19.48	19.43

Note:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

WCDMA Conducted Power

1. The following tests were conducted according to the test requirements outlines in 3GPP TS34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode to determine SAR test exclusion

A summary of the setting are illustrated below:

HSDPA Setup Configuration:

- a) The EUT was connected to base station RS CMU200 referred to the setup configuration
- b) The RF path losses were compensated into the measurements
- c) A call was established between EUT and base station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each specific sub-test in the following table, C10.1.4, Quoted from the TS 34.121
 - ii. Set RMC 12.2Kbps + HSDPA mode
 - iii. Set Cell Power=-86dBm
 - iv. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - v. Select HSDPA uplink parameters
 - vi. Set Delta ACK, Delta NACK and Delta CQI=8
 - vii. Set Ack-Nack repetition Factor to 3
 - viii. Set CQI FeedBack Cycle (K) to 4ms
 - ix. Set CQI repetition factor to 2
 - x. Power ctrl mode= all up bits
- d) The transmitter maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a) The EUT was connected to base station RS CMU200 referred to the setup configuration
- b) The RF path losses were compensated into the measurements
- c) A call was established between EUT and base station with following setting:
 - i. Call configs = 5.2b, 5.9b, 5.10b, and 5.13.2B with QPSK
 - ii. Set Gain Factors (β_c and β_d) and parameters (AG index) were set according to each specific sub-test in the following table, C11.1.3, Quoted from the TS 34.121
 - iii. Set Cell Power=-86dBm
 - iv. Set channel type= 12.2Kbps + HSPA mode
 - v. Set UE Target power
 - vi. Set Ctrl mode=Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal the target E-TFCI of 75 for Sub-test 1, and other subtest's E-TFCI
- d) The transmitter maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{EC}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF1) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

General Note:

- Per KDB 941225 D01, SAR for Head / Hotspot / Body-worn Exposure is measured using a 12.2Kbps RMC with TPC bit configured to all 1s
- Per KDB 941225 D01 RMC12.2Kbps setting is used to evaluate SAR. If the maximum output power and Tune-up tolerance specified for production units in HSDPA/HSUPA is $\leq 1/4$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC 12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

Mode		WCDMA Band II			WCDMA Band V		
		Conducted Power (dBm)			Conducted Power (dBm)		
		CH9262	CH9400	CH9538	CH4132	CH4183	CH4233
		1852.4	1880.0	1907.6	826.4	836.6	846.6
AMR 12.2K		21.84	21.65	21.62	22.75	22.71	22.70
RMC 12.2K		21.86	21.68	21.63	22.78	22.74	22.71
HSDPA	Subtest-1	21.13	21.16	21.37	22.44	22.29	22.33
	Subtest-2	21.05	21.13	21.29	22.36	22.13	22.12
	Subtest-3	21.15	21.17	21.31	22.29	22.15	22.16
	Subtest-4	21.09	21.13	21.24	22.19	22.11	22.14
HSUPA	Subtest-1	18.97	19.08	19.20	20.44	20.24	20.24
	Subtest-2	18.82	19.08	19.10	20.27	20.13	20.09
	Subtest-3	18.46	18.63	18.78	19.94	19.73	19.76
	Subtest-4	19.09	19.25	19.31	20.58	20.42	20.34
	Subtest-5	20.19	20.31	20.36	21.55	21.46	21.37

Mode		WCDMA Band IV		
		Conducted Power (dBm)		
		CH1312	CH1413	CH1513
		1712.4	1732.6	1752.6
AMR 12.2K		21.81	21.87	21.93
RMC 12.2K		21.83	21.90	21.94
HSDPA	Subtest-1	21.57	21.69	21.61
	Subtest-2	21.48	21.51	21.45
	Subtest-3	21.48	21.47	21.46
	Subtest-4	21.43	21.41	21.51
HSUPA	Subtest-1	19.36	19.77	19.37
	Subtest-2	19.18	19.55	19.22
	Subtest-3	18.89	19.30	18.90
	Subtest-4	19.43	19.77	19.49
	Subtest-5	20.44	20.85	20.50

LTE Conducted Power

General Note:

1. CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel, bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.

LTE-FDD Band 2				Actual output Power (dBm)		
Band-width	Modulation	RB allocation	RB offset	Low	Middle	High
1.4	QPSK	1	Low	23.30	23.41	23.19
			Middle	23.32	23.36	23.16
			High	23.31	23.38	23.13
		3	Low	23.13	23.19	23.21
			Middle	23.16	23.22	23.16
			High	23.27	23.19	23.14
		6	/	22.89	22.95	23.25
	16QAM	1	Low	23.05	23.04	23.27
			Middle	23.16	23.29	23.46
			High	23.20	23.18	23.47
		3	Low	22.81	22.98	23.35
			Middle	22.84	23.09	23.40
			High	22.93	23.04	23.37
		6	/	22.49	22.72	22.75
3	QPSK	1	Low	23.37	23.37	23.50
			Middle	23.45	23.45	23.44
			High	23.41	23.40	23.49
		8	Low	22.65	22.59	22.73
			Middle	22.64	22.63	22.84
			High	22.67	22.65	22.91
		15	/	22.65	22.61	22.81
	16QAM	1	Low	23.04	23.02	22.99
			Middle	22.83	22.81	23.02
			High	23.17	23.09	23.23
		8	Low	22.39	22.30	22.21
			Middle	22.40	22.34	22.33
			High	22.41	22.36	22.38
		15	/	22.45	22.25	22.33

5	QPSK	1	Low	23.54	23.40	23.47
			Middle	23.63	23.37	23.56
			High	23.75	23.32	23.62
		12	Low	22.42	22.35	22.19
			Middle	22.56	22.54	22.54
			High	22.50	22.45	22.64
		25	/	22.42	22.41	22.44
	16QAM	1	Low	22.49	22.39	22.18
			Middle	22.82	22.83	22.85
			High	22.54	22.58	22.80
		12	Low	22.31	22.00	21.77
			Middle	22.45	22.20	22.11
			High	22.26	22.10	22.21
		25	/	22.23	22.10	21.97
10	QPSK	1	Low	23.46	23.42	23.12
			Middle	23.55	23.39	23.16
			High	23.52	23.35	23.40
		25	Low	22.63	22.37	21.85
			Middle	22.54	22.50	22.08
			High	22.37	22.60	22.48
		50	/	22.51	22.48	22.16
	16QAM	1	Low	22.47	22.32	21.92
			Middle	22.91	22.87	22.36
			High	22.35	22.38	22.62
		25	Low	22.30	22.00	21.41
			Middle	22.22	22.15	21.61
			High	22.04	22.23	22.02
		50	/	22.19	22.14	21.71

15	QPSK	1	Low	23.53	23.50	23.16
			Middle	23.51	23.42	23.20
			High	23.47	23.34	23.38
		38	Low	22.33	22.27	22.00
			Middle	22.26	22.37	22.02
			High	22.10	22.28	22.03
		75	/	22.12	22.24	22.13
	16QAM	1	Low	22.05	21.75	21.55
			Middle	22.75	22.77	22.05
			High	21.62	21.96	22.26
		38	Low	22.01	21.94	21.58
			Middle	21.94	22.02	21.57
			High	21.82	21.91	21.58
		75	/	21.76	21.87	21.71
20	QPSK	1	Low	23.35	23.29	23.20
			Middle	23.35	23.24	23.23
			High	23.30	23.23	23.44
		50	Low	22.49	22.44	22.24
			Middle	22.43	22.59	22.34
			High	22.23	22.54	22.18
		100	/	22.61	22.64	22.78
	16QAM	1	Low	23.58	23.06	23.23
			Middle	22.88	22.95	22.62
			High	23.16	23.43	23.56
		50	Low	22.18	22.15	21.97
			Middle	22.20	22.26	21.90
			High	21.91	22.18	21.74
		100	/	22.19	22.13	22.24

LTE-FDD Band 4				Actual output Power (dBm)		
Band-width	Modulation	RB allocation	RB offset	Low	Middle	High
1.4	QPSK	1	Low	23.40	23.44	23.56
			Middle	23.34	23.44	23.60
			High	23.34	23.41	23.63
		3	Low	23.34	23.37	23.47
			Middle	23.37	23.40	23.50
			High	23.30	23.33	23.46
		6	/	23.06	23.27	23.27
	16QAM	1	Low	23.12	23.46	23.54
			Middle	23.33	23.67	23.66
			High	23.18	23.76	23.52
		3	Low	23.21	23.27	23.34
			Middle	23.23	23.30	23.37
			High	23.17	23.46	23.32
		6	/	22.60	22.77	23.02
3	QPSK	1	Low	23.23	23.46	23.45
			Middle	23.36	23.51	23.49
			High	23.33	23.60	23.59
		8	Low	22.97	23.10	23.24
			Middle	22.99	23.30	23.22
			High	23.06	23.30	23.27
		15	/	22.99	23.09	23.19
	16QAM	1	Low	23.49	23.42	23.68
			Middle	23.27	23.40	23.40
			High	23.48	23.59	23.71
		8	Low	22.50	22.59	22.91
			Middle	22.54	22.69	22.91
			High	22.58	22.68	22.89
		15	/	22.55	22.63	22.83

5	QPSK	1	Low	23.40	23.36	23.65
			Middle	23.48	23.36	23.62
			High	23.43	23.35	23.62
		12	Low	22.77	22.89	22.95
			Middle	22.97	23.01	23.11
			High	22.80	23.08	23.01
		25	/	22.86	22.88	22.99
	16QAM	1	Low	22.84	22.90	23.05
			Middle	23.24	23.17	23.39
			High	22.98	23.04	23.17
		12	Low	22.44	22.43	22.64
			Middle	22.64	22.55	22.80
			High	22.46	22.49	22.70
		25	/	22.44	22.45	22.62
10	QPSK	1	Low	23.19	23.38	23.34
			Middle	23.25	23.44	23.33
			High	23.23	23.43	23.40
		25	Low	22.86	23.00	23.04
			Middle	23.02	22.98	23.05
			High	23.21	23.08	23.10
		50	/	23.02	22.90	23.05
	16QAM	1	Low	22.79	22.76	22.90
			Middle	23.39	23.22	23.32
			High	22.99	22.79	22.98
		25	Low	22.44	22.54	22.68
			Middle	22.61	22.51	22.70
			High	22.79	22.48	22.73
		50	/	22.63	22.47	22.68

15	QPSK	1	Low	23.18	23.42	23.36
			Middle	23.18	23.41	23.36
			High	23.18	23.52	23.38
		38	Low	22.77	22.82	22.95
			Middle	23.16	22.92	23.05
			High	23.00	22.90	22.96
		75	/	23.06	22.75	22.95
	16QAM	1	Low	22.31	22.65	22.56
			Middle	23.12	23.39	23.34
			High	22.59	22.36	22.67
		38	Low	22.38	22.34	22.45
			Middle	22.76	22.45	22.54
			High	22.65	22.29	22.57
		75	/	22.65	22.28	22.46
20	QPSK	1	Low	23.16	23.17	23.31
			Middle	23.15	23.20	23.38
			High	23.25	23.26	23.47
		50	Low	22.87	22.78	22.88
			Middle	23.03	22.87	23.06
			High	22.90	22.78	22.90
		100	/	23.07	22.84	23.15
	16QAM	1	Low	22.91	22.98	23.21
			Middle	23.44	23.15	23.37
			High	23.10	22.74	23.25
		50	Low	22.49	22.33	22.28
			Middle	22.70	22.43	22.54
			High	22.47	22.17	22.49
		100	/	22.55	22.25	22.49

LTE-FDD Band 5				Actual output Power (dBm)		
Band-width	Modulation	RB allocation	RB offset	Low	Middle	High
1.4	QPSK	1	Low	24.45	24.50	24.34
			Middle	24.51	24.56	24.40
			High	24.51	24.56	24.40
		3	Low	24.37	24.42	24.26
			Middle	24.39	24.44	24.28
			High	24.41	24.46	24.30
		6	/	24.06	24.11	23.96
	16QAM	1	Low	24.37	24.42	24.26
			Middle	24.36	24.41	24.25
			High	24.31	24.36	24.20
		3	Low	24.27	24.32	24.16
			Middle	24.24	24.29	24.14
			High	24.14	24.19	24.04
		6	/	23.54	23.59	23.44
3	QPSK	1	Low	24.70	24.75	24.59
			Middle	24.80	24.85	24.69
			High	24.75	24.80	24.64
		8	Low	24.42	24.47	24.31
			Middle	24.50	24.55	24.39
			High	24.37	24.42	24.26
		15	/	24.31	24.36	24.20
	16QAM	1	Low	24.31	24.36	24.20
			Middle	24.50	24.55	24.39
			High	24.23	24.28	24.13
		8	Low	23.97	24.02	23.87
			Middle	24.04	24.09	23.94
			High	24.14	24.19	24.04
		15	/	23.82	23.87	23.72

5	QPSK	1	Low	24.61	24.66	24.50
			Middle	24.54	24.59	24.43
			High	24.57	24.62	24.46
		12	Low	24.57	24.62	24.46
			Middle	24.40	24.45	24.29
			High	24.28	24.33	24.17
		25	/	24.24	24.29	24.14
	16QAM	1	Low	24.32	24.37	24.21
			Middle	24.31	24.36	24.20
			High	24.36	24.41	24.25
		12	Low	24.06	24.11	23.96
			Middle	24.04	24.09	23.94
			High	24.18	24.23	24.08
		25	/	23.73	23.78	23.63
10	QPSK	1	Low	24.83	24.88	24.72
			Middle	24.79	24.84	24.68
			High	24.86	24.91	24.75
		25	Low	24.72	24.77	24.61
			Middle	24.64	24.69	24.53
			High	24.60	24.65	24.49
		50	/	24.37	24.42	24.26
	16QAM	1	Low	24.39	24.44	24.28
			Middle	24.30	24.35	24.19
			High	24.29	24.34	24.18
		25	Low	24.47	24.52	24.36
			Middle	24.20	24.25	24.10
			High	24.48	24.53	24.37
		50	/	23.87	23.92	23.77

LTE-FDD Band 7				Actual output Power (dBm)		
Band-width	Modulation	RB allocation	RB offset	Low	Middle	High
5	QPSK	1	Low	23.32	23.38	23.23
			Middle	23.36	23.42	23.27
			High	23.30	23.36	23.21
		12	Low	22.70	22.76	22.61
			Middle	22.85	22.91	22.76
			High	22.64	22.70	22.55
		25	/	22.71	22.77	22.62
	16QAM	1	Low	22.89	22.95	22.80
			Middle	22.73	22.79	22.64
			High	22.80	22.86	22.71
		12	Low	22.26	22.31	22.17
			Middle	22.37	22.42	22.28
			High	22.17	22.22	22.08
		25	/	22.13	22.18	22.04
10	QPSK	1	Low	23.22	23.28	23.13
			Middle	23.31	23.37	23.22
			High	23.23	23.29	23.14
		25	Low	22.78	22.84	22.69
			Middle	22.76	22.82	22.67
			High	22.66	22.72	22.57
		50	/	22.73	22.79	22.64
	16QAM	1	Low	22.45	22.50	22.36
			Middle	22.57	22.63	22.48
			High	22.73	22.79	22.64
		25	Low	22.23	22.28	22.14
			Middle	22.19	22.24	22.10
			High	22.09	22.14	22.00
		50	/	22.18	22.23	22.09

15	QPSK	1	Low	23.41	23.47	23.32
			Middle	23.27	23.33	23.18
			High	23.36	23.42	23.27
		38	Low	22.47	22.52	22.38
			Middle	22.72	22.78	22.63
			High	22.81	22.87	22.72
		75	/	22.56	22.62	22.47
	16QAM	1	Low	22.20	22.25	22.11
			Middle	22.29	22.34	22.20
			High	22.39	22.44	22.30
		38	Low	22.05	22.10	21.96
			Middle	22.12	22.17	22.03
			High	22.32	22.37	22.23
		75	/	21.98	22.03	21.89
20	QPSK	1	Low	23.50	23.56	23.41
			Middle	23.43	23.49	23.34
			High	23.52	23.58	23.43
		50	Low	22.45	22.50	22.36
			Middle	22.69	22.75	22.60
			High	22.76	22.82	22.67
		100	/	22.74	22.80	22.65
	16QAM	1	Low	22.95	23.01	22.86
			Middle	23.03	23.09	22.94
			High	23.05	23.11	22.96
		50	Low	22.08	22.13	21.99
			Middle	22.11	22.16	22.02
			High	22.28	22.33	22.19
		100	/	21.99	22.04	21.90

WLAN Conducted Power

For 2.4GHz WLAN SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were for SAR evaluation. 802.11g/n were not investigated since the average putput powers over all channels and data rates were not more than 0.25dB higher than the tested channel in the lowest data rate of 802.11b mode.

WIFI 2.4G			
Mode	Channel	Frequency (MHz)	Conducted Average Power (dBm)
802.11b	01	2412	11.68
	06	2437	11.14
	11	2462	11.40
802.11g	01	2412	9.10
	06	2437	8.91
	11	2462	9.54
802.11n(HT20)	01	2412	8.65
	06	2437	8.42
	11	2462	8.98

Note: The output power was test all data rate and recorded worst case at recorded data rate.

Bluetooth Conducted Power

Bluetooth			
Mode	Channel	Frequency (MHz)	Conducted power (dBm)
GFSK	0	2402	-3.04
	39	2441	-2.01
	78	2480	-1.36
$\pi/4$ QPSK	0	2402	-1.43
	39	2441	-0.97
	78	2480	0.22
8DPSK	0	2402	-1.09
	39	2441	-0.60
	78	2480	0.50
BLE	0	2402	-9.69
	19	2440	-9.34
	39	2480	-8.01

12. Maximum Tune-up Limit

GSM		
Mode	Maximum Tune-up (dBm)	
	GSM850	PCS1900
GSM (GMSK, 1Tx Slot)	33.00	29.50
GPRS (GMSK, 1Tx Slot)	33.00	29.50
GPRS (GMSK, 2Tx Slot)	32.50	28.50
GPRS (GMSK, 3Tx Slot)	31.00	27.00
GPRS (GMSK, 4Tx Slot)	28.50	24.50
EGPRS (8PSK, 1Tx Slot)	28.00	25.50
EGPRS (8PSK, 2Tx Slot)	27.20	25.00
EGPRS (8PSK, 3Tx Slot)	26.00	24.50
EGPRS (8PSK, 4Tx Slot)	25.00	23.00

WCDMA			
Mode	Maximum Tune-up (dBm)		
	WCDMA Band II	WCDMA Band IV	WCDMA Band V
AMR 12.2Kbps	22.00	22.00	23.00
RMC 12.2Kbps	22.00	22.00	23.00
HSDPA Subtest-1	21.50	22.00	22.50
HSDPA Subtest-2	21.50	22.00	22.50
HSDPA Subtest-3	21.50	22.00	22.50
HSDPA Subtest-4	21.50	22.00	22.50
HSUPA Subtest-1	19.50	20.00	20.50
HSUPA Subtest-2	19.50	20.00	20.50
HSUPA Subtest-3	19.00	19.50	20.00
HSUPA Subtest-4	19.50	20.00	21.00
HSUPA Subtest-5	20.50	21.00	22.00

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
LTE Band 2	1.4	QPSK	1	23.50
			3	23.50
			6	23.50
		16QAM	1	23.50
			3	23.50
			6	23.00
	3	QPSK	1	23.50
			8	23.00
			15	23.00
		16QAM	1	23.30
			8	22.50
			15	22.50
	5	QPSK	1	24.00
			12	23.00
			25	23.00
		16QAM	1	23.00
			12	22.50
			25	22.50
	10	QPSK	1	24.00
			25	23.00
			50	23.00
		16QAM	1	23.00
			25	22.50
			50	22.50
	15	QPSK	1	24.00
			38	23.00
			75	23.00
		16QAM	1	22.50
			38	22.50
			75	22.50
	20	QPSK	1	24.00
			50	23.00
			100	23.00
		16QAM	1	23.50
			50	22.50
			100	22.50

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
LTE Band 4	1.4	QPSK	1	24.00
			3	23.50
			6	23.50
		16QAM	1	24.00
			3	23.50
			6	23.50
	3	QPSK	1	24.00
			8	23.50
			15	23.50
		16QAM	1	24.00
			8	23.00
			15	23.00
	5	QPSK	1	24.00
			12	23.50
			25	23.50
		16QAM	1	24.00
			12	23.00
			25	23.00
	10	QPSK	1	24.00
			25	23.50
			50	23.50
		16QAM	1	24.00
			25	23.00
			50	23.00
	15	QPSK	1	24.00
			38	23.50
			75	23.50
		16QAM	1	24.00
			38	23.00
			75	23.00
	20	QPSK	1	24.00
			50	23.50
			100	23.50
		16QAM	1	24.00
			50	23.00
			100	23.00

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
LTE Band 5	1.4	QPSK	1	25.00
			3	25.00
			6	24.50
		16QAM	1	24.50
			3	24.50
			6	24.00
	3	QPSK	1	25.00
			8	25.00
			15	24.50
		16QAM	1	24.50
			8	24.50
			15	24.00
	5	QPSK	1	25.00
			12	25.00
			25	24.50
		16QAM	1	24.50
			12	24.50
			25	24.00
	10	QPSK	1	25.00
			25	25.00
			50	24.50
		16QAM	1	24.50
			25	24.50
			50	24.00

LTE				
Frequency Band	Band-width(MHz)	Modulation	RB allocation	Maximum Tune-up (dBm)
LTE Band 7	5	QPSK	1	24.00
			12	23.00
			25	23.00
		16QAM	1	23.00
			12	23.00
			25	22.50
	10	QPSK	1	24.00
			25	23.00
			50	23.00
		16QAM	1	23.00
			25	23.00
			50	22.50
	15	QPSK	1	24.00
			38	23.00
			75	23.00
		16QAM	1	23.00
			38	23.00
			75	22.50
	20	QPSK	1	24.00
			50	23.00
			100	23.00
		16QAM	1	23.00
			50	23.00
			100	22.50

LTE MPR will followup 3GPP setting as below:

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	1.4MHz	3.0MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

WIFI 2.4G	
Mode	Maximum Tune-up (dBm) Burst Average Power
802.11b	12.00
802.11g	10.00
802.11n(HT20)	9.00

Bluetooth	
Mode	Maximum Tune-up (dBm)
GFSK	-1.20
$\pi/4$ QPSK	0.30
8DPSK	0.50
BLE	-8.00

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm are determined by:


$[(\text{max. Power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

Band/Mode	F(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.45	Head	10	0.50	1.12	Yes
		Body	19	0.50	1.12	Yes

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5mm is applied to determine SAR test exclusion.

The test exclusion threshold is ≤ 3 , SAR testing is not required.

13. Antenna Location



Distance of the Antenna to the EUT surface/edge(mm)						
Antenna	Rear	Front	Top side	Bottom side	Right side	Left side
WWAN	3	4	135	2	23	2
WIFI/BT	3	4	2	130	2	57

Positions for SAR tests; Hotspot mode						
Antenna	Rear	Front	Top side	Bottom side	Right side	Left side
WWAN	Yes	Yes	No	Yes	Yes	Yes
WIFI/BT	Yes	Yes	Yes	No	Yes	No

General note:

Referring to KDB941225 D06, when the overall device length and width are >9cm*5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

14. SAR Measurement Results

Head SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (3Tx slot)	Left-Cheek	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	0.05	0.175	0.206	H1
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Left-Tilt	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	-0.06	0.134	0.158	-
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Right-Cheek	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	-0.02	0.162	0.191	-
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Right-Tilt	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	0.03	0.123	0.145	-
		251	848.8	30.24	31.00	1.19	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (2Tx slot)	Left-Cheek	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	0.13	0.168	0.175	H2
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Left-Tilt	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	0.09	0.135	0.141	-
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Right-Cheek	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	-0.07	0.161	0.168	-
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Right-Tilt	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	-0.08	0.127	0.132	-
		810	1909.8	27.67	28.50	1.21	-	-	-	-

Note:

Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2K bps	Left-Cheek	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	-0.19	0.315	0.339	H3
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Left-Tilt	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	-0.16	0.259	0.279	-
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Right-Cheek	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	-0.07	0.301	0.324	-
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Right-Tilt	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	0.08	0.241	0.259	-
		9538	1907.6	21.63	22.00	1.09	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2K bps	Left-Cheek	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	0.14	0.350	0.358	H4
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Left-Tilt	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	0.12	0.288	0.295	-
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Right-Cheek	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	0.19	0.334	0.342	-
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Right-Tilt	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	-0.06	0.268	0.274	-
		1513	1752.6	21.94	22.00	1.01	-	-	-	-

Note:

Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2K bps	Left-Cheek	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.13	0.201	0.213	H5
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Left-Tilt	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.07	0.162	0.172	-
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Right-Cheek	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	-0.18	0.194	0.206	-
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Right-Tilt	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	-0.07	0.153	0.162	-
		4233	846.6	22.71	23.00	1.07	-	-	-	-

Note:

Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1 RB	Left-Cheek	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	0.11	0.211	0.248	H6
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Left-Tilt	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	-0.08	0.173	0.203	-
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Right-Cheek	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	-0.05	0.206	0.242	-
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Right-Tilt	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	0.06	0.164	0.193	-
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
20M_5 0RB	Left-Cheek	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	0.14	0.147	0.162	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-
	Left-Tilt	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	-0.07	0.129	0.142	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-
	Right-Cheek	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	-0.06	0.136	0.149	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-
	Right-Tilt	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	0.05	0.116	0.127	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1 RB	Left-Cheek	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.03	0.239	0.283	H7
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Left-Tilt	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	0.00	0.179	0.212	-
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Right-Cheek	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	0.01	0.232	0.275	-
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Right-Tilt	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.01	0.180	0.213	-
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
20M_5 0RB	Left-Cheek	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	0.08	0.198	0.209	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-
	Left-Tilt	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	-0.06	0.156	0.165	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-
	Right-Cheek	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	-0.04	0.180	0.190	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-
	Right-Tilt	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	0.05	0.128	0.135	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
10M_1 RB	Left-Cheek	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	0.12	0.130	0.133	H8
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Left-Tilt	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	0.06	0.109	0.111	-
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Right-Cheek	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	-0.09	0.126	0.128	-
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Right-Tilt	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	0.04	0.100	0.102	-
		20600	844.0	24.75	25.00	1.06	-	-	-	-
10M_2 5RB	Left-Cheek	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	0.09	0.124	0.131	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-
	Left-Tilt	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	-0.05	0.096	0.101	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-
	Right-Cheek	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	0.04	0.123	0.130	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-
	Right-Tilt	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	0.05	0.101	0.106	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1 RB	Left-Cheek	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	-0.14	0.138	0.152	H9
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Left-Tilt	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	-0.01	0.121	0.133	-
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Right-Cheek	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	0.06	0.133	0.146	-
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Right-Tilt	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	-0.05	0.113	0.125	-
		21350	2560	23.43	24.00	1.14	-	-	-	-
20M_5 0RB	Left-Cheek	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	0.06	0.101	0.105	-
		21350	2560	22.67	23.00	1.08	-	-	-	-
	Left-Tilt	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	-0.02	0.092	0.096	-
		21350	2560	22.67	23.00	1.08	-	-	-	-
	Right-Cheek	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	0.01	0.096	0.100	-
		21350	2560	22.67	23.00	1.08	-	-	-	-
	Right-Tilt	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	-0.03	0.079	0.082	-
		21350	2560	22.67	23.00	1.08	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

WIFI 2.4G										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
802.11b 1Mbps	Left-Cheek	01	2412	11.68	12.00	1.08	-0.09	0.374	0.403	H10
		06	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Left-Tilt	01	2412	11.68	12.00	1.08	0.12	0.317	0.341	-
		06	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Right-Cheek	01	2412	11.68	12.00	1.08	0.05	0.359	0.387	-
		06	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Right-Tilt	01	2412	11.68	12.00	1.08	-0.06	0.302	0.325	-
		06	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-

Note:

- According to the above table, the initial test position for head is "LeftCheek", and its reported SAR is $\leq 0.4\text{W/kg}$. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposureconfiguration is $\leq 0.8\text{W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposureconfiguration.
- When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.
 - When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
 - When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{ W/kg}$, the 802.11g/n is not required.

WIFI 2.4G- Scaled Reported SAR							
Mode	Test Position	Frequency		Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
		CH	MHz				
802.11b 1Mbps	Left-Cheek	1	2412	98.69%	100%	0.403	0.408
	Left-Tilt	1	2412	98.69%	100%	0.341	0.346
	Right-Cheek	1	2412	98.69%	100%	0.387	0.392
	Right-Tilt	1	2412	98.69%	100%	0.325	0.329

Note:

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 98.69% is achievable for WLAN in this project.

Body SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (3Tx slot)	Front	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	-0.08	0.277	0.326	-
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Rear	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	0.16	0.419	0.493	B1
		251	848.8	30.24	31.00	1.19	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (2Tx slot)	Front	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	-0.07	0.183	0.191	-
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Rear	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	0.10	0.289	0.301	B2
		810	1909.8	27.67	28.50	1.21	-	-	-	-

Note:

- Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	0.04	0.305	0.329	-
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Rear	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	-0.11	0.429	0.462	B3
		9538	1907.6	21.63	22.00	1.09	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	0.03	0.370	0.379	-
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Rear	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	-0.07	0.520	0.532	B4
		1513	1752.6	21.94	22.00	1.01	-	-	-	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.01	0.184	0.195	-
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Rear	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.03	0.299	0.317	B5
		4233	846.6	22.71	23.00	1.07	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	-0.01	0.226	0.266	-
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Rear	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	0.03	0.376	0.443	B6
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
20M_50RB	Front	18700	1860.0	22.43	23.00	1.18	-	-	-	-
		18900	1880.0	22.59	23.00	1.18	-0.02	0.175	0.192	-
		19100	1900.0	22.34	23.00	1.18	-	-	-	-
	Rear	18700	1860.0	22.43	23.00	1.18	-	-	-	-
		18900	1880.0	22.59	23.00	1.14	0.12	0.309	0.340	-
		19100	1900.0	22.34	23.00	1.10	-	-	-	-

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.01	0.171	0.203	-
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Rear	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.05	0.367	0.435	B7
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
20M_50RB	Front	20050	1720.0	23.03	23.10	1.19	-	-	-	-
		20175	1732.5	22.87	23.10	1.19	-0.02	0.144	0.151	-
		20300	1745.0	23.06	23.10	1.19	-	-	-	-
	Rear	20050	1720.0	23.03	23.10	1.19	-	-	-	-
		20175	1732.5	22.87	23.10	1.02	0.11	0.329	0.347	-
		20300	1745.0	23.06	23.10	1.05	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
10M_1RB	Front	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	0.03	0.138	0.141	-
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Rear	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	-0.05	0.205	0.209	B8
		20600	844.0	24.75	25.00	1.06	-	-	-	-
10M_25RB	Front	20450	829.0	24.72	25.00	1.02	-	-	-	-
		20525	836.5	24.77	25.00	1.02	-0.09	0.108	0.114	-
		20600	844.0	24.61	25.00	1.02	-	-	-	-
	Rear	20450	829.0	24.72	25.00	1.02	-	-	-	-
		20525	836.5	24.77	25.00	1.07	0.14	0.197	0.208	-
		20600	844.0	24.61	25.00	1.05	-	-	-	-

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	0.01	0.493	0.543	-
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Rear	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	-0.05	0.698	0.769	B9
		21350	2560	23.43	24.00	1.14	-	-	-	-
20M_50RB	Front	20850	2510	22.76	23.00	1.10	-	-	-	-
		21100	2535	22.82	23.00	1.10	-0.03	0.406	0.424	-
		21350	2560	22.67	23.00	1.10	-	-	-	-
	Rear	20850	2510	22.76	23.00	1.10	-	-	-	-
		21100	2535	22.82	23.00	1.06	0.11	0.597	0.622	-
		21350	2560	22.67	23.00	1.04	-	-	-	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

WIFI 2.4G										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
802.11b 1Mbps	Front	1	2412	11.68	12.00	1.08	0.15	0.138	0.148	-
		6	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Rear	1	2412	11.68	12.00	1.08	-0.10	0.202	0.218	B10
		6	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-

Note:

1. According to the above table, the initial test position for body is "Rear", and its reported SAR is $\leq 0.4\text{W/kg}$. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8\text{W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposure configuration.

WIFI 2.4G- Scaled Reported SAR							
Mode	Test Position	Frequency		Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
		CH	MHz				
802.11b 1Mbps	Front	1	2412	98.69%	100%	0.148	0.150
	Rear	1	2412	98.69%	100%	0.218	0.220

Note:

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 98.69% is achievable for WLAN in this project.

Hotspot SAR

Positions for SAR tests; Hotspot mode						
Antenna	Rear	Front	Top side	Bottom side	Right side	Left side
WWAN	Yes	Yes	No	Yes	Yes	Yes
WIFI / BT	Yes	Yes	Yes	No	Yes	No

General note:

Referring to KDB941225 D06, when the overall device length and width are >9cm*5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (3Tx slot)	Front	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	-0.08	0.277	0.326	-
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Rear	128	824.2	30.51	31.00	1.12	-	-	-	-
		190	836.6	30.29	31.00	1.18	0.16	0.419	0.493	B1
		251	848.8	30.24	31.00	1.19	-	-	-	-
	Left	190	836.6	30.29	31.00	1.18	-0.09	0.300	0.353	-
	Right	190	836.6	30.29	31.00	1.18	0.06	0.134	0.157	-
	Top	190	836.6	30.29	31.00	1.18	-	-	-	-
	Bottom	190	836.6	30.29	31.00	1.18	0.06	0.285	0.336	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
GPRS (2Tx slot)	Front	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	-0.07	0.183	0.191	-
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Rear	512	1850.2	28.14	28.50	1.09	-	-	-	-
		661	1880.0	28.32	28.50	1.04	0.10	0.289	0.301	B2
		810	1909.8	27.67	28.50	1.21	-	-	-	-
	Left	661	1880.0	28.32	28.50	1.04	-0.05	0.175	0.182	-
	Right	661	1880.0	28.32	28.50	1.04	-0.03	0.096	0.100	-
	Top	661	1880.0	28.32	28.50	1.04	-	-	-	-
	Bottom	661	1880.0	28.32	28.50	1.04	0.10	0.182	0.189	-

Note:

Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	0.04	0.305	0.329	-
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Rear	9262	1852.4	21.86	22.00	1.03	-	-	-	-
		9400	1880.0	21.68	22.00	1.08	-0.11	0.429	0.462	B3
		9538	1907.6	21.63	22.00	1.09	-	-	-	-
	Left	9400	1880.0	21.68	22.00	1.08	-0.05	0.292	0.314	-
	Right	9400	1880.0	21.68	22.00	1.08	0.12	0.160	0.172	-
	Top	9400	1880.0	21.68	22.00	1.08	-	-	-	-
	Bottom	9400	1880.0	21.68	22.00	1.08	0.03	0.282	0.304	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	0.03	0.370	0.379	-
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Rear	1312	1712.4	21.83	22.00	1.04	-	-	-	-
		1413	1732.6	21.90	22.00	1.02	-0.07	0.520	0.532	B4
		1513	1752.6	21.94	22.00	1.01	-	-	-	-
	Left	1413	1732.6	21.90	22.00	1.02	-0.03	0.354	0.362	-
	Right	1413	1732.6	21.90	22.00	1.02	0.07	0.194	0.199	-
	Top	1413	1732.6	21.90	22.00	1.02	-	-	-	-
	Bottom	1413	1732.6	21.90	22.00	1.02	0.02	0.342	0.350	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
RMC 12.2Kbps	Front	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.01	0.184	0.195	-
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Rear	4132	826.4	22.78	23.00	1.05	-	-	-	-
		4183	836.6	22.74	23.00	1.06	0.03	0.299	0.317	B5
		4233	846.6	22.71	23.00	1.07	-	-	-	-
	Left	4183	836.6	22.74	23.00	1.06	-0.02	0.182	0.193	-
	Right	4183	836.6	22.74	23.00	1.06	0.04	0.112	0.118	-
	Top	4183	836.6	22.74	23.00	1.06	-	-	-	-
	Bottom	4183	836.6	22.74	23.00	1.06	0.02	0.181	0.192	-

Note:

Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	-0.01	0.226	0.266	-
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Rear	18700	1860.0	23.35	24.00	1.16	-	-	-	-
		18900	1880.0	23.29	24.00	1.18	0.03	0.376	0.443	B6
		19100	1900.0	23.20	24.00	1.20	-	-	-	-
	Left	18900	1880.0	23.29	24.00	1.18	-0.02	0.217	0.256	-
	Right	18900	1880.0	23.29	24.00	1.18	0.01	0.164	0.194	-
	Top	18900	1880.0	23.29	24.00	1.18	-	-	-	-
	Bottom	18900	1880.0	23.29	24.00	1.18	0.03	0.236	0.277	-
20M_50RB	Front	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	-0.02	0.175	0.192	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-
	Rear	18700	1860.0	22.43	23.00	1.14	-	-	-	-
		18900	1880.0	22.59	23.00	1.10	0.12	0.309	0.340	-
		19100	1900.0	22.34	23.00	1.16	-	-	-	-
	Left	18900	1880.0	22.59	23.00	1.10	-0.03	0.200	0.220	-
	Right	18900	1880.0	22.59	23.00	1.10	-0.03	0.125	0.137	-
	Top	18900	1880.0	22.59	23.00	1.10	-	-	-	-
	Bottom	18900	1880.0	22.59	23.00	1.10	0.12	0.195	0.215	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.01	0.171	0.203	-
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Rear	20050	1720.0	23.25	24.00	1.19	-	-	-	-
		20175	1732.5	23.26	24.00	1.19	-0.05	0.367	0.435	B7
		20300	1745.0	23.47	24.00	1.13	-	-	-	-
	Left	20175	1732.5	23.26	24.00	1.19	0.04	0.222	0.263	-
	Right	20175	1732.5	23.26	24.00	1.19	-0.01	0.151	0.179	-
	Top	20175	1732.5	23.26	24.00	1.19	-	-	-	-
	Bottom	20175	1732.5	23.26	24.00	1.19	-0.02	0.225	0.267	-
20M_50RB	Front	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	-0.02	0.144	0.151	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-
	Rear	20050	1720.0	23.03	23.10	1.02	-	-	-	-
		20175	1732.5	22.87	23.10	1.05	0.11	0.329	0.347	-
		20300	1745.0	23.06	23.10	1.01	-	-	-	-
	Left	20175	1732.5	22.87	23.10	1.05	-0.07	0.224	0.236	-
	Right	20175	1732.5	22.87	23.10	1.05	0.01	0.131	0.138	-
	Top	20175	1732.5	22.87	23.10	1.05	-	-	-	-
	Bottom	20175	1732.5	22.87	23.10	1.05	0.03	0.218	0.230	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
10M_1RB	Front	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	0.03	0.138	0.141	-
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Rear	20450	829.0	24.86	25.00	1.03	-	-	-	-
		20525	836.5	24.91	25.00	1.02	-0.05	0.205	0.209	B8
		20600	844.0	24.75	25.00	1.06	-	-	-	-
	Left	20525	836.5	24.91	25.00	1.02	0.02	0.145	0.148	-
	Right	20525	836.5	24.91	25.00	1.02	-0.02	0.089	0.091	-
	Top	20525	836.5	24.91	25.00	1.02	-	-	-	-
	Bottom	20525	836.5	24.91	25.00	1.02	-0.03	0.124	0.127	-
10M_25RB	Front	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	-0.09	0.108	0.114	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-
	Rear	20450	829.0	24.72	25.00	1.07	-	-	-	-
		20525	836.5	24.77	25.00	1.05	0.14	0.197	0.208	-
		20600	844.0	24.61	25.00	1.09	-	-	-	-
	Left	20525	836.5	24.77	25.00	1.05	-0.11	0.130	0.137	-
	Right	20525	836.5	24.77	25.00	1.05	0.05	0.086	0.090	-
	Top	20525	836.5	24.77	25.00	1.05	-	-	-	-
	Bottom	20525	836.5	24.77	25.00	1.05	0.02	0.108	0.114	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
20M_1RB	Front	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	0.01	0.493	0.543	-
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Rear	20850	2510	23.52	24.00	1.12	-	-	-	-
		21100	2535	23.58	24.00	1.10	-0.05	0.698	0.769	B9
		21350	2560	23.43	24.00	1.14	-	-	-	-
	Left	21100	2535	23.58	24.00	1.10	0.02	0.436	0.480	-
	Right	21100	2535	23.58	24.00	1.10	-0.01	0.242	0.267	-
	Top	21100	2535	23.58	24.00	1.10	-	-	-	-
	Bottom	21100	2535	23.58	24.00	1.10	-0.01	0.377	0.416	-
20M_50RB	Front	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	-0.03	0.406	0.424	-
		21350	2560	22.67	23.00	1.08	-	-	-	-
	Rear	20850	2510	22.76	23.00	1.06	-	-	-	-
		21100	2535	22.82	23.00	1.04	0.11	0.597	0.622	-
		21350	2560	22.67	23.00	1.08	-	-	-	-
	Left	21100	2535	22.82	23.00	1.04	-0.03	0.343	0.357	-
	Right	21100	2535	22.82	23.00	1.04	0.03	0.240	0.250	-
	Top	21100	2535	22.82	23.00	1.04	-	-	-	-
	Bottom	21100	2535	22.82	23.00	1.04	0.15	0.314	0.327	-

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

WIFI 2.4G										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Test Plot
		CH	MHz							
802.11b 1Mbps	Front	1	2412	11.68	12.00	1.08	0.15	0.138	0.148	-
		6	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Rear	1	2412	11.68	12.00	1.08	-0.10	0.202	0.218	B10
		6	2437	11.14	12.00	1.22	-	-	-	-
		11	2462	11.40	12.00	1.15	-	-	-	-
	Left	1	2412	11.68	12.00	1.08	-	-	-	-
	Right	1	2412	11.68	12.00	1.08	-0.07	0.169	0.182	-
	Top	1	2412	11.68	12.00	1.08	0.03	0.133	0.143	-
	Bottom	1	2412	11.68	12.00	1.08	-	-	-	-

Note:

- According to the above table, the initial test position for body is "Rear", and its reported SAR is $\leq 0.4\text{W/kg}$. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8\text{W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.
 - When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
 - When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{ W/kg}$, the 802.11g/n is not required

WIFI 2.4G- Scaled Reported SAR							
Mode	Test Position	Frequency		Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
		CH	MHz				
802.11b 1Mbps	Front	6	2437	98.69%	100%	0.148	0.150
	Rear	6	2437	98.69%	100%	0.218	0.220
	Right	6	2437	98.69%	100%	0.182	0.184
	Top	6	2437	98.69%	100%	0.143	0.145

Note:

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 98.69% is achievable for WLAN in this project.

SAR Test Data Plots

Test mode: GPRS850 3Tx slot

Test Position: Left Cheek Touch

Test Plot: H1

Date:2018-05-09

Communication System: UID 0, Generic GPRS(TDMA, GMSK, TN 0-1-2) (0); Frequency: 836.6 MHz;Duty Cycle: 1:2.67

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.933$ S/m; $\epsilon_r = 43.899$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.73, 10.73, 10.73); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mmInfo: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.214 W/kg


Left/Procedure/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.864 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.218 W/kg

SAR(1 g) = 0.175 W/kg; SAR(10 g) = 0.136 W/kgInfo: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.203 W/kg



0 dB = 0.203 W/kg = -6.93 dBW/kg

Test mode: GPRS1900 2Tx slot	Test Position: Left Cheek Touch	Test Plot: H2
------------------------------	---------------------------------	---------------

Date: 2018-05-14


Communication System: UID 0, Generic GPRS(TDMA, GMSK, TN 0-1) (0); Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 41.738$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.83, 8.83, 8.83); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.235 W/kg **Left/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 4.565 V/m ; Power Drift = 0.13 dB Peak SAR (extrapolated) = 0.266 W/kg **SAR(1 g) = 0.168 W/kg ; SAR(10 g) = 0.106 W/kg** Maximum value of SAR (measured) = 0.230 W/kg 0 dB = 0.230 W/kg = -6.38 dBW/kg

Test mode: WCDMA Band II

Test Position: Left Cheek Touch

Test Plot: H3

Date: 2018-05-14

Communication System: UID 0, Generic UMTS (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.455$ S/m; $\epsilon_r = 41.738$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.83, 8.83, 8.83); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.454 W/kg


Left/Procedure/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.274 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.492 W/kg

SAR(1 g) = 0.315 W/kg; SAR(10 g) = 0.200 W/kg

Maximum value of SAR (measured) = 0.427 W/kg



0 dB = 0.427 W/kg = -3.70 dBW/kg

Test mode: WCDMA Band IV

Test Position: Left Cheek Touch

Test Plot: H4

Date: 2018-05-09


Communication System: UID 0, Generic UMTS (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.6 \text{ MHz}$; $\sigma = 1.364 \text{ S/m}$; $\epsilon_r = 41.972$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.73, 10.73, 10.73); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (interpolated) = 0.492 W/kg **Left/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 5.180 V/m ; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.529 W/kg **SAR(1 g) = 0.350 W/kg ; SAR(10 g) = 0.230 W/kg** [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (measured) = 0.467 W/kg 0 dB = 0.467 W/kg = -3.31 dBW/kg

Test mode: WCDMA Band V

Test Position: Left Cheek Touch

Test Plot: H5

Date: 2018-05-09


Communication System: UID 0, Generic UMTS (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.933 \text{ S/m}$; $\epsilon_r = 43.899$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.73, 10.73, 10.73); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (interpolated) = 0.239 W/kg **Left/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 5.543 V/m ; Power Drift = 0.13 dB Peak SAR (extrapolated) = 0.258 W/kg **SAR(1 g) = 0.201 W/kg ; SAR(10 g) = 0.153 W/kg** [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (measured) = 0.239 W/kg 0 dB = 0.239 W/kg = -6.22 dBW/kg

Test mode: LTE Band 2

Test Position: Left Cheek Touch

Test Plot: H6

Date: 2018-05-14


Communication System: UID 0, Generic LTE-FDD (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.455 \text{ S/m}$; $\epsilon_r = 41.738$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.83, 8.83, 8.83); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.295 W/kg **Left/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 6.417 V/m ; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.321 W/kg **SAR(1 g) = 0.211 W/kg ; SAR(10 g) = 0.140 W/kg** Maximum value of SAR (measured) = 0.282 W/kg 0 dB = 0.282 W/kg = -5.50 dBW/kg

Test mode: LTE Band 4

Test Position: Left Cheek Touch

Test Plot: H7

Date: 2018-05-11

Communication System: UID 0, Generic LTE-FDD (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.363$ S/m; $\epsilon_r = 41.972$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(9.23, 9.23, 9.23); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.321 W/kg


Left/Procedure/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.263 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.239 W/kg; SAR(10 g) = 0.161 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.311 W/kg



Test mode: LTE Band 5

Test Position: Left Cheek Touch

Test Plot: H8

Date: 2018-05-09

Communication System: UID 0, Generic LTE-FDD (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.933$ S/m; $\epsilon_r = 43.899$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.73, 10.73, 10.73); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.156 W/kg


Left/Procedure/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.360 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.163 W/kg

SAR(1 g) = 0.130 W/kg; SAR(10 g) = 0.105 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.150 W/kg



0 dB = 0.150 W/kg = -8.24 dBW/kg

Test mode: LTE Band 7

Test Position: Left Cheek Touch

Test Plot: H9

Date: 2018-05-16


Communication System: UID 0, Generic LTE-FDD (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535 \text{ MHz}$; $\sigma = 1.914 \text{ S/m}$; $\epsilon_r = 40.778$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.92, 7.92, 7.92); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Left/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.187 W/kg **Left/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 2.696 V/m ; Power Drift = -0.14 dB Peak SAR (extrapolated) = 0.256 W/kg **SAR(1 g) = 0.138 W/kg ; SAR(10 g) = 0.075 W/kg** Maximum value of SAR (measured) = 0.210 W/kg 0 dB = 0.210 W/kg = -6.78 dBW/kg

Test mode: WLAN 802.11b

Test Position: Left Cheek Touch

Test Plot: H10

Date: 2018-05-16

Communication System: UID 0, Generic WIFI (0); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.829$ S/m; $\epsilon_r = 41.002$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.27, 8.27, 8.27); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Front/Procedure/Area Scan (71x151x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.521 W/kg


Front/Procedure/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.890 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.663 W/kg

SAR(1 g) = 0.374 W/kg; SAR(10 g) = 0.171 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.527 W/kg



0 dB = 1.27 W/kg = 1.04 dBW/kg

Test mode: GPRS850 3Tx slot

Test Position: Body- worn Rear

Test Plot: B1

Date:2018-05-10

Communication System: UID 0, Generic GPRS(TDMA, GMSK, TN 0-1-2) (0); Frequency: 836.6 MHz;Duty Cycle: 1:2.67

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.967$ S/m; $\epsilon_r = 55.399$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.5, 10.5, 10.5); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.501 W/kg


Rear/Procedure/Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.87 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.419 W/kg; SAR(10 g) = 0.319 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.510 W/kg



0 dB = 0.510 W/kg = -2.92 dBW/kg

Test mode: GPRS1900 2Tx slot

Test Position: Body- worn Rear

Test Plot: B2

Date:2018-05-15


Communication System: UID 0, Generic GPRS(TDMA, GMSK, TN 0-1) (0); Frequency: 1880 MHz;Duty Cycle: 1:4

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 53.741$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.42, 8.42, 8.42); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.423 W/kg **Rear/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 8.631 V/m ; Power Drift = 0.10 dB Peak SAR (extrapolated) = 0.477 W/kg **SAR(1 g) = 0.289 W/kg ; SAR(10 g) = 0.173 W/kg** Maximum value of SAR (measured) = 0.396 W/kg 0 dB = 0.816 W/kg = -0.88 dBW/kg

Test mode: WCDMA Band II

Test Position: Body- worn Rear

Test Plot: B3

Date:2018-05-15

Communication System: UID 0, Generic UMTS (0); Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.539$ S/m; $\epsilon_r = 53.741$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.42, 8.42, 8.42); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.636 W/kg


Rear/Procedure/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.68 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.715 W/kg

SAR(1 g) = 0.429 W/kg; SAR(10 g) = 0.255 W/kg

Maximum value of SAR (measured) = 0.597 W/kg



0 dB = 0.597 W/kg = -2.24 dBW/kg

Test mode: WCDMA Band IV

Test Position: Body- worn Rear

Test Plot: B4

Date:2018-05-10


Communication System: UID 0, Generic UMTS (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.6 \text{ MHz}$; $\sigma = 1.43 \text{ S/m}$; $\epsilon_r = 53.891$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.5, 10.5, 10.5); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (interpolated) = 0.693 W/kg **Rear/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 10.08 V/m ; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.805 W/kg **SAR(1 g) = 0.520 W/kg ; SAR(10 g) = 0.342 W/kg** [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (measured) = 0.698 W/kg 

Test mode: WCDMA Band V

Test Position: Body- worn Rear

Test Plot: B5

Date:2018-05-10


Communication System: UID 0, Generic UMTS (0); Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.967 \text{ S/m}$; $\epsilon_r = 55.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.5, 10.5, 10.5); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (interpolated) = 0.364 W/kg **Rear/Procedure/Zoom Scan (6x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 19.94 V/m ; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.399 W/kg **SAR(1 g) = 0.299 W/kg ; SAR(10 g) = 0.231 W/kg** [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (measured) = 0.361 W/kg 

Test mode: LTE Band 2

Test Position: Body- worn Rear

Test Plot: B6

Date:2018-05-15


Communication System: UID 0, Generic LTE-FDD (0); Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 53.741$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.42, 8.42, 8.42); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.548 W/kg **Rear/Procedure/Zoom Scan (6x6x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 9.280 V/m ; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.634 W/kg **SAR(1 g) = 0.376 W/kg ; SAR(10 g) = 0.228 W/kg** Maximum value of SAR (measured) = 0.536 W/kg 0 dB = 0.536 W/kg = -2.71 dBW/kg

Test mode: LTE Band 4

Test Position: Body- worn Rear

Test Plot: B7

Date:2018-05-11

Communication System: UID 0, Generic LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 53.892$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.77, 8.77, 8.77); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.451 W/kg


Rear/Procedure/Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.92 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.505 W/kg

SAR(1 g) = 0.367 W/kg; SAR(10 g) = 0.277 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.451 W/kg



Test mode: LTE Band 5

Test Position: Body- worn Rear

Test Plot: B8

Date:2018-05-10


Communication System: UID 0, Generic LTE-FDD (0); Frequency: 836.5 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.5 \text{ MHz}$; $\sigma = 0.967 \text{ S/m}$; $\epsilon_r = 55.399$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.5, 10.5, 10.5); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (interpolated) = 0.252 W/kg **Rear/Procedure/Zoom Scan (5x6x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 15.47 V/m ; Power Drift = -0.05 dB Peak SAR (extrapolated) = 0.285 W/kg **SAR(1 g) = 0.205 W/kg ; SAR(10 g) = 0.155 W/kg** [Info: Interpolated medium parameters used for SAR evaluation.](#)Maximum value of SAR (measured) = 0.252 W/kg 

Test mode: LTE Band 7

Test Position: Body- worn Rear

Test Plot: B9

Date: 2018-05-16


Communication System: UID 0, Generic LTE-FDD (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535 \text{ MHz}$; $\sigma = 2.082 \text{ S/m}$; $\epsilon_r = 52.884$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.51, 7.51, 7.51); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (61x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 0.875 W/kg **Rear/Procedure/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 17.23 V/m ; Power Drift = -0.05 dB Peak SAR (extrapolated) = 0.964 W/kg **SAR(1 g) = 0.698 W/kg ; SAR(10 g) = 0.521 W/kg** Maximum value of SAR (measured) = 0.864 W/kg 

Test mode: WLAN 802.11b

Test Position: Body- worn Rear

Test Plot: B10

Date:2018-05-16

Communication System: UID 0, Generic WIFI (0); Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.991$ S/m; $\epsilon_r = 53.023$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.08, 8.08, 8.08); Calibrated: 2/26/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/25/2018
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)

Rear/Procedure/Area Scan (71x131x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.349 W/kg


Rear/Procedure/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.234 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.202 W/kg; SAR(10 g) = 0.105 W/kg[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.320 W/kg



15. Simultaneous Transmission analysis

No.	Simultaneous Transmission Configurations	Head	Body-worn	Hotspot	Note
1	GSM(voice) + Bluetooth (data)	Yes	Yes		
2	GSM(voice) + WIFI (data)	Yes	Yes		
3	WCDMA(voice) + Bluetooth (data)	Yes	Yes		
4	WCDMA(voice) + WIFI (data)	Yes	Yes		
5	GPRS (data) + Bluetooth (data)	Yes	Yes	NA	
6	GPRS (data) + WIFI (data)	Yes	Yes	Yes	
7	WCDMA (data) + Bluetooth (data)	Yes	Yes	NA	
8	WCDMA (data) + WIFI (data)	Yes	Yes	Yes	
9	LTE + Bluetooth (data)	Yes	Yes	NA	
10	LTE + WIFI (data)	Yes	Yes	Yes	

General note:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. EUT will choose either GSM or WCDMA LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. The reported SAR summation is calculated based on the same configuration and test position
4. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below
 - a) $[(\text{max. Power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}/x] \text{W/kg}$ for test separation distances $\leq 50\text{mm}$; when $x=7.5$ for 1-g SAR, and $x=18.75$ for 10-g SAR.
 - b) When the minimum separation distance is $<5\text{mm}$, the distance is used 5mm to determine SAR test exclusion
 - c) 0.4 W/kg for 1-g SAR and 1.0W/kg for 10-g SAR, when the test separation distances is $>50\text{mm}$.

Bluetooth Max power	Exposure position	Head	Body worn
	Test separation	0mm	10mm
0.50 dBm	Estimated SAR (W/kg)	0.047	0.023

Maximum reported SAR value for Head

WWAN PCE + WLAN DTS					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR (W/kg)
			WWAN PCE	WLAN DTS	
GSM	GSM850	Left Cheek	0.206	0.408	0.614
		Left Tilted	0.158	0.346	0.504
		Right Cheek	0.191	0.392	0.583
		Right Tilted	0.145	0.329	0.474
	PCS1900	Left Cheek	0.175	0.408	0.583
		Left Tilted	0.141	0.346	0.487
		Right Cheek	0.168	0.392	0.561
		Right Tilted	0.132	0.329	0.462
WCDMA	Band II	Left Cheek	0.339	0.408	0.747
		Left Tilted	0.279	0.346	0.625
		Right Cheek	0.324	0.392	0.716
		Right Tilted	0.259	0.329	0.589
	Band IV	Left Cheek	0.358	0.408	0.766
		Left Tilted	0.295	0.346	0.640
		Right Cheek	0.342	0.392	0.734
		Right Tilted	0.274	0.329	0.603
	Band V	Left Cheek	0.213	0.408	0.621
		Left Tilted	0.172	0.346	0.518
		Right Cheek	0.206	0.392	0.598
		Right Tilted	0.162	0.329	0.491
LTE	B2 1RB	Left Cheek	0.248	0.408	0.657
		Left Tilted	0.203	0.346	0.549
		Right Cheek	0.242	0.392	0.634
		Right Tilted	0.193	0.329	0.522
	B2 50RB	Left Cheek	0.162	0.408	0.570
		Left Tilted	0.142	0.346	0.488
		Right Cheek	0.149	0.392	0.542
		Right Tilted	0.127	0.329	0.456
	B4 1RB	Left Cheek	0.283	0.408	0.692
		Left Tilted	0.212	0.346	0.558
		Right Cheek	0.275	0.392	0.667
		Right Tilted	0.213	0.329	0.543
	B4 50RB	Left Cheek	0.209	0.408	0.617
		Left Tilted	0.165	0.346	0.511
		Right Cheek	0.190	0.392	0.582
		Right Tilted	0.135	0.329	0.464

LTE	B5 1RB	Left Cheek	0.133	0.408	0.541
		Left Tilted	0.111	0.346	0.457
		Right Cheek	0.128	0.392	0.521
		Right Tilted	0.102	0.329	0.431
	B5 25RB	Left Cheek	0.131	0.408	0.539
		Left Tilted	0.101	0.346	0.447
		Right Cheek	0.130	0.392	0.522
		Right Tilted	0.106	0.329	0.436
	B7 1RB	Left Cheek	0.152	0.408	0.560
		Left Tilted	0.133	0.346	0.479
		Right Cheek	0.146	0.392	0.539
		Right Tilted	0.125	0.329	0.454
	B7 50RB	Left Cheek	0.105	0.408	0.513
		Left Tilted	0.096	0.346	0.442
		Right Cheek	0.100	0.392	0.493
		Right Tilted	0.082	0.329	0.411

WWAN PCE + Bluetooth					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR (W/kg)
			WWAN PCE	Bluetooth	
GSM	GSM850	Left Cheek	0.206	0.047	0.253
		Left Tilted	0.158	0.047	0.204
		Right Cheek	0.191	0.047	0.238
		Right Tilted	0.145	0.047	0.192
	PCS1900	Left Cheek	0.175	0.047	0.222
		Left Tilted	0.141	0.047	0.188
		Right Cheek	0.168	0.047	0.215
		Right Tilted	0.132	0.047	0.179
WCDMA	Band II	Left Cheek	0.339	0.047	0.386
		Left Tilted	0.279	0.047	0.326
		Right Cheek	0.324	0.047	0.371
		Right Tilted	0.259	0.047	0.306
	Band IV	Left Cheek	0.213	0.047	0.260
		Left Tilted	0.172	0.047	0.218
		Right Cheek	0.206	0.047	0.253
		Right Tilted	0.162	0.047	0.209
	Band V	Left Cheek	0.248	0.047	0.295
		Left Tilted	0.203	0.047	0.250
		Right Cheek	0.242	0.047	0.289
		Right Tilted	0.193	0.047	0.240
LTE	B2 1RB	Left Cheek	0.162	0.047	0.208
		Left Tilted	0.142	0.047	0.188
		Right Cheek	0.149	0.047	0.196
		Right Tilted	0.127	0.047	0.174
	B2 50RB	Left Cheek	0.283	0.047	0.330
		Left Tilted	0.212	0.047	0.259
		Right Cheek	0.275	0.047	0.322
		Right Tilted	0.213	0.047	0.260
	B4 1RB	Left Cheek	0.209	0.047	0.256
		Left Tilted	0.165	0.047	0.212
		Right Cheek	0.190	0.047	0.236
		Right Tilted	0.135	0.047	0.181
	B4 50RB	Left Cheek	0.193	0.047	0.240
		Left Tilted	0.148	0.047	0.195
		Right Cheek	0.179	0.047	0.226
		Right Tilted	0.136	0.047	0.182

LTE	B5 1RB	Left Cheek	0.133	0.047	0.180
		Left Tilted	0.111	0.047	0.158
		Right Cheek	0.128	0.047	0.175
		Right Tilted	0.102	0.047	0.148
	B5 25RB	Left Cheek	0.131	0.047	0.178
		Left Tilted	0.101	0.047	0.148
		Right Cheek	0.130	0.047	0.177
		Right Tilted	0.106	0.047	0.153
	B7 1RB	Left Cheek	0.152	0.047	0.199
		Left Tilted	0.133	0.047	0.180
		Right Cheek	0.146	0.047	0.193
		Right Tilted	0.125	0.047	0.172
	B7 50RB	Left Cheek	0.105	0.047	0.152
		Left Tilted	0.096	0.047	0.143
		Right Cheek	0.100	0.047	0.147
		Right Tilted	0.082	0.047	0.129

Maximum reported SAR value for Body

WWAN PCE + WLAN DTS					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			WWAN PCE	WLAN DTS	(W/kg)
GSM	GSM850	Front	0.326	0.150	0.476
		Rear	0.493	0.220	0.714
	PCS1900	Front	0.191	0.150	0.341
		Rear	0.301	0.220	0.522
WCDMA	Band II	Front	0.329	0.150	0.479
		Rear	0.462	0.220	0.682
	Band IV	Front	0.379	0.150	0.529
		Rear	0.532	0.220	0.752
	Band V	Front	0.195	0.150	0.346
		Rear	0.317	0.220	0.538
LTE	B2 1RB	Front	0.266	0.150	0.416
		Rear	0.443	0.220	0.663
	B2 50RB	Front	0.192	0.150	0.342
		Rear	0.340	0.220	0.560
	B4 1RB	Front	0.203	0.150	0.353
		Rear	0.435	0.220	0.656
	B4 50RB	Front	0.151	0.150	0.302
		Rear	0.347	0.220	0.567
	B5 1RB	Front	0.141	0.150	0.291
		Rear	0.209	0.220	0.430
	B5 25RB	Front	0.114	0.150	0.264
		Rear	0.208	0.220	0.428
	B7 1RB	Front	0.543	0.150	0.693
		Rear	0.769	0.220	0.989
	B7 50RB	Front	0.424	0.150	0.574
		Rear	0.622	0.220	0.843

WWAN PCE + Bluetooth					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			WWAN PCE	Bluetooth	(W/kg)
GSM	GSM850	Front	0.326	0.023	0.349
		Rear	0.493	0.023	0.517
	PCS1900	Front	0.191	0.023	0.214
		Rear	0.301	0.023	0.325
WCDMA	Band II	Front	0.329	0.023	0.352
		Rear	0.462	0.023	0.485
	Band IV	Front	0.379	0.023	0.402
		Rear	0.532	0.023	0.555
	Band V	Front	0.195	0.023	0.219
		Rear	0.317	0.023	0.341
LTE	B2 1RB	Front	0.266	0.023	0.290
		Rear	0.443	0.023	0.466
	B2 50RB	Front	0.192	0.023	0.216
		Rear	0.340	0.023	0.363
	B4 1RB	Front	0.203	0.023	0.226
		Rear	0.435	0.023	0.459
	B4 50RB	Front	0.151	0.023	0.175
		Rear	0.347	0.023	0.370
	B5 1RB	Front	0.141	0.023	0.165
		Rear	0.209	0.023	0.233
	B5 25RB	Front	0.114	0.023	0.137
		Rear	0.208	0.023	0.231
	B7 1RB	Front	0.543	0.023	0.566
		Rear	0.769	0.023	0.792
	B7 50RB	Front	0.424	0.023	0.447
		Rear	0.622	0.023	0.646

Maximum reported SAR value for Hotspot mode

WWAN PCE + WLAN DTS					
WWAN Band		Exposure Position	Max SAR (W/kg)		Summed SAR
			WWAN PCE	WLAN DTS	(W/kg)
GSM	GSM850	Front	0.326	0.150	0.476
		Rear	0.493	0.220	0.714
		Left side	0.353	-	0.353
		Right side	0.157	0.184	0.342
		Top side	-	0.145	0.145
		Bottom side	0.336	-	0.336
	PCS1900	Front	0.191	0.150	0.341
		Rear	0.301	0.220	0.522
		Left side	0.212	-	0.212
		Right side	0.100	0.184	0.284
		Top side	-	0.145	0.145
		Bottom side	0.189	-	0.189
WCDMA	Band II	Front	0.329	0.150	0.479
		Rear	0.462	0.220	0.682
		Left side	0.314	-	0.314
		Right side	0.172	0.184	0.357
		Top side	-	0.145	0.145
		Bottom side	0.304	-	0.304
	Band IV	Front	0.379	0.150	0.529
		Rear	0.532	0.220	0.752
		Left side	0.362	-	0.362
		Right side	0.199	0.184	0.383
		Top side	-	0.145	0.145
		Bottom side	0.350	-	0.350
	Band V	Front	0.195	0.150	0.346
		Rear	0.317	0.220	0.538
		Left side	0.193	-	0.193
		Right side	0.118	0.184	0.303
		Top side	-	0.145	0.145
		Bottom side	0.192	-	0.192


LTE	B2 1RB	Front	0.266	0.150	0.416
		Rear	0.443	0.220	0.663
		Left side	0.256	-	0.256
		Right side	0.194	0.184	0.378
		Top side	-	0.145	0.145
		Bottom side	0.277	0.000	0.277
	B2 50RB	Front	0.192	0.150	0.342
		Rear	0.340	0.220	0.560
		Left side	0.220	-	0.220
		Right side	0.137	0.184	0.321
		Top side	-	0.145	0.145
		Bottom side	0.215	-	0.215
	B4 1RB	Front	0.203	0.150	0.353
		Rear	0.435	0.220	0.656
		Left side	0.263	-	0.263
		Right side	0.179	0.184	0.363
		Top side	-	0.145	0.145
		Bottom side	0.267	-	0.267
	B4 50RB	Front	0.151	0.150	0.302
		Rear	0.347	0.220	0.567
		Left side	0.236	-	0.236
		Right side	0.138	0.184	0.322
		Top side	-	0.145	0.145
		Bottom side	0.230	-	0.230
	B5 1RB	Front	0.141	0.150	0.291
		Rear	0.209	0.220	0.430
		Left side	0.148	-	0.148
		Right side	0.091	0.184	0.275
		Top side	-	0.145	0.145
		Bottom side	0.127	-	0.127
	B5 25RB	Front	0.114	0.150	0.264
		Rear	0.208	0.220	0.428
		Left side	0.137	-	0.137
		Right side	0.090	0.184	0.275
		Top side	-	0.145	0.145
		Bottom side	0.114	-	0.114

LTE	B7 1RB	Front	0.543	0.150	0.693
		Rear	0.769	0.220	0.989
		Left side	0.480	-	0.480
		Right side	0.267	0.184	0.451
		Top side	-	0.145	0.145
		Bottom side	0.416	-	0.416
	B7 50RB	Front	0.424	0.150	0.574
		Rear	0.622	0.220	0.843
		Left side	0.357	-	0.357
		Right side	0.250	0.184	0.435
		Top side	-	0.145	0.145
		Bottom side	0.327	-	0.327


16. TestSetup Photos




Liquid depth in the head phantom



Liquid depth in the body phantom




Left Head Touch




Right Head Touch




Left Head Tilt (15°)



Right Head Tilt (15°)





17. External and Internal Photos of the EUT

Please reference to the report No.: TRE1805006301

-----End of Report-----

1.1. DAE4 Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **CCIC - HTW (Auden)**

Certificate No: **DAE4-1549_Apr18**

CALIBRATION CERTIFICATE

Object **DAE4 - SD 000 D04 BN - SN: 1549**

Calibration procedure(s) **QA CAL-06.v29**
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: **April 25, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	31-Aug-17 (No:21092)	Aug-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Auto DAE Calibration Unit Calibrator Box V2.1	SE UWS 053 AA 1001	04-Jan-18 (in house check)	In house check: Jan-19
	SE UMS 006 AA 1002	04-Jan-18 (in house check)	In house check: Jan-19

Calibrated by:	Name Eric Hainfeld	Function Laboratory Technician	Signature
Approved by:	Sven Kühn	Deputy Manager	

Issued: April 25, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

DAE data acquisition electronics
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity:* Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity:* Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation:* Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted:* Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement:* Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current:* Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - *Input resistance:* Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage:* Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption:* Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1μV, full range = -100...+300 mV
 Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	406.286 ± 0.02% (k=2)	405.992 ± 0.02% (k=2)	406.121 ± 0.02% (k=2)
Low Range	3.98481 ± 1.50% (k=2)	3.99129 ± 1.50% (k=2)	3.99380 ± 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	19.5 ° ± 1 °
---	--------------

Appendix (Additional assessments outside the scope of SCS0108)

1. DC Voltage Linearity

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	200032.88	-6.49	-0.00
Channel X + Input	20007.86	2.59	0.01
Channel X - Input	-19999.45	5.51	-0.03
Channel Y + Input	200041.48	8.18	0.00
Channel Y + Input	20005.02	-0.19	-0.00
Channel Y - Input	-20006.61	-1.53	0.01
Channel Z + Input	200032.37	-0.87	-0.00
Channel Z + Input	20003.95	-1.15	-0.01
Channel Z - Input	-20006.60	-1.44	0.01

Low Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	2001.67	0.37	0.02
Channel X + Input	201.82	0.29	0.15
Channel X - Input	-198.25	0.31	-0.16
Channel Y + Input	2001.35	0.05	0.00
Channel Y + Input	200.82	-0.59	-0.29
Channel Y - Input	-199.06	-0.48	0.24
Channel Z + Input	2000.94	-0.41	-0.02
Channel Z + Input	200.84	-0.55	-0.27
Channel Z - Input	-199.79	-1.17	0.59

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	-15.83	-18.16
	- 200	21.36	19.06
Channel Y	200	20.98	20.64
	- 200	-22.25	-22.23
Channel Z	200	5.37	5.05
	- 200	-7.46	-7.54

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	-	-1.66	-2.66
Channel Y	200	5.97	-	-0.75
Channel Z	200	9.87	3.19	-

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16424	16943
Channel Y	15770	17113
Channel Z	15616	15207

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M Ω

	Average (μ V)	min. Offset (μ V)	max. Offset (μ V)	Std. Deviation (μ V)
Channel X	-0.33	-1.57	0.89	0.48
Channel Y	0.13	-0.93	1.54	0.52
Channel Z	-0.98	-2.13	0.50	0.47

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

1.2. Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
 Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **CCIC-HTW (Auden)**

Certificate No: **EX3-7494_Feb18**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7494**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,
 QA CAL-25.v6
 Calibration procedure for dosimetric E-field probes**

Calibration date: **February 26, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ($22 \pm 3^\circ\text{C}$) and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
			Issued: February 27, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-7494_Feb18

Page 1 of 39

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

EX3DV4 – SN:7494

February 26, 2018

Probe EX3DV4

SN:7494

Manufactured: March 20, 2017
Calibrated: February 26, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

EX3DV4- SN:7494

February 26, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7494**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.40	0.46	0.38	$\pm 10.1 \%$
DCP (mV) ^B	96.1	100.9	97.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	139.9	$\pm 3.0 \%$
		Y	0.0	0.0	1.0		130.5	
		Z	0.0	0.0	1.0		141.2	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms}\cdot\text{V}^{-2}$	T2 $\text{ms}\cdot\text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	35.16	262.6	35.64	5.712	0.042	5.019	0.180	0.312	1.002
Y	33.86	260.4	37.41	4.029	0.204	5.030	0.324	0.359	1.006
Z	29.60	221.1	35.61	5.101	0.000	5.027	0.562	0.186	1.003

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).^B Numerical linearization parameter; uncertainty not required.^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:7494

February 26, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7494**Calibration Parameter Determined in Head Tissue Simulating Media**

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
150	52.3	0.76	13.63	13.63	13.63	0.00	1.00	± 13.3 %
450	43.5	0.87	11.70	11.70	11.70	0.14	1.25	± 13.3 %
750	41.9	0.89	11.02	11.02	11.02	0.43	0.86	± 12.0 %
835	41.5	0.90	10.73	10.73	10.73	0.44	0.82	± 12.0 %
1750	40.1	1.37	9.23	9.23	9.23	0.30	0.96	± 12.0 %
1900	40.0	1.40	8.83	8.83	8.83	0.36	0.84	± 12.0 %
2450	39.2	1.80	8.27	8.27	8.27	0.32	0.85	± 12.0 %
2600	39.0	1.96	7.92	7.92	7.92	0.35	0.84	± 12.0 %
5200	36.0	4.66	5.63	5.63	5.63	0.35	1.80	± 13.1 %
5300	35.9	4.76	5.40	5.40	5.40	0.35	1.80	± 13.1 %
5500	35.6	4.96	5.06	5.06	5.06	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.93	4.93	4.93	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.90	4.90	4.90	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:7494

February 26, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7494**Calibration Parameter Determined in Body Tissue Simulating Media**

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^d (mm)	Unc (k=2)
150	61.9	0.80	12.81	12.81	12.81	0.00	1.00	± 13.3 %
450	56.7	0.94	11.87	11.87	11.87	0.08	1.25	± 13.3 %
750	55.5	0.96	10.87	10.87	10.87	0.41	0.85	± 12.0 %
835	55.2	0.97	10.50	10.50	10.50	0.38	0.85	± 12.0 %
1750	53.4	1.49	8.77	8.77	8.77	0.31	0.90	± 12.0 %
1900	53.3	1.52	8.42	8.42	8.42	0.36	0.84	± 12.0 %
2450	52.7	1.95	8.08	8.08	8.08	0.24	1.07	± 12.0 %
2600	52.5	2.16	7.51	7.51	7.51	0.19	1.10	± 12.0 %
5200	49.0	5.30	5.30	5.30	5.30	0.35	1.90	± 13.1 %
5300	48.9	5.42	4.97	4.97	4.97	0.40	1.90	± 13.1 %
5500	48.6	5.65	4.62	4.62	4.62	0.40	1.90	± 13.1 %
5600	48.5	5.77	4.51	4.51	4.51	0.40	1.90	± 13.1 %
5800	48.2	6.00	4.61	4.61	4.61	0.40	1.90	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:7494

February 26, 2018

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)