

# FCC REPORT (Bluetooth)

Applicant: AZUMI S.A

Address of Applicant: Avenida Aquilino de la Guardia con Calle 47, PH Ocean Plaza,  
Piso 16 of. 16-01, Marbella, Ciudad de Panamá City, Rep.  
Panamá

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: L2N

FCC ID: QRP-AZUMIL2N

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247:2011

Date of sample receipt: 02 Apr., 2013

Date of Test: 03 Apr., to 15 Apr., 2013

Date of report issued: 16 Apr., 2013

Test Result : PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue stamp with the text "SHENZHEN ZHONGJIAN NANFANG TESTING CO., LTD." around the perimeter and "CCIS" in the center. Overlaid on the stamp is a handwritten signature in black ink, which appears to be "Bruce Zhang".

Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

| Version No. | Date         | Description |
|-------------|--------------|-------------|
| 00          | 16 Apr.,2013 | Original    |
|             |              |             |
|             |              |             |
|             |              |             |
|             |              |             |

**Prepared By:**

*Lisa chen*

**Report Clerk**

**Date:**

16 Apr.,2013

**Check By:**

*Joe. Zhou*

**Project Engineer**

**Date:**

16 Apr.,2013

## 3 Contents

Page

|          |                                               |           |
|----------|-----------------------------------------------|-----------|
| <b>1</b> | <b>COVER PAGE.....</b>                        | <b>1</b>  |
| <b>2</b> | <b>VERSION.....</b>                           | <b>2</b>  |
| <b>3</b> | <b>CONTENTS.....</b>                          | <b>3</b>  |
| <b>4</b> | <b>TEST SUMMARY.....</b>                      | <b>4</b>  |
| <b>5</b> | <b>GENERAL INFORMATION.....</b>               | <b>5</b>  |
| 5.1      | CLIENT INFORMATION.....                       | 5         |
| 5.2      | GENERAL DESCRIPTION OF E.U.T. ....            | 5         |
| 5.3      | TEST MODE.....                                | 7         |
| 5.4      | LABORATORY FACILITY.....                      | 7         |
| 5.5      | LABORATORY LOCATION.....                      | 7         |
| 5.6      | TEST INSTRUMENTS LIST.....                    | 8         |
| <b>6</b> | <b>TEST RESULTS AND MEASUREMENT DATA.....</b> | <b>9</b>  |
| 6.1      | ANTENNA REQUIREMENT: .....                    | 9         |
| 6.2      | CONDUCTED EMISSIONS.....                      | 10        |
| 6.3      | CONDUCTED OUTPUT POWER .....                  | 13        |
| 6.4      | 20dB OCCUPY BANDWIDTH.....                    | 17        |
| 6.5      | CARRIER FREQUENCIES SEPARATION.....           | 21        |
| 6.6      | HOPPING CHANNEL NUMBER.....                   | 26        |
| 6.7      | DWELL TIME .....                              | 28        |
| 6.8      | PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....  | 32        |
| 6.9      | BAND EDGE .....                               | 33        |
| 6.9.1    | Conducted Emission Method .....               | 33        |
| 6.9.2    | Radiated Emission Method.....                 | 37        |
| 6.10     | SPURIOUS EMISSION.....                        | 39        |
| 6.10.1   | Conducted Emission Method.....                | 39        |
| 6.10.2   | Radiated Emission Method.....                 | 43        |
| <b>7</b> | <b>TEST SETUP PHOTO.....</b>                  | <b>48</b> |
| <b>8</b> | <b>EUT CONSTRUCTIONAL DETAILS .....</b>       | <b>50</b> |

#### 4 Test Summary

| Test Item                               | Section in CFR 47                                | Result |
|-----------------------------------------|--------------------------------------------------|--------|
| Antenna Requirement                     | 15.203/15.247 (c)                                | Pass   |
| AC Power Line Conducted Emission        | 15.207                                           | Pass   |
| Conducted Peak Output Power             | 15.247 (b)(1)                                    | Pass   |
| 20dB Occupied Bandwidth                 | 15.247 (a)(1)                                    | Pass   |
| Carrier Frequencies Separation          | 15.247 (a)(1)                                    | Pass   |
| Hopping Channel Number                  | 15.247 (a)(1)                                    | Pass   |
| Dwell Time                              | 15.247 (a)(1)                                    | Pass   |
| Pseudorandom Frequency Hopping Sequence | 15.247(b)(4)&TCB Exclusion List<br>(7 July 2002) | Pass   |
| Radiated Emission                       | 15.205/15.209                                    | Pass   |
| Band Edge                               | 15.247(d)                                        | Pass   |

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

|                          |                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant:               | AZUMI S.A                                                                                                                                 |
| Address of Applicant:    | Avenida Aquilino de la Guardia con Calle 47, PH Ocean Plaza, Piso 16 of. 16-01, Marbella, Ciudad de Panamá City, Rep. Panamá              |
| Manufacturer:            | AZUMI (HK) Limited                                                                                                                        |
| Address of Manufacturer: | RM 2309, 23/F HO KING COMM CTR, 2-16 FAYUEN ST, MONGKOK KOWLOON, HONG KONG                                                                |
| Factory:                 | Longconn Electronics(Shenzhen) Co., Ltd.                                                                                                  |
| Address of Factory:      | (Xinchuangji Industrial park) NO.42, Xingye 1 Road, Phoenix 1 <sup>st</sup> Industrial Zone, Fuyong Town, Baoan District, Shenzhen ,China |

### 5.2 General Description of E.U.T.

|                        |                                                           |
|------------------------|-----------------------------------------------------------|
| Product Name:          | Mobile Phone                                              |
| Model No.:             | L2N                                                       |
| Operation Frequency:   | 2402MHz~2480MHz                                           |
| Transfer rate:         | 1/2/3 Mbits/s                                             |
| Number of channel:     | 79                                                        |
| Modulation type:       | GFSK, $\pi/4$ -DQPSK, 8DPSK                               |
| Modulation technology: | FHSS                                                      |
| Antenna Type:          | Integral Antenna                                          |
| Antenna gain:          | -2dBi                                                     |
| AC adapter:            | Input:100-240V AC,50/60Hz 0.15A<br>Output:5V DC MAX 400mA |
| Power supply:          | Rechargeable Li-ion Battery DC3.7V/650mAh                 |

| Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK     |           |         |           |         |           |         |           |
|-------------------------------------------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                                                                 | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 0                                                                       | 2402MHz   | 20      | 2422MHz   | 40      | 2442MHz   | 60      | 2462MHz   |
| 1                                                                       | 2403MHz   | 21      | 2423MHz   | 41      | 2443MHz   | 61      | 2463MHz   |
| 2                                                                       | 2404MHz   | 22      | 2424MHz   | 42      | 2444MHz   | 62      | 2464MHz   |
| 3                                                                       | 2405MHz   | 23      | 2425MHz   | 43      | 2445MHz   | 63      | 2465MHz   |
| 4                                                                       | 2406MHz   | 24      | 2426MHz   | 44      | 2446MHz   | 64      | 2466MHz   |
| 5                                                                       | 2407MHz   | 25      | 2427MHz   | 45      | 2447MHz   | 65      | 2467MHz   |
| 6                                                                       | 2408MHz   | 26      | 2428MHz   | 46      | 2448MHz   | 66      | 2468MHz   |
| 7                                                                       | 2409MHz   | 27      | 2429MHz   | 47      | 2449MHz   | 67      | 2469MHz   |
| 8                                                                       | 2410MHz   | 28      | 2430MHz   | 48      | 2450MHz   | 68      | 2470MHz   |
| 9                                                                       | 2411MHz   | 29      | 2431MHz   | 49      | 2451MHz   | 69      | 2471MHz   |
| 10                                                                      | 2412MHz   | 30      | 2432MHz   | 50      | 2452MHz   | 70      | 2472MHz   |
| 11                                                                      | 2413MHz   | 31      | 2433MHz   | 51      | 2453MHz   | 71      | 2473MHz   |
| 12                                                                      | 2414MHz   | 32      | 2434MHz   | 52      | 2454MHz   | 72      | 2474MHz   |
| 13                                                                      | 2415MHz   | 33      | 2435MHz   | 53      | 2455MHz   | 73      | 2475MHz   |
| 14                                                                      | 2416MHz   | 34      | 2436MHz   | 54      | 2456MHz   | 74      | 2476MHz   |
| 15                                                                      | 2417MHz   | 35      | 2437MHz   | 55      | 2457MHz   | 75      | 2477MHz   |
| 16                                                                      | 2418MHz   | 36      | 2438MHz   | 56      | 2458MHz   | 76      | 2478MHz   |
| 17                                                                      | 2419MHz   | 37      | 2439MHz   | 57      | 2459MHz   | 77      | 2479MHz   |
| 18                                                                      | 2420MHz   | 38      | 2440MHz   | 58      | 2460MHz   | 78      | 2480MHz   |
| 19                                                                      | 2421MHz   | 39      | 2441MHz   | 59      | 2461MHz   |         |           |
| Remark: Channel 0, 39 & 78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK. |           |         |           |         |           |         |           |

## 5.3 Test mode

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Transmitting mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Keep the EUT in transmitting mode with worst case data rate. |
| Remark                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | GFSK is the worst case mode.                                 |
| <p>The sample was placed 0.8m above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p> |                                                              |

## 5.4 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.5 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.  
 Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
 Bao'an District, Shenzhen, Guangdong, China  
 Tel: 0755-23118282  
 Fax: 0755-23116366



## 5.6 Test Instruments list

| Radiated Emission: |                                      |                                      |                             |               |                      |                          |
|--------------------|--------------------------------------|--------------------------------------|-----------------------------|---------------|----------------------|--------------------------|
| Item               | Test Equipment                       | Manufacturer                         | Model No.                   | Inventory No. | Cal. Date (dd-mm-yy) | Cal. Due date (dd-mm-yy) |
| 1                  | 3m Semi- Anechoic Chamber            | SAEMC                                | 9(L)*6(W)* 6(H)             | CCIS0001      | June 09 2012         | June 08 2013             |
| 2                  | Control Room                         | ZhongYu Electron                     | 6.2(L)*2.5(W)* 2.4(H)       | CCIS0002      | N/A                  | N/A                      |
| 3                  | BiConiLog Antenna                    | SCHWARZBECK<br>MESS-ELEKTRONIK       | VULB9163                    | CCIS0005      | June 04 2012         | June 03 2013             |
| 4                  | Double -ridged waveguide horn        | SCHWARZBECK<br>MESS-ELEKTRONIK       | BBHA9120D                   | CCIS0006      | May 30 2012          | May 29 2013              |
| 5                  | EMI Test Software                    | AUDIX                                | E3                          | N/A           | N/A                  | N/A                      |
| 6                  | Coaxial Cable                        | CCIS                                 | N/A                         | CCIS0016      | Apr. 01 2013         | Mar. 31 2014             |
| 7                  | Coaxial Cable                        | CCIS                                 | N/A                         | CCIS0017      | Apr. 01 2013         | Mar. 31 2014             |
| 8                  | Coaxial cable                        | CCIS                                 | N/A                         | CCIS0018      | Apr. 01 2013         | Mar. 31 2014             |
| 9                  | Coaxial Cable                        | CCIS                                 | N/A                         | CCIS0019      | Apr. 01 2013         | Mar. 31 2014             |
| 10                 | Coaxial Cable                        | CCIS                                 | N/A                         | CCIS0087      | Apr. 01 2013         | Mar. 31 2014             |
| 11                 | Amplifier(10kHz-1.3GHz)              | HP                                   | 8447D                       | CCIS0003      | Apr. 01 2013         | Mar. 31 2014             |
| 12                 | Amplifier(1GHz-18GHz)                | Compliance Direction<br>Systems Inc. | PAP-1G18                    | CCIS0011      | June 09 2012         | June 08 2013             |
| 13                 | Pre-amplifier (18-26GHz)             | Rohde & Schwarz                      | AFS33-18002<br>650-30-8P-44 | GTS218        | Apr. 01 2013         | Mar. 31 2014             |
| 14                 | Horn Antenna                         | ETS-LINDGREN                         | 3160                        | GTS217        | Mar. 30 2013         | Mar. 29 2014             |
| 15                 | Printer                              | HP                                   | HP LaserJet P1007           | N/A           | N/A                  | N/A                      |
| 16                 | Positioning Controller               | UC                                   | UC3000                      | CCIS0015      | N/A                  | N/A                      |
| 17                 | Spectrum analyzer 9k-30GHz           | Rohde & Schwarz                      | FSP                         | CCIS0023      | May. 29 2012         | May. 28 2013             |
| 18                 | Loop antenna                         | Laplace instrument                   | RF300                       | EMC0701       | Aug. 12 2012         | Aug. 11 2013             |
| 19                 | EMI Test Receiver                    | Rohde & Schwarz                      | ESPI                        | CCIS0022      | Apr 01 2013          | Mar. 31 2014             |
| 20                 | Universal radio communication tester | Rohde & Schwarz                      | CMU200                      | CCIS0069      | May. 29 2012         | May. 28 2013             |


| Conducted Emission: |                   |                    |                       |               |                     |                          |
|---------------------|-------------------|--------------------|-----------------------|---------------|---------------------|--------------------------|
| Item                | Test Equipment    | Manufacturer       | Model No.             | Inventory No. | Cal.Date (dd-mm-yy) | Cal. Due date (dd-mm-yy) |
| 1                   | Shielding Room    | ZhongShuo Electron | 11.0(L)x4.0(W)x3.0(H) | CCIS0061      | June 09 2012        | June 08 2013             |
| 2                   | EMI Test Receiver | Rohde & Schwarz    | ESCI                  | CCIS0002      | May 25 2012         | May 24 2013              |
| 3                   | LISN              | CHASE              | MN2050D               | CCIS0074      | Apr 01 2013         | Mar. 31 2014             |
| 4                   | Coaxial Cable     | CCIS               | N/A                   | CCIS0086      | Apr. 01 2013        | Mar. 31 2014             |
| 5                   | EMI Test Software | AUDIX              | E3                    | N/A           | N/A                 | N/A                      |

## 6 Test results and Measurement Data

### 6.1 Antenna requirement:


|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | FCC Part15 C Section 15.203 /247(c) |
| <p><i>15.203 requirement:</i><br/> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i></p> <p><i>15.247(c) (1)(i) requirement:</i><br/> <i>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</i></p> |                                     |
| <b>E.U.T Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                     |
| <p><i>The Bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is -2 dBi</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                     |
| <div style="display: flex; align-items: center;"> <div style="flex: 1; padding-right: 10px;"> <p>Bluetooth Antenna</p>  </div> <div style="flex: 2;">  </div> </div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                     |

### 6.2 Conducted Emissions

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |              |           |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| Test Requirement:                                | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |           |
| Test Method:                                     | ANSI C63.4:2003                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |              |           |
| Test Frequency Range:                            | 150kHz to 30MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |              |           |
| Class / Severity:                                | Class B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |              |           |
| Receiver setup:                                  | RBW=9kHz, VBW=30kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |              |           |
| Limit:                                           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Limit (dBuV) |           |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Quasi-peak   | Average   |
|                                                  | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 66 to 56*    | 56 to 46* |
|                                                  | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 56           | 46        |
|                                                  | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 60           | 50        |
| * Decreases with the logarithm of the frequency. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |              |           |
| Test setup:                                      |  <p>Remark:<br/>E.U.T.: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |              |           |
| Test procedure:                                  | <ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.</li> </ol> |              |           |
| Test Instruments:                                | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |              |           |
| Test mode:                                       | Bluetooth mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |              |           |
| Test results:                                    | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |              |           |

### Measurement Data


Line:



Site :  
 Condition : FCC PART15 B QP LISN LINE  
 Job. no : 091RF  
 EUT : Mobile phone  
 Model : L2N  
 Test Mode : BT mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Joe

|    | Freq  | Read Level | LISN Factor | Cable Loss | Level | Limit Line | Over Limit | Remark  |
|----|-------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz   | dBuV       | dB          | dB         | dBuV  | dBuV       | dB         |         |
| 1  | 0.150 | 44.36      | 10.25       | 0.79       | 55.40 | 66.00      | -10.60     | QP      |
| 2  | 0.170 | 43.05      | 10.23       | 0.78       | 54.06 | 64.94      | -10.88     | QP      |
| 3  | 0.170 | 24.99      | 10.23       | 0.78       | 36.00 | 54.94      | -18.94     | Average |
| 4  | 0.200 | 40.14      | 10.21       | 0.76       | 51.11 | 63.62      | -12.51     | QP      |
| 5  | 0.200 | 22.89      | 10.21       | 0.76       | 33.86 | 53.62      | -19.76     | Average |
| 6  | 0.871 | 18.11      | 10.20       | 0.84       | 29.15 | 46.00      | -16.85     | Average |
| 7  | 2.554 | 32.55      | 10.28       | 0.94       | 43.77 | 56.00      | -12.23     | QP      |
| 8  | 2.594 | 20.64      | 10.28       | 0.94       | 31.86 | 46.00      | -14.14     | Average |
| 9  | 3.241 | 33.33      | 10.29       | 0.90       | 44.52 | 56.00      | -11.48     | QP      |
| 10 | 3.293 | 20.92      | 10.29       | 0.90       | 32.11 | 46.00      | -13.89     | Average |
| 11 | 3.820 | 21.27      | 10.29       | 0.89       | 32.45 | 46.00      | -13.55     | Average |
| 12 | 3.985 | 31.67      | 10.29       | 0.89       | 42.85 | 56.00      | -13.15     | QP      |

Neutral:



Trace: 1


Site :  
 Condition : FCC PART15 B QP LISN NEUTRAL  
 Job. no : 091RF  
 EUT : Mobile phone  
 Model : L2N  
 Test Mode : BT mode  
 Power Rating : AC 120V/60Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Joe\

|       | Read  | LISN   | Cable | Limit | Over  |                      |
|-------|-------|--------|-------|-------|-------|----------------------|
| Freq  | Level | Factor | Loss  | Line  | Limit | Remark               |
| ----- | ----- | -----  | ----- | ----- | ----- | -----                |
| MHz   | dBuV  | dB     | dB    | dBuV  | dBuV  | dB                   |
| 1     | 0.150 | 44.87  | 10.27 | 0.79  | 55.93 | 66.00 -10.07 QP      |
| 2     | 0.150 | 25.75  | 10.27 | 0.79  | 36.81 | 56.00 -19.19 Average |
| 3     | 0.170 | 26.78  | 10.25 | 0.78  | 37.81 | 54.94 -17.13 Average |
| 4     | 0.175 | 44.14  | 10.25 | 0.77  | 55.16 | 64.72 -9.56 QP       |
| 5     | 0.894 | 31.55  | 10.19 | 0.85  | 42.59 | 56.00 -13.41 QP      |
| 6     | 0.894 | 18.13  | 10.19 | 0.85  | 29.17 | 46.00 -16.83 Average |
| 7     | 2.608 | 20.59  | 10.27 | 0.94  | 31.80 | 46.00 -14.20 Average |
| 8     | 2.636 | 33.12  | 10.27 | 0.94  | 44.33 | 56.00 -11.67 QP      |
| 9     | 3.293 | 22.47  | 10.28 | 0.90  | 33.65 | 46.00 -12.35 Average |
| 10    | 3.328 | 33.59  | 10.28 | 0.90  | 44.77 | 56.00 -11.23 QP      |
| 11    | 3.985 | 31.94  | 10.28 | 0.89  | 43.11 | 56.00 -12.89 QP      |
| 12    | 4.158 | 21.26  | 10.28 | 0.89  | 32.43 | 46.00 -13.57 Average |

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. The average value is too low, so not show in test data in this report.

## 6.3 Conducted Output Power


|                   |                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                            |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                                                                                  |
| Receiver setup:   | RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤ 1 MHz)<br>RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)                                                                                                                                                                                                                                                             |
| Limit:            | 125 mW(21 dBm)                                                                                                                                                                                                                                                                                                                                                                |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a table labeled 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.</p> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                              |
| Test mode:        | Non-hopping mode                                                                                                                                                                                                                                                                                                                                                              |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                          |

## Measurement Data

| GFSK mode           |                         |             |        |
|---------------------|-------------------------|-------------|--------|
| Test channel        | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest              | 3.62                    | 21          | Pass   |
| Middle              | 3.19                    | 21          | Pass   |
| Highest             | 2.83                    | 21          | Pass   |
| $\pi/4$ -DQPSK mode |                         |             |        |
| Test channel        | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest              | 2.58                    | 21          | Pass   |
| Middle              | 2.80                    | 21          | Pass   |
| Highest             | 2.34                    | 21          | Pass   |
| 8DPSK mode          |                         |             |        |
| Test channel        | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest              | 3.34                    | 21          | Pass   |
| Middle              | 2.95                    | 21          | Pass   |
| Highest             | 2.49                    | 21          | Pass   |


Test plot as follows:

|                  |      |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|




Date: 11.APR.2013 17:31:26

Lowest channel



Date: 11.APR.2013 17:40:43


Middle channel



Date: 11.APR.2013 17:50:04


Highest channel

|                  |                |
|------------------|----------------|
| Modulation mode: | $\pi/4$ -DQPSK |
|------------------|----------------|




Date: 17.APR.2013 19:14:23

### Lowest channel



Date: 11.APR.2013 18:03:21


### Middle channel



Date: 11.APR.2013 18:07:54


### Highest channel

|                  |       |
|------------------|-------|
| Modulation mode: | 8DPSK |
|------------------|-------|




Date: 11.APR.2013 18:17:17

## Lowest channel



Date: 11.APR.2013 18:26:19


## Middle channel



Date: 11.APR.2013 18:34:59

## Highest channel

## 6.4 20dB Occupy Bandwidth


|                   |                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                      |
| Receiver setup:   | RBW=30kHz, VBW=100kHz,detector=Peak                                                                                                                                                                                                                                                                               |
| Limit:            | NA                                                                                                                                                                                                                                                                                                                |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                  |
| Test mode:        | Non-hopping mode                                                                                                                                                                                                                                                                                                  |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                              |

### Measurement Data

| Test channel | 20dB Occupy Bandwidth (kHz) |                |       |
|--------------|-----------------------------|----------------|-------|
|              | GFSK                        | $\pi/4$ -DQPSK | 8DPSK |
| Lowest       | 764                         | 1124           | 1156  |
| Middle       | 748                         | 1116           | 1164  |
| Highest      | 744                         | 1112           | 1160  |

Test plot as follows:

|                  |      |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|




Date: 11.APR.2013 17:35:30

## Lowest channel



Date: 11.APR.2013 17:42:15


## Middle channel



Date: 11.APR.2013 17:50:58


## Highest channel

|                  |                |
|------------------|----------------|
| Modulation mode: | $\pi/4$ -DQPSK |
|------------------|----------------|




Date: 11.APR.2013 17:56:47

### Lowest channel



Date: 11.APR.2013 18:04:06

### Middle channel



Date: 11.APR.2013 18:08:40


### Highest channel

|                  |       |
|------------------|-------|
| Modulation mode: | 8DPSK |
|------------------|-------|




Date: 11.APR.2013 18:18:27

### Lowest channel



Date: 11.APR.2013 18:27:12


### Middle channel



Date: 11.APR.2013 18:35:37

### Highest channel

## 6.5 Carrier Frequencies Separation

|                   |                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                      |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                                                                                                            |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, detector=Peak                                                                                                                                                                                                                                                                                                                                                                   |
| Limit:            | 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)                                                                                                                                                                                                                                                                                                                                            |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer, shown with a green trace on its screen, is connected to an E.U.T. (Equipment Under Test) by a red cable. Both instruments are placed on a 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane', represented by a thick grey bar.</p> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                                        |
| Test mode:        | Hopping mode                                                                                                                                                                                                                                                                                                                                                                                            |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                    |

### Measurement Data


| GFSK mode           |                                      |             |        |
|---------------------|--------------------------------------|-------------|--------|
| Test channel        | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest              | 1000                                 | 509.333     | Pass   |
| Middle              | 1000                                 | 509.333     | Pass   |
| Highest             | 1000                                 | 509.333     | Pass   |
| $\pi/4$ -DQPSK mode |                                      |             |        |
| Test channel        | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest              | 1000                                 | 749.333     | Pass   |
| Middle              | 1008                                 | 749.333     | Pass   |
| Highest             | 1000                                 | 749.333     | Pass   |
| 8DPSK mode          |                                      |             |        |
| Test channel        | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
| Lowest              | 1004                                 | 776.000     | Pass   |
| Middle              | 1004                                 | 776.000     | Pass   |
| Highest             | 1004                                 | 776.000     | Pass   |

Note: According to section 5.4

| Mode           | 20dB bandwidth (kHz)<br>(worse case) | Limit (kHz)<br>(Carrier Frequencies Separation) |
|----------------|--------------------------------------|-------------------------------------------------|
| GFSK           | 764                                  | 509.333                                         |
| $\pi/4$ -DQPSK | 1124                                 | 749.333                                         |
| 8DPSK          | 1164                                 | 776.000                                         |


Test plot as follows:

|                  |      |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|




Date: 11.APR.2013 17:39:20

## Lowest channel



Date: 11.APR.2013 17:48:30


## Middle channel



Date: 11.APR.2013 17:53:55


## Highest channel

|                  |                |
|------------------|----------------|
| Modulation mode: | $\pi/4$ -DQPSK |
|------------------|----------------|




Date: 11.APR.2013 18:01:52

## Lowest channel



Date: 11.APR.2013 18:06:44


## Middle channel



Date: 11.APR.2013 18:14:50


## Highest channel

|                  |       |
|------------------|-------|
| Modulation mode: | 8DPSK |
|------------------|-------|




Date: 11.APR.2013 18:24:52

### Lowest channel



Date: 11.APR.2013 18:33:52


### Middle channel



Date: 11.APR.2013 18:40:38

### Highest channel


## 6.6 Hopping Channel Number

|                   |                                                                                                                                                                                                                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                   |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak                                                                                                                                                                                                                                       |
| Limit:            | 15 channels                                                                                                                                                                                                                                                                                                    |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                               |
| Test mode:        | Hopping mode                                                                                                                                                                                                                                                                                                   |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                           |

### Measurement Data:


| Mode                         | Hopping channel numbers | Limit | Result |
|------------------------------|-------------------------|-------|--------|
| GFSK, $\pi/4$ -DQPSK, 8DPSK, | 79                      | 15    | Pass   |

## GFSK




Date: 11.APR.2013 19:14:35

## $\pi/4$ -DQPSK




Date: 11.APR.2013 19:25:43

## 8DPSK



Date: 11.APR.2013 19:28:02

## 6.7 Dwell Time

|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                 |
| Test Method:      | ANSI C63.4:2003 and KDB DA00-705                                                   |
| Receiver setup:   | RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak                                        |
| Limit:            | 0.4 Second                                                                         |
| Test setup:       |  |
| Test Instruments: | Refer to section 5.6 for details                                                   |
| Test mode:        | Hopping mode                                                                       |
| Test results:     | Pass                                                                               |

### Measurement Data (Worse case)

| Mode           | Packet | Dwell time (second) | Limit (second) | Result |
|----------------|--------|---------------------|----------------|--------|
| GFSK           | DH1    | 0.13440             | 0.4            | Pass   |
|                | DH3    | 0.27280             |                |        |
|                | DH5    | 0.31724             |                |        |
| $\pi/4$ -DQPSK | 2-DH1  | 0.14080             | 0.4            | Pass   |
|                | 2-DH3  | 0.27840             |                |        |
|                | 2-DH5  | 0.31809             |                |        |
| 8DPSK          | 3-DH1  | 0.13632             | 0.4            | Pass   |
|                | 3-DH3  | 0.27680             |                |        |
|                | 3-DH5  | 0.31554             |                |        |

For GFSK,  $\pi/4$ -DQPSK and 8DPSK:

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as below

DH1 time slot =  $0.420(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 134.40\text{ms}$

DH3 time slot =  $1.705(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 272.80\text{ms}$

DH5 time slot =  $2.976(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 317.24\text{ms}$

2-DH1 time slot =  $0.440 (\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 140.80\text{ms}$

2-DH3 time slot =  $1.740(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 278.40\text{ms}$

2-DH5 time slot =  $2.984\text{ms} \times (1600 / (6 \times 79)) \times 31.6 = 318.09\text{ms}$


3-DH1 time slot =  $0.426 (\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 136.32\text{ms}$

3-DH3 time slot =  $1.730(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 276.80\text{ms}$

3-DH5 time slot =  $2.960(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 315.54\text{ms}$


Test plot as follows:

|                  |      |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|




Date: 11.APR.2013 18:55:19

DH1



Date: 11.APR.2013 18:56:06

DH3




Date: 11.APR.2013 18:57:07

DH5


Modulation mode:

$\pi/4$ -DQPSK




Date: 11.APR.2013 18:52:48

2-DH1



Date: 11.APR.2013 18:53:33

2-DH3




Date: 11.APR.2013 18:54:13

2-DH5


Modulation mode:

8DPSK




Date: 11.APR.2013 18:49:36

3-DH1



Date: 11.APR.2013 18:50:36



3-DH3



Date: 11.APR.2013 18:51:55


3-DH5

## 6.8 Pseudorandom Frequency Hopping Sequence

| Test Requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | FCC Part15 C Section 15.247 (a)(1) requirement: |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <p>Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</p> <p>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> |                                                 |
| EUT Pseudorandom Frequency Hopping Sequence                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                 |
| <p>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none"> <li>• Number of shift register stages: 9</li> <li>• Length of pseudo-random sequence: <math>2^9 - 1 = 511</math> bits</li> <li>• Longest sequence of zeros: 8 (non-inverted signal)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                            |                                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                 |
| <p><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                 |
| <p>Each frequency used equally on the average by each transmitter.</p> <p>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                 |

## 6.9 Band Edge


### 6.9.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                         |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                                                                                            |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Detector=Peak                                                                                                                                                                                                                                                                                                                                                   |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>                             |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                        |
| Test mode:        | Non-hopping mode and hopping mode                                                                                                                                                                                                                                                                                                                                                       |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                    |

Test plot as follows:


GFSK

| Test channel: | Lowest channel |
|---------------|----------------|
|---------------|----------------|



Date: 11.APR.2013 17:36:20


No-hopping mode



Date: 11.APR.2013 19:17:21


Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|



Date: 11.APR.2013 17:51:31

No-hopping mode




Date: 11.APR.2013 19:19:18

Hopping mode


$\pi/4$ -DQPSK

| Test channel: | Lowest channel |
|---------------|----------------|
|---------------|----------------|



Date: 11.APR.2013 17:57:25


No-hopping mode



Date: 11.APR.2013 19:23:55


Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|



Date: 11.APR.2013 18:11:06

No-hopping mode




Date: 11.APR.2013 19:21:41

Hopping mode


8DPSK

| Test channel: | Lowest channel |
|---------------|----------------|
|---------------|----------------|



Date: 11.APR.2013 18:19:20


No-hopping mode



Date: 11.APR.2013 19:29:24


Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|



Date: 11.APR.2013 18:37:26


No-hopping mode



Date: 11.APR.2013 19:30:56

Hopping mode

### 6.9.2 Radiated Emission Method

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          |                    |      |               |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------------------|------|---------------|
| Test Requirement:     | FCC Part15 C Section 15.209 and 15.205                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |                    |      |               |
| Test Method:          | ANSI C63.4: 2003                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test Frequency Range: | 2.3GHz to 2.5GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test site:            | Measurement Distance: 3m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |          |                    |      |               |
| Receiver setup:       | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Detector | RBW                | VBW  | Remark        |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Peak     | 1MHz               | 3MHz | Peak Value    |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Peak     | 1MHz               | 10Hz | Average Value |
| Limit:                | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |          | Limit (dBuV/m @3m) |      | Remark        |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          | 54.00              |      | Average Value |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          | 74.00              |      | Peak Value    |
| Test setup:           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |               |
| Test Procedure:       | <div>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</div> <div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div> <div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div> <div>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</div> <div>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</div> <div>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</div> |          |                    |      |               |
| Test Instruments:     | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test mode:            | Non-hopping mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test results:         | Passed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |                    |      |               |

#### Remark:

1. During the test, pre-scan the GFSK,  $\pi/4$ -DQPSK, 8DPSK, and found the GFSK modulation is the worst case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.

| Test channel:   |                     | Lowest              |                 |                          | Level:         |                     | Peak            |              |
|-----------------|---------------------|---------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
| 2390.00         | 41.89               | 27.58               | 5.67            | 31.35                    | 43.79          | 74.00               | -30.21          | Horizontal   |
| 2390.00         | 41.01               | 27.58               | 5.67            | 31.35                    | 42.91          | 74.00               | -31.09          | Vertical     |

| Test channel:   |                     | Lowest              |                 |                          | Level:         |                     | Average         |              |
|-----------------|---------------------|---------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
| 2390.00         | 29.37               | 27.58               | 5.67            | 31.35                    | 31.27          | 54.00               | -22.73          | Horizontal   |
| 2390.00         | 28.97               | 27.58               | 5.67            | 31.35                    | 30.87          | 54.00               | -23.13          | Vertical     |

| Test channel:   |                     | Highest             |                 |                          | Level:         |                     | Peak            |              |
|-----------------|---------------------|---------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
| 2483.50         | 50.86               | 27.52               | 5.70            | 37.26                    | 46.82          | 74.00               | -27.18          | Horizontal   |
| 2483.50         | 53.77               | 27.52               | 5.70            | 37.26                    | 49.73          | 74.00               | -24.27          | Vertical     |


| Test channel:   |                     | Highest             |                 |                          | Level:         |                     | Average         |              |
|-----------------|---------------------|---------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| Frequency (MHz) | Read Level (dBuV/m) | Antenna Factor (dB) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
| 2483.50         | 35.67               | 27.52               | 5.70            | 37.26                    | 31.63          | 54.00               | -22.37          | Horizontal   |
| 2483.50         | 35.47               | 27.52               | 5.70            | 37.26                    | 31.43          | 54.00               | -22.57          | Vertical     |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.


## 6.10 Spurious Emission

### 6.10.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.4:2003 and DA00-705                                                                                                                                                                                                                                                                                                                                                                                                |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.                                     |
| Test setup:       |  <p>The diagram illustrates the test setup for conducted emission measurements. A Spectrum Analyzer is connected to an Equipment Under Test (E.U.T) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                                                            |
| Test mode:        | Non-hopping mode                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                        |

GFSK


### Lowest channel



Date: 17.MAR.2013 08:22:10

### 30MHz~25GHz


### Middle channel



Date: 17.MAR.2013 08:24:35

### 30MHz~25GHz

### Highest channel




Date: 17.MAR.2013 08:27:15

### 30MHz~25GHz

$\pi/4$ -DQPSK


### Lowest channel



Date: 17.MAR.2013 08:40:05

30MHz~25GHz


### Middle channel



Date: 17.MAR.2013 08:32:59

30MHz~25GHz

### Highest channel




Date: 17.MAR.2013 08:29:26

30MHz~25GHz

8DPSK


## Lowest channel



Date: 17.MAR.2013 08:41:51

## 30MHz~25GHz


## Middle channel



Date: 17.MAR.2013 08:43:43

## 30MHz~25GHz



## Highest channel



Date: 17.MAR.2013 08:45:15

## 30MHz~25GHz

## 6.10.2 Radiated Emission Method

|                       |                                                                                      |            |                    |        |                  |
|-----------------------|--------------------------------------------------------------------------------------|------------|--------------------|--------|------------------|
| Test Requirement:     | FCC Part15 C Section 15.209                                                          |            |                    |        |                  |
| Test Method:          | ANSI C63.4: 2003                                                                     |            |                    |        |                  |
| Test Frequency Range: | 9kHz to 25GHz                                                                        |            |                    |        |                  |
| Test site:            | Measurement Distance: 3m                                                             |            |                    |        |                  |
| Receiver setup:       | Frequency                                                                            | Detector   | RBW                | VBW    | Remark           |
|                       | 30MHz-1GHz                                                                           | Quasi-peak | 100kHz             | 300kHz | Quasi-peak Value |
|                       | Above 1GHz                                                                           | Peak       | 1MHz               | 3MHz   | Peak Value       |
|                       |                                                                                      | Peak       | 1MHz               | 10Hz   | Average Value    |
| Limit:                | Frequency                                                                            |            | Limit (dBuV/m @3m) |        | Remark           |
|                       | 30MHz-88MHz                                                                          |            | 40.0               |        | Quasi-peak Value |
|                       | 88MHz-216MHz                                                                         |            | 43.5               |        | Quasi-peak Value |
|                       | 216MHz-960MHz                                                                        |            | 46.0               |        | Quasi-peak Value |
|                       | 960MHz-1GHz                                                                          |            | 54.0               |        | Quasi-peak Value |
|                       | Above 1GHz                                                                           |            | 54.0               |        | Average Value    |
|                       |                                                                                      |            | 74.0               |        | Peak Value       |
| Test setup:           | Below 1GHz                                                                           |            |                    |        |                  |
|                       |  |            |                    |        |                  |
| Test setup:           | Above 1GHz                                                                           |            |                    |        |                  |
|                       |  |            |                    |        |                  |

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol> |
| Test Instruments: | Refer to section 5.6 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test mode:        | Non-hopping mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

**Remark:**

1. During the test, pre-scan the GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.
3. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.

**Measurement data:**

**Below 1GHz**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 58.00           | 37.07             | 12.83                 | 1.37            | 29.03              | 22.24          | 40.00               | -17.76          | Vertical     |
| 145.86          | 45.91             | 8.23                  | 2.46            | 29.29              | 27.31          | 43.50               | -16.19          | Vertical     |
| 239.15          | 43.42             | 12.04                 | 2.82            | 29.64              | 28.64          | 46.00               | -17.36          | Vertical     |
| 408.95          | 43.87             | 15.27                 | 3.10            | 30.00              | 32.24          | 46.00               | -13.76          | Vertical     |
| 432.55          | 40.21             | 15.53                 | 3.16            | 30.31              | 28.59          | 46.00               | -17.41          | Vertical     |
| 622.89          | 39.89             | 18.54                 | 3.90            | 30.56              | 31.77          | 46.00               | -14.23          | Vertical     |
| 143.83          | 53.97             | 8.22                  | 2.44            | 29.32              | 35.31          | 43.50               | -8.19           | Horizontal   |
| 145.86          | 55.64             | 8.23                  | 2.46            | 29.29              | 37.04          | 43.50               | -6.46           | Horizontal   |
| 191.75          | 46.62             | 10.56                 | 2.81            | 29.83              | 30.16          | 43.50               | -13.34          | Horizontal   |
| 239.99          | 52.15             | 12.09                 | 2.82            | 29.64              | 37.42          | 46.00               | -8.58           | Horizontal   |
| 336.04          | 43.79             | 13.99                 | 3.05            | 29.61              | 31.22          | 46.00               | -14.78          | Horizontal   |
| 408.95          | 45.88             | 15.27                 | 3.10            | 30.00              | 34.25          | 46.00               | -11.75          | Horizontal   |

### Above 1GHz

|               |        |        |      |
|---------------|--------|--------|------|
| Test channel: | Lowest | Level: | Peak |
|---------------|--------|--------|------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 57.15             | 31.53                 | 8.90            | 40.24                    | 57.34          | 74.00               | -16.66          | Vertical     |
| 7206.00         | 59.73             | 36.47                 | 10.59           | 41.24                    | 65.55          | 74.00               | -8.45           | Vertical     |
| 9608.00         | 50.05             | 38.10                 | 13.16           | 41.40                    | 59.91          | 74.00               | -14.09          | Vertical     |
| 4804.00         | 49.15             | 31.53                 | 8.90            | 40.24                    | 49.34          | 74.00               | -24.66          | Horizontal   |
| 7206.00         | 52.49             | 36.47                 | 10.59           | 41.24                    | 58.31          | 74.00               | -15.69          | Horizontal   |
| 9608.00         | 47.34             | 38.10                 | 13.16           | 41.40                    | 57.20          | 74.00               | -16.80          | Horizontal   |

|               |        |        |         |
|---------------|--------|--------|---------|
| Test channel: | Lowest | Level: | Average |
|---------------|--------|--------|---------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 48.35             | 31.53                 | 8.90            | 40.24                    | 48.54          | 54.00               | -5.46           | Vertical     |
| 7206.00         | 44.37             | 36.47                 | 10.59           | 41.24                    | 50.19          | 54.00               | -3.81           | Vertical     |
| 9608.00         | 40.35             | 38.10                 | 13.16           | 41.40                    | 50.21          | 54.00               | -3.79           | Vertical     |
| 4804.00         | 43.21             | 31.53                 | 8.90            | 40.24                    | 43.40          | 54.00               | -10.60          | Horizontal   |
| 7206.00         | 44.24             | 36.47                 | 10.59           | 41.24                    | 50.06          | 54.00               | -3.94           | Horizontal   |
| 9608.00         | 41.28             | 38.10                 | 13.16           | 41.40                    | 51.14          | 54.00               | -2.86           | Horizontal   |

#### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means average level is not recorded when its peak level is less than average limit.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

|               |        |        |      |
|---------------|--------|--------|------|
| Test channel: | Middle | Level: | Peak |
|---------------|--------|--------|------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 52.34             | 31.57                 | 8.98            | 40.15              | 52.74          | 74.00               | -21.26          | Vertical     |
| 7323.00         | 56.65             | 36.47                 | 10.69           | 41.15              | 62.66          | 74.00               | -11.34          | Vertical     |
| 9764.00         | 47.43             | 38.53                 | 13.37           | 41.71              | 57.62          | 74.00               | -16.38          | Vertical     |
| 4882.00         | 46.97             | 31.58                 | 8.98            | 40.15              | 47.38          | 74.00               | -26.62          | Horizontal   |
| 7323.00         | 49.22             | 36.47                 | 10.69           | 41.15              | 55.23          | 74.00               | -18.77          | Horizontal   |
| 9764.00         | 46.21             | 38.45                 | 13.37           | 41.71              | 56.32          | 74.00               | -17.68          | Horizontal   |

|               |        |        |         |
|---------------|--------|--------|---------|
| Test channel: | Middle | Level: | Average |
|---------------|--------|--------|---------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 47.62             | 31.57                 | 8.98            | 40.15              | 48.02          | 54.00               | -5.98           | Vertical     |
| 7323.00         | 45.29             | 36.47                 | 10.69           | 41.15              | 51.30          | 54.00               | -2.70           | Vertical     |
| 9764.00         | 40.44             | 38.53                 | 13.37           | 41.71              | 50.63          | 54.00               | -3.37           | Vertical     |
| 4882.00         | 41.35             | 31.58                 | 8.98            | 40.15              | 41.76          | 54.00               | -12.24          | Horizontal   |
| 7323.00         | 44.26             | 36.47                 | 10.69           | 41.15              | 50.27          | 54.00               | -3.73           | Horizontal   |
| 9764.00         | 38.64             | 38.45                 | 13.37           | 41.71              | 48.75          | 54.00               | -5.25           | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means average level is not recorded when its peak level is less than average limit.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

|               |         |        |      |
|---------------|---------|--------|------|
| Test channel: | Highest | Level: | Peak |
|---------------|---------|--------|------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 48.84             | 31.69                 | 9.08            | 40.03                    | 49.58          | 74.00               | -24.42          | Vertical     |
| 7440.00         | 52.06             | 36.60                 | 10.80           | 41.05                    | 58.41          | 74.00               | -15.59          | Vertical     |
| 9920.00         | 44.90             | 38.66                 | 13.55           | 41.99                    | 55.12          | 74.00               | -18.88          | Vertical     |
| 4960.00         | 47.11             | 31.69                 | 9.08            | 40.03                    | 47.85          | 74.00               | -26.15          | Horizontal   |
| 7440.00         | 48.34             | 36.60                 | 10.80           | 41.05                    | 54.69          | 74.00               | -19.31          | Horizontal   |
| 9920.00         | 46.30             | 38.66                 | 13.55           | 41.99                    | 56.52          | 74.00               | -17.48          | Horizontal   |

|               |         |        |         |
|---------------|---------|--------|---------|
| Test channel: | Highest | Level: | Average |
|---------------|---------|--------|---------|

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 45.26             | 31.69                 | 9.08            | 40.03                    | 46.00          | 54.00               | -8.00           | Vertical     |
| 7440.00         | 45.04             | 36.60                 | 10.80           | 41.05                    | 51.39          | 54.00               | -2.61           | Vertical     |
| 9920.00         | 39.65             | 38.66                 | 13.55           | 41.99                    | 49.87          | 54.00               | -4.13           | Vertical     |
| 4960.00         | 44.11             | 31.69                 | 9.08            | 40.03                    | 44.85          | 54.00               | -9.15           | Horizontal   |
| 7440.00         | 44.27             | 36.60                 | 10.80           | 41.05                    | 50.62          | 54.00               | -3.38           | Horizontal   |
| 9920.00         | 41.65             | 38.66                 | 13.55           | 41.99                    | 51.87          | 54.00               | -2.13           | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means average level is not recorded when its peak level is less than average limit.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.