



FCC LISTED,
REGISTRATION
NUMBER: 905266

CENTRO DE
TECNOLOGÍA DE LAS
COMUNICACIONES, S.A.

Parque Tecnológico de Andalucía,
c/Severo Ochoa nº 2
29590 Campanillas/ Málaga/ España
Tel. 952 61 91 00 - Fax 952 61 91 13
MÁLAGA, C.I.F. A29 507 456
Registro Mercantil Tomo 1169 Libro 82
Folio 133 Hoja MA3729

TEST REPORT

Report No.: 26172RET.101

TEST NAME: FCC PART 15.247 RF TESTING FOR EQUIPMENT OPERATING IN THE
2400 – 2483.5 MHz FREQUENCY BAND

Product	:	Bluetooth barcode scanner
Trade Mark	:	Baracoda
Model/type Ref.	:	Baracoda D-FLY
Manufacturer	:	Baracoda Wireless Technology
Requested by	:	Baracoda Wireless Technology
Other identification of the product	:	Product ID (Type Designation): B4012000x FCC ID: QSHAIBDF
Standard(s)	:	USA FCC Part 15.247, 15.205, 15.209, 15.109, 15.207

This test report includes 3 annexes and therefore the total number of pages is 54.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, and must not be reproduced except in full without the written approval of Centro de Tecnología de las Comunicaciones, S.A. (AT4 WIRELESS).

Date: 2007-09-11	Test operator A. Llamas 	Approved by: Date: 2007.09.12 J.C. Soler Consultant  AT4 WIRELESS Centro de Tecnología de las Comunicaciones, S.A.	Page: 1 of 8
------------------	---	---	--------------

FDT08_04

INDEX

1. COMPETENCE AND GUARANTEES	3
2. GENERAL CONDITIONS	3
3. CHARACTERISTICS OF THE TEST	3
3.1 TEST REQUESTED.....	3
3.2 REQUIREMENTS AND METHOD	3
4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT.....	4
4.1 APPLICANT.....	5
4.2 REPRESENTATIVE.....	5
4.3 TEST SAMPLES SUPPLIER.....	5
4.4 IDENTIFICATION OF ITEM/ITEMS TESTED	5
5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS	5
5.1 USAGE OF SAMPLES	5
5.2 PERIOD OF TESTING	6
5.3 ENVIROMENTAL CONDITIONS.....	6
6. TEST RESULTS	8
7. REMARKS AND COMMENTS.....	8
8. SUMMARY.....	8

ANNEXES

ANNEX A. TEST RESULTS

ANNEX B. MEASURING RESULTS FOR ELECTROMAGNETIC EMISSION

ANNEX C. PHOTOGRAPHS

Report No.: 26172RET.101		Page: 2 of 8
Date: 2007-09-11		

1. COMPETENCE AND GUARANTEES

Centro de Tecnología de las Comunicaciones (AT4 WIRELESS), S.A. is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 905266.

In order to assure the traceability to other national and international laboratories, AT4 WIRELESS has a calibration and maintenance programme for its measuring equipment.

AT4 WIRELESS guarantees the reliability of the data presented in this report, which is the result of measurements and tests performed to the item under test on the date and under the conditions stated on the report and is based on the knowledge and technical facilities available at AT4 WIRELESS at the time of execution of the test.

AT4 WIRELESS is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the item under test and the results of the test.

2. GENERAL CONDITIONS

1. This report only refers to the item that has undergone the test.
2. This report does not constitute or imply by its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without written approval of AT4 WIRELESS.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of AT4 WIRELESS and the Accreditation Bodies.

3. CHARACTERISTICS OF THE TEST

3.1 TEST REQUESTED

1. Measurements for frequency hopping spread spectrum equipment (Bluetooth) operating in the 2400 MHz -2483.5 MHz band and using, according to FCC Part 15.247.
2. Continuous conducted emission, power leads:

Standard: FCC Rules and Regulations 47 CFR Part 15

Limit: Class B

Method: FCC Rules and Regulations 47 CFR Part 15, Subpart C

3.2 REQUIREMENTS AND METHOD

1. FCC parts 15.33, 15.35, 15.247, 15.207, 15.205, 15.209, 15.109 and the document DA 00-705:"Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems".

Report No.: 26172RET.101		Page: 3 of 8
Date: 2007-09-11		

The testing was performed according to the procedure in ANSI C63.4: 2003. Radiated testing was performed in AT4 WIRELESS' semi-anechoic chamber. This site has been fully described in a report submitted to the FCC and was accepted in a letter dated July 25, 2002.

2. FCC Rules and Regulations 47 CFR Part 15, Subpart C: Limits and methods of measurements for radio frequency devices. Intentional radiators.

The instrumentation used to perform the testing is listed below:

1. Semianechoic Absorber Lined Chamber IR 11. BS.
2. Control Chamber IR 12.BC.
3. Antenna mast EM 1072 NMT.
4. Rotating table EM 1084-4. ON.
5. Multi device controller ETS 2090.
6. Bilog antenna CHASE CBL6111.
7. Antenna tripod EMCO 11968C.
8. Double-ridge Guide Horn antenna 1-18 GHz HP 11966E.
9. Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J.
10. RF pre-amplifier Miteq JS4-12002600-30-5A.
11. Semianechoic Absorber Lined Chamber IR 11. BS.
12. RF pre-amplifier Miteq AFS5-04001300-15-10P-6.
13. RF pre-amplifier Schaffner CPA 9231.
14. Spectrum analyzer R&S ESIB 26.
15. Spectrum analyzer R&S FSM.
16. Transient limiter. HP 11947A.
17. Line Impedance Stabilization Network (L.I.S.N.) R&S. ESH2-Z5.
18. Bluetooth test set Anritsu MT8852A.

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data in this section has been supplied by the client.

Report No.: 26172RET.101		Page: 4 of 8
Date: 2007-09-11		

4.1 APPLICANT

Name or Company: Baracoda Wireless Technology

V.A.T.: FR64428768600

Address: 36, rue de Turin

City: Paris

Postal code: 75008

Country: FRANCE

Telephone: +33 1 30088900

Fax: +33 1 30088998

4.2 REPRESENTATIVE

Name: Thierry Fortune.

4.3 TEST SAMPLES SUPPLIER

Name or Company: Same as indicated in point 4.1

Samples undergoing test have been selected by: **the client.**

4.4 IDENTIFICATION OF ITEM/ITEMS TESTED

Product: Bluetooth barcode scanner

Trade mark: Baracoda

Model: Baracoda D-FLY

Other identification of the product: B4012000x FCC ID: QSHAIBDF

HW versión: BARLIB_V0.1

SW versión: V1.22

Manufacturer: Baracoda Wireless Technology

Country of manufacture: FRANCE

Description: Bluetooth barcode scanner.

5. USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS

5.1 USAGE OF SAMPLES

Sample M/01 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
26172/01	Bluetooth barcode reader with integral antenna	Baracoda D-FLY	CB07251000269	05/07/07

Sample M/02 is formed by the following elements:

<u>Control No.</u>	<u>Description</u>	<u>Model</u>	<u>Serial No.</u>	<u>Date of reception</u>
26172/13	Bluetooth barcode reader with antenna connector	Baracoda D-FLY	CB07251000270	05/07/07

Report No.: 26172RET.101		Page: 5 of 8
Date: 2007-09-11		

Sample S/01 is composed of the following elements:

Control No.	Description	Model	Serial No.	Date of reception
26172/24	Power supply	IU15-2050050-WP	---	22/07/07
26172/25	Pin head adaptors	---	---	22/07/07
26172/26	BT Barcode Scanner	Baracoda D-FLY	CB07251000273	22/07/07

1. Sample M/01 has undergone following test(s).
Radiated measurements indicated in annex A.
2. Sample M/02 has undergone following test(s).
All tests indicated in annex A, except radiated measurements.
3. Sample S/01 has undergone to the following test(s):
Continuous conducted emission, power leads.

5.2 PERIOD OF TESTING

The performed test started on 2007-08-06 and finished on 2007-08-07.

The tests as detailed in this report have been performed at AT4 WIRELESS.

5.3 ENVIRONMENTAL CONDITIONS

In the control chamber the following limits were not exceeded during the test:

Temperature	Min. = 23 °C Max. = 23 °C
Relative humidity	Min. = 60 % Max. = 60 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

Report No.: 26172RET.101		Page: 6 of 8
Date: 2007-09-11		

In the semianechoic chamber (21 meters x 11 meters x 8 meters) the following limits were not exceeded during the test.

Temperature	Min. = 24 °C Max. = 24 °C
Relative humidity	Min. = 58 % Max. = 58 %
Air pressure	Min. = 1019 mbar Max. = 1019 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements the following limits were not exceeded during the test:

Temperature	Min. = 23 °C Max. = 23 °C
Relative humidity	Min. = 52 % Max. = 52 %
Air pressure	Min. = 1020 mbar Max. = 1020 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 0,5 Ω

Report No.: 26172RET.101		Page: 7 of 8
Date: 2007-09-11		

6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

- P** Pass
- F** Fail
- NA** not applicable
- NM** not measured

FCC PART 15 PARAGRAPH	VERDICT			
	NA	P	F	NM
15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation		P		
15.247 Subclause (a) (1) (iii). Number of hopping channels		P		
15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)		P		
15.247 Subclause (b). Maximum peak output power and antenna gain		P		
15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)		P		
15.247 Subclause (d). Emission limitations conducted (Transmitter)		P		
15.247 Subclause (d). Emission limitations radiated (Transmitter)		P		
15.109. Receiver spurious radiation		P		
15.207. Continuous Conducted Emissions		P		

7. REMARKS AND COMMENTS

None.

8. SUMMARY

Based on the results of the performed test, stated in annex A the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 “TEST REQUESTED”.

NOTE: The results presented in this Test Report apply only to the particular item under test declared in section 4.4 “IDENTIFICATION OF ITEM/ITEMS TESTED” of this document, as presented for test on the date(s) declared in section 5, “USAGE OF SAMPLES, PERIOD OF TESTING AND ENVIRONMENTAL CONDITIONS”.

Report No.: 26172RET.101		Page: 8 of 8
Date: 2007-09-11		

ANNEX A

TEST RESULTS

Report No: 26172RET.101

Report No: 26172RET.101		Page: 1 of 34
Date: 2007-09-11		Annex A

INDEX

	Page
TEST CONDITIONS	3
Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation....	4
Section 15.247 Subclause (a) (1) (iii). Number of hopping channels	7
Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)	9
Section 15.247 Subclause (b). Maximum peak output power and antenna gain	12
Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)	17
Section 15.247 Subclause (d). Emission limitations conducted (Transmitter).....	20
Section 15.247 Subclause (d). Emission limitations radiated (Transmitter)	23
Section 15.109. Receiver spurious radiation	30

Report No: 26172RET.101		Page: 2 of 34 Annex A
Date: 2007-09-11		

TEST CONDITIONS

Power supply (V):

$V_{nominal} = 5.0 \text{ Vdc}$

Type of power supply = Rechargeable battery

Type of antenna = Integral antenna

Maximum Declared Gain for antenna = 2 dBi

Operating Temperature Range (°C):

$T_n = -10 \text{ to } +50$

TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

The test set-up was made in accordance to the general provisions of ANSI C63.4: 2003.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to a Bluetooth signalling unit (Bluetooth test set) and to the spectrum analyser using a 6 dB power splitter. The reading in the spectrum analyser is corrected taking into account the power splitter loss.

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Report No: 26172RET.101		Page: 3 of 34
Date: 2007-09-11		Annex A

Section 15.247 Subclause (a) (1). 20 dB Bandwidth and Carrier frequency separation**SPECIFICATION**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

RESULTS


20 dB Bandwidth (see next 3 plots).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
20 dB Spectrum bandwidth (kHz)	927	920	920
Measurement uncertainty (kHz)	<±110		

Report No: 26172RET.101		Page: 4 of 34
Date: 2007-09-11		Annex A


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.



20 dB BANDWIDTH.


Middle Channel: 2441 MHz.



20 dB BANDWIDTH.


Highest Channel: 2480 MHz.

Agilent



Carrier frequency separation (see next plot).

Agilent



The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

Report No: 26172RET.101		Page: 6 of 34
Date: 2007-09-11		Annex A


Section 15.247 Subclause (a) (1) (iii). Number of hopping channels

SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 channels.

RESULTS


The number of hopping channels is 79 (see next two plots).



Number of hopping frequencies: 39

Report No: 26172RET.101		Page: 7 of 34
Date: 2007-09-11		Annex A

Number of hopping frequencies: 40



Total number of hopping frequencies: 79

Verdict: PASS

Report No: 26172RET.101		Page: 8 of 34
Date: 2007-09-11		Annex A

Section 15.247 Subclause (a) (1) (iii). Time of occupancy (Dwell Time)

SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed = $0.4 \times 79 = 31.6$ seconds.


RESULTS

TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance.

Each Tx-time per appearance is 436.7 μ s (see next plot).

So we have $320.11 \times 436.7 \mu\text{s} = 139.79$ ms per 31.6 seconds.



Verdict: PASS


Report No: 26172RET.101		Page: 9 of 34
Date: 2007-09-11		Annex A

2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/4 = 400$ hops per second with 79 channels. So you have each channel $400/79 = 5.1$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $5.1 \times 31.6 = 161.16$ times of appearance.

Each Tx-time per appearance is 1.7 ms (see next plot).

So we have $161.16 \times 1.7 \text{ ms} = 273.97 \text{ ms}$ per 31.6 seconds.



Verdict: PASS


Report No: 26172RET.101		Page: 10 of 34
Date: 2007-09-11		Annex A

3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet need 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/6 = 266.67$ hops per second with 79 channels. So you have each channel $266.67/79 = 3.37$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $3.37 \times 31.6 = 106.49$ times of appearance.

Each Tx-time per appearance is 2.94 ms (see next plot).

So we have $106.49 \times 2.94 \text{ ms} = 313.08 \text{ ms}$ per 31.6 seconds.



Verdict: PASS

Report No: 26172RET.101		Page: 11 of 34
Date: 2007-09-11		Annex A

Section 15.247 Subclause (b). Maximum peak output power and antenna gain

SPECIFICATION

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt (30 dBm).

RESULTS

MAXIMUM PEAK OUTPUT POWER (CONDUCTED). See next plots.

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Maximum peak power (dBm)	-8.54	-8.86	-9.53
Measurement uncertainty (dB)		±1.5	

The maximum declared antenna gain for this device is 2 dBi, therefore the maximum theoretical peak radiated power (EIRP) in the three measurement channels for this device is -6.54 dBm or 0.22 mW.

The actual peak radiated power (EIRP) was measured for the lowest, middle and highest frequency (see next plots):

MAXIMUM PEAK OUTPUT POWER (RADIATED).

	Lowest frequency 2402 MHz	Middle frequency 2441 MHz	Highest frequency 2480 MHz
Correction Factor (dB)	35.00	35.10	35.20
Maximum EIRP peak power (dBm)	-2.48	-3.74	-3.13
Measurement uncertainty (dB)		±4.0	

Declared peak gain: 2 dBi


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS


Report No: 26172RET.101		Page: 12 of 34
Date: 2007-09-11		Annex A

PEAK OUTPUT POWER (CONDUCTED).

Lowest Channel: 2402 MHz.




Middle Channel: 2441 MHz.



Report No: 26172RET.101		Page: 13 of 34
Date: 2007-09-11		Annex A

Highest Channel: 2480 MHz.



Report No:
26172RET.101

Date: 2007-09-11


FET45_00.DOC

Page: 14 of 34


Annex A

PEAK OUTPUT POWER (RADIATED).

Lowest Channel: 2402 MHz.




Middle Channel: 2441 MHz.



Report No: 26172RET.101		Page: 15 of 34
Date: 2007-09-11		Annex A

Highest Channel: 2480 MHz.



Report No:
26172RET.101

Date: 2007-09-11

FET45_00.DOC

Page: 16 of 34

Annex A

Section 15.247 Subclause (d). Band-edge of conducted emissions (Transmitter)

SPECIFICATION


Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

RESULTS:

See next plots


Report No: 26172RET.101		Page: 17 of 34
Date: 2007-09-11		Annex A

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). CONDUCTED



Verdict: PASS


2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). CONDUCTED



Verdict: PASS


Report No: 26172RET.101		Page: 18 of 34
Date: 2007-09-11		Annex A

3. LOW FREQUENCY SECTION (HOPPING ON). CONDUCTED



Verdict: PASS

4. HIGH FREQUENCY SECTION (HOPPING ON). CONDUCTED



Verdict: PASS

Report No: 26172RET.101		Page: 19 of 34
Date: 2007-09-11		Annex A


Section 15.247 Subclause (d). Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

RESULTS:

1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 26172RET.101		Page: 20 of 34
Date: 2007-09-11		Annex A

2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 26172RET.101		Page: 21 of 34
Date: 2007-09-11		Annex A

3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

Report No: 26172RET.101		Page: 22 of 34
Date: 2007-09-11		Annex A

Section 15.247 Subclause (d). Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Report No: 26172RET.101		Page: 23 of 34
Date: 2007-09-11		Annex A

Frequency range 30 MHz-1000 MHz.

No spurious signals found in the three operating channels.

Frequency range 1 GHz-25 GHz

1. CHANNEL: LOWEST (2402 MHz).

No spurious signals found.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz and at the harmonic frequencies.

2. CHANNEL: MIDDLE (2441 MHz).

No spurious signals found.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz and at the harmonic frequencies.

3. CHANNEL: HIGHEST (2480 MHz).


No spurious signals found.

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz and at the harmonic frequencies.

Verdict: PASS

Report No: 26172RET.101		Page: 24 of 34
Date: 2007-09-11		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels).

FREQUENCY RANGE 1 GHz to 3 GHz.

CHANNEL: Lowest (2402 MHz).


 Agilent



Note: The peak above the limit is the carrier frequency.

CHANNEL: Middle (2441 MHz).


 Agilent



Note: The peak above the limit is the carrier frequency.

Report No: 26172RET.101		Page: 26 of 34
Date: 2007-09-11		Annex A

CHANNEL: Highest (2480 MHz).




Note: The peak above the limit is the carrier frequency.

Report No: 26172RET.101		Page: 27 of 34
Date: 2007-09-11		Annex A

FREQUENCY RANGE 3 GHz to 12.75 GHz.


* Agilent



(This plot is valid for all three channels).

FREQUENCY RANGE 12.75 GHz to 18 GHz.

* Agilent




(This plot is valid for all three channels).

Report No: 26172RET.101		Page: 28 of 34
Date: 2007-09-11		Annex A

FREQUENCY RANGE 18 GHz to 25 GHz.

* Agilent



(This plot is valid for all three channels).

Section 15.109. Receiver spurious radiation

SPECIFICATION

The field strength shall not exceed the following values:

Frequency Range (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyser. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Report No: 26172RET.101		Page: 30 of 34
Date: 2007-09-11		Annex A

It is not possible to select individual receiving channels in the equipment under test. The equipment under test is set in inquiry scan mode with the receiver open and scanning through receiving channels.

Frequency range 30 MHz-1000 MHz.

No spurious signals found.

Frequency range 1 GHz-25 GHz.

Spurious levels (radiated).


Spurious frequency (MHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
2443.600	H	Peak	37.77	\pm 4.0
2443.600	H	Average	34.39	\pm 4.0

Additionally, no spurious signals were found inside the restricted bands 2310-2390 MHz and 2483.5-2500 MHz.

Verdict: PASS.

Report No: 26172RET.101		Page: 31 of 34
Date: 2007-09-11		Annex A

FREQUENCY RANGE 30 MHz-1000 MHz.



Report No:
26172RET.101

Date: 2007-09-11


FET45_00.DOC

Page: 32 of 34

Annex A


FREQUENCY RANGE 1 GHz-12.75 GHz.

 Agilent




FREQUENCY RANGE 12.75 GHz-18 GHz.

 Agilent



FREQUENCY RANGE 18 GHz-25 GHz.

 Agilent



Report No:
26172RET.101

Date: 2007-09-11

FET45_00.DOC

Page: 34 of 34

Annex A

ANNEX B

MEASURING RESULTS FOR

ELECTROMAGNETIC EMISSION

Report No: 26172RET.101

For the sample under test, named S/01, and that was formed by the elements described in the clause "Identification of the tested item/items" of this test report.

Report No: 26172RET.101		Page: 1 of 5
Date: 2007-09-11		Annex B

INDEX:

1. - CONTINUOUS CONDUCTED EMISSION, POWER LEADS ON THE SAMPLE S/01.....	3
2. - GRAPH RESULTS	3

* * *

Report No: 26172RET.101		Page: 2 of 5
Date: 2007-09-11		Annex B

1. - CONTINUOUS CONDUCTED EMISSION, POWER LEADS ON THE SAMPLE S/01

LIMITS OF INTERFERENCE

The applied limit for continuous conducted emissions in power leads, according with the requirements of FCC Rules and Regulations 47 CFR Part 15, Subpart B in the frequency range 0,15 to 30 MHz, for Class B equipment was:

Frequency range (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0,15 to 0,5	66-56	56-46
0,5 to 5	56	46
5 to 30	60	50

TEST METHOD

According to Part 15, Subpart B of FCC Rules.

OPERATING MODES OF EUT

Different tested operating modes (OM)

- OM#02: EUT ON. Reading bar-codes continuously.

TEST RESULTS

CCmnnnxx: CC, Conduction condition; mm: sample number; nn: operation mode; xx: wire.

- OM#01.

CDmnnnxx	Description	Result
CC01020N	Interference voltage on Neutral wire	PASS
CC0102L1	Interference voltage on phase wire	PASS


2. - GRAPH RESULTS

See next pages.

Report No: 26172RET.101		Page: 3 of 5
Date: 2007-09-11		Annex B

Continuous conducted emission: CC01020N (Peak and Average)
EMC32 Report
Test Information

Proyecto: 26172biem.002
 Empresa: Baracoda
 Muestra: M/01
 Modo operacion: MO#02
 Fecha: 2007-08-03 14:24
 Setup: EMI conducted
 Mode: EBP ON. Charging batteries. Communication mode. Reading bar-code continuously. Neutral Noise.

EC FCC Clase B ESIB26 CC

Max PK-AVG

Frequency (MHz)	MaxPeak-ClearWrite (dBµV)	Average-ClearWrite (dBµV)	Comment
0.150000	48.4	17.7	
0.166000	44.2	14.8	
0.202000	51.7	40.9	
0.270000	49.1	43.7	
0.342000	44.9	36.9	
0.402000	40.1	34.9	
0.474000	36.0	29.9	
6.926000	35.1	31.4	
7.810000	34.9	32.3	
8.218000	35.0	29.4	
8.614000	35.1	22.3	
8.758000	35.3	30.5	
9.034000	35.0	29.9	
9.370000	36.0	31.7	

Report No: 26172RET.101		Page: 4 of 5
Date: 2007-09-11		Annex B


Continuous conducted emission: CC0102L1 (Peak and Average)

EMC32 Report

Test Information

Proyecto: 26172biem.002
 Empresa: Baracoda
 Muestra: M/01
 Modo operacion: MO#02
 Fecha: 2007-08-03 14:42
 Setup: EMI conducted
 Mode: EBP ON. Charging batteries. Communication mode. Reading bar-code continuously. Neutral Noise.

EC FCC Clase B ESIB26 CC



Max PK-AVG

Frequency (MHz)	MaxPeak-ClearWrite (dBµV)	Average-ClearWrite (dBµV)	Comment
0.150000	47.0	23.2	
0.174000	48.7	24.4	
0.250000	45.5	26.8	
0.302000	37.3	25.0	
0.342000	37.6	28.8	
0.406000	34.4	29.3	
0.486000	34.1	22.6	
1.018000	35.6	27.8	
1.086000	34.1	25.7	
1.762000	35.2	26.3	
2.562000	34.0	17.9	
2.918000	34.7	21.2	
2.982000	34.7	19.3	
3.322000	34.0	25.4	

Report No: 26172RET.101		Page: 5 of 5
Date: 2007-09-11		Annex B

ANNEX C

PHOTOGRAPHS

(Number of photographs: 7)

Report No.: 26172RET.101

Report No.: 26172RET.101		Page: 1 of 7
Date: 2007-09-11		Annex C

1. Equipment (front view)




2. Equipment (back view).




Report No.: 26172RET.101	Page: 2 of 7
Date: 2007-09-11	Annex C

3. Equipment for conducted measurements



Report No.: 26172RET.101		Page: 3 of 7
Date: 2007-09-11		Annex C

4. General test set-up for radiated measurements.




Report No.:
26172RET.101

Date: 2007-09-11

Page: 4 of 7


Annex C

5. Test set-up for radiated measurements below 1 GHz.



Report No.: 26172RET.101		Page: 5 of 7
Date: 2007-09-11		Annex C

6. Test set-up for radiated measurements above 1 GHz.



Report No.:
26172RET.101


Date: 2007-09-11

FET18_00.DOC

Page: 6 of 7

Annex C

7. Test set-up for conducted measurements.



Report No.:
26172RET.101

Date: 2007-09-11

FET18_00.DOC

Page: 7 of 7

Annex C