

FCC PART 15.247
MEASUREMENT AND TEST REPORT

For

Power7 Technology (Dongguan) Co., Ltd.

No. 28 Binjiang Blvd., Shishuikou Village, Qiaotou Town,
Dongguan, Guangdong, China

FCC ID: QT72014PON0001

Report Type: Original Report	Product Type: WIFISD With Power Bank
Test Engineer: <u>Simon Wang</u> <i>Simon wang</i>	
Report Number: <u>RSZ140325002-00B</u>	
Report Date: <u>2014-04-23</u>	
Reviewed By: <u>RF Engineer</u>	<i>Jimmy xiao</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	10
APPLICABLE STANDARD	10
RESULT	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) - CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	12
EMI TEST RECEIVER SETUP	13
TEST EQUIPMENT LIST AND DETAILS	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	13
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD	17
MEASUREMENT UNCERTAINTY	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS	18
TEST RESULTS SUMMARY	19
TEST DATA	19
FCC §15.247(a) (2) – 6 dB EMISSIONS BANDWIDTH	42
APPLICABLE STANDARD	42

TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(b) (3) - MAXIMUM OUTPUT POWER	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST EQUIPMENT LIST AND DETAILS.....	50
TEST DATA	50
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST DATA	59
FCC §15.247(e) - POWER SPECTRAL DENSITY	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST EQUIPMENT LIST AND DETAILS.....	64
TEST DATA	64
PRODUCT SIMILARITY DECLARATION LETTER	72

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Power7 Technology (Dong Guan) Co., Ltd.'s product, model number: PON-WIFI-D11U-C52-WG, PON-WIFI-D11U-C26-WG (FCC ID: QT72014PON0001) or the "EUT" as referred to in this report was a WIFISD With Power Bank, which was measured approximately: 73 mm (L) x 70 mm (W) x 23 mm (H) for model PON-WIFI-D11U-C52-WG, 73 mm (L) x 53 mm (W) x 23 mm (H) for model PON-WIFI-D11U-C26-WG, rated input voltage: DC 3.7V.

Note: The product, series model PON-WIFI-D11U-C26-WG, DOS-WIFI-D11U-C26-BK, STA-WIFI-D11U-C26-BK and PON-WIFI-D11U-C52-WG are electrically identical, they are different in battery capacity and the appearance size, which was explained in the attached declaration letter. And the model PON-WIFI-D11U-C52-WG was selected for fully testing, and model PON-WIFI-D11U-C26-WG was selected for different testing.

** All measurement and test data in this report was gathered from production sample serial number: 1403159 (Assigned by the BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-03-25.*

Objective

This report is prepared on behalf of Power7 Technology (Dong Guan) Co., Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submission with FCC ID: QT72014PON0001.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

EUT Exercise Software

WinPcap_4_0_2.exe

The test was performed under:

802.11b: Data rate: 1 Mbps, Power level: 13

802.11g: Data rate: 6 Mbps, Power level: 10

802.11n-HT20: Data rate: MCS0 Mbps, Power level: 0C

802.11n-HT40: Data rate: MCS0 Mbps, Power level: 0A

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293
Motorola	Smartphone	TX535	N/A
Kingston	Micro SD card	4 GB	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Shielding Detachable Serial Cable	1.2	Host PC	Modem
Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Shielding Detachable USB Cable	1.5	Host PC	Mouse
Shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Unshielding Detachable USB Cable	0.5	EUT	Host PC
Unshielding Detachable AC Power Cable	2.0	PC/Host	LISN 1
Unshielding Detachable AC Power Cable	2.0	Monitor	LISN 2
Unshielding Detachable USB Cable	0.5	EUT	Smartphone
Unshielding Detachable RJ45 Cable	5	EUT	Internet

Block Diagram of Test Setup

Conducted Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Output Power	Compliance
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2437	2.5	1.78	16.51	44.77	20	0.016	1.0

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has a ceramic antenna arrangement for WiFi, which was permanently attached and the gain was 2.5 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) - CONDUCTED EMISSIONS

Applicable Standard

According to FCC§15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The PC was connected to a 120 V_{AC}/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2013-06-17	2014-06-17
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	Transient limiter	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Pulse Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Pulse Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the worst margin reading as below:

8.3 dB at 27.119230 MHz in the Neutral conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cisp}}r$$

in BACL, $U_{(L_m)}$ is less than $U_{\text{cisp}}r$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-03-27.

EUT operation mode: Transmitting & Charging

AC 120V / 60Hz – Line


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK /QP/Ave.)
0.206500	36.3	19.6	63.3	27.0	QP
0.206500	32.1	19.6	53.3	21.2	Ave.
0.253500	33.8	19.5	61.6	27.8	QP
0.253500	29.6	19.5	51.6	22.0	Ave.
0.443310	31.0	19.6	57.0	26.0	QP
0.443310	25.4	19.6	47.0	21.6	Ave.
0.947690	26.8	19.5	56.0	29.2	QP.
0.947690	19.9	19.5	46.0	26.1	Ave.
1.093590	27.6	19.5	56.0	28.4	QP
1.093590	20.9	19.5	46.0	25.1	Ave.
27.119230	40.0	20.1	60.0	20.0	QP
27.119230	39.9	20.1	50.0	10.1	Ave.

AC 120V / 60Hz – Neutral:

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK /QP/Ave.)
0.205500	37.6	19.6	63.4	25.8	QP
0.205500	33.2	19.6	53.4	20.2	Ave.
0.419670	33.6	19.6	57.5	23.9	QP
0.419670	26.8	19.6	47.5	20.7	Ave.
0.448630	27.4	19.6	56.9	29.5	QP
0.448630	22.7	19.6	46.9	24.2	Ave.
1.010850	28.9	19.5	56.0	27.1	QP.
1.010850	21.3	19.5	46.0	24.7	Ave.
1.069890	27.6	19.5	56.0	28.4	QP
1.069890	21.4	19.5	46.0	24.6	Ave.
27.119230	41.9	20.2	60.0	18.1	QP
27.119230	41.7	20.2	50.0	8.3	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz. and 4.92 dB for above 1GHz, and it will not be taken into consideration for the test data recorded in the report

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The PC was connected to an AC 120V/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2013-04-03	2014-04-03
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2013-08-03	2014-08-03
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the worst margin reading as below:

10.66 dB at 4874.0 MHz in the Vertical polarization for 802.11b mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

in BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	20~26 °C
Relative Humidity:	50~56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang from 2014-03-27 to 2014-03-28.

EUT operation mode: Transmitting

30 MHz-25 GHz**Model: PON-WIFI-D11U-C52-WG****802.11b mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	38.41	QP	35	1.7	H	-11.5	26.91	46	19.09
2412.0	92.63	PK	211	1.1	H	6.13	98.76	/	/
2412.0	90.01	Ave.	211	1.1	H	6.13	96.14	/	/
2412.0	92.43	PK	199	1.6	V	6.13	98.56	/	/
2412.0	87.30	Ave.	199	1.6	V	6.13	93.43	/	/
2343.7	34.67	PK	221	1.6	H	5.48	40.15	74	33.85
2343.7	20.74	Ave.	221	1.6	H	5.48	26.22	54	27.78
2220.1	34.28	PK	129	1.4	V	4.4	38.68	74	35.32
2220.1	21.26	Ave.	129	1.4	V	4.4	25.66	54	28.34
2488.4	35.77	PK	5	1.2	H	7.21	42.98	74	31.02
2488.4	20.86	Ave.	5	1.2	H	7.21	28.07	54	25.93
4824.0	40.63	PK	130	1.5	H	12.44	53.07	74	20.93
4824.0	30.72	Ave.	130	1.5	H	12.44	43.16	54	10.84
7236.0	36.43	PK	353	1.3	H	17.06	53.49	74	20.51
7236.0	24.99	Ave.	353	1.3	H	17.06	42.05	54	11.95
Middle Channel (2437 MHz)									
405.6	38.26	QP	93	1.7	H	-11.5	26.76	46	19.24
2437.0	92.84	PK	216	1.1	H	7.21	100.05	/	/
2437.0	90.87	Ave.	216	1.1	H	7.21	98.08	/	/
2437.0	93.26	PK	238	1.0	V	7.21	100.47	/	/
2437.0	87.77	Ave.	238	1.0	V	7.21	94.98	/	/
2355.0	35.19	PK	96	1.7	V	5.48	40.67	74	33.33
2355.0	21.60	Ave.	96	1.7	V	5.48	27.08	54	26.92
2245.7	34.71	PK	286	2.1	V	4.4	39.11	74	34.89
2245.7	21.50	Ave.	286	2.1	V	4.4	25.90	54	28.10
2490.4	36.41	PK	109	1.9	H	7.21	43.62	74	30.38
2490.4	21.26	Ave.	109	1.9	H	7.21	28.47	54	25.53
4874.0	40.81	PK	146	1.7	V	12.4	53.21	74	20.79
4874.0	30.94	Ave.	146	1.7	V	12.4	43.34	54	10.66
7311.0	36.60	PK	335	2.1	H	16.62	53.22	74	20.78
7311.0	25.22	Ave.	335	2.1	H	16.62	41.84	54	12.16

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	38.33	QP	220	1.7	H	-11.5	26.83	46	19.17
2462.0	92.58	PK	146	1.2	H	7.21	99.79	/	/
2462.0	89.82	Ave.	146	1.2	H	7.21	97.03	/	/
2462.0	92.11	PK	188	1.3	V	7.21	99.32	/	/
2462.0	87.08	Ave.	188	1.3	V	7.21	94.29	/	/
2341.6	34.40	PK	266	1.2	V	5.48	39.88	74	34.12
2341.6	20.43	Ave.	266	1.2	V	5.48	25.91	54	28.09
2237.2	34.20	PK	123	2.1	H	4.4	38.60	74	35.40
2237.2	20.54	Ave.	123	2.1	H	4.4	24.94	54	29.06
2489.9	35.44	PK	138	2.0	H	7.21	42.65	74	31.35
2489.9	20.16	Ave.	138	2.0	H	7.21	27.37	54	26.63
4924.0	39.72	PK	30	1.5	V	12.46	52.18	74	21.82
4924.0	30.28	Ave.	30	1.5	V	12.46	42.74	54	11.26
7386.0	35.87	PK	31	1.4	H	15.91	51.78	74	22.22
7386.0	24.98	Ave.	31	1.4	H	15.91	40.89	54	13.11

802.11g mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	37.95	QP	291	1.9	H	-11.5	26.45	46	19.55
2412.0	90.29	PK	235	1.7	H	6.13	96.42	/	/
2412.0	88.01	Ave.	235	1.7	H	6.13	94.14	/	/
2412.0	91.01	PK	233	1.8	V	6.13	97.14	/	/
2412.0	85.47	Ave.	233	1.8	V	6.13	91.6	/	/
2328.2	33.23	PK	161	2.2	H	4.99	38.22	74	35.78
2328.2	20.17	Ave.	161	2.2	H	4.99	25.16	54	28.84
2271.5	34.42	PK	330	1.0	V	4.4	38.82	74	35.18
2271.5	20.31	Ave.	330	1	V	4.4	24.71	54	29.29
2485.9	33.79	PK	284	1.4	H	7.21	41.00	74	33.00
2485.9	19.73	Ave.	284	1.4	H	7.21	26.94	54	27.06
4824.0	38.06	PK	333	1.0	H	12.44	50.50	74	23.50
4824.0	29.34	Ave.	333	1	H	12.44	41.78	54	12.22
7236.0	35.04	PK	359	1.7	H	17.06	52.10	74	21.90
7236.0	22.99	Ave.	359	1.7	H	17.06	40.05	54	13.95
Middle Channel (2437 MHz)									
405.6	38.13	QP	327	1.2	H	-11.5	26.63	46	19.37
2437.0	90.84	PK	307	1.2	H	7.21	98.05	/	/
2437.0	88.66	Ave.	307	1.2	H	7.21	95.87	/	/
2437.0	91.58	PK	304	1.4	V	7.21	98.79	/	/
2437.0	85.65	Ave.	304	1.4	V	7.21	92.86	/	/
2365.7	33.43	PK	8	1.1	H	5.48	38.91	74	35.09
2365.7	20.81	Ave.	8	1.1	H	5.48	26.29	54	27.71
2243.3	35.27	PK	73	1.6	V	4.4	39.67	74	34.33
2243.3	21.24	Ave.	73	1.6	V	4.4	25.64	54	28.36
2493.4	33.83	PK	69	2.1	H	7.21	41.04	74	32.96
2493.4	20.52	Ave.	69	2.1	H	7.21	27.73	54	26.27
4874.0	38.10	PK	289	1.5	V	12.4	50.50	74	23.50
4874.0	30.01	Ave.	289	1.5	V	12.4	42.41	54	11.59
7311.0	35.88	PK	38	1.6	H	16.62	52.50	74	21.50
7311.0	23.93	Ave.	38	1.6	H	16.62	40.55	54	13.45

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	37.89	QP	38	1.1	H	-11.5	26.39	46	19.61
2462.0	89.32	PK	124	1.3	H	7.21	96.53	/	/
2462.0	87.07	Ave.	124	1.3	H	7.21	94.28	/	/
2462.0	90.97	PK	285	1.7	V	7.21	98.18	/	/
2462.0	85.28	Ave.	285	1.7	V	7.21	92.49	/	/
2361.0	32.59	PK	358	1.4	V	5.48	38.07	74	35.93
2361.0	19.56	Ave.	358	1.4	V	5.48	25.04	54	28.96
2255.8	34.30	PK	315	1.3	H	4.4	38.70	74	35.30
2255.8	20.15	Ave.	315	1.3	H	4.4	24.55	54	29.45
2492.4	32.95	PK	192	1.2	H	7.21	40.16	74	33.84
2492.4	19.67	Ave.	192	1.2	H	7.21	26.88	54	27.12
4924.0	37.38	PK	257	2.2	H	12.46	49.84	74	24.16
4924.0	28.44	Ave.	257	2.2	H	12.46	40.90	54	13.10
7386.0	34.70	PK	292	1.5	V	15.91	50.61	74	23.39
7386.0	22.93	Ave.	292	1.5	V	15.91	38.84	54	15.16

802.11n-HT20 mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	37.68	QP	325	1.1	H	-11.5	26.18	46	19.82
2412.0	89.84	PK	77	2.0	H	6.13	95.97	/	/
2412.0	86.98	Ave.	77	2	H	6.13	93.11	/	/
2412.0	89.36	PK	255	1.9	V	6.13	95.49	/	/
2412.0	84.20	Ave.	255	1.9	V	6.13	90.33	/	/
2328.4	32.36	PK	272	1.9	H	4.99	37.35	74	36.65
2328.4	19.62	Ave.	272	1.9	H	4.99	24.61	54	29.39
2218.6	33.34	PK	184	1.8	V	4.4	37.74	74	36.26
2218.6	20.09	Ave.	184	1.8	V	4.4	24.49	54	29.51
2494.5	31.12	PK	171	1.9	H	7.21	38.33	74	35.67
2494.5	20.50	Ave.	171	1.9	H	7.21	27.71	54	26.29
4824.0	37.20	PK	16	1.3	H	12.44	49.64	74	24.36
4824.0	26.83	Ave.	16	1.3	H	12.44	39.27	54	14.73
7236.0	33.22	PK	137	1.6	H	17.06	50.28	74	23.72
7236.0	21.24	Ave.	137	1.6	H	17.06	38.30	54	15.70
Middle Channel (2437 MHz)									
405.6	37.75	QP	134	1.2	H	-11.5	26.25	46	19.75
2437.0	89.10	PK	205	1.5	H	7.21	96.31	/	/
2437.0	86.47	Ave.	205	1.5	H	7.21	93.68	/	/
2437.0	88.37	PK	217	1.2	V	7.21	95.58	/	/
2437.0	83.24	Ave.	217	1.2	V	7.21	90.45	/	/
2321.3	31.38	PK	130	2.0	V	4.99	36.37	74	37.63
2321.3	19.40	Ave.	130	2	V	4.99	24.39	54	29.61
2236.5	32.88	PK	78	1.8	H	4.4	37.28	74	36.72
2236.5	19.38	Ave.	78	1.8	H	4.4	23.78	54	30.22
2486.1	30.20	PK	289	1.1	H	7.21	37.41	74	36.59
2486.1	20.45	Ave.	289	1.1	H	7.21	27.66	54	26.34
4874.0	37.02	PK	166	1.5	H	12.4	49.42	74	24.58
4874.0	26.61	Ave.	166	1.5	H	12.4	39.01	54	14.99
7311.0	33.20	PK	315	2.1	V	16.62	49.82	74	24.18
7311.0	20.29	Ave.	315	2.1	V	16.62	36.91	54	17.09

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	37.6	QP	20	2.1	H	-11.5	26.10	46	19.90
2462.0	88.79	PK	55	1.0	H	7.21	96.00	/	/
2462.0	86.05	Ave.	55	1	H	7.21	93.26	/	/
2462.0	88.02	PK	314	2.0	V	7.21	95.23	/	/
2462.0	84.02	Ave.	314	2	V	7.21	91.23	/	/
2379.7	32.00	PK	311	1.1	H	5.48	37.48	74	36.52
2379.7	19.73	Ave.	311	1.1	H	5.48	25.21	54	28.79
2249.3	33.34	PK	342	1.8	V	4.4	37.74	74	36.26
2249.3	19.87	Ave.	342	1.8	V	4.4	24.27	54	29.73
2495.0	30.84	PK	140	1.8	H	7.21	38.05	74	35.95
2495.0	20.17	Ave.	140	1.8	H	7.21	27.38	54	26.62
4924.0	36.21	PK	129	2.1	V	12.46	48.67	74	25.33
4924.0	26.67	Ave.	129	2.1	V	12.46	39.13	54	14.87
7386.0	32.59	PK	62	1.3	H	15.91	48.50	74	25.50
7386.0	20.94	Ave.	62	1.3	H	15.91	36.85	54	17.15

802.11n-HT40 mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
405.6	37.83	QP	105	2.2	H	-11.5	26.33	46	19.67
2422.0	88.37	PK	103	1.7	H	6.13	94.5	/	/
2422.0	84.62	Ave.	103	1.7	H	6.13	90.75	/	/
2422.0	87.23	PK	10	1.5	V	6.13	93.36	/	/
2422.0	82.02	Ave.	10	1.5	V	6.13	88.15	/	/
2335.4	30.30	PK	322	1.4	H	4.99	35.29	74	38.71
2335.4	19.92	Ave.	322	1.4	H	4.99	24.91	54	29.09
2283.5	32.39	PK	100	1.3	H	4.99	37.38	74	36.62
2283.5	20.55	Ave.	100	1.3	H	4.99	25.54	54	28.46
2494.9	30.01	PK	236	2.1	V	7.21	37.22	74	36.78
2494.9	19.66	Ave.	236	2.1	V	7.21	26.87	54	27.13
4844.0	35.21	PK	281	1.5	H	12.4	47.61	74	26.39
4844.0	26.29	Ave.	281	1.5	H	12.4	38.69	54	15.31
7266.0	31.15	PK	96	1.2	H	16.62	47.77	74	26.23
7266.0	20.02	Ave.	96	1.2	H	16.62	36.64	54	17.36
Middle Channel(2437 MHz)									
405.6	37.66	QP	119	1.3	H	-11.5	26.16	46	19.84
2437.0	87.91	PK	60	2.1	H	7.21	95.12	/	/
2437.0	84.43	Ave.	60	2.1	H	7.21	91.64	/	/
2437.0	86.76	PK	158	1.7	V	7.21	93.97	/	/
2437.0	81.93	Ave.	158	1.7	V	7.21	89.14	/	/
2320.1	30.15	PK	357	2.1	H	4.99	35.14	74	38.86
2320.1	19.88	Ave.	357	2.1	H	4.99	24.87	54	29.13
2233.6	32.17	PK	93	1.7	H	4.4	36.57	74	37.43
2233.6	19.42	Ave.	93	1.7	H	4.4	23.82	54	30.18
2497.0	29.94	PK	260	2.1	H	7.21	37.15	74	36.85
2497.0	19.29	Ave.	260	2.1	H	7.21	26.50	54	27.50
4874.0	35.21	PK	268	2.0	V	12.4	47.61	74	26.39
4874.0	26.16	Ave.	268	2.0	V	12.4	38.56	54	15.44
7311.0	30.92	PK	105	1.6	V	16.62	47.54	74	26.46
7311.0	19.94	Ave.	105	1.6	V	16.62	36.56	54	17.44

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
High Channel (2452 MHz)									
405.6	37.58	QP	129	1.1	H	-11.5	26.08	46	19.92
2452.0	88.33	PK	266	1.4	H	7.21	95.54	/	/
2452.0	84.47	Ave.	266	1.4	H	7.21	91.68	/	/
2452.0	87.45	PK	175	1.3	V	7.21	94.66	/	/
2452.0	82.05	Ave.	175	1.3	V	7.21	89.26	/	/
2359.2	30.26	PK	297	1.8	H	5.48	35.74	74	38.26
2359.2	19.11	Ave.	297	1.8	H	5.48	24.59	54	29.41
2293.8	32.81	PK	305	1.9	H	4.99	37.80	74	36.20
2293.8	20.12	Ave.	305	1.9	H	4.99	25.11	54	28.89
2492.0	30.28	PK	30	2.1	V	7.21	37.49	74	36.51
2492.0	20.23	Ave.	30	2.1	V	7.21	27.44	54	26.56
4904.0	35.76	PK	218	1.5	H	12.46	48.22	74	25.78
4904.0	26.23	Ave.	218	1.5	H	12.46	38.69	54	15.31
7356.0	31.62	PK	301	1.0	H	16.49	48.11	74	25.89
7356.0	20.11	Ave.	301	1.0	H	16.49	36.60	54	17.40

Model: PON-WIFI-D11U-C26-WG**802.11b mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	38.25	QP	87	1.2	H	-11.5	26.75	46	19.25
2412.0	92.17	PK	113	1.6	H	6.13	98.76	/	/
2412.0	89.42	Ave.	113	1.6	H	6.13	96.14	/	/
2412.0	92.34	PK	349	1.4	V	6.13	98.56	/	/
2412.0	86.47	Ave.	349	1.4	V	6.13	93.43	/	/
2336.4	34.48	PK	41	1.2	H	4.99	39.47	74	34.53
2336.4	20.46	Ave.	41	1.2	H	4.99	25.45	54	28.55
2247.6	33.58	PK	177	2.0	V	4.4	37.98	74	36.02
2247.6	21.12	Ave.	177	2	V	4.4	25.52	54	28.48
2490.1	34.81	PK	45	1.6	H	7.21	42.02	74	31.98
2490.1	21.07	Ave.	45	1.6	H	7.21	28.28	54	25.72
4824.0	39.67	PK	139	2.1	H	12.44	52.11	74	21.89
4824.0	29.82	Ave.	139	2.1	H	12.44	42.26	54	11.74
7236.0	35.99	PK	255	1.6	H	17.06	53.05	74	20.95
7236.0	24.45	Ave.	255	1.6	H	17.06	41.51	54	12.49
Middle Channel (2437 MHz)									
405.6	37.96	QP	30	1.2	H	-11.5	26.46	46	19.54
2437.0	91.20	PK	229	1.8	H	7.21	100.05	/	/
2437.0	90.76	Ave.	229	1.8	H	7.21	98.08	/	/
2437.0	92.39	PK	223	1.3	V	7.21	100.47	/	/
2437.0	87.15	Ave.	223	1.3	V	7.21	94.98	/	/
2321.3	33.43	PK	135	1.2	V	4.99	38.42	74	35.58
2321.3	20.45	Ave.	135	1.2	V	4.99	25.44	54	28.56
2269.7	33.80	PK	354	2.1	V	4.4	38.20	74	35.80
2269.7	20.16	Ave.	354	2.1	V	4.4	24.56	54	29.44
2485.1	36.23	PK	160	1.4	H	7.21	43.44	74	30.56
2485.1	22.18	Ave.	160	1.4	H	7.21	29.39	54	24.61
4874.0	39.57	PK	204	1.6	V	12.4	51.97	74	22.03
4874.0	30.31	Ave.	204	1.6	V	12.4	42.71	54	11.29
7311.0	36.36	PK	71	2.0	H	16.62	52.98	74	21.02
7311.0	23.72	Ave.	71	2	H	16.62	40.34	54	13.66

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	38.03	QP	78	1.2	H	-11.5	26.53	46	19.47
2462.0	91.34	PK	137	1.6	H	7.21	99.79	/	/
2462.0	89.69	Ave.	137	1.6	H	7.21	97.03	/	/
2462.0	90.14	PK	321	2.0	V	7.21	99.32	/	/
2462.0	86.40	Ave.	321	2	V	7.21	94.29	/	/
2341.6	34.26	PK	97	1.7	V	5.48	39.74	74	34.26
2341.6	20.75	Ave.	97	1.7	V	5.48	26.23	54	27.77
2237.2	32.41	PK	90	1.1	H	4.4	36.81	74	37.19
2237.2	20.10	Ave.	90	1.1	H	4.4	24.50	54	29.50
2489.9	34.54	PK	208	1.3	H	7.21	41.75	74	32.25
2489.9	21.25	Ave.	208	1.3	H	7.21	28.46	54	25.54
4924.0	39.25	PK	140	2.1	V	12.46	51.71	74	22.29
4924.0	29.20	Ave.	140	2.1	V	12.46	41.66	54	12.34
7386.0	34.41	PK	186	1.3	H	15.91	50.32	74	23.68
7386.0	24.39	Ave.	186	1.3	H	15.91	40.30	54	13.70

802.11g mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	37.81	QP	199	1.2	H	-11.5	26.31	46	19.69
2412.0	88.95	PK	88	1.3	H	6.13	96.42	/	/
2412.0	86.77	Ave.	88	1.3	H	6.13	94.14	/	/
2412.0	89.41	PK	173	2.0	V	6.13	97.14	/	/
2412.0	84.70	Ave.	173	2	V	6.13	91.6	/	/
2318.2	32.47	PK	121	1.1	H	4.99	37.46	74	36.54
2318.2	19.79	Ave.	121	1.1	H	4.99	24.78	54	29.22
2229.7	33.08	PK	295	2.0	V	4.4	37.48	74	36.52
2229.7	21.07	Ave.	295	2	V	4.4	25.47	54	28.53
2487.4	33.06	PK	208	1.4	H	7.21	40.27	74	33.73
2487.4	19.32	Ave.	208	1.4	H	7.21	26.53	54	27.47
4824.0	36.13	PK	272	1.8	H	12.44	48.57	74	25.43
4824.0	27.57	Ave.	272	1.8	H	12.44	40.01	54	13.99
7236.0	35.02	PK	357	1.7	H	17.06	52.08	74	21.92
7236.0	21.10	Ave.	357	1.7	H	17.06	38.16	54	15.84
Middle Channel (2437 MHz)									
405.6	37.77	QP	82	1.2	H	-11.5	26.27	46	19.73
2437.0	90.14	PK	298	1.1	H	7.21	98.05	/	/
2437.0	88.21	Ave.	298	1.1	H	7.21	95.87	/	/
2437.0	91.39	PK	9	2.1	V	7.21	98.79	/	/
2437.0	85.58	Ave.	9	2.1	V	7.21	92.86	/	/
2350.8	32.93	PK	274	1.9	H	5.48	38.41	74	35.59
2350.8	20.62	Ave.	274	1.9	H	5.48	26.10	54	27.90
2267.1	34.52	PK	105	1.3	V	4.4	38.92	74	35.08
2267.1	20.97	Ave.	105	1.3	V	4.4	25.37	54	28.63
2495.2	32.93	PK	111	1.8	H	7.21	40.14	74	33.86
2495.2	20.36	Ave.	111	1.8	H	7.21	27.57	54	26.43
4874.0	37.93	PK	225	1.3	V	12.4	50.33	74	23.67
4874.0	29.86	Ave.	225	1.3	V	12.4	42.26	54	11.74
7311.0	35.65	PK	247	1.5	H	16.62	52.27	74	21.73
7311.0	23.76	Ave.	247	1.5	H	16.62	40.38	54	13.62

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	37.68	QP	248	1.2	H	-11.5	26.18	46	19.82
2462.0	89.19	PK	236	1.3	H	7.21	96.53	/	/
2462.0	86.31	Ave.	236	1.3	H	7.21	94.28	/	/
2462.0	90.55	PK	332	1.2	V	7.21	98.18	/	/
2462.0	85.07	Ave.	332	1.2	V	7.21	92.49	/	/
2372.9	32.45	PK	32	1.5	V	5.48	37.93	74	36.07
2372.9	19.88	Ave.	32	1.5	V	5.48	25.36	54	28.64
2231.2	34.06	PK	319	1.0	H	4.4	38.46	74	35.54
2231.2	19.95	Ave.	319	1	H	4.4	24.35	54	29.65
2490.0	32.87	PK	158	1.0	H	7.21	40.08	74	33.92
2490.0	20.68	Ave.	158	1	H	7.21	27.89	54	26.11
4924.0	37.13	PK	11	1.9	H	12.46	49.59	74	24.41
4924.0	27.46	Ave.	11	1.9	H	12.46	39.92	54	14.08
7386.0	33.96	PK	228	1.4	V	15.91	49.87	74	24.13
7386.0	22.67	Ave.	228	1.4	V	15.91	38.58	54	15.42

802.11n-HT20 mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
405.6	37.8	QP	156	1.2	H	-11.5	26.30	46	19.70
2412.0	89.12	PK	182	1.8	H	6.13	95.97	/	/
2412.0	86.68	Ave.	182	1.8	H	6.13	93.11	/	/
2412.0	88.47	PK	341	1.8	V	6.13	95.49	/	/
2412.0	84.14	Ave.	341	1.8	V	6.13	90.33	/	/
2353.1	32.18	PK	134	1.0	H	5.48	37.66	74	36.34
2353.1	20.13	Ave.	134	1	H	5.48	25.61	54	28.39
2227.9	32.48	PK	67	1.3	V	4.4	36.88	74	37.12
2227.9	19.81	Ave.	67	1.3	V	4.4	24.21	54	29.79
2488.5	30.25	PK	144	1.5	H	7.21	37.46	74	36.54
2488.5	20.46	Ave.	144	1.5	H	7.21	27.67	54	26.33
4824.0	36.95	PK	34	1.5	H	12.44	49.39	74	24.61
4824.0	26.39	Ave.	34	1.5	H	12.44	38.83	54	15.17
7236.0	33.04	PK	189	1.1	H	17.06	50.10	74	23.90
7236.0	21.01	Ave.	189	1.1	H	17.06	38.07	54	15.93
Middle Channel (2437 MHz)									
405.6	38.01	QP	312	1.2	H	-11.5	26.51	46	19.49
2437.0	88.65	PK	146	2.1	H	7.21	96.31	/	/
2437.0	85.12	Ave.	146	2.1	H	7.21	93.68	/	/
2437.0	88.06	PK	245	2.2	V	7.21	95.58	/	/
2437.0	82.04	Ave.	245	2.2	V	7.21	90.45	/	/
2315.7	30.21	PK	162	1.6	V	4.99	35.20	74	38.80
2315.7	19.74	Ave.	162	1.6	V	4.99	24.73	54	29.27
2240.3	31.44	PK	56	1.9	H	4.4	35.84	74	38.16
2240.3	19.55	Ave.	56	1.9	H	4.4	23.95	54	30.05
2485.9	30.00	PK	49	1.2	H	7.21	37.21	74	36.79
2485.9	19.26	Ave.	49	1.2	H	7.21	26.47	54	27.53
4874.0	36.58	PK	314	1.3	H	12.4	48.98	74	25.02
4874.0	25.01	Ave.	314	1.3	H	12.4	37.41	54	16.59
7311.0	32.43	PK	293	2.0	V	16.62	49.05	74	24.95
7311.0	19.09	Ave.	293	2	V	16.62	35.71	54	18.29

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
405.6	37.59	QP	152	1.2	H	-11.5	26.09	46	19.91
2462.0	88.55	PK	272	1.2	H	7.21	96.00	/	/
2462.0	85.43	Ave.	272	1.2	H	7.21	93.26	/	/
2462.0	87.54	PK	159	2.1	V	7.21	95.23	/	/
2462.0	83.99	Ave.	159	2.1	V	7.21	91.23	/	/
2371.7	31.71	PK	309	1.3	H	5.48	37.19	74	36.81
2371.7	19.41	Ave.	309	1.3	H	5.48	24.89	54	29.11
2257.1	32.74	PK	98	1.7	V	4.4	37.14	74	36.86
2257.1	19.82	Ave.	98	1.7	V	4.4	24.22	54	29.78
2494.0	30.45	PK	173	2.2	H	7.21	37.66	74	36.34
2494.0	19.94	Ave.	173	2.2	H	7.21	27.15	54	26.85
4924.0	36.17	PK	240	1.1	V	12.46	48.63	74	25.37
4924.0	26.27	Ave.	240	1.1	V	12.46	38.73	54	15.27
7386.0	31.60	PK	25	1.1	H	15.91	47.51	74	26.49
7386.0	20.55	Ave.	25	1.1	H	15.91	36.46	54	17.54

802.11n-HT40 mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
405.6	37.63	QP	13	1.2	H	-11.5	26.13	46	19.87
2422.0	87.65	PK	282	1.6	H	6.13	94.5	/	/
2422.0	82.98	Ave.	282	1.6	H	6.13	90.75	/	/
2422.0	86.18	PK	298	1.2	V	6.13	93.36	/	/
2422.0	80.11	Ave.	298	1.2	V	6.13	88.15	/	/
2331.6	29.66	PK	86	1.6	H	4.99	34.65	74	39.35
2331.6	19.90	Ave.	86	1.6	H	4.99	24.89	54	29.11
2276.5	31.82	PK	315	1.4	H	4.99	36.81	74	37.19
2276.5	19.36	Ave.	315	1.4	H	4.99	24.35	54	29.65
2493.4	29.20	PK	131	2.1	V	7.21	36.41	74	37.59
2493.4	19.20	Ave.	131	2.1	V	7.21	26.41	54	27.59
4844.0	33.54	PK	305	1.8	H	12.4	45.94	74	28.06
4844.0	24.46	Ave.	305	1.8	H	12.4	36.86	54	17.14
7266.0	30.53	PK	318	1.7	H	16.62	47.15	74	26.85
7266.0	19.16	Ave.	318	1.7	H	16.62	35.78	54	18.22
Middle Channel (2437 MHz)									
405.6	37.66	QP	96	2.2	H	-11.5	26.16	46	19.84
2437.0	87.73	PK	347	1.8	H	7.21	95.12	/	/
2437.0	84.26	Ave.	347	1.8	H	7.21	91.64	/	/
2437.0	86.54	PK	336	1.2	V	7.21	93.97	/	/
2437.0	81.50	Ave.	336	1.2	V	7.21	89.14	/	/
2338.2	29.40	PK	201	1.5	H	4.99	34.39	74	39.61
2338.2	19.29	Ave.	201	1.5	H	4.99	24.28	54	29.72
2206.7	31.19	PK	93	1.1	H	3.94	35.13	74	38.87
2206.7	19.27	Ave.	93	1.1	H	3.94	23.21	54	30.79
2491.9	29.11	PK	8	1.9	H	7.21	36.32	74	37.68
2491.9	19.18	Ave.	8	1.9	H	7.21	26.39	54	27.61
4874.0	35.16	PK	305	1.8	V	12.4	47.56	74	26.44
4874.0	25.17	Ave.	305	1.8	V	12.4	37.57	54	16.43
7311.0	30.63	PK	48	1.8	V	16.62	47.25	74	26.75
7311.0	19.98	Ave.	48	1.8	V	16.62	36.60	54	17.40



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2452 MHz)									
405.6	37.47	QP	56	1.2	H	-11.5	25.97	46	20.03
2452.0	87.20	PK	147	1.3	H	7.21	95.54	/	/
2452.0	83.95	Ave.	147	1.3	H	7.21	91.68	/	/
2452.0	86.36	PK	333	2.1	V	7.21	94.66	/	/
2452.0	81.60	Ave.	333	2.1	V	7.21	89.26	/	/
2387.0	28.45	PK	19	1.3	H	5.48	33.93	74	40.07
2387.0	19.54	Ave.	19	1.3	H	5.48	25.02	54	28.98
2211.2	32.79	PK	150	1.7	H	3.94	36.73	74	37.27
2211.2	19.47	Ave.	150	1.7	H	3.94	23.41	54	30.59
2492.0	30.23	PK	269	2.1	V	7.21	37.44	74	36.56
2492.0	18.59	Ave.	269	2.1	V	7.21	25.80	54	28.20
4904.0	34.25	PK	269	1.5	H	12.46	46.71	74	27.29
4904.0	24.43	Ave.	269	1.5	H	12.46	36.89	54	17.11
7356.0	30.92	PK	242	1.7	H	16.49	47.41	74	26.59
7356.0	19.73	Ave.	242	1.7	H	16.49	36.22	54	17.78

Note:


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) + cable loss – amplifier factor


Margin = Limit- Corr. Amplitude

Conducted Spurious Emissions at Antenna Port:**802.11b Low Channel****802.11b Middle Channel**


802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n-HT20 Low Channel




802.11n-HT20 Middle Channel




802.11n-HT20 High Channel




802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



FCC §15.247(a) (2) – 6 dB EMISSIONS BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20~26 °C
Relative Humidity:	50~56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-03-27 and 2014-03-28.


EUT operation mode: Transmitting

Test Result: Pass.


Please refer to the following tables and plots.

Channel	Frequency (MHz)	Data Rate (Mbps)	6dB Emissions Bandwidth (MHz)	Limit (kHz)	Result
802.11b mode					
Low	2412	1	10.100	≥ 500	Pass
Middle	2437	1	10.100	≥ 500	Pass
High	2462	1	10.100	≥ 500	Pass
802.11g mode					
Low	2412	6	16.473	≥ 500	Pass
Middle	2437	6	16.473	≥ 500	Pass
High	2462	6	16.473	≥ 500	Pass
802.11n-HT20 mode					
Low	2412	MCS0	17.675	≥ 500	Pass
Middle	2437	MCS0	17.675	≥ 500	Pass
High	2462	MCS0	17.675	≥ 500	Pass
802.11n-HT40 mode					
Low	2422	MCS0	36.553	≥ 500	Pass
Middle	2437	MCS0	36.553	≥ 500	Pass
High	2452	MCS0	36.553	≥ 500	Pass


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n-HT20 Low Channel




802.11n-HT20 Middle Channel




802.11n-HT20 High Channel




802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



FCC §15.247(b) (3) - MAXIMUM OUTPUT POWER


Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
HP	Power Meter	EPM-441A	GB37481494	2013-11-24	2014-11-24
HP	Power Sensor	EPM-441A	GB37481494	2013-11-24	2014-11-24

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Simon Wang from 2014-04-03.

EUT operation mode: Transmitting


Channel	Frequency (MHz)	Data Rate (Mbps)	Peak Output Power (dBm)	Average Output Power (dBm)	Limit (dBm)
802.11b					
Low	2412	1	13.26	10.44	30
Middle	2437	1	13.21	10.57	30
High	2462	1	13.30	10.47	30
802.11g					
Low	2412	6	16.42	8.89	30
Middle	2437	6	16.51	8.70	30
High	2462	6	16.48	8.74	30
802.11n-HT20					
Low	2412	MCS0	16.30	8.00	30
Middle	2437	MCS0	16.03	7.95	30
High	2462	MCS0	16.23	8.05	30
802.11n-HT40					
Low	2422	MCS0	14.84	7.52	30
Middle	2437	MCS0	14.75	7.54	30
High	2452	MCS0	14.46	7.54	30

Note: The AVG power was test by power meter.


802.11b RF Peak Output Power, Low Channel




802.11b RF Peak Output Power, Middle Channel




802.11b RF Peak Output Power, High Channel




802.11g RF Peak Output Power, Low Channel




802.11g RF Peak Output Power, Middle Channel




802.11g RF Peak Output Power, High Channel




802.11n-HT20 RF Peak Output Power, Low Channel




802.11n-HT20 RF Peak Output Power, Middle Channel





802.11n-HT20 RF Peak Output Power, High Channel



802.11n-HT40 RF Peak Output Power, Low Channel



802.11n-HT40 RF Peak Output Power, Middle Channel**802.11n-HT40 RF Peak Output Power, High Channel**

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	20~26 °C
Relative Humidity:	50~56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2014-03-27 and 2014-03-28.


EUT operation mode: Transmitting

Test Result: *Compliance.* Please refer to following plots.


802.11b Band Edge, Left Side




802.11b Band Edge, Right Side




802.11g Band Edge, Left Side




802.11g Band Edge, Right Side




802.11n-HT20 Band Edge, Left Side




802.11n-HT20 Band Edge, Right Side



802.11n-HT40 Band Edge, Left Side



802.11n-HT40 Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY


Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Set analy center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measurement value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20~26 °C
Relative Humidity:	50~56 %
ATM Pressure:	101.0 kPa


The testing was performed by Simon Wang on 2014-03-27 and 2014-04-03.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	Data Rate (Mbps)	Correct Power spectral density (dBm/3 kHz)	≤Limit (dBm)
802.11b mode				
Low	2412	1	-10.86	≤8
Middle	2437	1	-10.22	≤8
High	2462	1	-11.16	≤8
802.11g mode				
Low	2412	6	-16.82	≤8
Middle	2437	6	-16.48	≤8
High	2462	6	-16.72	≤8
802.11n-HT20 mode				
Low	2412	MCS0	-16.86	≤8
Middle	2437	MCS0	-16.34	≤8
High	2462	MCS0	-16.41	≤8
802.11n-HT40 mode				
Low	2422	MCS0	-23.35	≤8
Middle	2437	MCS0	-23.83	≤8
High	2452	MCS0	-23.16	≤8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n-HT20 Low Channel




Power Spectral Density, 802.11n-HT20 Middle Channel





Power Spectral Density, 802.11n-HT20 High Channel



Power Spectral Density, 802.11n-HT40 Low Channel



Power Spectral Density, 802.11n-HT40 Middle Channel**Power Spectral Density, 802.11n-HT40 High Channel**

PRODUCT SIMILARITY DECLARATION LETTER

Power7 Technology (Dong Guan) Co., Ltd.
No. 28 Binjiang Blvd Shishuikou Village, Qiao tou Town, DongGuan, China
Tel: 86-769-89297777 Fax: 86-769-89299777

2014-04-23

Product Similarity Declaration


To Whom It May Concern,

We, Power7 Technology (Dong Guan) Co., Ltd. hereby declare that our WIFI SD With Power bank, Model Number PON-WIFI-D11U-C26-WG, DOS-WIFI-D11U-C26-BK, STA-WIFI-D11U-C26-BK, PON-WIFI-D11U-C52-WG are electrically identical. They are different in battery capacity and the appearance size. And the models PON-WIFI-D11U-C26-WG and PON-WIFI-D11U-C52-WG were tested by BACL.

In addition, the models PON-WIFI-D11U-C26-WG, DOS-WIFI-D11U-C26-BK, STA-WIFI-D11U-C26-BK have one 2600mAh battery, The PON-WIFI-D11U-C52-WG has one 5200mAh battery.

Please contact me if you have any question.

Signature:



ST Wang

Vice General Manager

*****END OF REPORT*****