

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-576_02.doc	Date of Report:	17-Dec-2009
Number of pages:	17	Customer's Contact person:	Shao Xu
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-576 / Battery BL-4CT, AC charger AC-8E, Headset HS-105		
FCC ID:	QTKRM-576	IC:	661AD-RM576
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 2, June 2007) and RSS-210 (Issue 7, June 2007). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Jari Jantunen, System Manager, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	18-Nov-2009
Testing completed	25-Nov-2009
The customer's contact person	Shao Xu
Test Plan referred to	T:\Projects\RM-576\TestPlan_RS\RS_testplan_RM-576.xls
Notes	-
Document name	FCC15C_RM-576_02.doc

1.1. EUT and Accessory Information

The EUT is a 7-band (GSM850/900/1800/1900 and WCDMA Band I/II(1900)/VIII) mobile phone with GPRS, EGPRS and Bluetooth. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-576	004401108387198;0580662	0300A	-	031.005	42100
Battery	BL-4CT	3820669341218462340;0670565	-	-	-	42102
AC charger	AC-8E	1103338411070317367;0675387	-	-	-	41980
Headset	HS-105	0694287913411200016	-	-	-	41981

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Conducted peak output power	NP
15.247(d)	A8.5	Band edge compliance of RF emissions	PASSED
15.247(d)	A8.5	Spurious RF conducted emissions	NP
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.2	AC powerline conducted emissions	PASSED
15.247(a)(1)	A8.1 (a)	20 dB bandwidth	NP
15.247(a)(1)	A8.1 (b)	Carrier frequency separation	NP
15.247(a)(1)(iii)	A8.1 (d)	Number of hopping frequencies	NP
15.247(a)(1)(iii)	A8.1 (d)	Time of occupancy	NP

PASSED

The EUT complies with the essential requirements in the standard.

FAILED

The EUT does not comply with the essential requirements in the standard.

NP


The test was not performed by the TCC Nokia Tampere Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups.....	4
2.1. Conducted RF test setup	4
2.2. AC powerline conducted emissions test setup.....	4
2.3. Radiated test setup	4
3. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5).....	5
3.1. Test method and limit.....	5
3.2. Bluetooth Test results	6
4. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5).....	10
4.1. Test method and limit.....	10
4.2. Bluetooth Test results	12
5. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	14
5.1. Test method and limit.....	14
5.2. Bluetooth Test results	15
6. Test Equipment.....	16
6.1. Conducted measurements	16
6.2. Radiated measurements	16

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Radiated test setup



3. Band edge compliance of RF emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-576 DUT42100
Accessories with DUT numbers	BL-4CT DUT42102, AC-8E DUT42102, HS-105 DUT41981
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 47 / 99.2
Date of measurements	23-Nov-2009
Measured by	Hannu Söderholm

3.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit Average [dBμV/m]	Limit Peak [dBμV/m]
Below 2390 and above 2483.5	≤ 54	≤ 74

3.2. Bluetooth Test results


3.2.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	45.30	PASSED
Average	25.90	PASSED

Channel 78 / 2480 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	51.60	PASSED
Average	26.40	PASSED

Hopping on, low end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	47.50	PASSED
Average	31.10	PASSED


Hopping on, high end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	54.90	PASSED
Average	31.70	PASSED


3.2.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	46.60	PASSED
Average	25.90	PASSED

Channel 78 / 2480 MHz




Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	53.80	PASSED
Average	26.50	PASSED

Hopping on, low end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	46.60	PASSED
Average	31.10	PASSED

Hopping on, high end



Detector (RBW: 1 MHz)	E [dB μ V/m]	Result
Peak	53.90	PASSED
Average	32.10	PASSED

4. Spurious radiated emissions (FCC §15.247(d), §15.209, RSS-210 A8.5)

EUT with DUT number	RM-576 DUT42100
Accessories with DUT numbers	BL-4CT DUT42102, AC-8E DUT42102, HS-105 DUT41981
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 47 / 99.2
Date of measurements	20-Nov-2009
Measured by	Hannu Söderholm

4.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu\text{V/m}$]	Limit [dB $\mu\text{V/m}$]	Detector
30 – 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

4.2. Bluetooth Test results

4.2.1 GFSK modulation, PRBS packet type

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	41.60	120.23	42.60	-1.0	HORIZONTAL	PASSED
7206.000000	42.30	130.32	39.90	2.4	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	28.10	25.41	29.10	-1.0	HORIZONTAL	PASSED
7206.000000	30.10	31.99	27.70	2.4	VERTICAL	PASSED

TX mode, channel 40 / 2442 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
32.945291	29.10	28.51	39.80	-10.7	VERTICAL	PASSED
37.876353	17.20	7.24	31.20	-14.0	VERTICAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4963.931864	41.20	114.82	41.70	-0.5	HORIZONTAL	PASSED
4963.933868	40.50	105.93	41.00	-0.5	HORIZONTAL	PASSED
7312.629259	43.40	147.91	40.40	3.0	VERTICAL	PASSED
7325.653307	43.50	149.62	40.60	2.9	HORIZONTAL	PASSED
17493.983968	52.40	416.87	33.50	18.9	VERTICAL	PASSED
17752.005010	55.00	562.34	34.10	20.9	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4964.933868	28.30	26.00	28.80	-0.5	HORIZONTAL	PASSED
7314.629259	30.70	34.28	27.70	3.0	VERTICAL	PASSED
7323.653307	30.40	33.11	27.50	2.9	HORIZONTAL	PASSED
17491.983968	39.80	97.72	21.00	18.8	VERTICAL	PASSED
17756.005010	42.20	128.82	21.30	20.9	VERTICAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	41.20	114.82	41.70	-0.5	VERTICAL	PASSED
7440.000000	42.80	138.04	39.60	3.2	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	28.20	25.70	28.70	-0.5	VERTICAL	PASSED
7440.000000	29.80	30.90	26.60	3.2	HORIZONTAL	PASSED

4.2.2 8DPSK modulation, PRBS packet type

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	42.90	139.64	43.90	-1.0	HORIZONTAL	PASSED
7206.000000	43.30	146.22	40.90	2.4	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	31.70	38.46	32.70	-1.0	HORIZONTAL	PASSED
7206.000000	30.20	32.36	27.80	2.4	HORIZONTAL	PASSED

TX mode, channel 40 / 2442 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
37.976353	15.40	5.89	29.50	-14.1	VERTICAL	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4953.899800	41.00	112.20	41.70	-0.7	VERTICAL	PASSED
7319.631263	43.50	149.62	40.50	3.0	HORIZONTAL	PASSED
7328.157315	43.20	144.54	40.30	2.9	VERTICAL	PASSED
17491.481964	53.00	446.68	34.20	18.8	HORIZONTAL	PASSED
17804.105210	55.20	575.44	34.40	20.8	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4953.899800	27.90	24.83	28.60	-0.7	VERTICAL	PASSED
4964.433868	28.00	25.12	28.50	-0.5	HORIZONTAL	PASSED
7319.131263	30.30	32.73	27.20	3.1	HORIZONTAL	PASSED
7332.157315	30.40	33.11	27.50	2.9	VERTICAL	PASSED
17487.481964	39.80	97.72	21.00	18.8	HORIZONTAL	PASSED
17802.605210	42.10	127.35	21.30	20.8	VERTICAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	40.80	109.65	41.30	-0.5	HORIZONTAL	PASSED
7440.000000	42.50	133.35	39.30	3.2	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4960.000000	28.30	26.00	28.80	-0.5	HORIZONTAL	PASSED
7440.000000	29.80	30.90	26.60	3.2	VERTICAL	PASSED

5. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-576 DUT42100
Accessories with DUT numbers	BL-4CT DUT42102, AC-8E DUT42102, HS-105 DUT41981
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 48 / 99.8
Date of measurements	25-Nov-2009
Measured by	Hanu Söderholm

5.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

5.2. Bluetooth Test results

5.2.1 GFSK modulation, PRBS packet type

Middle channel / 98.0 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.185000	33.90	N	PASSED
0.420000	27.60	N	PASSED
0.585000	24.60	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
2.625000	22.70	L1	PASSED
4.240000	23.50	L1	PASSED
7.065000	25.60	L1	PASSED

6. Test Equipment

6.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30597	Power splitter	11667A	Agilent	22/24/27, 15C
TM37499	Power splitter	11667A	Agilent	22/24/27, 15C
TM38111	Multimeter	34401A	Agilent	22/24/27, 15C
TM38112	DC power supply	6632A	Agilent	22/24/27, 15C
TM22901	Attenuator	8496A	Agilent	22/24/27, 15C
TM30636	Artificial mains net	L2-16	PMM	15C, 15B
TM37678	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B
TM37773	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B
TM30600	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum analyzer	FSU	R&S	22/24/27, 15C
TM22835	Multimeter	87	Fluke	15C, 15B
TM37500	Microwave switch system	7116-MSW	Keithley	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	Transmatic	22/24/27, 15C, 15B
	Temperature chamber	VT4002	Vötsch	22/24/27, 15C
2058	EMI Test receiver	ESPC	R&S	15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B

6.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	22/24/27, 15C, 15B
TM38845	EMI receiver	ESI 40	R&S	22/24/27, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	22/24/27, 15C, 15B
TM37516	Biconilog antenna	HL562	R&S	22/24/27, 15C, 15B
TM26496	Double ridged waveguide antenna	3115	EMCO	22/24/27, 15C, 15B
TM39158	Horn antenna	3116	EMCO	22/24/27, 15C, 15B
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	22/24/27, 15C, 15B
TM37501	Dipole antenna	3125-870	EMCO	22/24/27
TM37502	Dipole antenna	3125-1880	EMCO	22/24/27
TM37773	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B
TM38631	Signal generator	83640L	Agilent	22/24/27, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24/27, 15C, 15B
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24/27
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24/27
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Mast/Turntable controller	HD-100	Deisel	22/24/27, 15C, 15B
TM26500	Turntable	DS412	Deisel	22/24/27, 15C, 15B
TM38842	Antenna mast controller	2090	EMCO	22/24/27, 15C, 15B
TM38843	Antenna mast	2075	EMCO	22/24/27, 15C, 15B
TM38114	DC power supply	6632A	Agilent	22/24/27, 15C, 15B
TM38323	Preamplifier	PA-02 18-26 GHz	EMC Automation	22/24/27, 15C, 15B
TM37678	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	Transmatic	22/24/27, 15C, 15B
TM23892	Yaesu controller	G-1000SDX	Yaesu	22/24/27, 15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Radio communication tester	CMU-200	R&S	22/24/27, 15C, 15B

