

FCC Part 22/24 Compliance Test Report

Test Report no.:	FCC22&24_RM-577_03.doc	Date of Report:	14-Jan-2010
Number of pages:	19	Customer's Contact person:	Shao Xu
Testing laboratory:	TCC Nokia Salo Laboratory P.O.Box(86) Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Customer:	Nokia Corporation Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-577 / Battery BL-4CT		
FCC ID:	QTKRM-577	IC:	661AD-RM577
Supplement reports:	The results in this report are based on results from report FCC22&24_RM-576_11.		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 22 and 24, TIA-603-C-2004 and IC standards RSS-GEN (Issue 2, June 2007) and RSS-132 (Issue 2, September 2005) and RSS-133 (Issue 5, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Christian Andersen, System Specialist, EMC

1. Summary for FCC Part 22/24 Compliance Test Report

Date of receipt	17-Nov-2009
Testing completed	07-Dec-2009
The customer's contact person	Shao Xu
Test Plan referred to	T:\Projects\RM-576\TestPlan_RS\RS_testplan_RM-576.xls
Notes	-
Document name	T:\Projects\RM-576\EMC\FCC22&24_RM-576_11.doc

1.1. EUT and Accessory Information

The EUT is a 7-band (GSM850/900/1800/1900) and WCDMA Band (I/II/V) mobile phone with GPRS, EGPRS, HSDPA, HSUPA and Bluetooth.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-576	004401108388733	0300A		031.005	14347
Battery	BL-4CT	3932139094E5017424100670566	-	-	-	14302

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	PASSED
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

GSM 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA 1900 (Band II):

Section in CFR 47	Section in <i>RSS-GEN</i> or <i>RSS-133</i>	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED

The EUT complies with the essential requirements in the standard.

FAILED

The EUT does not comply with the essential requirements in the standard.

NP

The test was not performed by the TCC Nokia Laboratory.

The test results of QTKRM-576 are re-used for certification of the QTKRM-577. The table above indicates the results, which will be re-used.


CONTENTS

1. Summary for FCC Part 22/24 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power	
(FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4)	5
2.1. Test Setup	5
2.2. Test method and limit	5
2.3. GSM850 TX Test results	7
2.4. GSM1900 TX Test results	8
2.5. WCDMA2 TX Test results	8
3. Band edge compliance	
(FCC §22.917(a), 24.238(a), RSS-132 4.5, RSS-133 6.5).....	9
3.1. Test Setup	9
3.2. Test method and limit	9
3.3. GSM850 Test results	10
4. Test Equipment.....	18
4.1. Conducted measurements	18
4.2. Radiated measurements	18

2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4)

EUT with DUT number	RM-576, 14347
Accessories with DUT numbers	BL-4CT, 14302
Result	PASSED
Remarks	Phone tested slide open and slide closed mode.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 50 / 101.9
Date of measurements	07-Dec-2009
Measured by	Sami Lehtonen

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST\ TX} - P_{SUBST\ RX} - L_{SUBST\ CABLES} + G_{SUBST\ TX\ ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. $P_{SUBST\ TX}$ is signal generator level, $P_{SUBST\ RX}$ is receiver level, $L_{SUBST\ CABLES}$ is cable losses including both TX and RX cables and $G_{SUBST\ TX\ ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P[dBm] = P_{MEAS} + A_{TOT}$$

Where P_{MEAS} is receiver reading in dBm and A_{TOT} is total correction factor including cable loss and substitution correction ($A_{TOT} = L_{CABLES} + A_{SUBST}$).

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit([dBm])
824 - 849	7	38.5
1850 - 1910	2	33

2.3. GSM850 TX Test results

Slide open

GSM mode

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	31.84	1.528	5.49	37.33	VERTICAL	PASSED
190 / 836.6	31.82	1.521	4.42	36.24	VERTICAL	PASSED
251 / 848.8	30.83	1.211	4.23	35.06	VERTICAL	PASSED

Slide closed

GSM mode

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	31.84	1.528	5.49	37.33	VERTICAL	PASSED
190 / 836.6	31.82	1.521	4.42	36.24	VERTICAL	PASSED
251 / 848.8	30.83	1.211	4.23	35.06	VERTICAL	PASSED

Slide Open

EGPRS mode, 1 TX Slot

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	21.95	0.157	15.38	37.33	VERTICAL	PASSED
190 / 836.6	22.09	0.162	14.15	36.24	VERTICAL	PASSED
251 / 848.8	22.96	0.198	12.1	35.06	VERTICAL	PASSED

Slide closed

EGPRS mode, 1 TX Slot

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	19.81	0.096	16.42	36.23	HORIZONTAL	PASSED
190 / 836.6	21.82	0.152	13.82	35.64	HORIZONTAL	PASSED
251 / 848.8	23.64	0.231	12.12	35.76	HORIZONTAL	PASSED

2.4. GSM1900 TX Test results

Slide Open

GSM mode

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	29.61	0.914	16.28	45.89	VERTICAL	PASSED
661 / 1880	30.39	1.094	16.21	46.6	VERTICAL	PASSED
810 / 1909.8	28.71	0.743	17.84	46.55	VERTICAL	PASSED

Slide closed

GSM mode

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	30.02	1.005	11.88	45.69	HORIZONTAL	PASSED
661 / 1880	30.53	1.130	11.82	45.5	HORIZONTAL	PASSED
810 / 1909.8	30.43	1.104	13.96	45.85	HORIZONTAL	PASSED

Slide open

EGPRS mode, 1 TX Slot

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	29.32	0.855	16.37	45.69	HORIZONTAL	PASSED
661 / 1880	29.13	0.818	16.37	45.5	HORIZONTAL	PASSED
810 / 1909.8	27.60	0.575	18.25	45.85	HORIZONTAL	PASSED

Slide closed

EGPRS mode, 1 TX Slot

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	25.78	0.378	19.91	45.69	HORIZONTAL	PASSED
661 / 1880	26.42	0.439	20.18	46.6	VERTICAL	PASSED
810 / 1909.8	25.88	0.387	19.97	45.85	HORIZONTAL	PASSED

2.5. WCDMA2 TX Test results

Slide open

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
9262 / 1852.4	25.77	0.378	20.14	45.91	VERTICAL	PASSED
9400 / 1880	26.68	0.466	19.92	46.6	VERTICAL	PASSED
9538 / 1907.6	24.94	0.312	21.83	46.77	VERTICAL	PASSED


Slide closed

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
9262 / 1852.4	27.75	0.596	17.86	45.61	HORIZONTAL	PASSED
9400 / 1880	28.26	0.67	17.24	45.5	HORIZONTAL	PASSED
9538 / 1907.6	26.47	0.444	19.4	45.87	HORIZONTAL	PASSED

3. Band edge compliance (FCC §22.917(a), 24.238(a), RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-576, 14347
Accessories with DUT numbers	BL-4CT, 14302
Result	PASSED
Remarks	Phone tested slide open and slide closed mode.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 50 / 101.9
Date of measurements	07-Dec-2009
Measured by	Sami Lehtonen

3.1. Test Setup



3.2. Test method and limit

The measurement is made according to FCC rules parts 22 and 24 and IC standards RSS-132 and RSS-133.

Limits for band edge compliance measurements


Operation band	Frequency range [MHz]	Limit [dBm]
GSM850	Below 824 and above 849	-13
GSM 1900 / WCDMA 1900	Below 1850 and above 1910	-13

3.3. GSM850 Test results


Operation mode (TX on)	Channel / f_c [MHz]	Level [dBm]
GSM	128 / 824.2	-14.19
EGPRS	128 / 824.2	-30.87
EGPRS	251 / 848.8	-28.93
GSM	251 / 848.8	-14.98

Slide open:

GSM, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz)




EGPRS, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz)




Slide closed:

EGPRS, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz)



GSM, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz)




GSM1900 Test results


Operation mode (TX on)	Channel / f_c [MHz]	Level [dBm]
GSM	512 / 1850.2	-14.38
GSM	810 / 1909.8	-13.64
EGPRS	512 / 1850.2	-23.27
EGPRS	810 / 1909.8	-20.02
EGPRS	512 / 1850.2	-23.27
GSM	512 / 1850.2	-14.38
GSM	810 / 1909.8	-14.19
EGPRS	810 / 1909.8	-20.08
EGPRS	512 / 1850.2	-22.82

Slide Open:


GSM, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz)




GSM, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz)



EGPRS, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz)




EGPRS, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz)




Slide closed


GSM, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz)




GSM, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz)



EGPRS, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz)



EGPRS, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz)




WCDMA2 Test results


Operation mode (TX on)	Channel / f_c [MHz]	Level [dBm]
FDD	9262 / 1852.4	-15.33
FDD	9538 / 1907.6	-15.58
FDD	9262 / 1852.4	-22.74
FDD	9538 / 1907.6	-22.68

Slide open:


FDD, channel 9262 / 1852.4 MHz (Peak detector, RBW: 50 kHz)




FDD, channel 9538 / 1907.6 MHz (Peak detector, RBW: 50 kHz)



Channel 9262 / 1852.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Channel 9538 / 1907.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1872	Thermo- Hygograph	00.02520.150700	Lambrecht	15C, 15B
1916	Communication Tester	CMTA84	R&S	15B
1986	GPS Antenna	AMHP10-15R/390	European Antenna	15C, 15B
1992	Signal Generator	83630B	Agilent	15C, 15B
2039	Power Supply	PL330QMD	Thurlby	15C, 15B
2060	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
2068	CDN	S1	NMP	15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
2156	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2206	Signal Generator	SMX	R&S	15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2352	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C
2359	Temperature Test Chamber	VT4002	Vötsch	22/24/27
2360	Serial Bus Converter	Serial 488A	IO Tech	22/24/27
2362	Power Supply	NGPX 70/5	R&S	22/24/27
2388	Bluetooth Tester	CBT	R&S	15B
2389	Signal Generator	SMJ 100A	R&S	15B
2390	Directional Coupler	DC2600	AR	-
6009	GPS Antenna	SA-700	Chronos	15C
6010	GPS Network amplifier	NLA20FPDC	GPS Networking, Inc	15C
6011	GPS signal Splitter	LDCBS1x4	GPS Networking, Inc	15C
6012	CDN	CDN USB/c	Teseq	-
6015	Receiver	ESI	R&S	22/24, 15C, 15B
6016	ESD gun	PESD 1610	HAEFELY	-
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1917	Communication Tester	CMTA84	R&S	15B
1984	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C, 15B
1986	GPS Antenna	AMHP10-15R/390	European Antenna	15C, 15B
1988	Antenna	HL562	R&S	22/24/27, 15C, 15B
1989	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2009	Signal Generator	SMP 22	R&S	22/24/27, 15C, 15B
2027	CDN	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	CDN	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2029	Power Supply	PL330	Thurlby	22/24/27, 15C
2043	Band Reject Filter	WRCA824/849-0.2-	Wainwright	22
2047	Band Reject Filter	WRCC1800/2000-0.2-	Wainwright	24
2051	High Pass Filter	4HC1700-1-KK	R&S	22
2109	Power Supply	PL330QMD	Thurlby	22/24/27, 15C, 15B
2116	Controller	EMCO 2090	ETS	22/24/27, 15C, 15B
2135	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2140	Antenna	EMCO93110B	EMCO	22/24/27, 15C
2142	Antenna	3146	EMCO	22/24/27, 15C

2150	High Pass Filter	F-15041	RLC	22/24/27, 15C
2156	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2176	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2188	Preamplifier	AFS4-00100300-20-	Miteq	22/24/27, 15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2348	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
2349	Computer Controller	GS-232B	Yaesu	22/24/27, 15C, 15B
2350	Preamplifier	AMF-6D-020180-29-	Miteq	22/24/27, 15C, 15B
2353	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
2357	Band Reject Filter	WRCG2400/2483-	Wainwright	15C
2361	Anechoic Chamber	3 m Semi / Full	Euroshield	22/24/27, 15C, 15B
2364	Band Reject Filter	WRCG1877/1883 -	Wainwright	24
2366	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2384	Band Reject Filter	WRCG832/838-	Wainwright	22
2388	Bluetooth Tester	CBT	R&S	15B
2389	Signal Generator	SMJ 100A	R&S	15B
2391	Band Reject Filter	WRCG1729.4/1735.4-	Wainwright	27
6009	GPS Antenna	SA-700	Chronos	15C
6010	GPS Network amplifier	NLA20FPDC	GPS Networking, Inc	15C
6011	GPS signal Splitter	LDCBS1x4	GPS Networking, Inc	15C
6014	Substitute Calibration Cable	Sucoflex 104PB	Suhner	-
6017	Antenna	SBA 9113	Schwarzbeck	22 / 24 / 27
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B
-	RF immunity / Emission	EMC32	R&S	22/24/27, 15C, 15B