



A D T

# FCC TEST REPORT

**REPORT NO.:** RF980505A01C

**MODEL NO.:** BH-105

**VERSION:** HW: 0.41, SW: 1.01, MV: 0.4, Proto: B4.11

**RECEIVED:** June 11, 2009

**TESTED:** June 11 ~ 18, 2009

**ISSUED:** June 22, 2009

**APPLICANT:** Nokia(China) Investment Co., LTD.

**ADDRESS:** B2, Nokia China Campus.Beijing Economic and  
Tech Development Area, No.5. Donghuan  
Zhonglu.P.O. Box 100176, Beijing, China

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB LOCATION:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien, 244 Taiwan

This test report consists of 67 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

## TABLE OF CONTENTS

1. CERTIFICATION .....	4
2. SUMMARY OF TEST RESULTS .....	5
2.1 MEASUREMENT UNCERTAINTY .....	6
3. GENERAL INFORMATION .....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 DESCRIPTION OF TEST MODES .....	8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	10
3.2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	11
3.2.4 DESCRIPTION OF SUPPORT UNITS .....	11
4. TEST TYPES AND RESULTS .....	12
4.1 CONDUCTED EMISSION MEASUREMENT .....	12
4.2 RADIATED EMISSION MEASUREMENT .....	12
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	12
4.2.2 TEST INSTRUMENTS .....	13
4.2.3 TEST PROCEDURES .....	14
4.2.4 DEVIATION FROM TEST STANDARD .....	14
4.2.5 TEST SETUP .....	15
4.2.6 EUT OPERATING CONDITIONS .....	15
4.2.7 TEST RESULTS .....	16
4.3 NUMBER OF HOPPING FREQUENCY USED .....	26
4.3.1 LIMIT OF HOPPING FREQUENCY USED .....	26
4.3.2 TEST INSTRUMENTS .....	26
4.3.3 TEST PROCEDURES .....	26
4.3.4 DEVIATION FROM TEST STANDARD .....	27
4.3.5 TEST SETUP .....	27
4.3.6 TEST RESULTS .....	27
4.4 DWELL TIME ON EACH CHANNEL .....	30
4.4.1 LIMIT OF DWELL TIME USED .....	30
4.4.2 TEST INSTRUMENTS .....	30
4.4.3 TEST PROCEDURES .....	30
4.4.4 DEVIATION FROM TEST STANDARD .....	30
4.4.5 TEST SETUP .....	31
4.4.6 TEST RESULTS .....	31
4.5 CHANNEL BANDWIDTH .....	39
4.5.1 LIMITS OF CHANNEL BANDWIDTH .....	39
4.5.2 TEST INSTRUMENTS .....	39
4.5.3 TEST PROCEDURE .....	39
4.5.4 DEVIATION FROM TEST STANDARD .....	40
4.5.5 TEST SETUP .....	40
4.5.6 EUT OPERATING CONDITION .....	40
4.5.7 TEST RESULTS .....	41
4.6 HOPPING CHANNEL SEPARATION .....	45



A D T

4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION .....	45
4.6.2	TEST INSTRUMENTS .....	45
4.6.3	TEST PROCEDURES .....	45
4.6.4	DEVIATION FROM TEST STANDARD .....	46
4.6.5	TEST SETUP .....	46
4.6.6	TEST RESULTS .....	46
4.7	MAXIMUM PEAK OUTPUT POWER .....	51
4.7.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	51
4.7.2	TEST INSTRUMENTS .....	51
4.7.3	TEST PROCEDURES .....	51
4.7.4	DEVIATION FROM TEST STANDARD .....	51
4.7.5	TEST SETUP .....	52
4.7.6	EUT OPERATING CONDITION .....	52
4.7.7	TEST RESULTS .....	52
4.8	BAND EDGES MEASUREMENT .....	57
4.8.1	LIMITS OF BAND EDGES MEASUREMENT .....	57
4.8.2	TEST INSTRUMENTS .....	57
4.8.3	TEST PROCEDURE .....	57
4.8.4	DEVIATION FROM TEST STANDARD .....	57
4.8.5	EUT OPERATING CONDITION .....	57
4.8.6	TEST RESULTS .....	58
4.9	ANTENNA REQUIREMENT .....	64
4.9.1	STANDARD APPLICABLE .....	64
4.9.2	ANTENNA CONNECTED CONSTRUCTION .....	64
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	65
6.	INFORMATION ON THE TESTING LABORATORIES .....	66
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	67



A D T

## 1. CERTIFICATION

**PRODUCT:** Bluetooth Headset

**BRAND NAME:** NOKIA

**MODEL NO.:** BH-105

**APPLICANT:** Nokia(China) Investment Co., LTD.

**TESTED:** June 11 ~ 18, 2009

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 15, Subpart C (Section 15.247),

ANSI C63.4-2003

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Annie Chang , **DATE:** June 22, 2009  
( Annie Chang / Senior Specialist )

**TECHNICAL  
ACCEPTANCE** : Jamison Chan , **DATE:** June 22, 2009  
Responsible for RF  
( Jamison Chan / Supervisor )

**APPROVED BY** : Ken Liu , **DATE:** June 22, 2009  
( Ken Liu / Assistant Manager )



A D T

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Refer to Note below
15.247(a)(1) (iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater (see Note)  2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Spec.: max. 21dBm (see Note)	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit.  Minimum passing margin is -5.32dB at 2390.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.

**NOTE:**

1. If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. No need to re-test the AC Power Conducted Emission due to the change should not influence test result.



A D T

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	30MHz ~ 1GHz	3.72 dB
	1GHz ~ 40GHz	2.89 dB



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Bluetooth Headset
<b>MODEL NO.</b>	BH-105
<b>FCC ID</b>	QTLBH-106
<b>POWER SUPPLY</b>	5Vdc from adapter, 3.7Vdc from battery
<b>MODULATION TYPE</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>RADIO TECHNOLOGY</b>	FHSS
<b>TRANSFER RATE</b>	1/2/3Mbps
<b>OPERATING FREQUENCY</b>	2402 ~ 2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>OUTPUT POWER</b>	3.319mW
<b>ANTENNA TYPE</b>	IFA antenna with 2.82dBi gain
<b>I/O PORTS</b>	N/A
<b>DATA CABLE</b>	N/A
<b>ASSOCIATED DEVICES</b>	Refer to note 4 below

#### NOTE:

1. This report is a supplementary report or original one (BV CPS report no.: RF980505A01A) issued on June 5, 2009 to verify test result for some electronic and mechanical changes. The main change is adding the second source of following components:
  - ◆ Battery
  - ◆ PCB
  - ◆ Speaker
  - ◆ DC Jack
  - ◆ EEPROM
  - ◆ Balun filter
  - ◆ MIC
  - ◆ Software

2. This report is prepared for FCC class II permissive change.

3. The EUT is a Bluetooth Headset.

4. The EUT was power supplied from the following power adapter or battery:

Item	Brand	Model	Spec.
Adapter	NOKIA	AC-3U	AC I/P: 100-240V, 50-60Hz, 65mA DC O/P: 5.0V, 350mA Non-shielded DC (1.8m), AC 2-pin
Battery	-	-	3.7Vdc

5. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:


CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		




A D T

### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

#### FOR MODE A:



#### FOR MODE B:





A D T

### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	Note 1	√	√	√	Operating Mode (EUT+Adapter)
B	Note 2	√	-	-	Operating Mode (EUT only)

Where **PLC**: Power Line Conducted Emission**RE<1G**: Radiated Emission below 1GHz**RE≥1G**: Radiated Emission above 1GHz**APCM**: Antenna Port Conducted Measurement**NOTE:** 1. No need to re-tested the Conducted Emission due to the change should not influence test result.

2. No need to concern of Conducted Emission due to the EUT is powered by battery.

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, packet types data rate, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE	AXIS
A	0 to 78	0	FHSS	GFSK	DH5	1	X
B	0 to 78	0	FHSS	GFSK	DH5	1	X

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, packet types data rate, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE	AXIS
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5	1	X
A	0 to 78	0, 39, 78	FHSS	8DPSK	DH5	3	X



A D T

#### **BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE
A	0 to 78	0, 78	FHSS	GFSK	DH5	1
A	0 to 78	0, 78	FHSS	8DPSK	DH5	3

#### **ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types of the antenna and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5	1
A	0 to 78	0, 39, 78	FHSS	8DPSK	DH5	3

### **3.2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4- 2003**

All test items have been performed and recorded as per the above standards.

### **3.2.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together without any necessary accessory or support unit.



## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

N/A

### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	May 04, 2009	May 03, 2010
HP Preamplifier	8449B	3008A01924	Sep. 03, 2008	Sep. 02, 2009
HP Preamplifier	8449B	3008A01292	Aug. 06, 2008	Aug. 05, 2009
ROHDE & SCHWARZ TEST RECEIVER	ESI7	836697/012	Dec. 04, 2008	Dec. 03, 2009
Schwarzbeck Antenna	VULB 9168	137	Apr. 29, 2009	Apr. 28, 2010
Schwarzbeck Antenna	VHBA 9123	480	Apr. 21, 2009	Apr. 20, 2010
EMCO Horn Antenna	3115	6714	Oct. 17, 2008	Oct. 16, 2009
EMCO Horn Antenna	3115	9312-4192	Apr. 17, 2009	Apr. 16, 2010
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
SUHNER RF cable	SF104-26.5	CABLE-CH6-17 m-01	Aug. 22, 2008	Aug. 21, 2009
ROHDE & SCHWARZ Spectrum Analyzer	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:**

1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The FCC Site Registration No. is 447212.



A D T

### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

##### For Mode A:

- Connected the EUT with AC adapter placed on testing table.
- Set the EUT under transmission/receiving condition continuously at specific channel frequency.

##### For Mode B:

Set the EUT under transmission/receiving condition continuously at specific channel frequency.



A D T

## 4.2.7 TEST RESULTS

### GFSK MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 78% RH 1006hPa	TESTED BY	Nick Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1602.00	45.05 PK	74.00	-28.95	1.04 H	247	13.13	31.92
2	1602.00	37.27 AV	54.00	-16.73	1.04 H	247	5.35	31.92
3	2390.00	59.57 PK	74.00	-14.43	1.00 H	232	24.50	35.07
4	2390.00	48.68 AV	54.00	-5.32	1.00 H	232	13.61	35.07
5	#2400.00	66.22 PK	88.19	-21.97	1.00 H	232	31.13	35.09
6	#2400.00	36.12 AV	58.09	-21.97	1.00 H	232	1.03	35.09
7	*2402.00	108.19 PK			1.00 H	232	73.10	35.09
8	*2402.00	78.09 AV			1.00 H	232	43.00	35.09
9	4804.00	60.33 PK	74.00	-13.67	1.06 H	256	17.34	42.99
10	4804.00	30.23 AV	54.00	-23.77	1.06 H	256	-12.76	42.99

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 78% RH 1006hPa	TESTED BY	Nick Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1602.00	43.19 PK	74.00	-30.81	1.00 V	241	11.27	31.92
2	1602.00	29.54 AV	54.00	-24.46	1.00 V	241	-2.38	31.92
3	2390.00	58.98 PK	74.00	-15.02	1.00 V	237	23.91	35.07
4	2390.00	47.04 AV	54.00	-6.96	1.00 V	237	11.97	35.07
5	#2400.00	60.37 PK	82.34	-21.97	1.00 V	237	25.28	35.09
6	#2400.00	30.27 AV	52.24	-21.97	1.00 V	237	-4.82	35.09
7	*2402.00	102.34 PK			1.00 V	237	67.25	35.09
8	*2402.00	72.24 AV			1.00 V	237	37.15	35.09
9	4804.00	61.64 PK	74.00	-12.36	1.03 V	75	18.65	42.99
10	4804.00	31.54 AV	54.00	-22.46	1.03 V	75	-11.45	42.99

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 39		FREQUENCY RANGE 1 ~ 25GHz	
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS		25deg. C, 78% RH 1006hPa		TESTED BY Nick Chen	
TEST MODE		A			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1626.00	46.03 PK	74.00	-27.97	1.00 H	232	14.00	32.03
2	1626.00	40.49 AV	54.00	-13.51	1.00 H	232	8.46	32.03
3	*2441.00	108.54 PK			1.05 H	109	73.37	35.17
4	*2441.00	78.44 AV			1.05 H	109	43.27	35.17
5	4882.00	63.81 PK	74.00	-10.19	1.08 H	198	20.67	43.14
6	4882.00	33.71 AV	54.00	-20.29	1.08 H	198	-9.43	43.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1626.00	44.49 PK	74.00	-29.51	1.02 V	231	12.46	32.03
2	1626.00	35.17 AV	54.00	-18.83	1.02 V	231	3.14	32.03
3	*2441.00	100.89 PK			1.00 V	302	65.72	35.17
4	*2441.00	70.79 AV			1.00 V	302	35.62	35.17
5	4882.00	65.82 PK	74.00	-8.18	1.03 V	255	22.68	43.14
6	4882.00	35.72 AV	54.00	-18.28	1.03 V	255	-7.42	43.14

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 78% RH 1006hPa	TESTED BY	Nick Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#1652.00	45.64 PK	90.94	-45.30	1.00 H	298	13.49	32.15
2	#1652.00	37.09 AV	60.84	-23.75	1.00 H	298	4.94	32.15
3	*2480.00	110.94 PK			1.04 H	109	75.69	35.25
4	*2480.00	80.84 AV			1.04 H	109	45.59	35.25
5	2483.50	49.32 PK	74.00	-24.68	1.04 H	109	14.06	35.26
6	2483.50	19.22 AV	54.00	-34.78	1.04 H	109	-16.04	35.26
7	4960.00	65.32 PK	74.00	-8.68	1.00 H	198	22.02	43.30
8	4960.00	35.22 AV	54.00	-18.78	1.00 H	198	-8.08	43.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#1652.00	44.02 PK	81.68	-37.66	1.00 V	266	11.87	32.15
2	#1652.00	34.82 AV	51.58	-16.76	1.00 V	266	2.67	32.15
3	*2480.00	101.68 PK			1.00 V	256	66.43	35.25
4	*2480.00	71.58 AV			1.00 V	256	36.33	35.25
5	2483.50	40.06 PK	74.00	-33.94	1.00 V	256	4.80	35.26
6	2483.50	9.96 AV	54.00	-44.04	1.00 V	256	-25.30	35.26
7	4960.00	67.55 PK	74.00	-6.45	1.00 V	257	24.25	43.30
8	4960.00	37.45 AV	54.00	-16.55	1.00 V	257	-5.85	43.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

## 8DPSK MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 0	FREQUENCY RANGE		1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 78% RH 1006hPa	TESTED BY		Nick Chen
TEST MODE	A			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1602.00	45.01 PK	74.00	-28.99	1.00 H	293	13.09	31.92
2	1602.00	38.51 AV	54.00	-15.49	1.00 H	293	6.59	31.92
3	2390.00	59.68 PK	74.00	-14.32	1.00 H	29	24.61	35.07
4	2390.00	47.21 AV	54.00	-6.79	1.00 H	29	12.14	35.07
5	#2400.00	61.76 PK	88.36	-26.60	1.00 H	29	26.67	35.09
6	#2400.00	31.66 AV	58.26	-26.60	1.00 H	29	-3.43	35.09
7	*2402.00	108.36 PK			1.00 H	29	73.27	35.09
8	*2402.00	78.26 AV			1.00 H	29	43.17	35.09
9	4804.00	57.20 PK	74.00	-16.80	1.10 H	93	14.21	42.99
10	4804.00	27.10 AV	54.00	-26.90	1.10 H	93	-15.89	42.99

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* “: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 78% RH 1006hPa	TESTED BY	Nick Chen
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1602.00	43.25 PK	74.00	-30.75	1.04 V	178	11.33	31.92
2	1602.00	32.10 AV	54.00	-21.90	1.04 V	178	0.18	31.92
3	2390.00	59.24 PK	74.00	-14.76	1.00 V	255	24.17	35.07
4	2390.00	46.73 AV	54.00	-7.27	1.00 V	255	11.66	35.07
5	#2400.00	52.98 PK	79.58	-26.60	1.00 V	255	17.89	35.09
6	#2400.00	22.88 AV	49.48	-26.60	1.00 V	255	-12.21	35.09
7	*2402.00	99.58 PK			1.00 V	255	64.49	35.09
8	*2402.00	69.48 AV			1.00 V	255	34.39	35.09
9	4804.00	58.42 PK	74.00	-15.58	1.00 V	22	15.43	42.99
10	4804.00	28.32 AV	54.00	-25.68	1.00 V	22	-14.67	42.99

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 39		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 78% RH 1006hPa		TESTED BY Nick Chen
TEST MODE		A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1626.00	47.36 PK	74.00	-26.64	1.00 H	223	15.33	32.03
2	1626.00	42.42 AV	54.00	-11.58	1.00 H	223	10.39	32.03
3	*2441.00	107.27 PK			1.00 H	153	72.10	35.17
4	*2441.00	77.17 AV			1.00 H	153	42.00	35.17
5	4882.00	59.24 PK	74.00	-14.76	1.00 H	94	16.10	43.14
6	4882.00	29.14 AV	54.00	-24.86	1.00 H	94	-14.00	43.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1626.00	45.08 PK	74.00	-28.92	1.00 V	245	13.05	32.03
2	1626.00	36.20 AV	54.00	-17.80	1.00 V	245	4.17	32.03
3	*2441.00	101.89 PK			1.00 V	178	66.72	35.17
4	*2441.00	71.79 AV			1.00 V	178	36.62	35.17
5	4882.00	63.22 PK	74.00	-10.78	1.00 V	259	20.08	43.14
6	4882.00	33.12 AV	54.00	-20.88	1.00 V	259	-10.02	43.14

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 78		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 78% RH 1006hPa		TESTED BY Nick Chen
TEST MODE		A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#1652.00	46.35 PK	89.79	-43.44	1.00 H	300	14.20	32.15
2	#1652.00	39.73 AV	59.69	-19.96	1.00 H	300	7.58	32.15
3	*2480.00	109.79 PK			1.03 H	11	74.54	35.25
4	*2480.00	79.69 AV			1.03 H	11	44.44	35.25
5	2483.50	52.21 PK	74.00	-21.79	1.03 H	110	16.95	35.26
6	2483.50	22.11 AV	54.00	-31.89	1.03 H	110	-13.15	35.26
7	4960.00	62.02 PK	74.00	-11.98	1.00 H	201	18.72	43.30
8	4960.00	31.92 AV	54.00	-22.08	1.00 H	201	-11.38	43.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#1652.00	44.54 PK	80.51	-35.97	1.00 V	264	12.39	32.15
2	#1652.00	36.23 AV	50.41	-14.18	1.00 V	264	4.08	32.15
3	*2480.00	100.51 PK			1.00 V	257	65.26	35.25
4	*2480.00	70.41 AV			1.00 V	257	35.16	35.25
5	2483.50	42.93 PK	74.00	-31.07	1.00 V	257	7.67	35.26
6	2483.50	12.83 AV	54.00	-41.17	1.00 V	257	-22.43	35.26
7	4960.00	63.03 PK	74.00	-10.97	1.00 V	256	19.73	43.30
8	4960.00	32.93 AV	54.00	-21.07	1.00 V	256	-10.37	43.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB.
7. Average value = peak reading +  $20\log(\text{duty cycle})$ .
8. "#": The radiated frequency is out the restricted band.



A D T

## BELOW 1GHz WORST-CASE DATA : GFSK MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL		Channel 0		FREQUENCY RANGE	
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION	
ENVIRONMENTAL CONDITIONS		26deg. C, 81% RH 1002hPa		TESTED BY	
TEST MODE		A			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	80.54	24.62 QP	40.00	-15.38	1.01 H	295	14.96	9.66
2	718.14	23.03 QP	46.00	-22.97	1.00 H	301	-2.14	25.17
3	753.13	23.21 QP	46.00	-22.79	1.05 H	61	-2.64	25.85
4	788.12	23.89 QP	46.00	-22.11	1.00 H	148	-2.52	26.42
5	858.10	25.03 QP	46.00	-20.97	1.14 H	187	-2.47	27.50
6	902.81	25.38 QP	46.00	-20.62	1.16 H	151	-2.69	28.07
7	935.85	25.65 QP	46.00	-20.35	1.21 H	196	-2.78	28.43
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	76.65	22.70 QP	40.00	-17.30	1.00 V	40	12.14	10.56
2	747.30	23.72 QP	46.00	-22.28	1.12 V	298	-2.02	25.74
3	768.68	24.32 QP	46.00	-21.68	1.13 V	10	-1.78	26.10
4	807.56	23.66 QP	46.00	-22.34	1.05 V	25	-3.07	26.73
5	830.88	23.90 QP	46.00	-22.10	1.04 V	202	-3.20	27.10
6	937.80	25.82 QP	46.00	-20.18	1.13 V	13	-2.64	28.46
7	955.29	26.68 QP	46.00	-19.32	1.08 V	124	-1.97	28.65

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26deg. C, 81% RH 1002hPa	TESTED BY	Nick Chen
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	63.05	19.57 QP	40.00	-20.43	1.02 H	136	6.94	12.63
2	749.24	23.08 QP	46.00	-22.92	1.11 H	25	-2.70	25.78
3	772.57	23.19 QP	46.00	-22.81	1.00 H	46	-2.97	26.16
4	803.67	23.75 QP	46.00	-22.25	1.24 H	10	-2.92	26.67
5	830.88	24.45 QP	46.00	-21.55	1.00 H	313	-2.65	27.10
6	861.98	25.12 QP	46.00	-20.88	1.08 H	241	-2.43	27.55
7	900.86	25.31 QP	46.00	-20.69	1.23 H	115	-2.74	28.05
8	935.85	26.12 QP	46.00	-19.88	1.01 H	139	-2.31	28.43
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	84.43	17.85 QP	40.00	-22.15	1.02 V	175	8.83	9.02
2	751.18	23.38 QP	46.00	-22.62	1.21 V	178	-2.43	25.81
3	782.29	24.04 QP	46.00	-21.96	1.11 V	217	-2.28	26.32
4	799.78	25.00 QP	46.00	-21.00	1.08 V	43	-1.61	26.61
5	865.87	25.37 QP	46.00	-20.63	1.03 V	235	-2.23	27.60
6	904.75	25.67 QP	46.00	-20.33	1.10 V	346	-2.42	28.09
7	928.08	26.06 QP	46.00	-19.94	1.12 V	196	-2.29	28.35

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



## 4.3 NUMBER OF HOPPING FREQUENCY USED

### 4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

### 4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.3.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.




A D T

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.5 TEST SETUP





#### 4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



A D T



### Mode A: FOR GFSK





A D T

### Mode A: FOR 8DPSK





## 4.4 DWELL TIME ON EACH CHANNEL

### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.4.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.


### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation.



A D T

#### 4.4.5 TEST SETUP



#### 4.4.6 TEST RESULTS

##### Mode A: FOR GFSK



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) *6.32=322.32 times	0.474	152.77968	400
DH3	25 (times / 5 sec) *6.32=158.00 times	1.710	270.18000	400
DH5	17 (times / 5 sec) *6.32=107.44 times	2.960	318.02240	400

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.



A D T



DH1





A D T



DH3





A D T

DH5





A D T

**Mode A: FOR 8DPSK**



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) *6.32=316.00 times	0.468	147.88800	400
DH3	26 (times / 5 sec) *6.32=164.32 times	1.734	284.93088	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.000	322.32000	400

**NOTE:** Test plots of the transmitting time slot are shown on next 3 pages.



A D T



DH1





A D T



DH3





A D T

DH5





## 4.5 CHANNEL BANDWIDTH

### 4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.



A D T

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T


## 4.5.7 TEST RESULTS

FOR GFSK

TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.813
39	2441	0.838
78	2480	0.822


CH 0






A D T

CH 39



CH 78






A D T

## FOR 8DPSK

TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.290
39	2441	1.246
78	2480	1.258


CH 0






A D T

CH 39



CH 78





## 4.6 HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.




A D T

#### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.5 TEST SETUP



#### 4.6.6 TEST RESULTS

##### FOR GFSK

TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.005	0.813	0.542	PASS
39	2441	1.008	0.838	0.559	PASS
78	2480	1.004	0.822	0.548	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth. Test results please refer to following three plots.




A D T

CH 0




CH 39





A D T

CH 78





A D T


## FOR 8DPSK

TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.002	1.290	0.860	PASS
39	2441	1.004	1.246	0.831	PASS
78	2480	1.000	1.258	0.839	PASS

NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to following three plots.


## CH 0






A D T

CH 39



CH 78





## 4.7 MAXIMUM PEAK OUTPUT POWER

### 4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 125mW.

### 4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.7.3 TEST PROCEDURES

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.


### 4.7.4 DEVIATION FROM TEST STANDARD

No deviation



A D T

#### 4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

#### 4.7.7 TEST RESULTS

##### FOR GFSK


TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	5.21	3.319	125	PASS
39	2441	4.96	3.133	125	PASS
78	2480	4.99	3.155	125	PASS




A D T

CH 0




CH 39





A D T

CH 78






A D T

FOR 8DPSK

TEST MODE	A	CHANNEL	0, 39, 78
INPUT POWER	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63% RH, 1004hPa
TESTED BY	Chad Lee		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	4.17	2.612	125	PASS
39	2441	3.56	2.270	125	PASS
78	2480	3.32	2.148	125	PASS


CH 0






A D T

CH 39



CH 78





## 4.8 BAND EDGES MEASUREMENT

### 4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

### 4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 03, 2009	Apr. 02, 2010

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots are attached on the following pages.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



A D T

## 4.8.6 TEST RESULTS

The spectrum plots are attached on the following 8 images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

### Mode A: FOR GFSK

#### NOTE 1:

The band edge emission plot on the next page shows 62.38dBc between carrier maximum power and local maximum emission in restrict band (2.3504GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 108.19dBuV/m (Peak), so the maximum field strength in restrict band is  $108.19 - 62.38 = 45.81$  dBuV/m, which is under 74 dBuV/m limit.

Average value =  $45.81 - 30.10 = 15.71$  dBuV/m, which is under 54dBuV/m limit.

\*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30.1$  dB.

Average value = peak reading -30.10.

#### NOTE 2:

The band edge emission plot on the next second page shows 61.34dBc between carrier maximum power and local maximum emission in restrict band (2.4870GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 110.94dBuV/m (Peak), so the maximum field strength in restrict band is  $110.94 - 61.34 = 49.60$  dBuV/m, which is under 74 dBuV/m limit.



Average value =  $49.60 - 30.10 = 19.50$  dBuV/m, which is under 54dBuV/m limit.

\*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30.1$  dB.

Average value = peak reading -30.10.





A D T





A D T





A D T

## Mode A: FOR 8DPSK

### NOTE 1:

The band edge emission plot on the next page shows 51.33dBc between carrier maximum power and local maximum emission in restrict band (2.3854GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 108.36dBuV/m (Peak), so the maximum field strength in restrict band is  $108.36 - 51.33 = 57.03$ dBuV/m, which is under 74 dBuV/m limit.

Average value =  $57.03 - 30.10 = 26.93$ dBuV/m, which is under 54dBuV/m limit.

\*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30.1$  dB.

Average value = peak reading -30.10.

### NOTE 2:

The band edge emission plot on the next second page shows 58.42dBc between carrier maximum power and local maximum emission in restrict band (2.4836GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 109.79dBuV/m (Peak), so the maximum field strength in restrict band is  $109.79 - 58.42 = 51.37$ dBuV/m, which is under 74 dBuV/m limit.



Average value =  $51.37 - 30.10 = 21.27$ dBuV/m, which is under 54dBuV/m limit.

\*The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30.1$  dB.

Average value = peak reading -30.10.





A D T





A D T





A D T

## 4.9 ANTENNA REQUIREMENT

### 4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is IFA antenna without antenna connector. The maximum gain of this antenna is 2.82dBi.



A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA, CSA
<b>R.O.C.</b>	TAF, BSMI, NCC
<b>Netherlands</b>	Telefication
<b>Singapore</b>	GOST-ASIA (MOU)
<b>Russia</b>	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**  
Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**  
Tel: 886-3-3183232  
Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## 7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---