

FCC Part 24 Compliance Test Report

Test Report no.:	Bej_FCC_0843_11.doc	Date of Report:	31-Oct-2008
Number of pages:	10	Customer's Contact person:	Helen Hu
Testing laboratory:	TCC Nokia Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Nokia Corporation Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-458 / Battery BL-4S, AC-charger AC-8E, Headset HS-48		
FCC ID:	QTLRM-458	IC:	661AB-RM458
Supplement reports:			
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 24, TIA-603-C-2004 and IC standard RSS-133 (Issue 4, February 2008). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Zou Ming, Engineer

1. Summary for FCC Part 24 Compliance Test Report

Date of receipt	15-Oct-2008
Testing completed	23-Oct-2008
The customer's contact person	Helen Hu
Test Plan referred to	T:\Projects\RM-458\TestPlan_RS\RS_Testplan_RM-458.xls
Notes	-
Document name	T:\Projects\RM-458\EMC\Results\FCC\Bej_FCC_0843_11.doc

1.1. EUT and Accessory Information

The EUT is a 3-band (GSM900/1800/1900) mobile phone with GPRS, EGPRS and Bluetooth.
The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-458	004401101586754	0201	-	lu07w41_08w 38	50914
Battery	BL-4S	3820668266210316238;0670577	-	-	-	50903
AC-charger	AC-8E	3997918362060300097;0675387	-	-	-	51034
Headset	HS-48	06945818263K2100333	-	-	-	51042

1.2. Summary of Test Results

GSM 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Beijing Laboratory.


CONTENTS

1. Summary for FCC Part 24 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power (FCC §24.232(b), RSS-133 6.4)	4
2.1. Test setup	4
2.2. Test method and limit	4
2.3. GSM 1900 Test results	5
3. Band edge compliance (FCC 24.238(a), RSS-133 6.5)	7
3.1. Test setup	7
3.2. Test method and limit	7
3.3. GSM 1900 Test results	8
4. Test Equipment.....	10
4.1. Conducted measurements	10
4.2. Radiated measurements	10

2. Radiated RF output power (FCC §24.232(b), RSS-133 6.4)

EUT with DUT number	RM-458, DUT 50914
Accessories with DUT numbers	BL-4S, DUT 50903; AC-8E, DUT 51034; HS-48, DUT 51042
Operation Voltage [V] / [Hz]	110 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19 / 37 / 100.5
Date of measurements	23-Oct-2008
Measured by	Zou Ming

2.1. Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. P_{SUBST_TX} is signal generator level, P_{SUBST_RX} is receiver level, L_{SUBST_CABLES} is cable losses including both TX and RX cables and $G_{SUBST_TX_ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P [dBm] = P_{MEAS} + A_{TOT}$$

Where P_{MEAS} is receiver reading in dBm and A_{TOT} is total correction factor including cable loss and substitution correction ($A_{TOT} = L_{CABLES} + A_{SUBST}$).

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
1850 - 1910	2	33

2.3. GSM 1900 Test results

GSM mode

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	29.20	0.832	-15.90	45.10	HORIZONTAL	PASSED
661 / 1880.0	28.40	0.692	-15.50	43.90	VERTICAL	PASSED
810 / 1909.8	27.50	0.562	-16.50	44.00	VERTICAL	PASSED

GPRS mode, 2 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	26.80	0.479	-18.30	45.10	HORIZONTAL	PASSED
661 / 1880.0	26.20	0.417	-17.70	43.90	VERTICAL	PASSED
810 / 1909.8	25.50	0.355	-18.50	44.00	VERTICAL	PASSED

GPRS mode, 3 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	24.80	0.302	-20.30	45.10	HORIZONTAL	PASSED
661 / 1880.0	24.00	0.251	-19.90	43.90	VERTICAL	PASSED
810 / 1909.8	23.30	0.214	-20.70	44.00	VERTICAL	PASSED

EGPRS mode, 1 TX Slot

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	24.70	0.295	-20.40	45.10	HORIZONTAL	PASSED
661 / 1880.0	23.70	0.234	-20.20	43.90	VERTICAL	PASSED
810 / 1909.8	22.20	0.166	-21.80	44.00	VERTICAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	24.40	0.275	-20.70	45.10	HORIZONTAL	PASSED
661 / 1880.0	24.10	0.257	-19.80	43.90	VERTICAL	PASSED
810 / 1909.8	22.60	0.182	-21.40	44.00	VERTICAL	PASSED


EGPRS mode, 3 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	24.20	0.263	-20.90	45.10	HORIZONTAL	PASSED
661 / 1880.0	23.60	0.229	-20.30	43.90	VERTICAL	PASSED
810 / 1909.8	23.00	0.200	-21.00	44.00	VERTICAL	PASSED

3. Band edge compliance (FCC 24.238(a), RSS-133 6.5)

EUT with DUT number	RM-458, DUT50914
Accessories with DUT numbers	BL-4S, DUT50903; AC-8E, DUT51034; HS-48, DUT51042
Operation Voltage [V] / [Hz]	110 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19 / 37 / 100.5
Date of measurements	23-Oct-2008
Measured by	Zou Ming

3.1. Test setup



3.2. Test method and limit

The measurement is made according to FCC rules part 24 and IC standard RSS-133.


Limits for band edge compliance measurements

Operation band	Frequency range [MHz]	Limit [dBm]
GSM 1900	Below 1850 and above 1910	-13

3.3. GSM 1900 Test results


Operation mode (TX on)	Channel / f_c [MHz]	Level [dBm]
GSM	512 / 1850.2	-15.00
GSM	810 / 1909.8	-16.70
EGPRS	512 / 1850.2	-22.40
EGPRS	810 / 1909.8	-32.90

GSM mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	512 / 1850.2	-15.00

GSM mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	810 / 1909.8	-16.70

EGPRS mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	512 / 1850.2	-22.40

EGPRS mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	810 / 1909.8	-32.90

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCPT0039	LISN	ESH3-Z5	BJPCPT0039	15C, 15B
BJPCPT0040	TEST RECEIVER	ESCS30	BJPCPT0040	15C, 15B
BJPCPT0069	LISN	ESH3-Z5	BJPCPT0069	15C, 15B
BJPCPT0079	LISN	ESH3-Z5	BJPCPT0079	15C, 15B
BJPCPT0191	PULSE LIMITER	ESH3-Z2	BJPCPT0191	15C, 15B

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCPT0129	Relay Unit	TS-RSP	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCPT0130	Relay Unit	TS-RSP	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCPT0080	Device Controller	EMCO2090	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0048	RF Preamplifier 10MHz-3GHz (Metal chassis)	AFS4-00100300-10-10P-4	MITEQ	22/24/27, 15C, 15B
BJPCTC0007	Ultra Broadband Antenna 30MHz-3000MHz	HL562	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCPT0162	Horn Antenna 1GHz-18GHz	HF906	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCTC0029	Horn Antenna 1GHz-18GHz	HF906	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCTC0049	RF preamplifier 3GHz-18GHz	BLMA-0118-1A-BT	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCTC0072	3m anechoic chamber	-	ETS-Lindgren	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2088	ETS-EMCO	22/24/27, 15C, 15B
BJPCPT0072	EMI Test Receiver 20Hz-26.5GHz	ESIB26	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCPT0150	High Pass filter	WHKS 1200-10SS	Wainwright instruments	22/24/27, 15C, 15B
BJPCTC0034	Notch Filter	WRCT800/880-0.2/40-5SSK	Wainwright instruments	22, 15B
BJPCPT0151	Notch Filter	WRCD1800/2000-0.2/40-5SSK	Wainwright instruments	24, 15B
BJPCTC0017	Radio Communication Tester	CMU200	Rohde&Schwarz	22/24/27, 15C, 15B
BJPCPT0154	Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright instruments	15C, 15B
BJPCTC0058	Bluetooth tester	CBT	Rohde&Schwarz	15C, 15B
BJPCTC0064	WCDMA II FILTER	WRCG1877/1883-1870/1890-40/6SS	Wainwright instruments	24, 15B
BJPCTC0065	WCDMA V FILTER	WRCG832/838-825/845-40/5SS	Wainwright instruments	22, 15B