

## FCC Part 22/24 Compliance Test Report

|                                                         |                                                                                                                                                                                                                                                                                                                  |                                   |                                                                                                                                                                                    |
|---------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Report no.:</b>                                 | FCC22&24_RM-579_03.docx                                                                                                                                                                                                                                                                                          | <b>Date of Report:</b>            | 16-Aug-2010                                                                                                                                                                        |
| <b>Number of pages:</b>                                 | 8                                                                                                                                                                                                                                                                                                                | <b>Customer's Contact person:</b> | Xu Helen                                                                                                                                                                           |
| <b>Testing laboratory:</b>                              | TCC Nokia Beijing Laboratory<br>Beijing Economic and Technological Development Area<br>No.5 Donghuan Zhonglu<br>Beijing<br>PRC China 100176<br>Tel. +86 10 8711 8888<br>Fax. +86 10 8711 4550                                                                                                                    | <b>Customer:</b>                  | Nokia Corporation<br>Beijing Economic and Technological Development Area<br>No.5 Donghuan Zhonglu<br>Beijing<br>PRC China 100176<br>Tel. +86 10 8711 8888<br>Fax. +86 10 8711 4550 |
| <b>FCC listing no.:</b>                                 | 975940                                                                                                                                                                                                                                                                                                           |                                   |                                                                                                                                                                                    |
| <b>IC recognition no.:</b>                              | 661AH-1                                                                                                                                                                                                                                                                                                          |                                   |                                                                                                                                                                                    |
| <b>Tested devices/ accessories:</b>                     | <b>Phone RM-579 / Battery BL-5C</b>                                                                                                                                                                                                                                                                              |                                   |                                                                                                                                                                                    |
| <b>FCC ID:</b>                                          | QTLRM-579X                                                                                                                                                                                                                                                                                                       | <b>IC:</b>                        | 661AB-RM579                                                                                                                                                                        |
| <b>Supplement reports:</b>                              | -                                                                                                                                                                                                                                                                                                                |                                   |                                                                                                                                                                                    |
| <b>Testing has been carried out in accordance with:</b> | CFR 47, FCC rules Parts 22/24 , TIA-603-C-2004 and IC standards, RSS-GEN (Issue 2, June 2007), RSS-132 (Issue 2, September 2005), RSS-133 (Issue 5, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit". |                                   |                                                                                                                                                                                    |
| <b>Documentation:</b>                                   | The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.                                                             |                                   |                                                                                                                                                                                    |
| <b>Test Results:</b>                                    | <b>The EUT complies with the requirements in respect of all parameters subject to the test.</b><br>The test results relate only to devices specified in this document                                                                                                                                            |                                   |                                                                                                                                                                                    |
| <b>Date and signature for the contents:</b>             |                                                                                                                                                                                                                                                                                                                  |                                   |                                                                                                                                                                                    |

Jia Dongsheng, System Manager

## 1. Summary for FCC Part 22/24 Compliance Test Report

|                               |                                                               |
|-------------------------------|---------------------------------------------------------------|
| Date of receipt               | 11-Aug-2010                                                   |
| Testing completed             | 13-Aug-2010                                                   |
| The customer's contact person | Xu Helen                                                      |
| Test Plan referred to         | T:\Projects\RM-579\TestPlan_RS\RS_testplan_RM-579_CR_CR30.xls |
| Notes                         | -                                                             |
| Document name                 | FCC22&24_RM-579_03.docx                                       |

### 1.1. EUT and Accessory Information

The EUT is a 6-band (GSM850/900/1800/1900) and WCDMA Band (II(1900)/V(850)) mobile phone with GPRS, EGPRS and Bluetooth. The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

| Product | Type   | SN                         | HW   | MV | SW    | DUT   |
|---------|--------|----------------------------|------|----|-------|-------|
| Phone   | RM-579 | 004401107591220            | 9019 | -  | 07.70 | 51797 |
| Battery | BL-5C  | 0670397462040R093B22024008 | -    | -  | -     | 51798 |

### 1.2. Summary of Test Results

#### GSM850:

| Section in CFR 47     | Section in RSS-GEN or RSS-132 | Name of the test                           | Result |
|-----------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a), 22.913(a) | 4.4                           | Conducted RF output power                  | NP     |
| §22.913(a)            | 4.4                           | Radiated RF output power                   | PASSED |
| §2.1049(h)            | 4.6.1                         | 99 % occupied bandwidth                    | NP     |
| §22.917(a)            | 4.5                           | Band edge compliance                       | NP     |
| §22.917(a), §2.1051   | 4.5                           | Spurious emissions at antenna terminals    | NP     |
| §22.917(a), §2.1053   | 4.5                           | Spurious radiated emissions                | NP     |
| §2.1055(a)            | 4.3                           | Frequency stability, temperature variation | NP     |
| §2.1055(d)            | 4.3                           | Frequency stability, voltage variation     | NP     |

#### WCDMA 850 (Band V):

| Section in CFR 47     | Section in RSS-GEN or RSS-132 | Name of the test                           | Result |
|-----------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a), 22.913(a) | 4.4                           | Conducted RF output power                  | NP     |
| §22.913(a)            | 4.4                           | Radiated RF output power                   | PASSED |
| §2.1049(h)            | 4.6.1                         | 99 % occupied bandwidth                    | NP     |
| §22.917(a)            | 4.5                           | Band edge compliance                       | NP     |
| §22.917(a), §2.1051   | 4.5                           | Spurious emissions at antenna terminals    | NP     |
| §22.917(a), §2.1053   | 4.5                           | Spurious radiated emissions                | NP     |
| §2.1055(a)            | 4.3                           | Frequency stability, temperature variation | NP     |
| §2.1055(d)            | 4.3                           | Frequency stability, voltage variation     | NP     |

**GSM1900:**

| Section in CFR 47   | Section in RSS-GEN or RSS-133 | Name of the test                           | Result |
|---------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a)          | 6.4                           | Conducted RF output power                  | NP     |
| §24.232(b)          | 6.4                           | Radiated RF output power                   | PASSED |
| §2.1049(h)          | 4.6.1                         | 99 % occupied bandwidth                    | NP     |
| §24.238(a)          | 6.5                           | Band edge compliance                       | NP     |
| §24.238(a), §2.1051 | 6.5                           | Spurious emissions at antenna terminals    | NP     |
| §24.238(a), §2.1053 | 6.5                           | Spurious radiated emissions                | NP     |
| §2.1055(a)          | 6.3                           | Frequency stability, temperature variation | NP     |
| §2.1055(d)          | 6.3                           | Frequency stability, voltage variation     | NP     |

**WCDMA 1900 (Band II):**

| Section in CFR 47   | Section in RSS-GEN or RSS-133 | Name of the test                           | Result |
|---------------------|-------------------------------|--------------------------------------------|--------|
| §2.1046(a)          | 6.4                           | Conducted RF output power                  | NP     |
| §24.232(b)          | 6.4                           | Radiated RF output power                   | PASSED |
| §2.1049(h)          | 4.6.1                         | 99 % occupied bandwidth                    | NP     |
| §24.238(a)          | 6.5                           | Band edge compliance                       | NP     |
| §24.238(a), §2.1051 | 6.5                           | Spurious emissions at antenna terminals    | NP     |
| §24.238(a), §2.1053 | 6.5                           | Spurious radiated emissions                | NP     |
| §2.1055(a)          | 6.3                           | Frequency stability, temperature variation | NP     |
| §2.1055(d)          | 6.3                           | Frequency stability, voltage variation     | NP     |

PASSED  
FAILED  
NP

The EUT complies with the essential requirements in the standard.  
The EUT does not comply with the essential requirements in the standard.  
The test was not performed by the TCC Nokia Laboratory.


## CONTENTS

|                                                                     |          |
|---------------------------------------------------------------------|----------|
| <b>1. Summary for FCC Part 22/24 Compliance Test Report.....</b>    | <b>2</b> |
| 1.1. EUT and Accessory Information .....                            | 2        |
| 1.2. Summary of Test Results .....                                  | 2        |
| <b>2. Radiated RF output power</b>                                  |          |
| <b>(FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4) .....</b> | <b>5</b> |
| 2.1. Test Setup.....                                                | 5        |
| 2.2. Test method and limit .....                                    | 5        |
| 2.3. GSM850 TX Test results .....                                   | 7        |
| 2.4. GSM1900 TX Test results .....                                  | 7        |
| 2.5. WCDMA2 TX Test results .....                                   | 7        |
| 2.6. WCDMA5 TX Test results .....                                   | 7        |
| <b>3. Test Equipment .....</b>                                      | <b>8</b> |
| 3.1. Conducted measurements .....                                   | 8        |
| 3.2. Radiated measurements .....                                    | 8        |

## 2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4)

|                                                 |                   |
|-------------------------------------------------|-------------------|
| EUT with DUT number                             | RM-579, DUT 51797 |
| Accessories with DUT numbers                    | BL-5C, DUT 51798  |
| Operation Voltage [V] / [Hz]                    | Nominal           |
| Results                                         | PASSED            |
| Remarks                                         | -                 |
| Temp [°C] / Humidity [%RH] / Air Pressure [kPa] | 22 / 70 / 99.8    |
| Date of measurements                            | 13-Aug-2010       |
| Measured by                                     | Zou Ming          |

### 2.1. Test Setup



### 2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST\ TX} - P_{SUBST\ RX} - L_{SUBST\ CABLES} + G_{SUBST\ TX\ ANT}$$

Where  $A_{SUBST}$  is the final substitution correction including receive antenna gain.  $P_{SUBST\ TX}$  is signal generator level,  $P_{SUBST\ RX}$  is receiver level,  $L_{SUBST\ CABLES}$  is cable losses including both TX and RX cables and  $G_{SUBST\ TX\ ANT}$  is substitution antenna gain.

The measurement results are obtained as described below:

$$P[dBm] = P_{MEAS} + A_{TOT}$$

Where  $P_{MEAS}$  is receiver reading in dBm and  $A_{TOT}$  is total correction factor including cable loss and substitution correction ( $A_{TOT} = L_{CABLES} + A_{SUBST}$ ).

Limits for radiated RF output power measurements

| Frequency range [MHz] | Limit [W] | Limit([dBm]) |
|-----------------------|-----------|--------------|
| 824 - 849             | 7         | 38.5         |
| 1710 - 1755           | 1         | 30           |
| 1850 - 1910           | 2         | 33           |

## 2.3. GSM850 TX Test results

GSM mode

| Channel / f <sub>c</sub> [MHz] | ERP [dBm] | ERP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|-----------|---------|-------------------------|-----------------------|--------------|--------|
| 128 / 824.2                    | 27.41     | 0.551   | -6.65                   | 34.06                 | VERTICAL     | PASSED |
| 190 / 836.6                    | 27.28     | 0.535   | -5.98                   | 33.26                 | VERTICAL     | PASSED |
| 251 / 848.8                    | 27.96     | 0.625   | -6.18                   | 34.14                 | VERTICAL     | PASSED |

EGPRS mode, 1 TX Slot

| Channel / f <sub>c</sub> [MHz] | ERP [dBm] | ERP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|-----------|---------|-------------------------|-----------------------|--------------|--------|
| 128 / 824.2                    | 24.41     | 0.276   | -9.65                   | 34.06                 | VERTICAL     | PASSED |
| 190 / 836.6                    | 24.33     | 0.271   | -8.93                   | 33.26                 | VERTICAL     | PASSED |
| 251 / 848.8                    | 25.04     | 0.319   | -9.1                    | 34.14                 | VERTICAL     | PASSED |

## 2.4. GSM1900 TX Test results

GSM mode

| Channel / f <sub>c</sub> [MHz] | EIRP [dBm] | EIRP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|------------|----------|-------------------------|-----------------------|--------------|--------|
| 512 / 1850.2                   | 30.05      | 1.012    | -15.26                  | 45.31                 | HORIZONTAL   | PASSED |
| 661 / 1880                     | 30.45      | 1.109    | -15                     | 45.45                 | HORIZONTAL   | PASSED |
| 810 / 1909.8                   | 29.46      | 0.883    | -16.46                  | 45.92                 | HORIZONTAL   | PASSED |

EGPRS mode, 1 TX Slot

| Channel / f <sub>c</sub> [MHz] | EIRP [dBm] | EIRP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|------------|----------|-------------------------|-----------------------|--------------|--------|
| 512 / 1850.2                   | 29.05      | 0.804    | -16.26                  | 45.31                 | HORIZONTAL   | PASSED |
| 661 / 1880                     | 29.19      | 0.83     | -16.26                  | 45.45                 | HORIZONTAL   | PASSED |
| 810 / 1909.8                   | 28.12      | 0.649    | -17.8                   | 45.92                 | HORIZONTAL   | PASSED |

## 2.5. WCDMA2 TX Test results

| Channel / f <sub>c</sub> [MHz] | EIRP [dBm] | EIRP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|------------|----------|-------------------------|-----------------------|--------------|--------|
| 9262 / 1852.4                  | 24.16      | 0.261    | -21.16                  | 45.32                 | HORIZONTAL   | PASSED |
| 9400 / 1880                    | 23.8       | 0.24     | -21.65                  | 45.45                 | HORIZONTAL   | PASSED |
| 9538 / 1907.6                  | 22.54      | 0.179    | -23.11                  | 45.65                 | HORIZONTAL   | PASSED |

## 2.6. WCDMA5 TX Test results

| Channel / f <sub>c</sub> [MHz] | ERP [dBm] | ERP [W] | P <sub>MEAS</sub> [dBm] | A <sub>TOT</sub> [dB] | Polarisation | Result |
|--------------------------------|-----------|---------|-------------------------|-----------------------|--------------|--------|
| 4132 / 826.4                   | 23.93     | 0.247   | -10.28                  | 34.21                 | VERTICAL     | PASSED |
| 4183 / 836.6                   | 24.21     | 0.264   | -9.05                   | 33.26                 | VERTICAL     | PASSED |
| 4233 / 846.6                   | 24.66     | 0.292   | -9.54                   | 34.2                  | VERTICAL     | PASSED |

### 3. Test Equipment

#### 3.1. Conducted measurements

| Eq. No     | Equipment                | Type                | Manufacturer               | Used in            |
|------------|--------------------------|---------------------|----------------------------|--------------------|
| -          | RF Emission Software     | EMC32 Test Software | R&S                        | 22/24/27, 15C, 15B |
| BJPCHW0020 | DC Power supply          | Hp6632B             | HP                         | 22/24/27, 15C      |
| BJPCPT0040 | Receiver                 | ESCS30              | R&S                        | 15C,15B            |
| BJPCPT0073 | Signal Generator         | SMR 20              | R&S                        | 22/24/27, 15C, 15B |
| BJPCPT0079 | LISN 50 µH               | ESH3-Z5             | R&S                        | 15C,15B            |
| BJPCPT0131 | Communication Tester     | CMU200              | R&S                        | 15C,15B            |
| BJPCPT0191 | Pulse Limiter            | ESH3-Z2             | R&S                        | 15C,15B            |
| BJPCTC0017 | Communication Tester     | CMU200              | R&S                        | 22/24/27, 15C, 15B |
| BJPCTC0067 | Bluetooth Tester         | CBT                 | R&S                        | 22/24/27, 15C      |
| BJPCTC0089 | Temperature Test chamber | VT4002              | Votsch<br>industrietechnik | 22/24/27, 15C      |
| BJPCTC0090 | FSP spectrum analyzer    | FSP30               | R&S                        | 22/24/27, 15C      |
| BJPCTC0094 | GPIO-RS232 convertor     | GPIO-RS232          | NI                         | 22/24/27, 15C      |
| BJPCTC0112 | Power Splitter           | 11667B              | Agilent                    | 22/24/27, 15C      |
| BJPCTC0114 | Signal Generator         | E8357C              | Agilent                    | 22/24/27, 15C      |
| BJPCTC0115 | Communication Tester     | CMU200              | R&S                        | 22/24/27, 15B, 15C |

#### 3.2. Radiated measurements

| Eq. No     | Equipment               | Type                              | Manufacturer | Used in            |
|------------|-------------------------|-----------------------------------|--------------|--------------------|
| -          | BT / WLAN Antenna       | SPA 2400/75/9/0/V                 | Huber-Suhner | 15C, 15B           |
| -          | BT / WLAN Antenna       | SPA 2400/75/9/0/V                 | Huber-Suhner | 15C, 15B           |
| -          | RF Emission Software    | EMC32 Test Software               | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0072 | Receiver                | ESI B26                           | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0130 | Relay Switch Unit       | TS-RSP                            | R&S          | 22/24/27, 15C, 15B |
| BJPCPT0150 | High Pass Filter        | WHKS1200-10SS                     | Wainwright   | 22/24/27, 15C, 15B |
| BJPCPT0151 | Band Reject Filter      | WRCD1880/2000-0.2/40-5SSK         | Wainwright   | 24, 15B            |
| BJPCPT0154 | Band Reject Filter      | WRCT2402/2480-2400/2483.5-30-20SS | Wainwright   | 15C, 15B           |
| BJPCPT0162 | Antenna                 | HF906                             | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0007 | Antenna                 | HL562                             | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0029 | Antenna                 | HF906                             | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0034 | Band Reject Filter      | WRCT 800/880-0.2/40-5SSK          | Wainwright   | 22, 15B            |
| BJPCTC0049 | Preamplifier            | Blma 0118-1A-Bt                   | Bonn         | 22/24/27, 15C, 15B |
| BJPCTC0055 | Communication Tester    | CMU200                            | R&S          | 22/24/27, 15C, 15B |
| BJPCTC0058 | Bluetooth Tester        | CBT                               | R&S          | 15C, 15B           |
| BJPCTC0064 | Band Reject Filter      | WRCG1877/1883-1870/1890-40/6SS    | Wainwright   | 24, 15B            |
| BJPCTC0065 | Band Reject Filter      | WRCG832/838-825/845-40/5SS        | Wainwright   | 27, 15B            |
| BJPCTC0071 | Multi-Device Controller | 2090                              | EMCO         | 22/24/27, 15C, 15B |
| BJPCTC0072 | Anechoic Chamber        | 3 m Semi / Full Anechoic Chamber  | ETS          | 22/24/27, 15C, 15B |
| BJPCTC0073 | MAST                    | Model-TR/POL                      | ETS          | 22/24/27, 15C, 15B |
| BJPCTC0074 | MAST                    | Model 2070-2                      | ETS          | 22/24/27, 15C, 15B |
| BJPCTC0075 | Turntable               | Model 2188                        | ETS-EMCO     | 22/24/27, 15C, 15B |
| BJPCTC0096 | Preamplifier            | AFS4-00100300-20-23P-6            | Miteq        | 22/24/27, 15C, 15B |
| BJPCTC0113 | Receiver                | ESI B26                           | R&S          | 22/24/27, 15B, 15C |
| BJPCTC0115 | Communication Tester    | CMU200                            | R&S          | 22/24/27, 15B, 15C |