

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-709_03.docx	Date of Report:	09-Sep-2010
Number of pages:	21	Customer's Contact person:	Qiu Rain
Testing laboratory:	TCC Nokia Copenhagen Laboratory Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934	Customer:	Nokia Corporation Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550
FCC listing no.:	99059		
IC recognition no.:	661AL-1		
Tested devices/ accessories:	Phone RM-709 / Battery BL-5C / AC-Charger AC-3E / Headset WH-102		
FCC ID:	QTLRM-709	IC:	661AB-RM709
Supplement reports:			
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 2, June 2007) and RSS-210 (Issue 7, June 2007). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Christian Andersen, System Specialist, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	24-Aug-2010
Testing completed	03-Sep-2010
The customer's contact person	Qui Rain
Test Plan referred to	T:\Projects\RM-709\TestPlan\RS_testplan_RM-709.xls
Notes	None
Document name	FCC15C_RM-709_03.docx

1.1. EUT and Accessory Information

The EUT is a 4-band (GSM850/900/1800/1900) mobile phone with GPRS, EGPRS and Bluetooth. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-709	004402/13/227237/2	0201	-	V tw92_10w31SSC	24125
Battery	BL-5C	0670400382066R12405GL62068	-	-	-	24116
AC charger	AC-3E	4419298322052137241;0675370	-	-	-	26915
Headset	WH-102	06943249152U4106313	-	-	-	24865
Phone	RM-709	004402/13/168893/3	0201	-	V tw92_10w31SSC	24134
Battery	BL-5C	0670400382066R12405GL62092	-	-	-	24123
AC charger	AC-3E	4419298432052200002;0675370	-	-	-	24105
Headset	WH-102	06943249132U4102635	-	-	-	24109
Phone	RM-709	004402/13/227236/4	0201	-	V tw92_10w31SSC	24135
Battery	BL-5C	0670400382066R12405GL61927	-	-	-	24117
AC charger	AC-3E	4419298432052200058;0675370	-	-	-	24104
Headset	WH-102	06943249041E2607011	-	-	-	24110

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in <i>RSS-GEN</i> or <i>RSS-210</i>	Name of the test	Result
15.247(b)(1)	A8.4 (2)	Conducted peak output power	NP
15.247(d)	A8.5	Band edge compliance of RF emissions	NP
15.247(d)	A8.5	Spurious RF conducted emissions	NP
15.247(d), 15.209	A8.5	Spurious radiated emissions	NP
15.207	7.2.2	AC powerline conducted emissions	Passed
15.247(a)(1)	A8.1 (a)	20 dB bandwidth	Passed
15.247(a)(1)	A8.1 (b)	Carrier frequency separation	Passed
15.247(a)(1)(iii)	A8.1 (d)	Number of hopping frequencies	Passed
15.247(a)(1)(iii)	A8.1 (d)	Time of occupancy	Passed

PASSED
FAILED
NP


The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Copenhagen Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups.....	4
2.1. Conducted RF test setup.....	4
2.2. AC powerline conducted emissions test setup.....	4
2.3. Radiated test setup	4
3. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)	5
3.1. Test method and limit	5
3.2. Bluetooth Test results.....	6
4. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (a))	7
4.1. Test method and limit	7
4.2. Bluetooth Test results.....	8
5. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (b)).....	11
5.1. Test method and limit	11
5.2. Bluetooth Test results.....	12
6. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))	14
6.1. Test method and limit	14
6.2. Bluetooth Test results.....	15
7. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d)).....	17
7.1. Test method and limit	17
7.2. Bluetooth test results	18
8.....	20
9. Test Equipment.....	20
9.1. Conducted measurements	20
9.2. Radiated measurements	20

2. Test setups


2.1. Conducted RF test setup



2.2. AC powerline conducted emissions test setup



2.3. Radiated test setup



3. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-709, DUT 24134
Accessories with DUT numbers	BL-5C, DUT 24123 ; AC-3E, DUT 24105 ; WH-102, DUT 24109
Operation Voltage [V] / [Hz]	115 / 60
Result	Passed
Remarks	none
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 41 / 101
Date of measurements	03-Sep-2010
Measured by	Bo Moltved Christiansen

3.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$


Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.

CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

3.2. Bluetooth Test results

Channel 40 / 2442 MHz



Quasi peak

Frequency [MHz]	Level [dBμV]	IF-BW[kHz]	Line	Margin	Result
0.525	40.82	10	N	15.2	Passed
0.54	42.6	10	N	13.4	Passed
0.56	43.65	10	N	12.4	Passed
0.57	41.97	10	N	14	Passed
0.98	38.69	10	N	17.3	Passed
1.915	37.05	10	N	19	Passed

Average

Frequency [MHz]	Level [dBμV]	IF-BW[kHz]	Line	Margin	Result
0.36	36	10	N	12.73	Passed
0.515	37.73	10	N	8.3	Passed
0.535	28.81	10	N	17.2	Passed
0.565	37.22	10	N	8.8	Passed
0.62	32.06	10	N	13.9	Passed
0.98	32.06	10	N	13.9	Passed

4. 20 dB bandwidth (FCC §15.247(a)(1), RSS-210 A8.1 (a))

EUT with DUT number	RM-709; DUT 24125
Accessories with DUT numbers	BL-5C; DUT 24116, AC-3; DUT 26915, WH-102; DUT 24865
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	Passed
Remarks	None
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23 / 45 / 101.3
Date of measurements	30-Aug-2010
Measured by	Ruben Hansen

4.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements

Limit [MHz]
N/A

4.2. Bluetooth Test results


4.2.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	792.000	PASSED
40 / 2442	992.000	PASSED
78 / 2480	776.000	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz




Channel 78 / 2480 MHz




4.2.2 8DPSK modulation, PRBS packet type

Channel / f _c [MHz]	20 dB bandwidth [kHz]	Result
0 / 2402	1308.000	PASSED
40 / 2442	1312.000	PASSED
78 / 2480	1308.000	PASSED


Channel 0 / 2402 MHz



Channel 40 / 2442 MHz



Channel 78 / 2480 MHz



5. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1 (b))

EUT with DUT number	RM-709; DUT 24125
Accessories with DUT numbers	BL-5C; DUT 24116, AC-3; DUT 26915, WH-102; DUT 24865
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	Passed
Remarks	None
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23 / 45 / 101.3
Date of measurements	30-Aug-2010
Measured by	Ruben Hansen

5.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or 2/3 of the 20 dB bandwidth

5.2. Bluetooth Test results

5.2.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
980	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



5.2.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
1010	PASSED

Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



6. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))

EUT with DUT number	RM-709; DUT 24125
Accessories with DUT numbers	BL-5C; DUT 24116, AC-3; DUT 26915, WH-102; DUT 24865
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	Passed
Remarks	None
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23 / 45 / 101.3
Date of measurements	30-Aug-2010
Measured by	Ruben Hansen

6.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

6.2. Bluetooth Test results

6.2.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
78	PASSED


Hopping on, number of hopping frequencies



6.2.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
69	PASSED

Hopping on, number of hopping frequencies



7. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1 (d))

EUT with DUT number	RM-709; DUT 24125
Accessories with DUT numbers	BL-5C; DUT 24116, AC-3; DUT 26915, WH-102; DUT 24865
Operation Voltage [V] / [Hz]	115V / 60Hz
Result	Passed
Remarks	None
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23 / 45 / 101.3
Date of measurements	30-Aug-2010
Measured by	Ruben Hansen

7.1. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

7.2. Bluetooth test results


7.2.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
93	2,920	0.271560	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz




Hopping on, duration of one transmission, channel 40 / 2442 MHz




7.2.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [μs]	Time of occupancy [s]	Result
95	2,928	0.278160	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



8.

9. Test Equipment

9.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
20168	Bluetooth Tester	CBT	Rohde&Schwarz	22/24/27, 15C, 15B
18772	Shielded Chamber	RFD-100	ETS-Lindgren	15C, 15B
13037	Power Supply 0-15V 10A	EA3012	LP Instruments	15C, 15B
13513	Pulse Limiter	ESH3Z2	Rohde&Schwarz	15C, 15B
13666	Receiver	ESPC	Rohde&Schwarz	15C, 15B
13935	LISN	ESH3-Z5	Rohde&Schwarz	15C, 15B
16995	Directional Coupler 20dB 0,5-2,0 GHz SMA Conn.	1538RA-20	Weinschel	15C, 15B
18772	Shielded Chamber	RFD-100	ETS-Lindgren	15C, 15B
19171	Communication Tester	CMU200	Rohde&Schwarz	15C, 15B
11386	DC Power Supply	HP6632A	Hewlett Packard	22/24/27, 15C, 15B
19678	Spectrum Analyzer	FSP	Rohde&Schwarz	22/24/27, 15C, 15B
16601	Communication Tester	CMU200	Rohde&Schwarz	22/24/27, 15C, 15B
19625	Climatic Chamber	VT4002EMC	Vötsch	22/24/27, 15C, 15B
13357	Signal Generator	SMP02	Rohde&Schwarz	22/24/27, 15C, 15B
19116	Power splitter	-	various	22/24/27, 15C, 15B
20544	Transformer. 230/115V	-	Nokia	22/24/27, 15C, 15B
20543	UPS. 700V/A 490W	PW 9120 700i	Powerware	22/24/27, 15C, 15B

9.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
18792	Mast/turntable controller	2090	ETS-EMCO	22/24/27, 15C, 15B
18416	Communication Tester	CMU200	Rohde&Schwarz	22/24/27, 15C, 15B
20168	Bluetooth Tester	CBT	Rohde&Schwarz	22/24/27, 15C, 15B
13077	Power Supply	EA-3016	-	22/24/27, 15C, 15B
15742	Programmable Relay Switching System	-----	Pickering	22/24/27, 15C, 15B
20078	Relay 2x6 Chnl μ Wave Mux	10-785B-522	Pickering	22/24/27, 15C, 15B
14021	Relay Dual 6 Chnl μ Wave Mux	10-785-522	-	22/24/27, 15C, 15B
-	Relay Dual 6 Chnl μ Wave Mux	10-785-522	-	22/24/27, 15C, 15B
17644	Dual 6 Channel MUX Microwave Relay SMA 50 Ohm	10-785-522	Pickering	22/24/27, 15C, 15B
16948	Dual 6 Channel MUX Microwave Relay SMA 50 Ohm	10-785-522	Pickering	22/24/27, 15C, 15B
16949	Dual 6 Channel MUX Microwave Relay SMA 50 Ohm	10-785-522	Pickering	22/24/27, 15C, 15B
18861	Receiver	EMI Test Receiver 20Hz-26,5GHz ESI	Rohde&Schwarz	22/24/27, 15C, 15B
18860	Antenna	HL562	Rohde&Schwarz	22/24/27, 15C, 15B
18773	Anechoic chamber	RFD-100	ETS-Lindgren	22/24/27, 15C, 15B
18774	Anechoic chamber	RFSD-F/A-100	ETS-Lindgren	22/24/27, 15C, 15B
19151	High Pass Filter	WHJS3000-10SS	Wainwright	22/24/27, 15C, 15B
13937	Band reject filter	WRCA902.4-0.2/40-6SS	Wainwright Instruments	22/24/27, 15C, 15B
13936	Band reject filter	WRCD1747.5-0.2/40-10SS	Wainwright Instruments	22/24/27, 15C, 15B
14114	Highpass Filter	WHK1000-12SS	Wainwright Instruments	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
14188	Band reject filter	WRCA902.4-0.2/40-6SS	Wainwright	22/24/27, 15C, 15B
14187	Band reject filter	WRCD1747.5-0.2/40-10SS	Wainwright	22/24/27, 15C, 15B
16633	Band reject filter	WRCD1880.0-0.2/40-10SS	Wainwright	22/24/27, 15C, 15B
19587	Band reject filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	22/24/27, 15C, 15B
20115	Band reject filter	-	Wainwright	22/24/27, 15C, 15B
20114	Band reject filter	WRCG1737/1743-1733/1747-40/6SS	Wainwright	22/24/27, 15C, 15B
20116	Band reject filter	WRCG832/83/-825/845-40/5SS	Wainwright	22/24/27, 15C, 15B
20698	Antenna	BBHA 9120 D	SCHWARZBECK	22/24/27, 15C, 15B
19966	Antenna	HFH2-Z2	Rohde&Schwarz	15C, 15B
13799	Signal Generator	SMP02	Rohde&Schwarz	22/24/27, 15C, 15B
15191	Turntable Contoller Unit	G-800SDX	YAESU	22/24/27, 15C, 15B
14900	Antenna Controller	HD100	HD GmbH	22/24/27, 15C, 15B
20544	Transformer. 230/115V	-	Nokia	22/24/27, 15C, 15B
20543	UPS. 700V/A 490W	PW 9120 700i	Powerware	22/24/27, 15C, 15B