



# **Test Setup photos for RM-898 SAR Compliance Test Report**

Test report no.: **Template version: Testing laboratory:**  SAR Photo RM-898 02 19.3

TCC Nokia Beijing Laboratory **Beijing Economic and** 

**Technological Development Area** No.5 Donghuan Zhonglu

Beijing

PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550

Responsible test

engineer:

FCC ID:

Measurements made by:

Luwen

Liu Xianchao

Liu Xianchao; Liang Dong; Zhang

Product contact person:

2012-08-22

**Number of pages:** 7

Date of report:

**Nokia Corporation** Client:

IC: -

**Beijing Economic and** 

Technological Development Area

No.5 Donghuan Zhonglu

Beijing

PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550

Hu Helen

Tested device:

RM-898

**OTLRM-898** 

FCC\_RM-898\_01

Testing has been carried out in accordance with:

**Supplement reports:** 

47CFR §2.1093

Radiofrequency Radiation Exposure Evaluation: Portable Devices

FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01)

Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency

**Electromagnetic Fields** 

RSS-102

Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

IEEE 1528 - 2003

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices:

Measurement Technique

**Documentation:** 

The documentation of the testing performed on the tested devices is archived for 15 years at

TCC Nokia.

**Test results:** 

The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not

be reproduced except in full, without written approval of the laboratory.

**Date and signatures:** 

For the contents:





# CONTENTS

1. SUI	MMARY OF SAR TEST REPORT	3
1.1 1.2	TEST DETAILS PICTURE OF THE DEVICE	
,_	ST POSITIONS	
2.1	AGAINST PHANTOM HEAD	3
2.2	Body Worn Configuration	
2.3	WIRELESS ROLLTER CONFIGURATION	





### 1. SUMMARY OF SAR TEST REPORT

### 1.1 Test Details

Period of test	2012-08-09 to 2012-08-27
SN, HW and SW numbers of tested	SN: 353661/05/000049/8, HW: 2000, SW:
device	1102.0000.8779.12290, DUT: 52795
	SN: 353661/05/000046/4, HW: 2000, SW:
	1102.0000.8779.12290, DUT: 52794
	SN: 353661/05/000056/3, HW: 2000, SW:
	1102.0000.8779.12290, DUT: 52793
Batteries used in testing	BP-3L LG, DUT: 52796, 52797,52798, 52800, 52801
	BP-3L Sony, DUT: 52803, 52802
Headsets used in testing	WH-108, DUT: 52805, 52806, 52807
Other accessories used in testing	-
State of sample	Prototype unit
Notes	-

### 1.2 Picture of the Device



### 2. TEST POSITIONS

## 2.1 Against Phantom Head

Measurements were made in "cheek" and "tilt" positions on both the left hand and right hand sides of the phantom.





The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".



Photo of the Device in "cheek" position



Photo of the Device in "tilt" position

#### 2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in the photo below using a separate flat spacer that was removed before the start of the measurements. The device was oriented with both sides facing the phantom to find the highest results.



Photo of the device positioned for Body SAR measurement. The spacer was removed for the tests.

Nokia body-worn accessories are commonly available for the separation distance used in this testing.





### **2.3 Wireless Router Configuration**

The device was placed in the SPEAG holder using the Nokia spacer and positioned 10.0mm away from the flat phantom. The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – display facing phantom.

The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – back facing phantom.

The spacer was removed before the start of the measurements.







Photo of the device positioned for WR mode measurement – top edge facing phantom. The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – bottom edge facing phantom. The spacer was removed before the start of the measurements.







Photo of the device positioned for WR mode measurement – left edge facing phantom. The spacer was removed before the start of the measurements.



Photo of the device positioned for WR mode measurement – right edge facing phantom. The spacer was removed before the start of the measurements.