


Instruction Manual

- 1) Open the battery cover in underbody, install 5 pcs of 1.2V AA batteries to the car bottom and close the battery cover..
- 2) Turn on the switch of the car.
- 3) Adjust the regulating rod of underbody to make the car run in a straight line.
- 4) Open the battery cover of controller, install 1 pcs of 9V battery to the controller bottom and close the battery cover.
- 5) Turn on the switch of the controller, use it to control the car.



Warnings

1. Use the same type of batteries, do not mix old and new batteries.
2. Insert the batteries properly, do not misplace +/- electrode.
3. Remove exhausted batteries from the car.
4. Non-rechargeable batteries can not be charging, rechargeable batteries are only to be charged under adult supervision.
5. Please take out the batteries when not in use for a long time.

Caution: The user is cautioned that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. +

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. +

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: +

- Reorient or relocate the receiving antenna. +
- Increase the separation between the equipment and receiver. +
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. +
- Consult the dealer or an experienced radio/TV technician for help. +