

FCC Part 22/24 Compliance Test Report

Test Report no.:	Salo_FCC_0836_11.doc	Date of Report:	02-Oct-2008
Number of pages:	37	Customer's Contact person:	Asko Pasanen
Testing laboratory:	TCC Nokia Salo Laboratory P.O. Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Customer:	Nokia Corporation P.O. Box 50 Mattianniemi 6-8 FIN-40101 JYVÄSKYLÄ, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 78000
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-334 / Battery BL-5K, Headset HS-45, Audio Adapter AD-54, AC-Charger AC-10		
FCC ID:	QURRM-334	IC:	661AC-RM334
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22, 24, TIA-603-C-2004 and IC standards RSS-GEN (Issue 2, June 2007), RSS-132 (Issue 2, September 2005), RSS-133 (Issue 4, February 2008) and RSS-139 (Issue 1, February 2008). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Sami Lehtonen, Test System Manager

1. Summary for FCC Part 22/24 Compliance Test Report

Date of receipt	21-Aug-2008
Testing completed	26-Sep-2008
The customer's contact person	Asko Pasanen
Test Plan referred to	T:\Projects\RM-334\TestPlan_RS\RS_Testplan_RM-334.xls
Notes	-
Document name	T:\Projects\RM-334\EMC\Results\FCC\Salo_FCC_0836_11.doc

1.1. EUT and Accessory Information

The EUT is a 7-band (GSM850/900/1800/1900 and WCDMA Band I/II(1900)/V(850)) mobile phone with GPRS, EGPRS, Bluetooth, WLAN and FM transmitter. The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-334	004401100556220	1210	-	10.014	13149
Phone	RM-334	004401100556196	1210	-	10.014	13134
Battery	BL-5K	4620408135J10002334;0670580	-	-	-	13150
Battery	BL-5K	4620408135J10002191;0670580	-	-	-	13173
Headset	HS-45	06946447463Q1B14975	-	-	-	13151
Headset	HS-45	06946447463Q1B14996	-	-	-	13155
Audio Adapter	AD-54	07508387301J2102804	-	-	-	13152
Audio Adapter	AD-54	07508387322J2100502	-	-	-	12914
AC-Charger	AC-10	3997918262110501436;0675408	-	-	-	13153
AC-Charger	AC-10	3997918262110501439;0675408	-	-	-	13192

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	PASSED
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	PASSED
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

GSM 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	PASSED
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA 850 (Band V):

Section in CFR 47	Section in <i>RSS-GEN</i> or <i>RSS-132</i>	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	PASSED
§22.917(a)	4.5	Band edge compliance	PASSED
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	PASSED
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

WCDMA 1900 (Band II):

Section in CFR 47	Section in <i>RSS-GEN</i> or <i>RSS-133</i>	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	PASSED
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	PASSED
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Salo Laboratory.


CONTENTS

1. Summary for FCC Part 22/24 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4)	5
2.1. Test setup	5
2.2. Test method and limit	5
2.3. GSM 850 Test results	6
2.4. GSM 1900 Test results	8
2.5. WCDMA 850 Test results	10
2.6. WCDMA 1900 Test results	11
3. 99 % occupied bandwidth (FCC §2.1049(h), RSS-GEN 4.6.1)	12
3.1. Test setup	12
3.2. Test method and limit	12
3.3. WCDMA 850 Test results	13
4. Band edge compliance (FCC §22.917(a), 24.238(a), RSS-132 4.5, RSS-133 6.5)	14
4.1. Test setup	14
4.2. Test method and limit	14
4.3. GSM 850 Test results	15
4.4. GSM 1900 Test results	21
4.5. WCDMA 850 Test results	27
4.6. WCDMA 1900 Test results	30
5. Spurious radiated emissions (FCC §22.917(a), §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5)	33
5.1. Test setup	33
5.2. Test method and limit	33
5.3. GSM 850 Test results	34
5.4. GSM 1900 Test results	35
5.5. WCDMA 850 Test results	35
5.6. WCDMA 1900 Test results	35
6. Test Equipment	36
6.1. Conducted measurements	36
6.2. Radiated measurements	36

2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 4.4, RSS-133 6.4)

EUT with DUT number	RM-334, DUT 13134
Accessories with DUT numbers	BL-5K, DUT 13173; HS-45, DUT 13155; AD-54, DUT 12914; AC-10E, DUT 13192
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Phone tested slide open and closed and MP#3 positions.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	18 / 42 / 101.2
Date of measurements	13-Sep-2008 & 26-Sep-2008
Measured by	Sami Lehtonen / Jouko Kaivonen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. P_{SUBST_TX} is signal generator level, P_{SUBST_RX} is receiver level, L_{SUBST_CABLES} is cable losses including both TX and RX cables and $G_{SUBST_TX_ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P [dBm] = P_{MEAS} + A_{TOT}$$

Where P_{MEAS} is receiver reading in dBm and A_{TOT} is total correction factor including cable loss and substitution correction ($A_{TOT} = L_{CABLES} + A_{SUBST}$).

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
824 - 849	7	38.5
1850 - 1910	2	33

2.3. GSM 850 Test results

Slide open:

GSM mode

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	30.00	1.000	- 5.80	35.80	VERTICAL	PASSED
190 / 836.6	30.10	1.023	- 6.20	36.30	VERTICAL	PASSED
251 / 848.8	28.90	0.776	- 6.10	35.00	VERTICAL	PASSED

GPRS mode, 2 TX Slots

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	27.50	0.562	- 8.30	35.80	VERTICAL	PASSED
190 / 836.6	27.30	0.537	- 9.00	36.30	VERTICAL	PASSED
251 / 848.8	26.70	0.468	- 8.30	35.00	VERTICAL	PASSED

GPRS mode, 3 TX Slots

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	25.40	0.347	- 10.40	35.80	VERTICAL	PASSED
190 / 836.6	25.70	0.372	- 10.60	36.30	VERTICAL	PASSED
251 / 848.8	25.20	0.331	- 9.80	35.00	VERTICAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f_c [MHz]	ERP [dBm]	ERP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
128 / 824.2	16.50	0.045	- 19.30	35.80	VERTICAL	PASSED
190 / 836.6	20.00	0.100	- 16.30	36.30	VERTICAL	PASSED
251 / 848.8	20.00	0.100	- 15.00	35.00	VERTICAL	PASSED

Slide closed:

GSM mode

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	27.10	0.513	- 8.70	35.80	VERTICAL	PASSED
190 / 836.6	26.80	0.479	- 9.80	36.60	HORIZONTAL	PASSED
251 / 848.8	24.30	0.269	- 10.70	35.00	VERTICAL	PASSED

GPRS mode, 2 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	24.70	0.295	- 11.10	35.80	VERTICAL	PASSED
190 / 836.6	25.40	0.347	- 11.20	36.60	HORIZONTAL	PASSED
251 / 848.8	23.00	0.200	- 12.00	35.00	VERTICAL	PASSED

GPRS mode, 3 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	22.70	0.186	- 13.10	35.80	VERTICAL	PASSED
190 / 836.6	23.50	0.224	- 13.10	36.60	HORIZONTAL	PASSED
251 / 848.8	21.20	0.132	- 13.80	35.00	VERTICAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	17.10	0.051	- 18.70	35.80	VERTICAL	PASSED
190 / 836.6	18.10	0.065	- 18.50	36.60	HORIZONTAL	PASSED
251 / 848.8	16.70	0.047	- 18.30	35.00	VERTICAL	PASSED

Slide MP3:

GSM mode

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	24.60	0.288	- 12.60	37.20	HORIZONTAL	PASSED
190 / 836.6	23.10	0.204	- 13.50	36.60	HORIZONTAL	PASSED
251 / 848.8	21.60	0.145	- 13.90	35.50	HORIZONTAL	PASSED

GPRS mode, 2 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	22.40	0.174	- 14.80	37.20	HORIZONTAL	PASSED
190 / 836.6	21.40	0.138	- 15.20	36.60	HORIZONTAL	PASSED
251 / 848.8	19.90	0.098	- 15.60	35.50	HORIZONTAL	PASSED

GPRS mode, 3 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	20.20	0.105	- 17.00	37.20	HORIZONTAL	PASSED
190 / 836.6	19.70	0.093	- 16.90	36.60	HORIZONTAL	PASSED
251 / 848.8	18.10	0.065	- 17.40	35.50	HORIZONTAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
128 / 824.2	15.20	0.033	- 22.00	37.20	HORIZONTAL	PASSED
190 / 836.6	15.10	0.032	- 21.50	36.60	HORIZONTAL	PASSED
251 / 848.8	13.30	0.021	- 22.20	35.50	HORIZONTAL	PASSED

2.4. GSM 1900 Test results

Slide open:

GSM mode

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	31.80	1.514	- 14.70	46.50	HORIZONTAL	PASSED
661 / 1880.0	32.20	1.660	- 14.70	46.90	HORIZONTAL	PASSED
810 / 1909.8	30.60	1.148	- 13.90	44.50	HORIZONTAL	PASSED

GPRS mode, 2 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	31.60	1.445	- 14.90	46.50	HORIZONTAL	PASSED
661 / 1880.0	32.10	1.622	- 14.80	46.90	HORIZONTAL	PASSED
810 / 1909.8	30.30	1.072	- 14.20	44.50	HORIZONTAL	PASSED

GPRS mode, 3 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	16.50	0.045	- 30.00	46.50	HORIZONTAL	PASSED
661 / 1880.0	26.20	0.417	- 20.70	46.90	HORIZONTAL	PASSED
810 / 1909.8	23.70	0.234	- 20.80	44.50	HORIZONTAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	26.50	0.447	- 20.00	46.50	HORIZONTAL	PASSED
661 / 1880.0	26.50	0.447	- 20.40	46.90	HORIZONTAL	PASSED
810 / 1909.8	25.10	0.324	- 19.40	44.50	HORIZONTAL	PASSED

Slide closed:

GSM mode

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	30.40	1.096	- 15.90	46.30	VERTICAL	PASSED
661 / 1880.0	28.80	0.759	- 17.20	46.00	VERTICAL	PASSED
810 / 1909.8	28.00	0.631	- 16.50	44.50	HORIZONTAL	PASSED

GPRS mode, 2 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	30.30	1.072	- 16.00	46.30	VERTICAL	PASSED
661 / 1880.0	28.30	0.676	- 17.70	46.00	VERTICAL	PASSED
810 / 1909.8	28.50	0.708	- 16.00	44.50	HORIZONTAL	PASSED

GPRS mode, 3 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	28.50	0.708	- 17.80	46.30	VERTICAL	PASSED
661 / 1880.0	26.60	0.457	- 19.40	46.00	VERTICAL	PASSED
810 / 1909.8	26.20	0.417	- 18.30	44.50	HORIZONTAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
512 / 1850.2	23.80	0.240	- 22.50	46.30	VERTICAL	PASSED
661 / 1880.0	22.60	0.182	- 23.40	46.00	VERTICAL	PASSED
810 / 1909.8	21.00	0.126	- 23.50	44.50	HORIZONTAL	PASSED

Slide MP3:
GSM mode

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	28.50	0.708	- 18.00	46.50	HORIZONTAL	PASSED
661 / 1880.0	29.10	0.813	- 17.80	46.90	HORIZONTAL	PASSED
810 / 1909.8	27.20	0.525	- 17.30	44.50	HORIZONTAL	PASSED

GPRS mode, 2 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	28.50	0.708	- 17.80	46.30	VERTICAL	PASSED
661 / 1880.0	27.50	0.562	- 18.50	46.00	VERTICAL	PASSED
810 / 1909.8	26.60	0.457	- 17.90	44.50	HORIZONTAL	PASSED

GPRS mode, 3 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	26.40	0.437	- 19.90	46.30	VERTICAL	PASSED
661 / 1880.0	25.40	0.347	- 20.60	46.00	VERTICAL	PASSED
810 / 1909.8	24.40	0.275	- 20.10	44.50	HORIZONTAL	PASSED

EGPRS mode, 2 TX Slots

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
512 / 1850.2	22.20	0.166	- 24.10	46.30	VERTICAL	PASSED
661 / 1880.0	21.50	0.141	- 24.50	46.00	VERTICAL	PASSED
810 / 1909.8	19.60	0.091	- 24.90	44.50	HORIZONTAL	PASSED

2.5. WCDMA 850 Test results

Slide open:

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
4132 / 826.4	19.10	0.081	- 15.70	34.80	HORIZONTAL	PASSED
4175 / 835.0	19.40	0.087	- 15.40	34.80	HORIZONTAL	PASSED
4233 / 846.6	20.20	0.105	- 14.80	35.00	HORIZONTAL	PASSED

Slide closed:

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
4132 / 826.4	15.20	0.033	- 19.20	34.40	VERTICAL	PASSED
4175 / 835.0	15.40	0.035	- 19.40	34.80	HORIZONTAL	PASSED
4233 / 846.6	15.30	0.034	- 19.40	34.70	VERTICAL	PASSED

Slide MP3:

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
4132 / 826.4	11.10	0.013	- 23.30	34.40	VERTICAL	PASSED
4175 / 835.0	12.10	0.016	- 22.40	34.50	VERTICAL	PASSED
4233 / 846.6	12.70	0.019	- 22.00	34.70	VERTICAL	PASSED

2.6. WCDMA 1900 Test results

Slide open:

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
9262 / 1852.4	24.20	0.263	- 21.10	45.30	HORIZONTAL	PASSED
9400 / 1880.0	22.50	0.178	- 22.10	44.60	HORIZONTAL	PASSED
9538 / 1907.6	22.10	0.162	- 22.70	44.80	HORIZONTAL	PASSED

Slide closed:

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
9262 / 1852.4	21.30	0.135	- 22.90	44.20	VERTICAL	PASSED
9400 / 1880.0	20.10	0.102	- 23.90	44.00	VERTICAL	PASSED
9538 / 1907.6	21.90	0.155	- 23.40	45.30	VERTICAL	PASSED


Slide MP3:

Channel / f_c [MHz]	EIRP [dBm]	EIRP [W]	P_{MEAS} [dBm]	A_{TOT} [dB]	Polarisation	Result
9262 / 1852.4	21.40	0.138	- 22.80	44.20	VERTICAL	PASSED
9400 / 1880.0	18.90	0.078	- 25.10	44.00	VERTICAL	PASSED
9538 / 1907.6	19.50	0.089	- 25.80	45.30	VERTICAL	PASSED

3. 99 % occupied bandwidth (FCC §2.1049(h), RSS-GEN 4.6.1)

EUT with DUT number	RM-334, DUT 13149
Accessories with DUT numbers	BL-5K, DUT 13150; HS-45, DUT 13151; AD-54, DUT 13152; AC-10, DUT 13153
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 45 / 100
Date of measurements	04-Aug-2008
Measured by	Anni Manninen

3.1. Test setup




3.2. Test method and limit

The measurement is made according to FCC rules part 22 and IC standard RSS-GEN.

3.3. WCDMA 850 Test results

Operation mode (TX on)	99% occupied bandwidth [kHz]
FDD	4140.000


Channel 4175 / 835.0 MHz



4. Band edge compliance (FCC §22.917(a), 24.238(a), RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-334, DUT 13134
Accessories with DUT numbers	BL-5K, DUT 13173; HS-45, DUT 13155; AD-54, DUT 12914; AC-10E, DUT 13192
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Phone tested slide open and closed and MP3 positions.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	18 / 42 / 101.2
Date of measurements	13-Sep-2008 & 26-Sep-2008
Measured by	Sami Lehtonen

4.1. Test setup



4.2. Test method and limit

The measurement is made according to FCC rules parts 22 and 24 and IC standards RSS-132 and RSS-133.


Limits for band edge compliance measurements

Operation band	Frequency range [MHz]	Limit [dBm]
GSM 850 / WCDMA 850	Below 824 and above 849	-13
GSM 1900 / WCDMA 1900	Below 1850 and above 1910	-13

4.3. GSM 850 Test results


Slide open:

GSM mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	128 / 824.2	-15.70

GSM mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	251 / 848.8	-16.70

EGPRS mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	128 / 824.2	-32.60


EGPRS mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	251 / 848.8	-30.00


Slide closed:

GSM mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	128 / 824.2	-18.20

GSM mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	251 / 848.8	-19.70

EGPRS mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	128 / 824.2	-32.00


EGPRS mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	251 / 848.8	-35.70


Slide MP3:

GSM mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	128 / 824.2	-21.60

GSM mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	251 / 848.8	-21.70

EGPRS mode, channel 128 / 824.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	128 / 824.2	-36.10

EGPRS mode, channel 251 / 848.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	251 / 848.8	-37.20

4.4. GSM 1900 Test results


Slide open:

GSM mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	512 / 1850.2	-13.60

GSM mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	810 / 1909.8	-15.10

EGPRS mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	512 / 1850.2	-24.90


EGPRS mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	810 / 1909.8	-31.60


Slide closed:

GSM mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	512 / 1850.2	-16.00

GSM mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	810 / 1909.8	-17.10

EGPRS mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	512 / 1850.2	-34.20


EGPRS mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	810 / 1909.8	-36.50


Slide MP3:

GSM mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	512 / 1850.2	-15.50

GSM mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
GSM	810 / 1909.8	-17.00

EGPRS mode, channel 512 / 1850.2 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	512 / 1850.2	-35.50

EGPRS mode, channel 810 / 1909.8 MHz (Peak detector, RBW: 3 kHz, VBW: 3 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
EGPRS	810 / 1909.8	-37.30

4.5. WCDMA 850 Test results


Slide open:

Channel 4132 / 826.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4132 / 826.4	-24.20


Channel 4233 / 846.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4233 / 846.6	-22.90


Slide closed:

Channel 4132 / 826.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4132 / 826.4	-25.00


Channel 4233 / 846.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4233 / 846.6	-22.70


Slide MP3:

Channel 4132 / 826.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4132 / 826.4	-29.10

Channel 4233 / 846.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	4233 / 846.6	-25.50

4.6. WCDMA 1900 Test results


Slide open:

Channel 9262 / 1852.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9262 / 1852.4	-19.50


Channel 9538 / 1907.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9538 / 1907.6	-21.60


Slide closed:

Channel 9262 / 1852.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9262 / 1852.4	-19.70


Channel 9538 / 1907.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9538 / 1907.6	-21.30


Slide MP3:

Channel 9262 / 1852.4 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)



Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9262 / 1852.4	-20.00

Channel 9538 / 1907.6 MHz (Peak detector, RBW: 50 kHz, VBW: 50 kHz)




Operation mode (TX on)	Channel / f_c [MHz]	P [dBm]
FDD	9538 / 1907.6	-20.60

5. Spurious radiated emissions

(FCC §22.917(a), §24.238(a), §2.1053, RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-334, DUT 13134
Accessories with DUT numbers	BL-5K, DUT 13173; HS-45, DUT 13155; AD-54, DUT 12914; AC-10E, DUT 13192
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Phone tested slide open and closed and MP3 positions.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	18 / 42 / 101.2
Date of measurements	13-Sep-2008
Measured by	Sami Lehtonen / Jouko Kaivonen

5.1. Test setup



5.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The substitution method is used. Substitution values at each frequencies are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. P_{SUBST_TX} is signal generator level, P_{SUBST_RX} is receiver level, L_{SUBST_CABLES} is cable losses including both TX and RX cables and $G_{SUBST_TX_ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P [dBm] = P_{MEAS} + A_{TOT}$$

Where P_{MEAS} is receiver reading in dBm and A_{TOT} is total correction factor including cable loss, preamplifier gain and substitution correction ($A_{TOT} = L_{CABLES} - G_{PREAMP} + A_{SUBST}$).

Limits for spurious radiated emissions measurements

Operation band	Frequency range [MHz]	Limit [dBm]
WCDMA 850	30 - 8500	-13
GSM 1900 / WCDMA 1700 / WCDMA 1900	30 - 18000	-13

5.3. GSM 850 Test results

GSM mode, channel 190 / 836.6 MHz

Frequency [MHz]	P [dBm]	P [μW]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
1673.143287	-37.00	0.19953	- 38.10	1.10	HORIZONTAL	PASSED
2509.820641	-38.10	0.15488	- 42.60	4.50	VERTICAL	PASSED
3346.189379	-53.60	0.00437	- 55.00	1.40	VERTICAL	PASSED

EGPRS mode, channel 190 / 836.6 MHz

Frequency [MHz]	P [dBm]	P [μW]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
1673.143287	-49.60	0.01096	- 50.70	1.10	HORIZONTAL	PASSED
2510.320641	-52.20	0.00603	- 56.70	4.50	VERTICAL	PASSED
3343.189379	-60.60	0.00087	- 61.90	1.30	VERTICAL	PASSED

5.4. GSM 1900 Test results

GSM mode, channel 661 / 1880.0 MHz

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
3760.023046	-46.00	0.02512	- 50.70	4.70	VERTICAL	PASSED
5640.278557	-49.60	0.01096	- 58.60	9.00	VERTICAL	PASSED
7521.050100	-48.40	0.01445	- 62.50	14.10	VERTICAL	PASSED

EGPRS mode, channel 661 / 1880.0 MHz

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
3760.023046	-46.60	0.02188	- 51.30	4.70	VERTICAL	PASSED
5640.778557	-52.70	0.00537	- 61.70	9.00	VERTICAL	PASSED
7524.550100	-48.20	0.01514	- 62.30	14.10	VERTICAL	PASSED

5.5. WCDMA 850 Test results

Channel 4175 / 835.0 MHz

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
1668.437876	-56.80	0.00209	- 58.20	1.40	HORIZONTAL	PASSED

5.6. WCDMA 1900 Test results

Channel 9400 / 1880.0 MHz

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Result
3761.523046	-54.70	0.00339	- 59.40	4.70	VERTICAL	PASSED
5643.790581	-50.70	0.00851	- 59.30	8.60	HORIZONTAL	PASSED
5655.810621	-53.00	0.00501	- 61.70	8.70	VERTICAL	PASSED
7516.534068	-47.20	0.01905	- 60.90	13.70	VERTICAL	PASSED

6. Test Equipment

6.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1742	EMI Test Receiver	ESMI	R&S	15C, 15B
1759	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
1872	Thermo- Hygrograph	00.02520.150700	Lambrecht	15C, 15B
1916	Radio Communication tester	CMTA84	R&S	15C, 15B
2039	Power Supply	PL330QMD	THURLBY	15C, 15B
2060	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
2068	CDN-Antenna line	S1	NMP	15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
2111	Multimeter	TX3	Tektronix	15C, 15B
2156	Digital Radio Communication Tester	CMU200	R&S	15C, 15B
2206	Signal generator	SMX	R&S	15C, 15B
2335	GPIO Switch 2 to 1	-	National Instruments	15C, 15B
2347	Digital Radio Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2352	Spectrum Analyzer	FSP	R&S	22/24/27, 15C
2359	Temperature Test system	VT4002	Vötsch Industrietechnik	22/24/27
2360	Serial Bus Converter	Serial 488A	IO Tech	22/24/27
2362	Power Supply	NGPX 70/5	R&S	22/24/27
2388	Bluetooth Tester	CBT	R&S	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B

6.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
1748	Log. per. Antenna	HL025	R&S	22/24/27, 15C
1749	Log. per. Antenna	HL025	R&S	22/24/27, 15C
1875	Thermo- Hygrograph	00.02520.150700	Lambrecht	22/24/27, 15C, 15B
1917	Radio Communication tester	CMTA84	R&S	22/24/27, 15C, 15B
1933	Precision half-wave dipole antennas	HZ-13	R&S	22/24/27, 15C
1938	Precision half-wave dipole antennas	HZ-12	R&S	22/24/27, 15C
2006	Radiation Reference Source	VSQ	MEB	22/24/27, 15C, 15B
2009	Signal generator	SMP 22	R&S	22/24/27, 15C, 15B
2019	Multimeter	34401A	HP	22/24/27, 15C, 15B
2027	Coupling and Decoupling Network	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	Coupling and Decoupling Network	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2029	Power Supply	PL330	THURLBY	22/24/27, 15C, 15B
2043	Band Reject Filter	WRCA824/849-0.2-6SS	Wainwright	22, 15C, 15B
2047	Band Reject Filter	WRCC1800/2000-0.2-10SS	Wainwright	24, 15C, 15B
2048	Band Reject Filter	WRCC1700/1800-0.2-10SS	Wainwright	27, 15C, 15B
2051	High Pass Filter	4HC1700-1-KK	R&S	22/24/27, 15C
2057	Log. per. Antenna	HL025	R&S	22/24/27, 15C
2109	Power Supply	PL330QMD	THURLBY	22/24/27, 15C, 15B
2110	Multimeter	34401A	HP	22/24/27, 15C, 15B
2112	Multimeter	TX3	Tektronix	22/24/27, 15C, 15B
2116	Controller	EMCO MODEL 2090	ETS	22/24/27, 15C, 15B
2133	Power Meter	NRVS	R&S	22/24/27, 15C
2134	Power Sensor	NRV-Z32	R&S	22/24/27, 15C
2135	Coupling and Decoupling Network	CDN 801-M3	LÜTHI	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
2138	Ultra Broadband Antenna	HL562	R&S	22/24/27, 15C, 15B
2140	Biconical Antenna	EMCO93110B	EMCO	22/24/27, 15C
2142	Log.-per.-dipol Antenna	3146	EMCO	22/24/27, 15C
2144	Attenuator	6803.17B	Huber-Suhner	22/24/27, 15C, 15B
2150	High Pass Filter	F-15041	RLC ELECTRONICS	22/24/27, 15C
2176	Coupling and Decoupling Network	CDN 801-M3	LÜTHI	22/24/27, 15C, 15B
2180	Digital Radio Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2188	Preamplifier	AFS4-00100300-20-23P-6	MITEQ	22/24/27, 15C, 15B
2330	EMI Test receiver	ESIB26	R&S	22/24/27, 15C, 15B
2334	GPIB Switch 2 to 1	-	National Instruments	22/24/27, 15C, 15B
2348	Yaesu controller	G-1000DXC	YAESU	22/24/27, 15C, 15B
2349	Computer controller (Yaesu)	GS-232B	YAESU	22/24/27, 15C, 15B
2350	Preamplifier	AMF-6D-020180-29-20P	MITEQ	22/24/27, 15C
2361	Anechoic chamber	3 meter semi/full anechoic chamber	Euroshield	22/24/27, 15C, 15B
2398	Horn antenna	HF906	R&S	22/24/27, 15C
2363	Band Reject Filter	WRCG 832/838-825/845/5SS	Wainwright	22/24/27
2364	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	22/24/27
2365	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2366	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
2384	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	22/24/27
2388	Bluetooth Tester	CBT	R&S	15C, 15B
-	RF Emission Software	ES-K1 v.1.71	R&S	22/24/27, 15C, 15B

Filename: Salo_FCC_0836_11.doc
Directory: T:\Projects\RM-334\EMC\Results\FCC
Template: T:\TCC_Nokia\Radio_Spectrum\EMC\Templates\Reports\FCC_Part22&24&27.dot
Title:
Subject:
Author: EMC_Salo2
Keywords:
Comments:
Creation Date: 04.09.2008 12:48:00
Change Number: 19
Last Saved On: 02.10.2008 13:15:00
Last Saved By: Lehtonen Sami
Total Editing Time: 5 193 Minutes
Last Printed On: 02.10.2008 13:16:00
As of Last Complete Printing
 Number of Pages: 37
 Number of Words: 5 730 (approx.)
 Number of Characters: 28 078 (approx.)