





# Test Report

Report No	EG1384-1
Client	Thing Magic 1 Broadway, 5th Floor Cambridge, MA 02142
Phone	617-758-4130
Fax	617-225-4410
FRN	0008403743
Model	M5
FCC ID	QV5MERCURY5
IC ID	5407A-MERCURY5
Equipment Type	Spread Spectrum Transmitter
Equipment Code	DSS
Emission Designator	350KA1D
Results	As detailed within this report
Prepared by	 Mairaj Hussain – Test Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	2/27/07
Conditions of issue	This Test Report is issued subject to the conditions stated in 'terms and conditions' section of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.

**Curtis-Straus** LLC • 527 Great Road • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



## Table of Contents

<i>Summary</i> .....	3
<i>Test Methodology</i> .....	3
<i>EUT Configuration</i> .....	4
<i>Radiated Spurious Emissions</i> .....	6
<i>Test Equipment Used</i> .....	10
FCC Requirements.....	14
<i>A2LA Accreditation</i> .....	19

## ***Summary***

This test report supports an application for class II permissive change for a transmitter operating under 47 CFR 15.247 and RSS210 Issue 6. The product is the Thing Magic M5 RF ID reader. It is a frequency hopper that operates in the range 902.75 – 927.25MHz. It utilizes a hopping table of 50 channels between channel 0 (902.75MHz) and channel 50 (927.25MHz) inclusively.

Class II permissive change is requested because Thing Magic intends to use the following new antenna with the product.

Manufacturer: MTi Wireless Edge Ltd  
Model #: MT-262010/TRLH/A/K  
Gain: 6dBi  
Frequency Range: 902 – 928MHz

## ***Test Methodology***

Testing is performed according to the procedures specified in ANSI C63.4 (2003). All testing was performed on a non conductive 80cm high table. Radiated spurious emissions were checked in restricted band around antenna pass band and up to 10<sup>th</sup> harmonic of the highest operating channel.

Frequency range investigated: 800MHz – 10GHz


Frequency Range	Distance
800MHz – 10GHz	3 m

The system employs 2 different cable lengths 6ft and 25ft. When using the 6ft cable the output power level is set to 30.9dB. When using the 20ft and 25ft cables the output power level is set to 32.5dB.

EUT antennas were maximized around their orthogonal axis. Peak and average readings were taken. If peak reading passed the average limits by more than 3db then average readings was not taken.

***EUT Configuration*****EUT Configuration****Work Order:** G1384**Company:** Thing Magic**Company Address:** 1 Broadway 5th Floor  
Cambridge, MA 02142**Contact:** Paul Franzosa**Person Present:** John Riley

	<b>MN</b>	<b>SN</b>		
<b>EUT:</b> Mercury 5		Test sample 1		
<b>EUT Description:</b> RF ID Reader				
<b>EUT Max Frequency:</b> 902.75MHz				
<b>Support Equipment:</b>	<b>MN</b>	<b>SN</b>		
Toshiba laptop	1805-5207	22021825PU		
EDA AC adapter	EA10603B	sample 1		
<b>EUT Cables:</b>	<b>Qty</b>	<b>Shielded?</b>	<b>Length</b>	<b>Ferrites</b>
Tx (coax)	1	Yes	25 ft and 6 ft	None
Rx (coax)	1	Yes	25 ft and 6 ft	None
DC power	1	No	3 ft	One
AC power	1	No	3 ft	None
Ethernet 1	1	No	6 ft	None
<b>Unpopulated EUT Ports:</b>	<b>Qty</b>	<b>Reason</b>		
Rx ports	3	Redundant		
Tx ports	3	Redundant		
dB-9	1	Setup and diagnostic		
<b>Software / Operating Mode Description:</b>				
Transmitting on either first or last channel.				



## Radiated Spurious Emissions

### LIMITS


“...radiated emissions which fall in the restricted bands, as defined in §15.209(a), must also comply with the radiated emission limits specified in §15.209(a)” [15.247(c)]  
 Furthermore, “...in any 100KHz band outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be 20dB below that in any 100KHz bandwidth within the band that contains the highest level of desired power, based on RF conducted or radiated measurement” [15.247(d)]

### MEASUREMENTS


The EUT was tested with the output at the port set to its highest power level 32.5dB, using the 20ft cable and a 6dBi antenna. This configuration would yield the highest spurious emissions outside the pass band 902.75-927.25MHz.

Plots below show compliance with band edge requirement


Antenna : MT-262010/TRLH/A/K




Vpk (First Channel)



Hpk (First channel)



Vpk (last channel)



Hpk (Last channel)

**Table 1**

Radiated Emissions Table								Curtis-Straus LLC							
Date: 16-Jan-07		Company: Thing Magic					Work Order: G1384								
Engineer: Mairaj Hussain															
Frequency Range: 800 - 1000MHz								Measurement Distance: 3 m							
Notes: Antenna: MT-262010/TRLH/A/K								EUT Max Freq: 927.25MHz							
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB $\mu$ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB $\mu$ V/m)				FCC Class B					
Hpk	960.0	27.5	20.5	22.1	4.7	33.8				Limit (dB $\mu$ V/m)					
										Margin (dB)					
										Result (Pass/Fail)					
<b>Table Result:</b> Pass by -12.2 dB								<b>Worst Freq:</b> 960.0 MHz							
Test Site: "T"			Pre-Amp: Green			Cable: EMIR-01			Analyzer: Blue						
								Antenna: Grn-Blk							

**Table 2**

Radiated Spurious Emissions Table								Curtis-Straus LLC							
Date: 16-Jan-07		Company: Thing Magic					Work Order: G1384								
Engineer: Mairaj Hussain															
Frequency Range: 1 - 10GHz								Measurement Distance: 3 m							
Notes: Antenna: MT-262010/TRLH/A/K w 25 ft cable								EUT Max Freq: 927.25MHz							
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB $\mu$ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB $\mu$ V/m)				FCC Class B					
Vpk	2281.2	57.2	39.6	29.9	3.0	50.5				Limit (dB $\mu$ V/m)					
Vavg	2281.2	41.0	39.6	29.9	3.0	34.3				Margin (dB)					
Vpk	2333.3	53.0	39.8	30.0	3.1	46.3				Result (Pass/Fail)					
Vpk	2498.4	50.0	39.3	30.3	3.2	44.2									
Hpk	4513.8	53.0	41.0	34.4	1.7	48.1									
Vpk	4513.8	53.5	41.0	34.4	1.7	48.6									
Vavg	3413.8	46.0	42.0	32.7	1.4	38.1									
Havg	4513.7	43.6	41.0	34.4	1.7	38.7									
<b>Table Result:</b> Pass by 7.7 dB								<b>Worst Freq:</b> 2333.3 MHz							
Test Site: "T"			Pre-Amp: Brown			Cable: EMIR-HIGH 9			Analyzer: Orange						
								Antenna: Black Horn							

**Table 3**

Radiated Spurious Emissions harmonics								Curtis-Straus LLC							
Date: 19-Jan-07		Company: Thing Magic					Work Order: G1384								
Engineer: Mairaj Hussain															
Frequency Range: 1 - 10GHz								Measurement Distance: 3 m							
Notes: With MT 262010/TRLH/A/K antenna & 6 ft cable Running at channel 1								EUT Max Freq: 927.25MHz							
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dB $\mu$ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dB $\mu$ V/m)				FCC Class B					
Vpk	2708.1	55.0	42.4	30.9	1.2	44.7				Limit (dB $\mu$ V/m)					
Vpk	3611.2	53.4	41.8	33.2	1.5	46.3				Margin (dB)					
Vpk	4514.0	52.3	41.0	34.4	1.7	47.4				Result (Pass/Fail)					
Vpk	5416.0	50.0	40.6	36.7	1.8	47.9									
<b>Table Result:</b> Pass by -6.1 dB								<b>Worst Freq:</b> 5416.0 MHz							
Test Site: "T"			Pre-Amp: Red-Gree			Cable: EMIR-HIGH-20			Analyzer: Orange						
								Antenna: Black Horn							

***Test Equipment Used***

REV. 12-JAN-2007

<b>SPECTRUM ANALYZERS / RECEIVERS</b>		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	9kHz-1.8GHz	8591E	Agilent	3441A03559	00024	I	08-JAN-2008	
WHITE	9kHz-22GHz	8593E	Agilent	3547U01252	00022	I	06-OCT-2007	
BLUE	9kHz-1.8GHz	8591E	Agilent	3223A00227	00070	I	18-DEC-2007	
YELLOW	9kHz-2.9GHz	8594E	Agilent	3523A01958	00100	I	05-JUN-2007	
GREEN	9kHz-26.5GHz	8593E	Agilent	3829A03618	00143	I	05-SEP-2007	
BLACK	9kHz-12.8GHz	8596E	Agilent	3710A00944	00337	I	08-DEC-2007	
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	2504A05219	00030	I	07-FEB-2007	
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	1750A03418	00558	1	23-MAY-2007	
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	1750A02762	01067	I	01-MAR-2007	
ORANGE	9kHz-26.5GHz	E4407B	Agilent	US39440975	00394	I	18-DEC-2007	
BROWN (RENTAL)	9kHz-26.5GHz	E4407B	Agilent	SG44210511	Rental	1	05-FEB-2007	
EMI TEST RECEIVER	20-1000MHz	ESVS30	R&S	827957/001	01098	I	27-OCT-2008	
RENTAL 7405A	100Hz-26.5 GHz	E7405A	Agilent	MY44212795	Rental	1	28-DEC-2007	
<b>LISNs/MEASUREMENT PROBES</b>		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	956348	00753	II	05-MAY-2007	
BLUE (DC)	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	956349	00752	II	05-MAY-2007	
YELLOW-BLACK	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	984735	00248	II	05-MAY-2007	
ORANGE	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	903707	00754	II	05-MAY-2007	
GOLD (DC)	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	984734	00247	II	05-MAY-2007	
BROWN	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411656	00986	II	05-MAY-2007	
GREEN	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411657	00987	II	08-MAY-2007	
YELLOW	10kHz-30MHz	8012-50-R-24-BNC	SOLAR	0411658	1080	II	05-MAY-2007	
WHITE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972019	00678	II	05-MAY-2007	
BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972017	00675	II	05-MAY-2007	
RED-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972016	00677	II	05-MAY-2007	
BLUE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972018	00676	II	05-MAY-2007	
BLUE MONITORING PROBE	0.01-150MHz	91550-2	TEGAM	12350	00807	I	26-MAY-2007	
YELLOW MONITORING PROBE	0.01-150MHz	91550-2	ETS	50972	00493	I	23-JAN-2008	
GREEN CURRENT TRANSFORMER	40Hz-20MHz	150	PEARSON	10226	00793	I	07-APR-2007	
BLUE CISPR LINE PROBE	150kHz-30MHz	N/A	C-S	N/A	00805	II	08-JUN-2007	
BLACK CISPR LINE PROBE	150kHz-30MHz	N/A	C-S	N/A	NONE	II	08-JUN-2007	
CISPR TELCO VOLTAGE PROBE	10kHz-30MHz	CS A/C-10	C-S	CS01	00296	II	17-NOV-2007	
CISPR 22 TELCO ISN	9kHz-30MHz	FCC-TLISN-T4	FISCHER	20115	00746	I	15-NOV-2007	
<b>OPEN AREA TEST SITES (OATS)</b>		FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE		
SITE F		93448	IC 2762A-1	R-1688	II	04-APR-2007		
SITE T		93448	IC 2762A-2	R-905	II	14-AUG-2007		
SITE A		93448	IC 2762-A	R-903	II	13-AUG-2007		
SITE M		93448	IC 2762-M	R-904	II	19-MAR-2007		
SITE J		93448	IC 2762A-3	R-2377	II	11-APR-2008		
<b>CONDUCTED TEST SITES (MAINS / TELCO)</b>		FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE		
EMI 1		93448	N/A	C-1801, T-268	III	NA		
EMI 2		93448	N/A	C-1802, T-269	III	NA		
EMI 3		93448	N/A	C-1803, T-270	III	NA		
<b>MIXERS/DIPLEXERS</b>		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	2332A01695/A046903-01	1087	I	23-AUG-2007	
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	3003A07825/A046903-01	1086	I	19-SEP-2007	
MIXER / HORN	40-60 GHz	M19HW/A	OML	U30110-1	00821	I	02-MAR-2007	
MIXER	33-50 GHz	11970Q	HP	3003A03155	00104	I	08-NOV-2007	
MIXER / HORN	50-75 GHz	11970V/QWH-VRPROO	HP/QUINSTAR	2521A01197/8794001	1179	I	15-NOV-2007	
MIXER	75-110 GHz	11970W	HP	2521A01334	00105	I	22-NOV-2007	
MIXER / HORN	60-90 GHz	M12HW/A	OML	E30110-1	00822	I	03-MAR-2007	
MIXER / HORN	90-140 GHz	MO8HW/A	OML	F21206-1	00811	I	03-MAR-2007	
MIXER / HORN	140-220 GHz	MO5HW/A	OML	G21206-1	00812	II		
DIPLEXER	40-220 GHz	DPL.26	OML	N/A	00813	I	03-MAR-2007	

ABSORBING CLAMPS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
FISCHER CLAMP	30-1000MHz	F-201-23MM	FISCHER	10	00081	I	20-JAN-2008
HARMONIC & FLICKER ANALYZER	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
HFTS 10001I/2 AC POWER SYSTEM	HP6842A (2) 500I	HP CALIFORNIA INSTRUMENTS	3531A-00169 HK53687/HK53688	00738 00376	II II	30-DEC-2007 09-JAN-2008	
PREAMPS / ATTENUATORS / FILTERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.10-2000MHz	ZFL-1000-LN	C-S	N/A	00798	II	28-JUL-2007
BLUE	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00759	II	20-JUL-2007
BLUE-BLACK	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00800	II	OUT OF SERVICE
GREEN	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00802	II	21-DEC-2007
BLACK	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00799	II	20-JUL-2007
ORANGE	0.01-2000MHz	ZFL-1000-LN	C-S	N/A	00765	II	21-DEC-2007
WHITE	1-20GHz	SMC-12A	C-S	426643	00760	II	22-JUL-2007
BROWN	1-20GHz	PM2-38-218-4R5-17-15-SFF	C-S	PL1655	1132	II	14-APR-2007
YELLOW-BLACK	1-20GHz	SMC-12A	C-S	535055	00801	II	22-JUL-2007
RED-GREEN	1-20GHz	PM2-38-218-4R5-17-15-SFF	C-S			II	14-AUG-2007
HF (YELLOW)	18-26.5GHz	AFS4-18002650-60-8P-4	C-S	467559	00758	II	23-AUG-2007
HIGH PASS FILTER	1-18 GHz	SPA-F-55204	K&L	36	00817	II	05-JAN-2008
LOW PASS FILTER	1-9 GHz	11SL10-4100/X4400-O/O	K&L	4	00816	II	05-JAN-2008
HF 20dB 50W ATTENUATOR	0.03-20 GHz	PE 7019-20	PASTERNACK	01	00791	II	10-MAY-2007
HF 30dB 50W ATTENUATOR	0.03-20 GHz	PE 7019-30	PASTERNACK	02	1168	II	10-MAY-2007
40dB 100W ATTENUATOR	0.09-4000MHz	BW-40N100W+	MINI-CIRCUITS	V N014900638	1231	II	08-NOV-2007
LOW FREQ LPF	10-100kHz	L200K1G1	MICROWAVE CIRCUITS	4460-01 DC0432	1019	II	OUT OF SERVICE
LOW FREQ LPF	10-100kHz	L200K1G1	MICROWAVE CIRCUITS	4777-01 DC0434	1088	II	OUT OF SERVICE
ANTENNAS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
GREEN BILOG	30-2000MHz	CBL6112B	CHASE	2742	00620	II	13-JAN-2008
GREEN-BLACK BILOG	30-2000MHz	CBL6112B	CHASE	2412	00127	II	13-JAN-2008
GREEN-RED BILOG	30-2000MHz	CBL6112B	CHASE	2435	00990	I	12-APR-2008
BLUE BILOG	30-1000MHz	3143	EMCO	1271	00803	II	06-MAY-2007
GRAY BILOG	20-2000MHz	3141	EMCO	9703-1038	00066	II	06-MAY-2007(EMI) / 30-JUN-2007(RFI)
YELLOW-BLACK BILOG	20-2000MHz	CBL6140A	CHASE	1112	00126	II	06-MAY-2007(EMI) / 01-MAY-2007(RFI)
RED-WHITE BILOG	30-2000MHz	JB1	SUNOL	A091604-1	01105	I	07-NOV-2008
RED-BLACK BILOG	30-2000MHz	JB1	SUNOL	A091604-2	01106	I	20-OCT-2008
RED-BROWN BILOG	30-2000MHz	JB1	SUNOL	A0032406	1218	I	04-AUG-2008
YELLOW HORN	1-18GHz	3115	EMCO	9608-4898	00037	I	27-MAY-2007(EMI) / 18-MAY-2007 (RFI)
BLACK HORN	1-18GHz	3115	EMCO	9703-5148	00056	I	17-JUN-2007
ORANGE HORN	1-18GHz	3115	EMCO	0004-6123	00390	I	09-JUN-2007
HF (WHITE) HORN	18-26.5GHz	801-WLM	WAVELINE	00758	00758	I	26-AUG-2007
SMALL LOOP	10kHz-30MHz	PLA-130/A	ARA	1024	00755	I	22-FEB-2008
LARGE LOOP	20Hz-5MHz	6511	EMCO	9704-1154	00067	I	23-JAN-2008
ACTIVE MONPOLE	30Hz-30MHz	3301B	EMCO	3824	00068	II	06-DEC-2007
INDUCTION COIL	50-60Hz	1000-4-8	C-S	N/A	00778	II	26-SEP-2007
ADJUSTABLE DIPOLE	30-1000MHz	3121C	EMCO	1370	00757	I	26-OCT-2008
ADJUSTABLE DIPOLE	30-1000MHz	3121C	EMCO	1371	00756	I	09-NOV-2008
RE101 LOOP SENSOR	30Hz-100kHz	RE101-13.3CM	C-S	N/A	00818	II	13-MAR-2007
RS101 RADIATING LOOP	30Hz-100kHz	RS101-12CM	C-S	N/A	00819	II	13-MAR-2007
RS101 LOOP SENSOR	30Hz-100kHz	RS101-4CM	C-S	N/A	00820	II	13-MAR-2007
EFT	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
EFT DIRECT COUPLING CAP	N/A	C-S	01	00794	II	06-FEB-2008	
ESD GENERATORS	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
GREEN	NSG435	SCHAFFNER	000839	00763	I	25-OCT-2007	
RED	NSG435	SCHAFFNER	001625	00762	I	06-FEB-2007	
NSG-438 RENTAL	NSG438	SCHAFFNER	292	5265	I	04-APR-2007	
YELLOW	930D	ETS	201	00673	I	18-AUG-2007	

MULTIFUNCTIONING SYSTEMS		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
BLUE BESTEMC-2	711-1100	SCHAFFNER	199824-002SC	00117	II		OUT FOR SERVICE	
RED BESTEMC-2	711-1100	SCHAFFNER	200122-074SC	00623	II		31-MAR-2007 (SURGE / D+I) / 07-APR-2007 (EFT)	
MODULA 6000		SCHAFFNER		DEMO	II		09-JAN-2008 (SURGE) / 10-JAN-2008 (EFT)	
EMC PRO		KEYTEK	0005292	RENTAL	II		04-JAN-2008 (SURGE)	
USC 500-M	USC 500 M6B	EMTEST	V0616101357	DEMO	II		09-JAN-2008 (SURGE)	
CHAMBERS AND STRIPLINE		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
RFI 1 CHAMBER	3 METER COMPACT		PANASHIELD	N/A	00797	II	01-MAY-2007	
RFI 2 CHAMBER	04' x 07' SHIELDING SYSTEM		LINDGREN	13329	00795	II	30-JUN-2007	
RFI 3 STRIPLINE	N/A		C-S	N/A	00796	III	NA	
ENVIRONMENTAL (SAFETY)	ECL5		B-M-A INC.	2041	00029	I	11-JAN-2007	
ENVIRONMENTAL (SAFETY)	SGTH-31S		B-M-A INC.	2245	00321	I	11-JAN-2007	
AMPLIFIERS		RANGE	MN	MFR	SN	ASSET	CALIBRATION DUE	
RED	0.5-1000MHz	10W1000B	AR	18708	00032	II	26-APR-2007 (RF1)	
GREEN	0.5-1000MHz	10W1000B	AR	23423	00123	II	13-APR-2007 (RF1)	
BLUE	0.01-250MHz	75A250	AR	19165	00039	II	03-NOV-2007 (NEBS & EU CRFI)	
BLACK	0.01-250MHz	75A250	AR	23411	00122	II	29-DEC-2007 (NEBS & EU CRFI)	
ORANGE	0.01-250MHz	75A250	AR	26827	00367	II	29-DEC-2007 (NEBS & EU CRFI) / 01-MAY-2007 (RF1)	
BROWN 150W	0.1-250MHz	150A250	AR	313454	RENTAL	II	30-JUN-2007 (RF1)	
GTC 1-2.6	1.0-2.6 GHz	GRF5016A	GTC	1221	RENTAL	II	18-MAY-2007	
HUGHES 10W	2.0-4.0GHz	1177H01	HUGHES	055	RENTAL	II	18-MAY-2007	
HUGHES 10W	4.0-8.0GHz	8010H02F	HUGHES	240	RENTAL	II	18-MAY-2007	
HUGHES 10W	8-10.0GHz	80108	HUGHES	138	RENTAL	II	18-MAY-2007	
HP495A	7.0-10.0GHz	HP495A	HP	304-00237	00086	II	OUT OF SERVICE (SPARE)	
AUDIO AMP	AUDIO FREQ	MPA-200	RADIO SHACK	700438	NONE	III	NA	
AUDIO AMP	AUDIO FREQ	MPA-200	RADIO SHACK	708545	00862	III	NA	
FIELD PROBES		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.01-1000MHz	HI-4422	HOLADAY	90369	00031	I	01-MAR-2007	
GREEN	0.01-1000MHz	HI-4422	HOLADAY	97363	00136	I	25-JUL-2007	
BLUE	0.01-1000MHz	HI-4422	HOLADAY	95696	01100	I	25-MAR-2007	
MICROWAVE SURVEY METER	2450MHz	HI-1501	HOLADAY	00075464	1244	I	09-JAN-2008	
SIGNAL GENERATORS		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.09-2000MHz	HP8648B	Agilent	3847U02192	00366	I	28-FEB-2007	
BLUE	0.1-1000MHz	HP8648A	Agilent	3426A00548	00034	I	23-AUG-2007	
GREEN	0.09-2000MHz	HP8648B	Agilent	3623A02072	00125	I	16-OCT-2007	
ORANGE	0.1-1000MHz	HP8648B	Agilent	3537A01210	00025	I	29-JUN-2007	
BROWN	0.01Hz-15MHz	HP33120A	Agilent	US36016621	1211	I	OUT OF SERVICE	
WHITE	0.01Hz-15MHz	HP33120A	Agilent	US36048143	1219	I	10-MAY-2007	
BROWN-WHITE	0.01Hz-15MHz	HP33120A	Agilent	SG40019842	1232	I	10-NOV-2007	
BLUE-WHITE	0.1Hz-13MHz	HP3312A	Agilent	1432A07632	00775	I	11-MAR-2007	
SWEEPER	0.01-20.0GHz	HP83752A	Agilent	3610A01133	00087	II	02-MAY-2007	
AM/FM STEREO SIG. GEN.	0.1-170MHz	LG3236	LEADER	3687301	00959	I	10-OCT-2008	
IMPULSE GENERATOR	1-100Hz	CIG-25	ELECTRO-METRICS	290	00942	I	05-AUG-2007	
BULK INJECTION CLAMPS		RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
GREEN (NEBS CRFI)	0.01-100MHz	95236-1	ETS	50215	00118	II	03-NOV-2007(BLUE AMP) 29-DEC-2007(ORANGE & BLK)	
GREEN (EU CRFI)	0.10-100MHz	95236-1	ETS	50215	00118	II	03-NOV-2007(BLUE AMP) 29-DEC-2007(ORANGE & BLK)	
RED (NEBS CRFI)	0.01-100MHz	95236-1	ETS	34026	1020	II	07-NOV-2007(BLUE AMP) 29-DEC-2007(ORANGE & BLK)	
RED (EU CRFI)	0.10-100MHz	95236-1	ETS	34026	1020	II	06-NOV-2007(BLUE AMP) 02-JAN-2008(ORANGE & BLK)	
RENTAL	2 - 450MHz	9142-1N	SOLAR	008508	RENTAL	II	10-AUG-2007	
ANSI T1.315		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
SBC NOISE CART		C-S				III	CALIBRATION NOT REQUIRED	
SBC TRANSIENT CART		C-S				III	WAVESHAPE VERIFIED BEFORE USE	
OSCILLOSCOPES		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE	
EMC 100MHz	TDS 220	TEKTRONIX		C036986	1166	I	28-AUG-2007	
ESD REFERENCE 1GHz	TDS 684B	TEKTRONIX		B011287	RENTAL	1	31-MAR-2007	
PRODUCT SAFETY 100 MHz	TDS 340	TEKTRONIX		B012357	00737	I	03-OCT-2007	
TELECOM 100 MHz	54645A	HP/AGILENT		US36320452	00103	I	30-JUN-2007	

CDN NETWORKS	RANGE	MN	MFR	ASSET	CAT	CALIBRATION DUE	
BLUE	0.10-100MHz	20A M-3	C-S	00806	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
RED	0.10-100MHz	15A M-3	C-S	00780	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
YELLOW-BLACK	0.10-100MHz	15A M-3	C-S	00784	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
GREEN	0.10-100MHz	30A M-3	C-S	00779	II	03-NOV-2007 (BLUE AMP)	04-AUG-2007 (ORANGE & BLK AMP)
YELLOW	0.10-100MHz	30A M-5	C-S	00804	II	03-NOV-2007 (BLUE AMP)	05-APR-2007 (ORANGE) 15-MAR-2007 (BLK)
BROWN	0.10-100MHz	M-3	C-S	1169	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
BROWN-WHITE	0.10-100MHz	M-3	C-S	1170	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
BROWN-BLACK	0.10-100MHz	M-2 (DC)	C-S	1171	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
RED-BLACK	0.10-100MHz	M-2 (DC)	C-S	1177	II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
GREEN-WHITE	0.10-100MHz	M-2 (DC)	C-S		II	03-NOV-2007 (BLUE AMP)	29-DEC-2007 (ORANGE & BLK AMP)
YELLOW (RES)	0.10-100MHz	100Ω RESISTOR	C-S	00810	II	04-NOV-2007 (BLUE AMP)	06-NOV-2007 (ORANGE) 02-JAN-2008 (BLK)
GREEN (RES)	0.10-100MHz	100Ω RESISTOR	C-S	1172	II	03-NOV-2007 (BLUE AMP)	06-NOV-2007 (ORANGE) 02-JAN-2008 (BLK)
RMS VOLTMETERS/CURRENT CLAMP		MN	MNFR	SN	ASSET	CAT	CALIBRATION DUE
TRUE-RMS MULTIMETER	79III	FLUKE	71700298	00769	I		27-OCT-2007
TRUE RMS MULTIMETER	179	FLUKE	89280616	1228	I		31-OCT-2007
TRUE-RMS MULTIMETER (REFERENCE)	177	FLUKE	83390024	00973	I		21-MAR-2007
TRUE-RMS MULTIMETER	177	FLUKE	83390025	00974	I		10-MAR-2007
TRUE-RMS MULTIMETER (TELECOM)	177	FLUKE	83430419	00975	I		21-MAR-2007
SURGE GENERATORS		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
TRANSIENT WAVEFORM MONITOR	TWM-5	CDI	003982	00323	II		05-JUN-2007
UNIVERSAL SURGE GENERATOR	M5	CDI	003966	00324	II		OUT OF CAL
THREE PHASE COUPLING NWK	3CN	CDI	003455	00325	II		OUT OF CAL
1.2X50US PLUGIN MODULE	1.2x50US PLUGIN	CDI	N/A	00842	II		OUT OF CAL
10x1600US PLUGIN MODULE	10x1600US PLUGIN	C-S	N/A	00843	II		08-JUN-2007
10x5600US PLUGIN MODULE	10x5600US PLUGIN	C-S	N/A	00841	II		08-JUN-2007
PSURGE CONTROLLER MODULE	PSURGE 8000	HAEFELY	150267	00879	II		06-JUN-2007
COUPLING/DECOPUPLING MODULE	PCD 900	HAEFELY	149213	00880	II		06-JUN-2007
IMPULSE MODULE	PIM 900	HAEFELY	149202	00881	II		06-JUN-2007
HIGH VOLTAGE CAP NWK 5kVDC, 18μF	CS-HVCC	C-S	01	00772	II		14-JUN-2008
NEBS SURGE GENERATOR	N/A	C-S	N/A	00088	II		18-OCT-2007
2x10US SURGE GENERATOR	2x10US	C-S	N/A	00846	II		06-JUN-2007
10x700US SURGE GENERATOR	10x700US	C-S	N/A	00847	II		08-JUN-2007
12 PAIR SURGE RESISTOR MODULE	N/A	C-S	N/A	00768	II		18-OCT-2007
VSS 500-M	TSS 500 M12 S2	EMTEST	V0502100032	1155	II		
TSS 500-M	TSS500 M10	EMTEST	V0502100031	1156	II		
SCHAFFBER 2050 1.2x50 GENERATOR	2050	SCHAFFNER		DEMO	II		09-JAN-2008
POWER/NOISE METERS		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
POWER METER	435B	HP	2445A11012	00773	I		12-APR-2007
POWER METER	437B	HP	2912A01367	01099	I		12-APR-2007
POWER SENSOR	8481A	HP	2702A61351	00774	I		12-APR-2007
PSOPHOMETER	2429	BRUEL & KJAER	1237642	00585	II		14-FEB-2007
TRANSMISSION LINE TESTER (dBRNC)	185T	AMREL	998658	00823	II		16-MAR-2007
OVERVOLTAGE CHAMBERS		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
72kW POWER FAULT SIMULATOR	OV1	C-S	N/A	00792	II		31-MAR-2007
POWER FAULT SIMULATOR	OV2	C-S	N/A	00116	II		31-MAR-2007
DIPOLE TAPE MEASURES		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
26FT TAPE #1	2338CME	LUFKIN	C3166-1	00776	I		13-MAR-2007
26FT TAPE #2	2338CME	LUFKIN	C3166-2	00777	I		13-MAR-2007
METEOROLOGICAL METERS		MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
TEMP./HUMIDITY/ATM. PRESSURE GAUGE	7400 PERCEPTION II	DAVIS	N/A	00965	II		08-FEB-2007
TEMPERATURE /HUMIDITY GAUGE	THG-912	HUGER	4000562	00789	I		01-FEB-2007
WEATHER CLOCK (PRESSURE ONLY)	BA928	OREGON SCIENTIFIC	C3166-1	00831	I		02-FEB-2007
CONSUMABLES		SPEC.	MFR	STOCK/MN	ASSET	CAT	CALIBRATION DUE
NEBS CHEESECLOTH	26-28M/KG	ED&D	ACC-01	N/A	III		N/A
NEBS CARBON BLOCK	3-MIL-GAP 1KV SURGE	RELIABLE	3AB	N/A	III		N/A

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

## FCC Requirements

### Required Equipment Authorization for Device Type

Type of Device	Equipment Authorization Required
TV broadcast receiver	Verification
FM broadcast receiver	Verification
CB receiver	Declaration of Conformity or Certification
Superregenerative receiver	Declaration of Conformity or Certification
Scanning receiver	Certification
All other receivers subject to part 15	Declaration of Conformity or Certification
TV interface device	Declaration of Conformity or Certification
Cable system terminal device	Declaration of Conformity
Stand-alone cable input selector switch	Verification
Class B personal computers and peripherals	Declaration of Conformity or Certification
CPU boards and internal power supplies used with Class B personal computers	Declaration of Conformity or Certification
Class B personal computers assembled using authorized CPU boards or power supplies	Declaration of Conformity
Class B external switching power supplies	Verification
Other Class B digital devices & peripherals	Verification
Class A digital devices, peripherals & external switching power supplies	Verification
All other devices	Verification

### FCC Required labeling for Verified Devices 47 CFR Part 15.19

Verified devices must have the following label permanently affixed in a location accessible to the user:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

No distinction is made between Class A or Class B devices on the label.

When the device is so small or for such use that it is not practicable to place label on it, the information may be shall be placed in a prominent location in the instruction manual supplied to the user or, alternatively, shall be placed on the container in which the device is marketed.


Where a device is constructed in two or more sections connected by wires and marketed together, the label is only required to be affixed to the main control unit.

**FCC Required Labeling for Class B Personal Computers and Peripherals Devices  
47 CFR Part 15.19 subject to Declaration of Conformity**


Personal computers and peripherals subject to authorization under a Declaration of Conformity shall be labeled as follows:

(1) The label shall be located in a conspicuous location on the device and shall contain the unique identification described in Section 2.1074 and the following logo:

(i) If the product is authorized based on testing of the product or system:



(ii) If the product is authorized based on assembly using separately authorized components and the resulting product is not separately tested:



(2) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (b)(1) of this section on it, such as for a CPU board or a plug-in circuit board peripheral device, the text associated with the logo may be placed in a prominent location in the instruction manual or pamphlet supplied to the user. However, the unique identification (trade name and model number) and the logo must be displayed on the device.

(3) The label shall not be a stick-on, paper label. The label on these products shall be permanently affixed to the product and shall be readily visible to the purchaser at the time of purchase, as described in Section 2.925(d). "Permanently affixed" means that the label is etched, engraved, stamped, silk-screened, indelibly printed, or otherwise permanently marked on a permanently attached part of the equipment or on a nameplate of metal, plastic, or other material fastened to the equipment by welding, riveting, or a permanent adhesive. The label must be designed to last the expected lifetime of the equipment in the environment in which the equipment may be operated and must not be readily detachable.

**FCC Required Instruction Manual Inserts CFR 47 Part 15.21 and 15.105**

The user's manual must caution the user that changes or modifications not expressly approved by the manufacturer could void the user's FCC granted authority to operate the equipment. In addition the following information should be inserted:

(a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

*Note: this equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications.*

*Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.*

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

*Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:*

- *Reorient or relocate the receiving antenna.*
- *Increase the separation between the equipment and receiver.*
- *Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.*
- *Consult the dealer or an experienced radio/TV technician for help.*

(c) The provisions of paragraphs (a) and (b) of this section do not apply to digital devices exempted from the technical standards under the provisions of § 15.103.

(d) For systems incorporating several digital devices, the statement shown in paragraph (a) or (b) of this section needs to be contained only in the instruction manual for the main control unit.

## Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "**BUREAU VERITAS**," "**BUREAU VERITAS CONSUMER PRODUCTS SERVICES**," "**BVCPs**," "**MTL**," "**ACTS**," "**MTL-ACTS**" and **CURTIS-STRAUS** (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST

ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

Rev.160009121(2)\_#684340 v13CS

## A2LA Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025-1999		Immunity	
<p>CURTIS-STRAUS<sup>1</sup> 527 Great Road Littleton, MA 01460 Barry Quinlan Phone: 978-486-8880 ELECTRICAL</p>		RRL No. 2005-130 (December 27, 2005) EN 61000-4-2; AS/NZS 61000.4.2; KN61000-4-2 EN 61000-4-3; AS/NZS 61000.4.3; KN61000-4-3 EN 61000-4-4; AS/NZS 61000.4.4; KN61000-4-4 EN 61000-4-5; AS/NZS 61000.4.5; KN61000-4-5 EN 61000-4-6; AS/NZS 61000.4.6; KN61000-4-6 EN 61000-4-8; AS/NZS 61000.4.8; KN61000-4-8 EN 61000-4-11; KN61000-4-11 EN 61000-2-2	
Valid until: July 31, 2007		Certificate Number: 1627.01	
In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Telecommunications, and Product Safety tests:		Family Product or Industry Specific Specifications including emissions and/or immunity GR-1089-CORE; GR-78-CORE (ESD) EN50081-1; EN50081-2; EN50082-2; EN50082-1; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 50091-2; EN 55024; CISPR 24 EN 55103-1; EN 55103-2; EN 61326; EN 61547; EN 50130-4; EN 50083-2; EN 60601-1-2; EN 60601-2-2; EN 60601-2-4; EN 60601-2-32; EN 60601-2-38; EN 60601-2-47; IEC 1800-3; EN 61800-3; EN 55020; CISPR 20; EN 60555 Part 2; EN 60555 Part 3; ETS 300 386-1; EN 300 386-2; EN 300 386; ETS 300 132-1; ETS 300 132-2; EN 60669-2-1; AS/NZS 3200.1.2; CNS 13783-1; ETR 283; C62.41	
Electromagnetic Compatibility (EMC) Radiated emissions testing (electric and magnetic fields)*; Conducted emissions testing (voltage and current)*; Electrostatic Discharge testing*; Electrical Fast Transient testing*; Radiated Immunity testing*; Conducted Immunity testing*; Lightning Immunity testing*; Voltage Dips*, Interrupts and Voltage Variations testing*; Magnetic Immunity testing*; RF Power measurements*; Frequency Stability Measurements*; Longitudinal Induction measurements*; Harmonic emissions testing*; Light flicker testing*; Low frequency disturbance voltage testing*; Disturbance Power measurements*; Power Cross Overvoltage testing*;		Radiocommunications EU R&TTE Radio Standards; EN 300 220-1; EN 300 220-3; EN 300 330-1; EN 300 330-2; EN 300 440-1; EN 300 440-2; EN 300 328; EN 300 385; EN 301 893	
Emissions Radiated and Conducted Emissions FCC 47 CFR Parts 15 & 18; C63.4; CISPR 22; EN5022; SABS CISPR 22; AS/NZS CISPR 22; AS/NZS 3548; Canada ICES-003; CNS13439; KN 22 (RRL No. 2005-82, September 29, 2005); CISPR 11; EN 55011; SABS CISPR 11; AS/NZS CISPR 11; AS/NZS 2064; Canada ICES-001; CNS13803; CISPR 13; EN 55013; SABS CISPR 13; AS/NZS CISPR 13; AS/NZS 1053; CISPR 14-1; EN 55014-1; SABS CISPR 14; AS/NZS CISPR 14; AS/NZS 1044; CNS 13439; CISPR 15; EN 55015; GR-1089-CORE; CSA C108.8-M1983;		EU R&TTE EMC Standards EN 301 339; EN 301 489-01; EN 301 489-03; EN 301 489-17	
Harmonics EN 61000-3-2; AS/NZS 61000.3.2		Canada Radio Standards RSS-102; RSS-117; RSS-118; RSS-119; RSS-123; RSS-125; RSS-128; RSS-129; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-136; RSS-137; RSS-138; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-187; RSS-188; RSS-191; RSS-192; RSS-193; RSS-195; RSS-210; RSS-212; RSS-213; RSS-215; RSS-243; RSS-GEN; RSS- 310; GL-36	
Flicker EN 61000-3-3; AS/NZS 61000.3.3		Australia/New Zealand Radio Standards AS/NZS 4268; AS/NZS 4771; RFS29; Radiocommunications (Data Transmission Equipment Using Spread Spectrum Modulation Techniques); Radiocommunications (Spread Spectrum Devices); Radiocommunications (Short Range Devices); Radiocommunications (Low Interference Potential Devices);	
1 Note: This accreditation covers testing performed at the laboratory listed above and the satellite facility located at 168 Ayer Rd, Littleton, MA 01460 and, for test types marked with an asterisk, at other sites as defined in "A2LA specific criteria for the accreditation of site testing and site calibration laboratories."		(A2LA Cert. No. 1627.01) 3/27/06 Page 1 of 10	
(A2LA Cert. No. 1627.01) 3/27/06 Page 1 of 10		(A2LA Cert. No. 1627.01) 3/27/06 Page 2 of 10	
Other Radio Standards RTTE 01 (DGT-Taiwan);		Telecommunications Telecommunications Registration; General test methods; Lightning surge*; Drop testing*; Balance testing*; Signal power (metallic and longitudinal)*; Frequency measurements*; Pulse templates*; Leakage testing*; Impedance testing*; Hearing Aid Compatibility testing (excluding volume control)*; Protocol analysis* and Jitter testing*.	
FCC Standards and Test methods Support TCB Status-- FCC Scope A – Unlicensed Radio Frequency Devices		Telecom Standards North American standards FCC 47 CFR Part 68 Telephone Terminal Equipment CS-03 Issue 9	
A1 1. 47 CFR Parts 11, 15 and 18 2. FCC MP-5. 3. ANSI C63.4-2003,		Title Connection of terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility.	
A2 1. 47 CFR Part 15, 2. ANSI C63.4-2003,		TIA/EIA TSB31-B 1998 TIA-968-A, A1, A2, A3	
A3 1. 47 CFR Part 15, 2. ANSI C63.17-1998, 3. ANSI C63.4-2003,		Title Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)	
A4 1. 47 CFR Part 15, 2. ANSI C63.4-2003,		TIA/EIA TSB31-B 1998 TIA-968-A, A1, A2, A3	
FCC Scope B – Licensed Radio Service Equipment		Title Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network Technical Requirements for SHDSL, HDSL2, HDSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry	
B1 1. 47 CFR Parts 2, 22, 24, 25, and 27 2. ANSI/TIA-603-C (2004)		AS/ACIF S016-2001	
B2 1. 47 CFR Parts 2, 22, 74, 90, 95, and 97 2. ANSI/TIA-603-C (2004)		AS/ACIF S031-2001	
B3 1. 47 CFR Parts 2, 80, and 87 2. ANSI/TIA-603-C (2004)		AS/ACIF S038-2001	
B4 1. 47 CFR Parts 2, 21, 74, and 101 2. ANSI/TIA-603-C (2004)		AS/ACIF S043-2001	
Country Specific Standards and Other		Australia standards AS/ACIF S002-2001	
ITU EMC Standards K.20; K.21; K.41; K.44		AS/ACIF S016-2001	
Swedish EMC Standards BAKOM 3336.3		AS/ACIF S031-2001	
South African EMC Standards other then CISPR equivalents		AS/ACIF S038-2001	
Hong Kong EMC Standards HKTA 1006; HKTA 1007; HKTA 1008; HKTA 1010; HKTA 1015; HKTA 1026; HKTA 1035; HKTA 1039; HKTA 1041; HKTA 1042; HKTA 1045		AS/ACIF S043-2001	
Singapore EMC Standards IDA TS SRD; IDA TS EMC		International standards ITU-T G.703	
Japanese VCCI Standards VCCI V-3, VCCI V-4		Hong Kong standards HKTA 2011	
(A2LA Cert. No. 1627.01) 3/27/06		HKTA 2014	
Page 3 of 10		(A2LA Cert. No. 1627.01) 3/27/06	
Page 3 of 10		Page 4 of 10	

<b>Telecom Standards</b>		
HKTA 2028	<b>Title</b> Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 1544 kbit/s	<b>European standards (cont'd)</b> TBR 21: 1998
HKTA 2029	Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 2048 kbit/s	Terminal Equipment (TE); Attachment requirements for pan-European approval for connection to the Analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signalling
HKTA 2030	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using Digital Leased Circuits at nx64 kbit/s	Business TeleCommunications (BTC); 34 Mbit/s Digital Unstructured and structured leased lines (D34U and D34S); Attachment requirements for Terminal equipment interface
HKTA 2031	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using Digital Leased Circuits below 64 kbit/s	Asymmetric Digital Subscriber Line Terminal Equipment and POTS Splitter Technical Specifications
HKTA 2032	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Networks in Hong Kong using Asymmetric Digital Subscriber Lines (ADSL) based on ITU-T Recommendation G.992.1	DS1 Equipment Type Approval Guidelines
HKTA 2033	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Fixed Telecommunications Networks in Hong Kong using Splitterless Asymmetric Digital Subscriber Lines (ADSL) based on ITU-T Recommendation G.992.2	ISDN Terminal Equipment Technical Specifications
<b>European standards</b>		Technical Specifications for Terminal Equipment for Connection to Public Switched Telephone Network
TBR 1: 1995	Attachment requirements for terminal equipment to Be connected to circuit switched data networks and Leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including, 1 984 kbit/s	Requirements for Connection of Customer Equipment to Analogue Lines
TBR 2: 1997	Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations X.21 and X.21 bit Integrated Services Digital Network (ISDN);	Requirements for Bandwidth Management Devices
TBR 3: 1995 + Amdt : 1997	Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access Integrated Services Digital Network (ISDN);	Telecom 2048 kbit/s Standard Network Interface
TBR 4: 1995 + Amdt : 1997	Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U); Attachment requirements for terminal equipment	Interim arrangements for ADSL CPE
TBR 012: 1993 + Amdt : 1996	Business TeleCommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface	
TBR 013: 1996		
(A2LA Cert. No. 1627.01) 3/27/06	Page 5 of 10	(A2LA Cert. No. 1627.01) 3/27/06
<b>Product Safety</b>		
General test methods:		
Power input*, Permanence of marking*, Accessibility*, Permissibly limits*, Energy hazard measurement*, SELV circuits*, TNV limits*, Limited current*, Capacitor Discharge / voltage limitation*, Ring signal*, Humidity conditioning*, Creepage / Clearance / Distance thru Insulation (excluding CTI)*, Limited power measurement*, Ground Bond/Earthing*, Ground continuity*, Temperature*, Stability*, Applied force*, Steel sphere impact*, Mold stress*, Battery reverse current*, Ball pressure*, Leakage current*, Component abnormal*, Electric strength*, Impulse*, Overvoltage*, Acoustic sound pressure*, 130mm / 20mm flame*, Needle flame*, Hot flaming oil*, Locked rotor/motor armature*, Vibration, Bump, Drop*, Strain relief*, Torque*, Insulation resistance*, Sound level*, Handle loading*, Liquid overflow*, Spillage*, Liquid leakage*, Transformer shorts/overloads*, Rain test*, Wall mount*, Laser radiation (excluding x-ray)*, Voltage surge*, Functionality*, Protective impedance abnormal*, Capacitor short circuit abnormal*, Output abnormal*, Multi-supply abnormal*, Cooling abnormal*, Heating device abnormal*, Interlock abnormal*, Rigidity*, Cleaning*		
<b>Product Safety Standards</b>	<b>Title</b>	
<b>Specific Product Safety Standards</b>		
UL 60950 2000	Safety of information technology equipment	<b>Title</b> Classification, requirements and user's guide.
IEC 60950 1999	Safety of information technology equipment	Safety of laser products – Part 2: Safety of optical communication systems
EN 60950 2000	Safety of information technology equipment, including Electrical business equipment.	Safety of laser products – Part 4: Laser guards
IEC 60950-1 2001		Performance standard for laser products
UL 60950-1 2003		Safety of household and similar electrical appliances
CSA C22.2 No. 60950-00		Part 1: General requirements
CSA C22.2 No. 60950-1 03		
IEC 61010-1 1993		
EN 61010-1 1993, 2001	Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements.	Electrical equipment for laboratory use; part 1: General requirements
IEC 61010-1 2001	Safety requirements for electrical equipment for measurement, control and laboratory use, Part 1: General requirements.	Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements
UL 61010B-1 2003		Safety information technology equipment
CAN/CSA 1010-1 1999 (Including AM 2)		Information Technology Equipment – Safety – Part 1: General Requirements
IEC 60601-1 1995	Electrical equipment for laboratory use Part 1: General requirements.	Information Technology Equipment – Safety – General requirements
EN 60601-1 1995 (Including AM 2)	Medical electrical equipment. Part 1: General requirements for safety.	Electrical Equipment for Measurement, Control and Laboratory Use; Part 1: General Requirements
UL 2601-1 1997	Medical electrical equipment.	Medical Electrical Equipment, Part 1: General Requirements for Safety
IEC 60065 1998, 2000	Medical electrical equipment. Part 1: General Requirements for safety.	Medical Electrical Equipment - Part 1: General Requirements For Safety 1: Collateral Standard: Safety Requirements For Medical Electrical Systems
ANSI/UL 6500: 1998	Medical electrical equipment. Part 1: General Requirements for safety.	Medical Electrical Equipment - Part 1: General Requirements For Safety 2: Medical Electrical Equipment
CAN/CSA 60065-00	Medical electrical equipment. Part 1: General Requirements for safety.	Requirements For Safety – Section 1-1, Collateral Standard: Safety Requirements For Medical Electrical Systems
AS/NZS 60065 2000	Audio, video and similar electronic apparatus – Safety requirements	Audio, Video and Similar Electronic Apparatus – Safety Requirements
Canadian C22.2 No. 1-94 (1-98) 1994, 1998	Audio, video and similar electronic apparatus	Audio, Video and Similar Electronic Apparatus – Safety Requirements
EN 60065 1994	Consumer and commercial products	Safety of Machinery – Electrical Equipment of Machines – Part 1: Specification for General Requirements
IEC 60825 1990	Safety requirements for main operated electronic and related apparatus for household and similar general use.	Compliance Test Specification – Safety and Electrical Protection Requirements for Subscriber Equipment
EN 60825-1 1994	Radiation safety of laser products, equipment	Connected to the Public Telecommunications Networks
	Classification, requirements and user's guide	
	Safety of laser products Part 1: equipment	
(A2LA Cert. No. 1627.01) 3/27/06	Page 7 of 10	(A2LA Cert. No. 1627.01) 3/27/06



<i>Environmental Simulation</i>		
<u>Test Technology</u>	<u>Test Standard</u>	<u>Supporting Standards</u>
Accessibility*	IEC 60529	IP-0x thru IP-6x
Acoustic Noise*	GR-63-CORE Sec 4.6	
Airborne Contaminants	GR-63-CORE Sec 4.5	MFG & Hygroscopic Dust
Altitude	GR-63-CORE Sec 4.1.3	
Cold Start*	ETS 300 019	IEC 60068-2-1
Drip	IEC 60529	IP-x1 & IP-x2
Drops*	ETS 300 019	IEC 60068-2-32
Dust	GR-63-CORE Sec 4.3	
Firearms Resistance Testing	IEC 60529	IP-5x & IP-6x
Fire Resistance	GR-487	
Heat Dissipation*	ANSI/TI.319	
Illumination	GR-63-CORE Sec 4.2	Fire & Needle Flame
Operational Temperature & Humidity (OpTH)*	GR-63-CORE Sec 4.1.4	
	GR-63-CORE Sec 4.7	
	ETS 300 019	IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-56
		GR-63-CORE Sec 4.1.2
Salt Fog & Spray	ASTM B117	
Spatial*	GR-63-CORE Sec 2.0 & 3.0	
Spraying-Splashing	IEC 60529	IP-x3 & IP-x4
Storage (Temperature & Humidity)*	ETS 300 019	IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-56
Vibration	GR-63-CORE Sec 4.1.1	
	ETS 300 019	IEC 60068-2-6 IEC 60068-2-27 IEC 60068-2-29 IEC 60068-2-32 IEC 60068-2-57 IEC 60068-2-64
Water Immersion	GR-63-CORE Sec 4.4	Earthquake, Office & Transportation
Water Jet	IEC 60529	IP-x7 & IP-x8
	IEC 60529	IP-x5 & IP-x6

(A2LA Cert. No. 1627.01) 3/27/06

Page 9 of 10

Note 1. For standards or methods listed on the scope of accreditation without a revision date, laboratories are expected to be competent in the use of the current version within one year of the date of publication of the standard test method or upon the date specified by the standard test method originator when the originator has implementation authority. When a superseded standard or method is required for an accredited test, the scope will include the superseded date/version. For those that support the TCB/CB status of the organization acting as a certifier on behalf of the FCC or IC the expectation is currency within 30 days of Federal Register publication of changes for FCC and 30 days after IC website update. This note shall not be construed as an Accreditation Body implication to adopt a more current standard than is required in a regulation or code (i.e. the legal requirement) which is adopted by the lab under their responsibility.

\* On-site test service is available for this technology, test, or method.

(A2LA Cert. No. 1627.01) 3/27/06

Page 10 of 10