

CERTIFICATION TEST REPORT

In Accordance With: FCC Part 15 Subpart C, 15.249
IC RSS-210 Issue 7 June 2007

Applicant: SMK Electronics Corp. USA
1055 Tierra Del Rey
Chula Vista, CA 91910

Equipment Under Test : ZWAVE Remote
Model: ZAGG

FCC ID: QVEZW4U2
IC: 3683B-ZW4U2

Tested By: Nemko USA Inc.
11696 Sorrento Valley Road, Suite F
San Diego, CA 92121

Test Report: 2010 03146433 FCCTX
Date: March 18, 2010
Project number: 40427-1
Nex Number: 146433

Total Number of Pages: 15

Section 1. Summary of Test Results

General

All measurements are traceable to national standards

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15; Subpart C. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

The assessment summary is as follows:

Apparatus Assessed:	ZWAVE Remote
Model:	ZAGG
Specification:	FCC Part 15 Subpart C, 15.249 IC RSS-210 Issue 7 June 2007
Date Received in Laboratory:	March 17, 2010
Compliance Status:	Complies
Exclusions:	None
Non-compliances:	None

Nemko USA, Inc.

FCC ID: QVEZW4U2

IC: 3683B-ZW4U2

11696 Sorrento Valley Road, Suite F, San Diego, CA 92121

Phone (858) 755-5525 Fax (858) 452-1810

Report Number: 2010 03146433 FCCTX

Specification: FCC Part 15 Subpart C, 15.249

Report Release History

REVISION	DATE	COMMENTS	
-	March 18, 2010	Prepared By:	Alan Laudani
-	March 18, 2010	Initial Release:	Alan Laudani

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025.

Nemko USA Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

TESTED BY:  Date: March 18, 2010
Alan Laudani, EMC Test Engineer



TABLE OF CONTENTS

Section 1. Summary of Test Results.....	2
Report Release History	3
Section 2: Equipment Under Test.....	5
2.1 Product Identification.....	5
2.2 Samples Submitted for Assessment.....	5
2.3 Theory of Operation	6
2.4 Technical Specifications of the EUT	6
Section 3: Test Conditions	7
3.1 Specifications	7
3.2 Deviations From Laboratory Test Procedures	7
3.3 Test Environment.....	7
3.4 Test Equipment	8
Section 4: Observations	9
4.1 Modifications Performed During Assessment.....	9
4.2 Record Of Technical Judgements.....	9
4.3 EUT Parameters Affecting Compliance	9
4.4 Tests Deleted	9
4.5 Additional Observations	9
Section 5: Results Summary.....	10
5.1 Results Summary.....	10
Appendix A: Test Results.....	1
Power line Conducted Emissions / Receiver or Stand-by Mode	1
Occupied Bandwidth	2
Duty Cycle Test.....	4
Field Strength of Emissions	5
Emissions radiated outside of the band	5
Receiver Spurious Emissions	8
APPENDIX B	1
B. Radiated Emissions Measurement Uncertainties.....	1
APPENDIX C	1
C. Nemko USA, Inc. Test Equipment & Facilities Calibration Program.....	1
APPENDIX D	3
D. NVLAP Accreditation	3

Section 2: Equipment Under Test

2.1 Product Identification

The Equipment Under Test for compliance with FCC Part 15.249 was identified as follows:

EUT:	ZWAVE Remote
Model:	ZAGG
Serial Number:	11

2.2 Samples Submitted for Assessment

The following samples of the apparatus have been submitted for type assessment:

DEVICE	MANUFACTURER MODEL # SERIAL #	POWER CABLE
EUT - ZWAVE Remote	SMK Electronics Corp. USA Model: ZAGG Serial #: 11	

CONNECTION	I/O CABLE
No connections	None - wireless



2.3 Theory of Operation

The **ZAGG** is a ZWAVE Remote to be used as a remote control. The ZAGG works at one frequency, 908.4 MHz. A keypad is reviled when it is slipped out. A designated test unit was provided for with continuous transmitting. As a handheld device, it was tested in all three axes and with the keypad open and closed.

The EUT's performance during test was evaluated against the performance criterion specified by applicable test standards. Performance results are detailed in the test results section of this report.

2.4 Technical Specifications of the EUT

Manufacturer: SMK Electronics Corp. USA

Operating Frequency: 908.4MHz in the 902 to 928 MHz Band

Number of Operating Frequencies: 1

Measured Field Strength: 85.6 dB μ V/m at 3m
or 19 mV/m

Modulation: GFSK

Emissions Designator: 148KF1D

Antenna Data: Trace on circuit board

Antenna Connector: None

Power Source: 2 AAA batteries, 3.0 VDC

Section 3: Test Conditions

3.1 Specifications

The apparatus was assessed against the following specifications:

FCC Part 15 Subpart C, 15.249

Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0-24.25 GHz bands.

IC RSS-210 Issue 7 June 2007

Low-power Licence-exempt Radio-communication Devices (All Frequency Bands): A2.9

IC RSS-Gen Issue 2 June 2007

General Requirements and Information for the Certification of Radio-communication Equipment

3.2 Deviations From Laboratory Test Procedures

No deviations from Laboratory Test Procedure

3.3 Test Environment

All tests were performed under the following environmental conditions:

Temperature range	16 – 20 °C
Humidity range	60-66 %
Pressure range	86 - 106 kPa

3.4 Test Equipment

Nemko ID	Device	Manufacturer	Model	Serial Number	Cal Date	Cal Due Date
110	Antenna, LPA	Electrometrics	LPA-25	1217	1/10/2009	2/10/2011
116	Antenna, Bicon	EMCO	3110	1267	11/12/2008	11/12/2010
317	Preamplifier	HP	8449A	2749A00167	4/16/2009	4/16/2010
835	Spectrum Analyzer	Rohde & Schwarz	RHDFSEK	829058/005	3/31/2009	3/31/2010
877	Antenna, DRG Horn, .7-18GHz	AH Systems	SAS-571	688	7/28/2008	7/28/2010

Registration of the OATS are on file with the Federal Communications Commission, under Registration Number 90579, the VCCI under registration number R-3027, and are also registered with Industry Canada under Site Numbers 2040B-1 and 2040B-2.



Section 4: Observations

4.1 Modifications Performed During Assessment

No modifications were performed during assessment.

4.2 Record Of Technical Judgements

No technical judgements were made during the assessment.

4.3 EUT Parameters Affecting Compliance

The user of the apparatus could not alter parameters that would affect compliance.

4.4 Tests Deleted

No Tests were deleted from this assessment.

4.5 Additional Observations

There were no additional observations made during this assessment.



Section 5: Results Summary

This section contains the following:

FCC Part 15 Subpart C: §15.249
IC RSS-210 Issue 7 June 2007 A2.9
IC RSS-Gen Issue 2 June 2007

The column headed "Required" indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

N No: not applicable / not relevant
Y Yes: Mandatory i.e. the apparatus shall conform to these tests.
N/T Not Tested, mandatory but not assessed. (See section 4.4 Test deleted)

The results contained in this section are representative of the operation of the apparatus as originally submitted.

5.1 Results Summary

FCC	Industry Canada	Test Description	Required	Result
15.107 (a)	RSS-Gen 7.2.2	Power line Conducted Emissions – Receive or Stand-by Mode	N	
15.207 (a)	RSS-Gen 7.2.2	Power line Conducted Emissions -- Transmit Mode	N	
15.215 (c)	RSS-Gen 4.6.1	Occupied Bandwidth	Y	Pass
		Duty Cycle Test	Y	Pass
15.249 (a)	RSS-Gen 4.8 & 4.9 & RSS-210 A2.9	Field Strength of Emissions	Y	Pass
15.249 (d)	RSS-Gen 4.9 & RSS-210 A2.9	Spurious Emissions Outside of the band	Y	Pass
15.209 (a)		Fixed Point-to-Point Operation	N	
15.249 (b)				
15.107 (a)	RSS-Gen 4.10 RSS-Gen 7.2.3	Receiver Spurious Emissions	Y	Pass

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A1 of 11

Appendix A: Test Results

Power line Conducted Emissions / Receiver or Stand-by Mode

RSS-Gen

Table 2 - AC Power Lines Conducted Emission Limits

Frequency range (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Test Conditions:

Sample Number:		Temperature:	
Date:		Humidity:	
Modulation State:		Tester:	
		Laboratory:	

Test Parameters:

Peak RBW: 100kHz VBW: 100kHz

Quasi-Peak: RBW 9kHz, VBW 30 kHz

Average: RBW 9kHz, VBW 30 kHz

Quasi-Peak Limit Blue Line, Average Limit Green Line

Test Results: EUT Not tested, battery operated device

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A2 of 12

Occupied Bandwidth

4.6.1 Occupied Bandwidth

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

Clause 15.215(c); Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Conditions:


Sample Number:	11	Temperature:	°C
Date:	3-17-2010	Humidity:	%
Modulation State:	Modulated	Tester:	Alan Laudani
Laboratory:			SOATS

Test Results: 148 kHz

- Span is wide enough to capture the channel transmission
- RBW is 1% of the span
- VBW is 3X RBW
- Sweep is auto
- Detector is Peak
- Trace is Max Hold
- A peak output max hold reading was taken, a display line was drawn 20 dB lower than peak level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

Nemko USA, Inc.11696 Sorrento Valley Road, Suite F, San Diego, CA 92121
Phone (858) 755-5525 - Fax (858) 452-1810

DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A3 of 13



Date: 17.MAR.2010 08:56:15

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A4 of 14


Duty Cycle Test

Test Conditions:

Sample Number:	11	Temperature:	17°C
Date:	3-1-2010	Humidity:	70%
Modulation State:	w/ modulation	Tester:	Alan Laudani
		Laboratory:	SOATS

Test Results: The modulation is Frequency Shift Keying

Duty cycle = 100%



Date: 17.MAR.2010 09:14:15

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A5 of 15

Field Strength of Emissions

15.249(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency (MHz)	Field strength of fundamental (mV/meter)	Field strength of harmonics (uV/meter)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

Emissions radiated outside of the band

15.249 (d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Sec. 15.209, whichever is the lesser attenuation.

Test Conditions:

Sample Number:	11	Temperature:	17°C
Date:	3-17-2010	Humidity:	40%
Modulation State:	w/ modulation	Tester:	Alan Laudani
			Laboratory: SOATS

Test Results:

See Table. EUT complies for fundamental power, band edges and spurious emissions.

Additional Observations:

- The Spectrum was searched from 30 MHz to the 10th Harmonic (9084 MHz), but no emissions within 20 dB of the limits were evident.
- All Measurements below 1 GHz were performed at 3m employing a CISPR quasi-peak detector
- Peak measurements above 1 GHz utilize a RBW of 1 MHz and a VBW of 3 MHz
- Measurements were made after installing fresh batteries.
- The RF module was investigated in three axes, with the keyboard open and closed
- As Occupied BW = 148 kHz, to ensure output power is captured, RBW > OBW, used 200 kHz RBW, VBW = 300 kHz. Peak Hold measurements.
- Band edge emission measurements were taken against ambients and/or noise floor. The single channel emission does not effect band edges.

Nemko USA, Inc.11696 Sorrento Valley Road, Suite F, San Diego, CA 92121
Phone (858) 755-5525 - Fax (858) 452-1810

DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A6 of 16

ERP Power Calculations:

Limit = 50 mV/m

Measured Peak reading 57.1 dBuV + antenna factor 23.4 dB/m + Cable loss 5.1 dB =
corrected average reading = 85.6 dBuV/m

$$10^{((85.6-120)/20)} = 0.019 \text{ V/m, or } 19 \text{ mV/m}$$

"Telepoartall" was engineering sample model number, Client updated it to "Zagg".

Radiated Emissions Data

Job #:	40427-1	Date :	3-17-2010	Page	1	of	1
NEX #:	146433	Time :	0900				
		Staff :	aal				
Client Name :	SMK Electronics Corp. USA			EUT Voltage :	3		
EUT Name :	ZWAVE Remote			EUT Frequency :	VDC		
EUT Model #:	Telepoartall			Phase:			
EUT Serial #:	11			NOATS			
EUT Config.:	FSK	Test mode, continuous transmit		SOATS	X		
		fresh batteries		Distance < 1000 MHz:	3 m		
				Distance > 1000 MHz:	3 m		
Specification :	CFR47 Part 15.249, Part 15.209						
Loop Ant. #:	NA						
Bicon Ant. #:	NA			Temp. (°C) :	17		
Log Ant. #:	110	3m		Humidity (%) :	40		
DRG Ant. #	877			Spec Analyzer #:	835		
Cable LF#:	SOATS			Analyzer Display #:	835		
Cable HF#:	SOATS			Quasi-Peak Detector #:	NA		
Preamp LF#:	826			Preselector #:	NA		
Preamp HF#	317						

Meas. Freq. (MHz)	Meter Reading Vertical	Meter Reading Horizontal	Det.	EUT Side F/L/R/B	Ant. Height m	Max. Reading (dB μ V)	Corrected Reading (dB μ V/m)	Spec. limit (dB μ V/m)	CR/SL Diff. (dB)	Pass Fail	Comment
908.4	45.6	46.2	P	-	1.5	46.2	74.7	114.0	-39.3	Pass	back open
908.4	50.8	44.8	P	-	1.0	50.8	79.3	114.0	-34.7	Pass	side open
908.4	48.3	51.0	P	-	1.0	51.0	79.5	114.0	-34.5	Pass	upright open
908.4	57.1	51.6	P	-	1.1	57.1	85.6	114.0	-28.4	Pass	upright closed
908.4	51.6	53.4	P	-	1.0	53.4	81.9	114.0	-32.1	Pass	side closed
908.4	51.8	54.8	P	-	1.0	54.8	83.3	114.0	-30.7	Pass	back closed
902.0	22.8	22.9	Q	-	1.0	22.9	19.3	46.0	-26.7	Pass	band edge
928.0	22.9	23.1	Q	-	1.0	23.1	19.5	46.0	-26.5	Pass	band edge
											no emissions present

HAND HELD DEVICE; MEASURED IN 3 AXES
 DEVICE TRANSMITS WITH KEYBOARD OPEN AND CLOSED
 BAND WIDTH 148 kHz SO MEASURED WITH RBW > 148 kHz, 200 kHz

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A7 of 17

Fixed Point-to-Point Operation

15.249 (b) Fixed, point-to-point operation as referred to in this paragraph shall be limited to systems employing a fixed transmitter transmitting to a fixed remote location. Point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information are not allowed. Fixed, point-to-point operation is permitted in the 24.05–24.25 GHz band subject to the following conditions:

- (1) The field strength of emissions in this band shall not exceed 2500 millivolts/meter.
- (2) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.001\%$ of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.
- (3) Antenna gain must be at least 33 dBi. Alternatively, the main lobe beamwidth must not exceed 3.5 degrees. The beamwidth limit shall apply to both the azimuth and elevation planes. At antenna gains over 33 dBi or beamwidths narrower than 3.5 degrees, power must be reduced to ensure that the field strength does not exceed 2500 millivolts/meter.

Test Conditions:

Sample Number:		Temperature:	
Date:		Humidity:	
Modification State:		Tester:	Alan Laudani
		Laboratory:	Nemko

Test Results: Not Applicable, EUT is not Point-to-Point.

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A8 of 18

Receiver Spurious Emissions

The following receiver spurious emission limits shall be complied with: If a radiated measurement is made, all spurious emissions shall comply with the limits of Table 1.

Table 1 - Spurious Emission Limits for Receivers

Spurious Frequency (MHz)	Field Strength (microvolt/m at 3 metres)
30-88	100
88-216	150
216-960	200
Above 960	500

Test Conditions:

Sample Number:	11	Temperature:	17°C
Date:	3-17-2010	Humidity:	40%
Modulation State:	Standby / receive	Tester:	Alan Laudani
			Laboratory:
			SOATS

Test Results:

See Table. EUT complies for stand by and receive spurious emissions.

Additional Observations:

- The Spectrum was searched from 30 MHz to the 5th Harmonic (4542 MHz), but no emissions within 20 dB of the limits were evident.

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A1 of 19

APPENDIX B

B. Radiated Emissions Measurement Uncertainties

1. Introduction

ISO/IEC 17025:2005 and ANSI/NCSL Z540.3: 2006 require that all measurements contained in a test report be "traceable". "Traceability" is defined in the *International Vocabulary of Basic and General Terms in Metrology* (ISO: 1993) as: "the property of the result of a measurement... whereby it can be related to stated references, usually national or international standards, through an unbroken chain of comparisons, *all having stated uncertainties*".

The purposes of this Appendix are to "state the *Measurement Uncertainties*" of the conducted emissions and radiated emissions measurements contained in Section 5 of this Test Report, and to provide a practical explanation of the meaning of these measurement uncertainties.

2. Statement of the Worst-Case Measurement Uncertainties for the Conducted and Radiated Emissions Measurements Contained in This Test Report

Table 1: Worst-Case Expanded Uncertainty "U" of Measurement for a k=2 Coverage Factor

Radiated Emissions Measurement Detection Systems	Applicable Frequency Range	"U" for a k=2 Coverage Factor
Spectrum Analyzer with QPA & Preamplifier	30 MHz - 200 MHz	+3.9 dB, -4.0 dB
Spectrum Analyzer with QPA & Preamplifier	200 MHz-1000 MHz	+/- 3.5 dB
Spectrum Analyzer with Preamplifier	1 GHz - 18 GHz	+2.5 dB, -2.6 dB
Spectrum Analyzer with Preamplifier	18 GHz - 40 GHz	+/- 3.4 dB

NOTES:

1. Applies to 3 and 10 meter measurement distances
2. Applies to all valid combinations of Transducers (i.e. LISNs, Line Voltage Probes, and Antennas, as appropriate)
3. Excludes the Repeatability of the EUT

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	A2 of 20

3. Practical Explanation of the Meaning of Radiated Emissions Measurement Uncertainties

In general, a “Statement of Measurement Uncertainty” means that with a certain (specified) confidence level, the “true” value of a measurand will be between a (stated) upper bound and a (stated) lower bound.

In the specific case of EMC Measurements in this test report, the measurement uncertainties of the conducted emissions measurements and the radiated emissions measurements have been calculated in accordance with the method detailed in the following documents:

- ANSI Z540.2 (2002) *Guide to the Expression of Uncertainty in Measurement*
- NIS 81:1994, *The Treatment of Uncertainty in EMC Measurements* (NAMAS, 1994)
- NIST Technical Note 1297(1994), *Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results* (NIST, 1994)

The calculation method used in these documents requires that the stated uncertainty of the measurements be expressed as an “expanded uncertainty”, U , with a $k=2$ coverage factor. The practical interpretation of this method of expressing measurement uncertainty is shown in the following example:

EXAMPLE: Assume that at 39.51 MHz, the (measured) radiated emissions level was equal to +26.5 dBuV/m, and that the +/- 2 standard deviations (i.e. 95% confidence level) measurement uncertainty was +/- 3.4 dB.

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	C1 of 21

APPENDIX C

C. Nemko USA, Inc. Test Equipment & Facilities Calibration Program

Nemko USA, Inc. operates a comprehensive Periodic Calibration Program in order to ensure the validity of all test data. Nemko USA's Periodic Calibration Program is fully compliant to the requirements of NVLAP Policy Guide PG-1-1988, ANSI/NCSL Z540.3: 2006, ISO 10012:2003, ISO/IEC 17025:2005, and ISO-9000: 2000. Nemko USA, Inc.'s calibrations program therefore meets or exceeds the US national commercial and military requirements [N.B. ANSI/NCSL Z540.1-1994 replaced MIL-STD-45662A].

Specifically, all of Nemko USA's *primary reference standard devices* (e.g. vector voltmeters, multimeters, attenuators and terminations, RF power meters and their detector heads, oscilloscope mainframes and plug-ins, spectrum analyzers, RF preselectors, quasi-peak adapters, interference analyzers, impulse generators, signal generators and pulse/function generators, field-strength meters and their detector heads, etc.) and certain *secondary standard devices* (e.g. RF Preamplifiers used in CISPR 11/22 and FCC Part 15/18 tests) are periodically recalibrated by:

- A Nemko USA-approved independent (third party) metrology laboratory that uses NIST-traceable standards and that is ISO Guide 25-accredited as a calibration laboratories by NIST; or,
- A Nemko USA-approved independent (third party) metrology laboratory that uses NIST-traceable standards and that is ISO Guide 25-accredited as a calibration laboratory by another accreditation body (such as A2LA) that is mutually recognized by NIST; or,
- A manufacturer of Measurement and Test Equipment (M&TE), if the manufacturer uses NIST-traceable standards and is ISO Guide 25-accredited as calibration laboratory either by NIST or by another accreditation body (such as A2LA) that is mutually recognized by NIST; or
- A manufacturer of M&TE (or by a Nemko USA-approved independent third party metrology laboratory) that is not ISO Guide 25-accredited. (In these cases, Nemko USA conducts an annual audit of the manufacturer or metrology laboratory for the purposes of proving traceability to NIST, ensuring that adequate and repeatable calibration procedures are being applied, and verifying conformity with the other requirements of ISO Guide 25).

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE	DOCUMENT NAME	DOCUMENT #	PAGE
March 18, 2010	SMK Electronics Corp. USA - ZAGG - EMC Test Report	2010 03146433 FCCTX	C2 of 22

In all cases, the entity performing the Calibration is required to furnish Nemko USA with a calibration test report and/or certificate of calibration, and a "calibration sticker" on each item of M&TE that is successfully calibrated.

Calibration intervals are normally one year, except when the manufacture advises a shorter interval or if US Government directives or client requirements demand a shorter interval. Items of instrumentation/related equipment which fail during routine use, or which suffer visible mechanical damage (during use or while in transit), are sidelined pending repair and recalibration. (Repairs are carried out either in-house [if minor] or by a Nemko USA-approved independent [third party] metrology laboratory, or by the manufacturer of the item of M&TE).

Each antenna used for CISPR 11 and CISPR 22 and FCC Part 15 and Part 18 radiated emissions testing (and for testing to the equivalent European Norms) is calibrated annually by either a NIST (or A2LA) ISO Standard 17025-Accredited third-party Antenna Calibration Laboratory or by the antenna's OEM if the OEM is NIST or A2LA ISO Standard 17025-accredited as an antenna calibration laboratory. The antenna calibrations are performed using the methods specified in Annex G.5 of CISPR 16-1(2003) or ANSI C63.5-2004, including the "Three-Antenna Method". Certain other kinds of antennas (e.g. magnetic-shielded loop antennas) are calibrated annually by either a NIST (or A2LA) ISO Standard 17025-accredited third-party antenna calibration laboratory, or by the antenna's OEM if the OEM is NIST or A2LA ISO Standard 17025-accredited as an antenna calibration laboratory using the procedures specified in the latest version of SAE ARP-958.

In accordance with FCC and other regulations, Nemko USA recalibrates its suite of antennas used for radiated emissions tests on an annual basis. These calibrations are performed as a precursor to the FCC-required annual revalidation of the Normalized Site Attenuation properties of Nemko USA's Open Area Test Site. Nemko USA, Inc. uses the procedures given in both Sub clause 16.6 and Annex G.2 of CISPR 16-1 (2003), and, ANSI C63.4-2003 when performing the normalized site attenuation measurements.

Nemko USA, Inc.		11696 Sorrento Valley Road, Suite F, San Diego, CA 92121 Phone (858) 755-5525 - Fax (858) 452-1810	
DATE March 18, 2010	DOCUMENT NAME SMK Electronics Corp. USA - ZAGG - EMC Test Report	DOCUMENT # 2010 03146433 FCCTX	PAGE D3 of 23

APPENDIX D

D. NVLAP Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200116-0

Nemko USA, Inc. - San Diego EMC Division
San Diego, CA


*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).*

2009-01-01 through 2009-12-31
Effective dates




For the National Institute of Standards and Technology

NVLAP-01C (REV. 2006-09-13)