

## TABLE OF CONTENTS

APPLICANT: ENGINEERED AUDIO, LLC

FCC ID: QWB-AUR1000

### TEST REPORT CONTAINING:

PAGE 1-4.....TEST EQUIPMENT LIST  
PAGE 5.....TEST PROCEDURE  
PAGE 6.....RADIATION INTERFERENCE TEST DATA  
PAGE 7.....OCCUPIED BANDWIDTH DATA  
PAGE 8-9.....OCCUPIED BANDWIDTH PLOTS  
PAGE 10.....POWER LINE CONDUCTED EMISSIONS  
PAGE 11-12.....POWER LINE CONDUCTED PLOTS

### EXHIBITS CONTAINING:

EXHIBIT 1.....CONFIDENTIALITY LETTER  
EXHIBIT 2.....BLOCK DIAGRAM  
EXHIBIT 3.....SCHEMATIC  
EXHIBIT 4.....INSTRUCTION MANUAL  
EXHIBIT 5.....LABEL SAMPLE  
EXHIBIT 6.....LABEL LOCATION  
EXHIBIT 7.....EXTERNAL PHOTOGRAPHS  
EXHIBIT 8.....INTERNAL PHOTOGRAPHS  
EXHIBIT 9.....CIRCUIT DESCRIPTION  
EXHIBIT 10.....TEST SET UP PHOTOGRAPH

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

TABLE OF CONTENTS LIST

## EMC Equipment List

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	3-Meter OATS	TEI	N/A	N/A	Listed 1/13/03	1/13/06
	3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
	Receiver, Beige Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03
	RF Preselector	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
	Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 8/31/01	8/31/03
X	Receiver, Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/15/03	4/15/05
X	RF Preselector	HP	85685A	2926A00983	CAL 4/15/03	4/15/05
X	Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/15/03	4/15/05
	Receiver, Silver/Grey Tower Spectrum Analyzer	HP	8566B Opt 462	3552A22064 3638A08608	CAL 10/14/02	10/14/04
	RF Preselector	HP	85685A	2620A00294	CAL 10/14/02	10/14/04
	Quasi-Peak Adapter	HP	85650A	3303A01844	CAL 10/14/02	10/14/04
	Preamplifier	HP	8449B	3008A01075	CHAR 1/28/02	1/28/04
X	Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
	Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
	Biconnical Antenna	Eaton	94455-1	1057	CAL 3/18/03	3/18/05
	BiconiLog Antenna	EMCO	3143	9409-1043		
X	Log-Periodic Antenna	Electro-Metrics	LPA-25	1122	CAL 10/2/01	10/2/03
	Log-Periodic Antenna	Electro-Metrics	EM-6950	632	CHAR 10/15/01	10/15/03
	Log-Periodic Antenna	Electro-Metrics	LPA-30	409	CAL 3/4/03	3/4/05
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/21/01	3/21/04
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	153	CAL 9/26/02	9/26/05

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 1 of 12

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
Double-Ridged Horn Antenna	Electro-Metrics	RGA-180	2319	CAL 2/17/03	2/17/05
Horn Antenna	Electro-Metrics	EM-6961	6246	CAL 3/31/03	3/31/05
Horn Antenna	ATM	19-443-6R	None	No Cal Required	
Passive Loop Antenna	EMC Test Systems	EMCO 6512	9706-1211	CHAR 7/10/01	7/10/03
Line Impedance Stabilization . . .	Electro-Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03
Line Impedance Stabilization . . .	Electro-Metrics	EM-7820	2682	CAL 3/12/03	3/12/05
Termaline Wattmeter	Bird Electronic Corporation	611	16405	CAL 5/25/99	5/25/01
Termaline Wattmeter	Bird Electronic Corporation	6104	1926	CHAR 12/12/01	12/12/03
Oscilloscope	Tektronix	2230	300572	CHAR 2/1/01	2/1/03
System One	Audio Precision	System One	SYS1-45868	CHAR 4/25/02	4/25/04
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 1/22/02	1/22/04
AC Voltmeter	HP	400FL	2213A14499	CAL 10/9/01	10/9/03
AC Voltmeter	HP	400FL	2213A14261	CHAR 10/15/01	10/15/03
AC Voltmeter	HP	400FL	2213A14728	CHAR 10/15/01	10/15/03
X Digital Multimeter	Fluke	77	35053830	CHAR 1/8/02	1/8/04
Digital Multimeter	Fluke	77	43850817	CHAR 1/8/02	1/8/04
Digital Multimeter	HP	E2377A	2927J05849	CHAR 1/8/02	1/8/04
Multimeter	Fluke	FLUKE-77-3	79510405	CHAR 9/26/01	9/26/03
Peak Power Meter	HP	8900C	2131A00545	CHAR 1/26/01	1/26/03
Power Meter	HP	432A	1141A07655	CAL 4/15/03	4/15/05
Power Meter And Sensor	Bird	4421-107 4022	0166 0218	CAL 4/16/03	4/16/05
Power Sensor	HP	478A	72129	CAL 4/15/03	4/15/05
Digital Thermometer	Fluke	2166A	42032	CAL 1/16/02	1/16/04
Thermometer	Traulsen	SK-128		CHAR 1/22/02	1/22/04

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 2 of 12

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
	Thermometer	Extech	4028	14871-2	CAL 3/7/03	3/7/05
X	Hygro-Thermometer	Extech	445703	0602	CAL 10/4/02	10/4/04
	Frequency Counter	HP	5352B	2632A00165	CAL 11/28/01	11/28/03
	Frequency Counter	HP	5385A	2730A03025	CAL 3/7/03	3/7/05
	Power Sensor	Agilent Technologies	84811A	2551A02705	CHAR 1/26/01	1/26/03
	Service Monitor	IFR	FM/AM 500A	5182	CAL 11/22/00	11/22/02
	Comm. Serv. Monitor	IFR	FM/AM 1200S	6593	CAL 5/12/02	5/12/04
	Signal Generator	HP	8640B	2308A21464	CAL 2/15/02	2/15/04
	Sweep Generator	Wiltron	6648	101009	CAL 4/15/03	4/15/05
	Sweep Generator	Wiltron	6669M	007005	CAL 3/3/03	3/3/05
	Modulation Analyzer	HP	8901A	3435A06868	CAL 9/5/01	9/5/03
	Modulation Meter	Boonton	8220	10901AB	CAL 4/15/03	4/15/05
	Near Field Probe	HP	HP11940A	2650A02748	CHAR 2/1/01	2/1/03
	BandReject Filter	Lorch Microwave	5BR4-2400/60-N	Z1	CHAR 3/2/01	3/2/03
	BandReject Filter	Lorch Microwave	6BR6-2442/300-N	Z1	CHAR 3/2/01	3/2/03
	BandReject Filter	Lorch Microwave	5BR4-10525/900-S	Z1	CHAR 3/2/01	3/2/03
	High Pass Filter	Microlab	HA-10N		CHAR 10/4/01	10/4/03
	High Pass Filter	Microlab	HA-20N		CHAR 2/7/03	2/7/05
	Audio Oscillator	HP	653A	832-00260	CHAR 3/1/01	3/1/03
	Frequency Counter	HP	5382A	1620A03535	CHAR 3/2/01	3/2/03
	Frequency Counter	HP	5385A	3242A07460	CAL 3/7/03	3/7/05
	Preamplifier	HP	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
	Amplifier	HP	11975A	2738A01969	CHAR 3/1/01	3/1/03
	Egg Timer	Unk			CHAR 8/31/01	8/31/03

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 3 of 12

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
Measuring Tape, 20M	Kraftixx	0631-20		CHAR 2/1/02	2/1/04
Measuring Tape, 7.5M	Kraftixx	7.5M PROFI		2/1/02	2/1/04
Coaxial Cable #51	Insulated Wire Inc.	NPS 2251-2880	Timco #51	CHAR 1/23/02	1/23/04
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 1/24/02	1/24/04
Coaxial Cable #65	General Cable Co.	E9917 RG233/U	Timco #65	CHAR 1/23/02	1/23/04
Coaxial Cable #106	Unknown	Unknown	Timco #106	CHAR 1/23/02	1/23/04

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 4 of 12

## TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

**RADIATION INTERFERENCE:** The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 86° with a humidity of 40%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

**ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES:** The unit under test was placed on a table 80 cm high and with dimensions of 1 m by 1.5 m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1 m to 4 m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 5 of 12

**APPLICANT:** ENGINEERED AUDIO, LLC

**FCC ID:** QWB-AUR1000

**NAME OF TEST:** RADIATION INTERFERENCE

**RULES PART NO.:** 15.239

**REQUIREMENTS:** CARRIER FREQUENCY WILL NOT EXCEEDS 48.0 dBuV/m (AVERAGE) AT 3M. OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

**TEST DATA:**

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV Peak	ANT. POLARITY	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
90.1	180.20	7.1	V	1.64	14.37	23.11	20.39
90.1	180.20	14.8	H	1.64	14.37	30.81	12.69
97.8	195.40	7.9	V	1.76	15.74	25.40	18.10
97.8	195.40	13.4	H	1.76	15.74	30.90	12.60
107.5	215.00	13.0	V	1.86	12.25	27.11	16.39
107.5	215.00	16.4	H	1.86	12.25	30.51	12.99
LIN AVE							
90.1	90.1	34.98	H	1.10	10.81	46.89	1.11
97.8	97.8	29.82	H	1.18	11.41	42.41	5.59
107.5	107.5	30.97	H	1.25	11.10	43.30	4.70

**SAMPLE CALCULATION:** FSdBuV/m = MR (dBuV) + ACFdB.

**TEST PROCEDURE:** The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

**TEST RESULTS:** THE UNIT DOES MEET THE FCC REQUIREMENTS.

**PERFORMED BY:** JOSEPH SCOGLIO

**DATE:** JUNE 20, 2003

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 6 of 12

**APPLICANT:** ENGINEERED AUDIO, LLC

**FCC ID:** QWB-AUR1000

**NAME OF TEST:** Occupied Bandwidth

**RULES PART NO.:** 15.239

**REQUIREMENTS:** Emissions from the device shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz.

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE EMISSIONS TAKEN FOR THIS DEVICE.


**METHOD OF MEASUREMENT:** The zero level was set without modulation. A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division; the horizontal scale is set to 100 kHz per division.

**TEST RESULTS:** The unit DOES meet the FCC requirements.

**PERFORMED BY:** JOSEPH SCOGLIO      **DATE:** JUNE 20, 2003

APPLICANT: ENGINEERED AUDIO, LLC.  
FCC ID: QWB-AUR1000  
REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc  
Page 7 of 12

OCCUPIED BANDWIDTH PLOT - MUSIC




APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 8 of 12

OCCUPIED BANDWIDTH PLOT - 15K TONE



APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 9 of 12

**APPLICANT:** ENGINEERED AUDIO, LLC

**FCC ID:** QWB-AUR1000

**NAME OF TEST:** POWER LINE CONDUCTED INTERFERENCE

**RULES PART NO.:** 15.107

<b>REQUIREMENTS:</b>	<b>QUASI-PEAK</b>	<b>AVERAGE</b>
.15 - 0.5 MHz	66-56 dBuV	56-46 dBuV
0.5 - 5.0	56	46
5.0 - 30.	60	50

**TEST PROCEDURE:** ANSI STANDARD C63.4-1992. The spectrum was scanned from .15 to 30 MHz.

**TEST DATA:**

THE HIGHEST EMISSION READ FOR LINE 1 WAS 166 uV @ 29.67 MHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 122 uV @ 29.22 MHz.

THE GRAPHS ON THE FOLLOWING PAGES REPRESENT THE EMISSIONS READ FOR POWER LINE CONDUCTED FOR THIS DEVICE.

**TEST RESULTS:** Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

**PERFORMED BY:** JOSEPH SCOGLIO


**DATE:** JUNE 20, 2002

APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc  
Page 10 of 12

POWER LINE CONDUCTED PLOT - LINE 1




APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 11 of 12

POWER LINE CONDUCTED PLOT - LINE 2



APPLICANT: ENGINEERED AUDIO, LLC.

FCC ID: QWB-AUR1000

REPORT #: T:\E\ENG\_AUDIO\848AUT3\848AUT3TestReport.doc

Page 12 of 12