Frequency

Table

Ant.

Humidity: 65 %

Margin

Limit @3m

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

74.0

---

52.6

48.8

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

54.0

---

-1.4

-5.2

---

190

180

1.0

1.4

b) Operation Mode : Receiving /Transmitting (Max Power)

Test Date : Mar. 17, 2003

Reading (dBuV)

(dBuV/m) (dBuV/m) (dB) Deg. Н (dB) High Peak Peak Ave. (Deg.) Ave (m) (MHz) Peak Ave Peak Ave Corr. 1100.000 -9.3 74.0 54.0 1400.000 -7.9 74.0 54.0 ------------------------1550.000 -7.2 74.0 54.0 <u>5</u>4.0 1645.900 74.0 47.5 46.8 -6.7 40.8 40.1 -13.9 175 1.1 1708.000 47.0 46.5 -6.3 40.7 40.2 74.0 54.0 -13.8 180 1.1 1719.800 -6.2 74.0 54.0 2250.000 -3.7 74.0 54.0 2350.000 -3.3 74.0 54.0 2494.800 -2.7 43.3 42.6 54.0 1.4 46.0 45.3 74.0 -11.4 180 2750.000 -2.0 74.0 54.0 3265.000 -0.6 74.0 54.0 3338.000 -0.4 74.0 54.0 3355.000 45.7 -0.3 45.4 44.8 74.0 54.0 180 45.1 -9.2 1.1 4120.000 44.5 43.9 2.0 46.5 45.9 74.0 54.0 90 -8.1 1.0

2.9

4.0

6.0

6.7

7.0

7.2

8.5

10.7

11.6 8.3

17.4

10.3

10.4

48.3

46.7

---

53.2

49.3

---

Temperature: 22

Result @3m

Factor

## 36470.000 Note:

5000.000

5380.000

7350.000

8340.000

9100.000

9400.000

11000.000

13300.000

14490.000

15800.000

18000.000

22500.000

23800.000

31500.000

---

46.5

41.0

---

45.9

40.5

---

- 1. Remark "---" means that the emissions level is too low to be measured.
- 2. The expanded uncertainty of the radiated emission tests is 3.53 dB.