

**RADIO FREQUENCY EXPOSURE****LIMIT**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

Conducted Power Results***Bluetooth***

Mode	Channel	Frequency(MHz)	PeakConducted Output Power (dBm)
GFSK-BLE	00	2402	5.31
	19	2440	4.96
	39	2480	4.23
GFSK	00	2402	3.00
	39	2441	3.18
	78	2480	2.41
8DPSK	00	2402	3.10
	39	2441	3.26
	78	2480	2.61
$\pi/4$ DQPSK	00	2402	3.04
	39	2441	3.13
	78	2480	2.48

Manufacturing tolerance***Bluetooth***

GFSK -BLE(Peak)			
Channel	Channel 00	Channel 19	Channel 39
Target (dBm)	5.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	3.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	3.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$DQPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	3.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



Compliance Certification Services Inc.

Report No: C151020Z03-RP1_MPE

FCC ID: QWHIP500

Date of Issue: November 25, 2015

EUT Specification

EUT	Powered Loudspeaker
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☒ Bluetooth: 2.402GHz~ 2.480GHz ☐ Others _
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure ($S = 5mW/cm^2$) ☒ General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	6dBm (3.98mW)
Antenna gain (Max)	0dBi (Numeric gain:1)
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Note:

1. The maximum output power(including turn tolerance) is 6dBm (3.98mW) and maximum antenna gain is 0dBi
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.



TEST RESULT

No non-compliance noted.

Calculation

Given $S = \frac{P \times G}{4\pi d^2}$ ***Equation 1***

Where d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW / cm²

Maximum Permissible Exposure

EUT Output Power=3.98mW

Numeric antenna gain=1

Substituting the MPE safe distance using d=20 cm into ***Equation 1*** :

Fields

The power density $S = 3.98 \times 1 / (4\pi \times 400) \text{ cm}^2 = 7.92 \times 10^{-4} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm² even if the calculation indicates that the power density would be larger.)