

FCC 47 CFR MPE REPORT

Empower Tribe Commercial FZE

Portable PA Speakers

Model Number: MPA100BT

FCC ID: QWHMPA100BTV3

Applicant:	Empower Tribe Commercial FZE
Address:	LB181504WS13, Jebel Ali Freezone Dubai, United Arab Emirates
Prepared By:	EST Technology Co., Ltd.
Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China	
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2506003
Date of Test:	May 13, 2025 to May 30, 2025
Date of Report:	Jun. 04, 2025

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	6.07	4.046
	2441	6.55	4.519
	2480	7.36	5.445
$\pi/4$ -DQPSK	2402	8.20	6.607
	2441	9.04	8.017
	2480	9.77	9.484
8-DPSK	2402	9.00	7.943
	2441	9.70	9.333
	2480	10.51	11.246
BLE 1M	2402	5.46	3.516
	2440	6.23	4.198
	2480	7.11	5.140
BLE 2M	2402	5.49	3.540
	2440	6.25	4.217
	2480	7.17	5.212

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	7.36	7±1	8	1.5	1.413	0.00177	1	Complies
$\pi/4$ -DQPSK	9.77	9±1	10	1.5	1.413	0.00281	1	Complies
8-DPSK	10.51	10±1	11	1.5	1.413	0.00354	1	Complies
BLE 1M	7.11	7±1	8	1.5	1.413	0.00177	1	Complies
BLE 2M	7.17	7±1	8	1.5	1.413	0.00177	1	Complies

End of Test Report