

FCC TEST REPORT (15.247)

REPORT NO.: RF110831C15

MODEL NO.: APL25-091

FCC ID: QWU-091

RECEIVED: Aug. 31, 2011

TESTED: Oct. 04 to 12, 2011

ISSUED: Oct. 19, 2011

APPLICANT: SonicWALL, Inc.

ADDRESS: 2001 Logic Drive San Jose, CA 95124, USA

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 120 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

RELEASE CONTROL RECORD	5
1. CERTIFICATION	6
2. SUMMARY OF TEST RESULTS	7
2.1 MEASUREMENT UNCERTAINTY	9
3. GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	13
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	14
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	17
3.4 DESCRIPTION OF SUPPORT UNITS.....	18
3.5 CONFIGURATION OF SYSTEM UNDER TEST	19
4. TEST TYPES AND RESULTS (2400 ~ 2483.5MHz Band).....	20
4.1 CONDUCTED EMISSION MEASUREMENT	20
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	20
4.1.2 TEST INSTRUMENTS.....	20
4.1.3 TEST PROCEDURES	21
4.1.4 DEVIATION FROM TEST STANDARD	21
4.1.5 TEST SETUP	22
4.1.6 EUT OPERATING CONDITIONS	22
4.1.7 TEST RESULTS (Mode 1)	23
4.1.8 TEST RESULTS (Mode 2)	25
4.2 RADIATED EMISSION MEASUREMENT	27
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	27
4.2.2 TEST INSTRUMENTS.....	28
4.2.3 TEST PROCEDURES	29
4.2.4 DEVIATION FROM TEST STANDARD	29
4.2.5 TEST SETUP	30
4.2.6 EUT OPERATING CONDITIONS	30
4.2.7 TEST RESULTS	31
4.3 6dB BANDWIDTH MEASUREMENT	60
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	60
4.3.2 TEST INSTRUMENTS.....	60
4.3.3 TEST PROCEDURE.....	60
4.3.4 DEVIATION FROM TEST STANDARD	60
4.3.5 TEST SETUP	60
4.3.6 EUT OPERATING CONDITIONS	60
4.3.7 TEST RESULTS	61
4.4 MAXIMUM PEAK OUTPUT POWER.....	65
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	65
4.4.2 INSTRUMENTS.....	65



A D T

4.4.3	TEST PROCEDURES	65
4.4.4	DEVIATION FROM TEST STANDARD	65
4.4.5	TEST SETUP	65
4.4.6	EUT OPERATING CONDITIONS	65
4.4.7	TEST RESULTS	66
4.5	POWER SPECTRAL DENSITY MEASUREMENT	68
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	68
4.5.2	TEST INSTRUMENTS	68
4.5.3	TEST PROCEDURE	68
4.5.4	DEVIATION FROM TEST STANDARD	68
4.5.5	TEST SETUP	68
4.5.6	EUT OPERATING CONDITION	68
4.5.7	TEST RESULTS	69
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	73
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	73
4.6.2	TEST INSTRUMENTS	73
4.6.3	TEST PROCEDURE	73
4.6.4	DEVIATION FROM TEST STANDARD	73
4.6.5	EUT OPERATING CONDITION	73
4.6.6	TEST RESULTS	73
5.	TEST TYPES AND RESULTS (5725~5850MHz Band)	82
5.1	CONDUCTED EMISSION MEASUREMENT	82
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	82
5.1.2	TEST INSTRUMENTS	82
5.1.3	TEST PROCEDURES	83
5.1.4	DEVIATION FROM TEST STANDARD	83
5.1.5	TEST SETUP	84
5.1.6	EUT OPERATING CONDITIONS	84
5.1.7	TEST RESULTS (Mode 1)	85
5.1.8	TEST RESULTS (Mode 2)	87
5.2	RADIATED EMISSION MEASUREMENT	89
5.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	89
5.2.2	TEST INSTRUMENTS	90
5.2.3	TEST PROCEDURES	91
5.2.4	DEVIATION FROM TEST STANDARD	91
5.2.5	TEST SETUP	92
5.2.6	EUT OPERATING CONDITIONS	92
5.2.7	TEST RESULTS	93
5.3	6dB BANDWIDTH MEASUREMENT	102
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	102
5.3.2	TEST INSTRUMENTS	102
5.3.3	TEST PROCEDURE	102



A D T

5.3.4	DEVIATION FROM TEST STANDARD	102
5.3.5	TEST SETUP	102
5.3.6	EUT OPERATING CONDITIONS	102
5.3.7	TEST RESULTS	103
5.4	MAXIMUM PEAK OUTPUT POWER	106
5.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	106
5.4.2	INSTRUMENTS.....	106
5.4.3	TEST PROCEDURES	106
5.4.4	DEVIATION FROM TEST STANDARD	106
5.4.5	TEST SETUP	106
5.4.6	EUT OPERATING CONDITIONS	106
5.4.7	TEST RESULTS	107
5.5	POWER SPECTRAL DENSITY MEASUREMENT	108
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	108
5.5.2	TEST INSTRUMENTS.....	108
5.5.3	TEST PROCEDURE.....	108
5.5.4	DEVIATION FROM TEST STANDARD	108
5.5.5	TEST SETUP	108
5.5.6	EUT OPERATING CONDITION.....	108
5.5.7	TEST RESULTS	109
5.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	112
5.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	112
5.6.2	TEST INSTRUMENTS.....	112
5.6.3	TEST PROCEDURE.....	112
5.6.4	DEVIATION FROM TEST STANDARD	112
5.6.5	EUT OPERATING CONDITION.....	112
5.6.6	TEST RESULTS	112
6.	INFORMATION ON THE TESTING LABORATORIES	119
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	120



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF110831C15	Original release	Oct. 19, 2011



A D T

1. CERTIFICATION

PRODUCT: Wireless 802.11 abgn Device
BRAND NAME: SonicWALL
MODEL NO.: APL25-091
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: SonicWALL, Inc.
TESTED: Oct. 04 to 12, 2011
STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.4-2003
ANSI C63.10-2009

The above equipment (Model: APL25-091) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Oct. 19, 2011
(Lori Chung, Specialist)

APPROVED BY :  , **DATE:** Oct. 19, 2011
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 2.4GHz, 2412~2462MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -8.88dB at 0.181MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -0.7dB at 2483.50MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connectors are RTNC and RSMA not standard connectors.

For 5GHz, 5725~5850MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -4.95dB at 0.170MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.2dB at 37.10MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connectors are RTNC and RSMA not standard connectors.

NOTE:

1. The EUT was operating in 2400 ~ 2483.5MHz, 5.15~5.25GHz and 5.725~5.850GHz frequencies band. This report was recorded the RF parameters including 2400 ~ 2483.5MHz and 5.725~5.850GHz. For the 5.15~5.25GHz RF parameters was recorded in another test report.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.89 dB
Radiated emissions (1GHz -18GHz)	2.19 dB
Radiated emissions (18GHz -40GHz)	2.56 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless 802.11 abgn Device
MODEL NO.	APL25-091
FCC ID	QWU-091
POWER SUPPLY	12Vdc (Adapter)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	■802.11b: 11 / 5.5 / 2 / 1Mbps ■802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps ■802.11a: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps ■802.11n: up to 450Mbps.
OPERATING FREQUENCY	For 15.407 5GHz: 5.18 ~ 5.24GHz
	For 15.247 2.4GHz: 2.412 ~ 2.462GHz
	5GHz: 5.745 ~ 5.825GHz
NUMBER OF CHANNEL	For 15.407 4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
	For 15.247(2.4GHz) 11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
	For 15.247(5GHz) 5 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
MAXIMUM OUTPUT POWER	For 15.407 802.11a: 19.5mW 802.11n (20MHz): 28.6mW 802.11n (40MHz): 29.1 mW For 15.247(2.4GHz) 802.11b: 154.8mW 802.11g: 504.2mW 802.11n (20MHz): 484.4mW 802.11n (40MHz): 741.4mW For 15.247(5GHz) 802.11a: 426.6mW 802.11n (20MHz): 493.6mW 802.11n (40MHz): 510.7mW
ANTENNA TYPE	Refer to note for more details

DATA CABLE	1.8m non-shielded RJ45 cable without core
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	Adapter

NOTE:

- The frequency bands used in this EUT are listed as below.

Frequency Band (MHz)	2412~2472	5180~5320	5745~5825
802.11b	√	-	-
802.11g	√	-	-
802.11a	-	√	√
802.11n (20MHz)	√	√	√
802.11n (40MHz)	√	√	√

- The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 2 receivers.

MODULATION MODE	TX FUNCTION
802.11b	3TX
802.11g	3TX
802.11a	3TX
802.11n (20MHz)	3TX
802.11n (40MHz)	3TX

- The antennas used in this EUT are listed as below table:

Transmitter Circuit	ANTENNA TYPE	ANTENNA CONNECTOR	GAIN (dBi)	
			2.4GHz BAND	5.0GHz BAND
Chain (0)	Dipole	RTNC	2.5	2.5
Chain (1)	Dipole	RSMA	3.0	3.0
Chain (2)	Dipole	RTNC	2.5	2.5

4. The EUT is powered by the following adapters. After pre-testing, the adapter 2 is the worst case for final test.

ADAPTER 1	
BRAND:	Sunny COMPUTER TECHNOLOGY CO,LTD.
MODEL:	SYS1359-3612-T3
INPUT:	100-240Vac, 1.5A MAX ,50-60Hz
OUTPUT:	12Vdc, 3.0A
POWER LINE:	AC 1.8m non-shielded cable without core DC 1.8m non-shielded cable with 1 core

ADAPTER 2	
BRAND:	SINO-AMERICAN
MODEL:	SA142B-12V
INPUT:	100-240Vac, 50-60Hz, 1.2A
OUTPUT:	12Vdc, 3.0A
POWER LINE:	AC 1.8m non-shielded cable without core DC 1.6m non-shielded cable with 1 core

5. 2.4GHz and 5GHz technology cannot transmit at same time.
6. The above EUT information is declared by the manufacturer and for more detailed feature description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

Operated in 5725 ~ 5850MHz band:

Five channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

Two channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY
151	5755 MHz
159	5795 MHz

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
MODE 1	√	-	-	-	-	Adapter 1
MODE 2	√	√	√	√	√	Adapter 2

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ³ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
For 2.4 GHz 802.11g	1 to 11	6	OFDM	BPSK	6
For 5 GHz 802.11n (20MHz)	149 to 165	165	OFDM	BPSK	6.5

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
For 2.4 GHz 802.11g	1 to 11	6	OFDM	BPSK	6	X
For 5 GHz 802.11n (20MHz)	149 to 165	165	OFDM	BPSK	6.5	X

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	X
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	X
For 2.4 GHz 802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	X
For 2.4 GHz 802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	X
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6	X
For 5 GHz 802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	6.5	X
For 5 GHz 802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	13.5	X

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (20MHz)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	13.5

※ Bandwidth as show worst chain in report base on preliminary measurement.

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 165	OFDM	BPSK	6
For 5 GHz 802.11n (20MHz)	149 to 165	149, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (40MHz)	151 to 159	151, 159	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	25deg. C, 67%RH	120Vac, 60Hz	Frank Liu
	26deg. C, 68%RH	120Vac, 60Hz	Frank Liu
RE ³ 1G	24deg. C, 64%RH	120Vac, 60Hz	Evan Huang
	24deg. C, 64%RH	120Vac, 60Hz	Frank Liu
RE<1G	24deg. C, 71%RH	120Vac, 60Hz	Evan Huang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Rex Huang
OB	25deg. C, 60%RH	120Vac, 60Hz	Rex Huang

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP19L	CN-OHC416-70 166-5CA-0448	PIW632500516610
3	HUB	ZyXEL	ES-116P	S060H0200021 5	FCC DoC
4	iPod shuffle	Apple	MC749TA/A	CC4DMFJUDFD M	NA
5	iPod shuffle	Apple	MC749TA/A	CC4DN25WDF DM	NA
6	SD card	Transcend	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP cable (10m)
2	UTP cable (10m)
3	UTP cable (10m)
4	USB cable (0.1m)
5	USB cable (0.1m)
6	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



NOTE: 1. The item A is support unit 6.

4. TEST TYPES AND RESULTS (2400 ~ 2483.5MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Test date: Oct. 08 to 12, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 09, 2011	Mar. 08, 2012
Line-Impedance Stabilization Network (for EUT)	ENV216	100072	June 10, 2011	June 09, 2012
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Nov. 03, 2010	Nov. 02, 2011
RF Cable (JYEBAO)	5DFB	COCCAB-002	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	3	Nov. 03, 2010	Nov. 02, 2011
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


1. Placed the EUT on testing table.
2. Prepared computer system (support unit 1~2) to act as communication partner and placed it outside of testing area.
3. The communication partners ran test program “art.exe” to enable EUT under transmission/receiving condition continuously via UTP cables transmission.

4.1.7 TEST RESULTS (Mode 1)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.09	55.60	43.23	55.69	43.32	64.98	54.98	-9.29	-11.66
2	0.220	0.10	43.62	26.89	43.72	26.99	62.81	52.81	-19.09	-25.82
3	0.369	0.11	42.89	30.76	43.00	30.87	58.53	48.53	-15.53	-17.66
4	0.474	0.11	39.70	28.82	39.81	28.93	56.44	46.44	-16.62	-17.50
5	0.564	0.12	37.19	25.60	37.31	25.72	56.00	46.00	-18.69	-20.28
6	6.633	0.42	31.89	29.28	32.31	29.70	60.00	50.00	-27.69	-20.30


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.08	55.73	43.59	55.81	43.67	64.98	54.98	-9.17	-11.31
2	0.224	0.09	46.96	33.07	47.05	33.16	62.66	52.66	-15.61	-19.50
3	0.373	0.11	42.87	28.88	42.98	28.99	58.44	48.44	-15.46	-19.45
4	0.474	0.11	40.34	29.59	40.45	29.70	56.44	46.44	-15.99	-16.74
5	0.568	0.12	37.68	26.31	37.80	26.43	56.00	46.00	-18.20	-19.57
6	9.664	0.40	29.86	25.67	30.26	26.07	60.00	50.00	-29.74	-23.93

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS (Mode 2)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.09	53.31	45.45	53.40	45.54	64.43	54.43	-11.02	-8.88
2	0.232	0.10	45.27	37.03	45.37	37.13	62.38	52.38	-17.01	-15.25
3	0.275	0.10	42.29	34.53	42.39	34.63	60.97	50.97	-18.57	-16.33
4	3.676	0.30	38.47	32.38	38.77	32.68	56.00	46.00	-17.23	-13.32
5	5.086	0.36	37.20	33.75	37.56	34.11	60.00	50.00	-22.44	-15.89
6	11.688	0.59	26.27	21.01	26.86	21.60	60.00	50.00	-33.14	-28.40


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.08	52.19	43.29	52.27	43.37	64.43	54.43	-12.15	-11.05
2	0.232	0.09	44.74	36.99	44.83	37.08	62.38	52.38	-17.54	-15.29
3	0.275	0.10	41.52	33.58	41.62	33.68	60.97	50.97	-19.35	-17.29
4	2.551	0.19	31.67	23.50	31.86	23.69	56.00	46.00	-24.14	-22.31
5	4.066	0.24	39.19	33.35	39.43	33.59	56.00	46.00	-16.57	-12.41
6	10.695	0.43	29.31	27.64	29.74	28.07	60.00	50.00	-30.26	-21.93

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. Section 15.205 restricted bands of operation shall compliance with the limits in Section 15.209.

4.2.2 TEST INSTRUMENTS

Test date: Oct. 04 to 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250253	Aug. 29, 2011	Aug. 28, 2012
Agilent Pre-Selector	N9039A	MY46520310	Aug. 29, 2011	Aug. 28, 2012
Agilent Signal Generator	N5181A	MY49060347	July 25, 2011	July 24, 2012
LIG NEX1 Test Receiver	ER-265	L09068005	Oct. 25, 2010	Oct. 24, 2011
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02465	Feb. 28, 2011	Feb. 27, 2012
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	Nov. 16, 2010	Nov. 15, 2011
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Apr. 14, 2011	Apr. 13, 2012
AISI Horn Antenna	AIH.8018	0000220091110	Nov. 22, 2010	Nov. 21, 2011
SCHWARZBECK Horn Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-205 RF104-207 RF104-202	Dec. 28, 2010	Dec. 27, 2011
RF Cable	NA	CHHCAB_001	Oct. 17, 2010	Oct. 16, 2011
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

3. The test was performed in 966 Chamber No. H.

4. The FCC Site Registration No. is 797305.

5. The CANADA Site Registration No. is IC 7450H-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meters chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : 802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 71%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	106.74	32.5 QP	43.5	-11.0	1.75 H	74	22.13	10.35
2	120.95	29.9 QP	43.5	-13.6	1.75 H	262	17.44	12.47
3	203.61	33.1 QP	43.5	-10.4	1.25 H	80	21.76	11.34
4	374.97	38.5 QP	46.0	-7.6	1.00 H	37	21.66	16.79
5	750.01	36.6 QP	46.0	-9.4	1.00 H	97	13.30	23.27
6	1000.00	40.3 QP	54.0	-13.7	1.25 H	360	13.31	27.03
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.90	38.9 QP	40.0	-1.1	1.00 V	318	25.17	13.73
2	122.13	34.9 QP	43.5	-8.6	1.00 V	4	22.30	12.57
3	195.20	32.0 QP	43.5	-11.5	1.25 V	0	20.46	11.57
4	625.07	41.4 QP	46.0	-4.6	1.00 V	73	19.70	21.73
5	750.01	34.1 QP	46.0	-11.9	1.25 V	184	10.82	23.27
6	875.06	32.9 QP	46.0	-13.1	1.00 V	360	7.47	25.47

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

ABOVE 1GHz WORST-CASE DATA

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.5 PK	74.0	-18.5	1.00 H	13	23.62	31.88
2	2390.00	44.6 AV	54.0	-9.4	1.00 H	13	12.72	31.88
3	*2412.00	107.2 PK			1.00 H	23	75.25	31.95
4	*2412.00	104.3 AV			1.00 H	23	72.35	31.95
5	4824.00	48.2 PK	74.0	-25.8	1.38 H	306	6.98	41.22
6	4824.00	36.4 AV	54.0	-17.6	1.38 H	306	-4.82	41.22
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.9 PK	74.0	-19.1	1.61 V	160	23.02	31.88
2	2390.00	45.4 AV	54.0	-8.6	1.61 V	160	13.52	31.88
3	*2412.00	111.4 PK			1.61 V	160	79.45	31.95
4	*2412.00	108.7 AV			1.61 V	160	76.75	31.95
5	4824.00	51.6 PK	74.0	-22.4	1.75 V	6	10.38	41.22
6	4824.00	44.2 AV	54.0	-9.8	1.75 V	6	2.98	41.22

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.1 PK			1.05 H	33	75.06	32.04
2	*2437.00	104.2 AV			1.05 H	33	72.16	32.04
3	4874.00	48.5 PK	74.0	-25.5	1.30 H	295	7.14	41.36
4	4874.00	36.6 AV	54.0	-17.4	1.30 H	295	-4.76	41.36
5	7311.00	53.2 PK	74.0	-20.8	1.06 H	166	7.53	45.67
6	7311.00	39.9 AV	54.0	-14.1	1.06 H	166	-5.77	45.67
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	114.3 PK			1.61 V	157	82.26	32.04
2	*2437.00	108.6 AV			1.61 V	157	76.56	32.04
3	4874.00	52.0 PK	74.0	-22.0	1.72 V	3	10.64	41.36
4	4874.00	44.5 AV	54.0	-9.5	1.72 V	3	3.14	41.36
5	7311.00	52.7 PK	74.0	-21.3	1.04 V	28	7.03	45.67
6	7311.00	40.2 AV	54.0	-13.8	1.04 V	28	-5.47	45.67



REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.7 PK			1.00 H	11	75.58	32.12
2	*2462.00	104.6 AV			1.00 H	11	72.48	32.12
3	2483.50	55.6 PK	74.0	-18.4	1.00 H	26	23.41	32.19
4	2483.50	44.1 AV	54.0	-9.9	1.00 H	26	11.91	32.19
5	4924.00	48.6 PK	74.0	-25.4	1.34 H	291	7.12	41.48
6	4924.00	36.8 AV	54.0	-17.2	1.34 H	291	-4.68	41.48
7	7386.00	53.2 PK	74.0	-20.8	1.11 H	169	7.29	45.91
8	7386.00	39.7 AV	54.0	-14.3	1.11 H	169	-6.21	45.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.6 PK			1.57 V	143	82.48	32.12
2	*2462.00	108.2 AV			1.57 V	143	76.08	32.12
3	2483.50	54.7 PK	74.0	-19.3	1.61 V	139	22.51	32.19
4	2483.50	44.1 AV	54.0	-9.9	1.61 V	139	11.91	32.19
5	4924.00	52.1 PK	74.0	-21.9	1.73 V	0	10.62	41.48
6	4924.00	44.9 AV	54.0	-9.1	1.73 V	0	3.42	41.48
7	7386.00	52.2 PK	74.0	-21.8	1.00 V	27	6.29	45.91
8	7386.00	39.9 AV	54.0	-14.1	1.00 V	27	-6.01	45.91

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11b MODE, CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11b MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11b MODE,CH11, HORIZONTAL)



RESTRICTED BANDEDGE (802.11b MODE,CH11, VERTICAL)



802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.2 PK	74.0	-15.8	1.00 H	24	26.32	31.88
2	2390.00	46.9 AV	54.0	-7.1	1.00 H	24	15.02	31.88
3	*2412.00	109.3 PK			1.00 H	36	77.35	31.95
4	*2412.00	99.6 AV			1.00 H	36	67.65	31.95
5	4824.00	48.4 PK	74.0	-25.6	1.31 H	251	7.18	41.22
6	4824.00	31.3 AV	54.0	-22.7	1.31 H	251	-9.92	41.22
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.9 PK	74.0	-11.1	1.34 V	163	31.02	31.88
2	2390.00	50.9 AV	54.0	-3.1	1.34 V	163	19.02	31.88
3	*2412.00	112.6 PK			1.54 V	133	80.65	31.95
4	*2412.00	103.4 AV			1.54 V	133	71.45	31.95
5	4824.00	50.4 PK	74.0	-23.6	1.64 V	23	9.18	41.22
6	4824.00	40.3 AV	54.0	-13.7	1.64 V	23	-0.92	41.22

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.7 PK			1.01 H	42	77.66	32.04
2	*2437.00	100.1 AV			1.01 H	42	68.06	32.04
3	4874.00	48.2 PK	74.0	-25.8	1.28 H	244	6.84	41.36
4	4874.00	31.3 AV	54.0	-22.7	1.28 H	244	-10.06	41.36
5	7311.00	52.7 PK	74.0	-21.3	1.06 H	174	7.03	45.67
6	7311.00	39.5 AV	54.0	-14.5	1.06 H	174	-6.17	45.67
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.2 PK			1.60 V	129	81.16	32.04
2	*2437.00	103.9 AV			1.60 V	129	71.86	32.04
3	4874.00	50.3 PK	74.0	-23.7	1.60 V	39	8.94	41.36
4	4874.00	40.0 AV	54.0	-14.0	1.60 V	39	-1.36	41.36
5	7311.00	52.3 PK	74.0	-21.7	1.00 V	37	6.63	45.67
6	7311.00	40.1 AV	54.0	-13.9	1.00 V	37	-5.57	45.67

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.5 PK			1.02 H	39	77.38	32.12
2	*2462.00	100.0 AV			1.02 H	39	67.88	32.12
3	2483.50	63.4 PK	74.0	-10.6	1.00 H	27	31.21	32.19
4	2483.50	49.7 AV	54.0	-4.3	1.00 H	27	17.51	32.19
5	4924.00	48.1 PK	74.0	-25.9	1.26 H	241	6.62	41.48
6	4924.00	31.5 AV	54.0	-22.5	1.26 H	241	-9.98	41.48
7	7386.00	52.9 PK	74.0	-21.1	1.10 H	183	6.99	45.91
8	7386.00	39.5 AV	54.0	-14.5	1.10 H	183	-6.41	45.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	112.6 PK			1.57 V	132	80.48	32.12
2	*2462.00	103.5 AV			1.57 V	132	71.38	32.12
3	2483.50	67.8 PK	74.0	-6.2	1.61 V	165	35.61	32.19
4	2483.50	51.7 AV	54.0	-2.3	1.61 V	165	19.51	32.19
5	4924.00	50.2 PK	74.0	-23.8	1.55 V	40	8.72	41.48
6	4924.00	40.0 AV	54.0	-14.0	1.55 V	40	-1.48	41.48
7	7386.00	53.0 PK	74.0	-21.0	1.00 V	34	7.09	45.91
8	7386.00	40.5 AV	54.0	-13.5	1.00 V	34	-5.41	45.91

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11g MODE, CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11g MODE, CH11, HORIZONTAL)



RESTRICTED BANDEDGE (802.11g MODE,CH11, VERTICAL)



802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.6 PK	74.0	-12.4	1.00 H	57	29.72	31.88
2	2390.00	48.7 AV	54.0	-5.3	1.00 H	57	16.82	31.88
3	*2412.00	109.7 PK			1.00 H	50	77.75	31.95
4	*2412.00	100.5 AV			1.00 H	50	68.55	31.95
5	4824.00	48.1 PK	74.0	-25.9	1.22 H	241	6.88	41.22
6	4824.00	31.5 AV	54.0	-22.5	1.22 H	241	-9.72	41.22
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.5 PK	74.0	-5.5	1.63 V	169	36.62	31.88
2	2390.00	52.5 AV	54.0	-1.5	1.63 V	169	20.62	31.88
3	*2412.00	112.3 PK			1.54 V	122	80.35	31.95
4	*2412.00	103.4 AV			1.54 V	122	71.45	31.95
5	4824.00	50.2 PK	74.0	-23.8	1.50 V	33	8.98	41.22
6	4824.00	39.8 AV	54.0	-14.2	1.50 V	33	-1.42	41.22

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.1 PK			1.00 H	58	78.06	32.04
2	*2437.00	100.9 AV			1.00 H	58	68.86	32.04
3	4874.00	47.8 PK	74.0	-26.2	1.26 H	249	6.44	41.36
4	4874.00	31.2 AV	54.0	-22.8	1.26 H	249	-10.16	41.36
5	7311.00	52.9 PK	74.0	-21.1	1.12 H	177	7.23	45.67
6	7311.00	39.2 AV	54.0	-14.8	1.12 H	177	-6.47	45.67
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	112.2 PK			1.51 V	112	80.16	32.04
2	*2437.00	103.1 AV			1.51 V	112	71.06	32.04
3	4874.00	50.2 PK	74.0	-23.8	1.58 V	37	8.84	41.36
4	4874.00	40.1 AV	54.0	-13.9	1.58 V	37	-1.26	41.36
5	7311.00	52.9 PK	74.0	-21.1	1.00 V	28	7.23	45.67
6	7311.00	40.6 AV	54.0	-13.4	1.00 V	28	-5.07	45.67

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.00 H	71	78.18	32.12
2	*2462.00	101.1 AV			1.00 H	71	68.98	32.12
3	2483.50	62.8 PK	74.0	-11.2	1.00 H	29	30.61	32.19
4	2483.50	48.0 AV	54.0	-6.0	1.00 H	29	15.81	32.19
5	4924.00	48.1 PK	74.0	-25.9	1.23 H	238	6.62	41.48
6	4924.00	31.8 AV	54.0	-22.2	1.23 H	238	-9.68	41.48
7	7386.00	52.8 PK	74.0	-21.2	1.06 H	185	6.89	45.91
8	7386.00	39.7 AV	54.0	-14.3	1.06 H	185	-6.21	45.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	112.1 PK			1.48 V	106	79.98	32.12
2	*2462.00	103.0 AV			1.48 V	106	70.88	32.12
3	2483.50	63.5 PK	74.0	-10.5	1.64 V	163	31.31	32.19
4	2483.50	51.7 AV	54.0	-2.3	1.64 V	163	19.51	32.19
5	4924.00	49.9 PK	74.0	-24.1	1.54 V	52	8.42	41.48
6	4924.00	39.9 AV	54.0	-14.1	1.54 V	52	-1.58	41.48
7	7386.00	53.1 PK	74.0	-20.9	1.00 V	40	7.19	45.91
8	7386.00	40.4 AV	54.0	-13.6	1.00 V	40	-5.51	45.91

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL)





RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, HORIZONTAL)



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL)



802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.3 PK	74.0	-6.7	1.00 H	36	35.42	31.88
2	2390.00	48.6 AV	54.0	-5.4	1.00 H	36	16.72	31.88
3	*2422.00	101.6 PK			1.00 H	73	69.62	31.98
4	*2422.00	91.9 AV			1.00 H	73	59.92	31.98
5	4844.00	48.6 PK	74.0	-25.4	1.21 H	234	7.32	41.28
6	4844.00	31.4 AV	54.0	-22.6	1.21 H	234	-9.88	41.28
7	7266.00	53.1 PK	74.0	-20.9	1.00 H	177	7.55	45.55
8	7266.00	39.4 AV	54.0	-14.6	1.00 H	177	-6.15	45.55
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.1 PK	74.0	-4.9	1.61 V	153	37.22	31.88
2	2390.00	53.1 AV	54.0	-0.9	1.61 V	153	21.22	31.88
3	*2422.00	107.8 PK			1.32 V	204	75.82	31.98
4	*2422.00	98.1 AV			1.32 V	204	66.12	31.98
5	4844.00	49.1 PK	74.0	-24.9	1.54 V	53	7.82	41.28
6	4844.00	36.4 AV	54.0	-17.6	1.54 V	53	-4.88	41.28
7	7266.00	53.5 PK	74.0	-20.5	1.00 V	46	7.95	45.55
8	7266.00	40.3 AV	54.0	-13.7	1.00 V	46	-5.25	45.55

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.2 PK			1.05 H	56	74.16	32.04
2	*2437.00	95.4 AV			1.05 H	56	63.36	32.04
3	4874.00	48.4 PK	74.0	-25.6	1.20 H	244	7.04	41.36
4	4874.00	31.3 AV	54.0	-22.7	1.20 H	244	-10.06	41.36
5	7311.00	53.1 PK	74.0	-20.9	1.00 H	170	7.43	45.67
6	7311.00	39.3 AV	54.0	-14.7	1.00 H	170	-6.37	45.67
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.5 PK			1.35 V	190	79.46	32.04
2	*2437.00	101.8 AV			1.35 V	190	69.76	32.04
3	4874.00	48.9 PK	74.0	-25.1	1.51 V	66	7.54	41.36
4	4874.00	36.2 AV	54.0	-17.8	1.51 V	66	-5.16	41.36
5	7311.00	53.0 PK	74.0	-21.0	1.01 V	48	7.33	45.67
6	7311.00	39.9 AV	54.0	-14.1	1.01 V	48	-5.77	45.67



- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Evan Huang



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	104.6 PK			1.00 H	65	72.51	32.09
2	*2452.00	93.9 AV			1.00 H	65	61.81	32.09
3	2483.50	66.8 PK	74.0	-7.2	1.00 H	46	34.61	32.19
4	2483.50	50.1 AV	54.0	-3.9	1.00 H	46	17.91	32.19
5	4904.00	48.5 PK	74.0	-25.5	1.17 H	244	7.06	41.44
6	4904.00	31.4 AV	54.0	-22.6	1.17 H	244	-10.04	41.44
7	7356.00	52.8 PK	74.0	-21.2	1.00 H	169	6.99	45.81
8	7356.00	39.4 AV	54.0	-14.6	1.00 H	169	-6.41	45.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	109.3 PK			1.58 V	196	77.21	32.09
2	*2452.00	98.4 AV			1.58 V	196	66.31	32.09
3	2483.50	72.3 PK	74.0	-1.7	1.59 V	143	40.11	32.19
4	2483.50	53.3 AV	54.0	-0.7	1.59 V	143	21.11	32.19
5	4904.00	48.9 PK	74.0	-25.1	1.52 V	55	7.46	41.44
6	4904.00	36.2 AV	54.0	-17.8	1.52 V	55	-5.24	41.44
7	7356.00	53.2 PK	74.0	-20.8	1.00 V	42	7.39	45.81
8	7356.00	40.2 AV	54.0	-13.8	1.00 V	42	-5.61	45.81

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, HORIZONTAL)





RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, VERTICAL)



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, HORIZONTAL)



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, VERTICAL)



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
1	2412	11.45	11.42	10.20	0.5	PASS
6	2437	12.05	11.31	8.30	0.5	PASS
11	2462	11.59	11.99	8.88	0.5	PASS


For CHAIN(0)
CH6



802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
1	2412	16.50	16.10	16.44	0.5	PASS
6	2437	16.41	15.79	16.13	0.5	PASS
11	2462	16.41	16.05	16.43	0.5	PASS


For CHAIN(0)
CH1



802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
1	2412	17.66	17.63	17.01	0.5	PASS
6	2437	17.68	16.96	17.37	0.5	PASS
11	2462	16.73	17.63	17.62	0.5	PASS


For CHAIN(0)
CH6



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
3	2422	35.63	36.42	36.53	0.5	PASS
6	2437	36.05	35.84	36.45	0.5	PASS
9	2452	35.86	35.85	35.78	0.5	PASS

For CHAIN(2)
CH3





A D T

4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Peak Power Meter	ML2495A	0824006	May 04, 2011	May 03, 2012
Power Sensor	MA2411B	0738172	May 03, 2011	May 02, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
1	2412	15.3	16.9	17.8	143.1	21.6	28.6	PASS
6	2437	16.1	16.1	18.0	144.6	21.6	28.6	PASS
11	2462	15.9	17.1	18.1	154.8	21.9	28.6	PASS

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$$

$$\text{Effective Legacy Gain (dBi)} = 7.4$$

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
1	2412	21.3	22.3	23.0	504.2	27.0	28.6	PASS
6	2437	21.1	21.6	23.0	472.9	26.7	28.6	PASS
11	2462	21.4	21.9	23.2	501.9	27.0	28.6	PASS

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$$

$$\text{Effective Legacy Gain (dBi)} = 7.4$$

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
1	2412	21.5	21.5	22.5	460.3	26.6	30	PASS
6	2437	21.2	21.7	23.0	479.3	26.8	30	PASS
11	2462	21.1	21.8	23.1	484.4	26.9	30	PASS

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
3	2422	22.2	23.3	23.3	593.6	27.7	30	PASS
6	2437	23.6	23.5	24.6	741.4	28.7	30	PASS
9	2452	22.6	23.0	23.2	590.4	27.7	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
1	2412	-8.9	-7.9	-10.3	-4.2	6.6	PASS
6	2437	-10.8	-13.2	-11.6	-7.0	6.6	PASS
11	2462	-9.3	-8.3	-10.0	-4.4	6.6	PASS


Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.4

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

For CHAIN(1)

CH1



802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
1	2412	-15.2	-14.2	-11.9	-8.8	6.6	PASS
6	2437	-15.4	-14.0	-12.8	-9.2	6.6	PASS
11	2462	-14.4	-15.8	-14.0	-9.9	6.6	PASS


Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.4

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

For CHAIN(2)

CH1




802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
1	2412	-15.2	-13.1	-13.7	-9.1	8	PASS
6	2437	-15.4	-13.4	-15.1	-9.8	8	PASS
11	2462	-15.7	-15.0	-13.1	-9.7	8	PASS

For CHAIN(2)

CH11




802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
3	2422	-20.2	-18.9	-19.6	-14.8	8	PASS
6	2437	-16.8	-16.9	-14.4	-11.1	8	PASS
9	2452	-18.1	-18.2	-18.8	-13.6	8	PASS

For CHAIN(2)

CH6



4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100MHz or 200MHz bandwidth from band edge. The band edges were measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



4.6.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).



Performing measurements: Measure and add 10 log(N) dB

802.11b DSSS MODULATION:

CH1





CH11





802.11g OFDM MODULATION:

CH1





CH11





802.11n (20MHz) OFDM MODULATION:

CH1





CH11





802.11n (40MHz) OFDM MODULATION:

CH3



CH9



5. TEST TYPES AND RESULTS (5725~5850MHz Band)

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.1.2 TEST INSTRUMENTS

Test date: Oct. 08 to 12, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 09, 2011	Mar. 08, 2012
Line-Impedance Stabilization Network (for EUT)	ENV216	100072	June 10, 2011	June 09, 2012
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Nov. 03, 2010	Nov. 02, 2011
RF Cable (JYEBAO)	5DFB	COCCAB-002	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	3	Nov. 03, 2010	Nov. 02, 2011
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
- 3 The VCCI Con C Registration No. is C-3611.


5.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.1.6 EUT OPERATING CONDITIONS


Same as the 4.1.6

5.1.7 TEST RESULTS (Mode 1)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.09	59.94	46.76	60.03	46.85	64.98	54.98	-4.95	-8.13
2	0.189	0.10	55.16	37.43	55.26	37.53	64.08	54.08	-8.82	-16.55
3	0.224	0.10	50.72	35.44	50.82	35.54	62.66	52.66	-11.84	-17.12
4	0.373	0.11	41.92	26.65	42.03	26.76	58.44	48.44	-16.41	-21.68
5	0.494	0.12	38.70	26.49	38.82	26.61	56.10	46.10	-17.29	-19.50
6	4.402	0.34	28.17	18.73	28.51	19.07	56.00	46.00	-27.49	-26.93


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.08	54.59	38.75	54.67	38.83	65.18	55.18	-10.51	-16.35
2	0.228	0.09	47.65	36.07	47.74	36.16	62.52	52.52	-14.78	-16.36
3	0.373	0.11	42.57	28.41	42.68	28.52	58.44	48.44	-15.76	-19.92
4	0.482	0.11	39.88	28.70	39.99	28.81	56.30	46.30	-16.31	-17.49
5	4.246	0.25	31.60	23.43	31.85	23.68	56.00	46.00	-24.15	-22.32
6	20.840	0.68	22.22	17.11	22.90	17.79	60.00	50.00	-37.10	-32.21

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




5.1.8 TEST RESULTS (Mode 2)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.09	42.47	27.48	42.56	27.57	66.00	56.00	-23.44	-28.43
2	0.189	0.10	48.49	40.92	48.59	41.02	64.08	54.08	-15.49	-13.06
3	0.236	0.10	41.20	34.42	41.30	34.52	62.24	52.24	-20.94	-17.72
4	0.279	0.10	37.76	29.18	37.86	29.28	60.85	50.85	-22.98	-21.56
5	3.684	0.30	38.86	32.87	39.16	33.17	56.00	46.00	-16.84	-12.83
6	4.242	0.33	38.35	32.54	38.68	32.87	56.00	46.00	-17.32	-13.13


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.07	42.53	28.47	42.60	28.54	66.00	56.00	-23.40	-27.46
2	0.185	0.09	48.67	40.14	48.76	40.23	64.25	54.25	-15.50	-14.03
3	0.236	0.09	41.36	34.10	41.45	34.19	62.24	52.24	-20.78	-18.04
4	0.279	0.10	38.19	29.31	38.29	29.41	60.85	50.85	-22.56	-21.44
5	2.887	0.20	29.83	22.06	30.03	22.26	56.00	46.00	-25.97	-23.74
6	4.086	0.24	42.19	39.05	42.43	39.29	56.00	46.00	-13.57	-6.71

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



5.2 RADIATED EMISSION MEASUREMENT

5.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. Section 15.205 restricted bands of operation shall compliance with the limits in Section 15.209.

5.2.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250253	Aug. 29, 2011	Aug. 28, 2012
Agilent Pre-Selector	N9039A	MY46520310	Aug. 29, 2011	Aug. 28, 2012
Agilent Signal Generator	N5181A	MY49060347	July 25, 2011	July 24, 2012
LIG NEX1 Test Receiver	ER-265	L09068005	Oct. 25, 2010	Oct. 24, 2011
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02465	Feb. 28, 2011	Feb. 27, 2012
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	Nov. 16, 2010	Nov. 15, 2011
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Apr. 14, 2011	Apr. 13, 2012
AISI Horn Antenna	AIH.8018	0000220091110	Nov. 22, 2010	Nov. 21, 2011
SCHWARZBECK Horn Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-205 RF104-207 RF104-202	Dec. 28, 2010	Dec. 27, 2011
RF Cable	NA	CHHCAB_001	Oct. 17, 2010	Oct. 16, 2011
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in 966 Chamber No. H.
 4. The FCC Site Registration No. is 797305.
 5. The CANADA Site Registration No. is IC 7450H-3.

5.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meters chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation

5.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.2.6 EUT OPERATING CONDITIONS

Same as the 5.1.6

5.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : 802.11a OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 71%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	106.74	32.5 QP	43.5	-11.0	1.74 H	75	22.19	10.35
2	120.99	29.8 QP	43.5	-13.7	1.76 H	263	17.33	12.47
3	202.00	33.0 QP	43.5	-10.5	1.24 H	81	21.72	11.28
4	382.00	38.5 QP	46.0	-7.5	1.00 H	38	21.60	16.94
5	750.20	36.7 QP	46.0	-9.3	1.00 H	98	13.41	23.27
6	994.00	40.3 QP	54.0	-13.7	1.26 H	359	13.31	26.95
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.10	38.8 QP	40.0	-1.2	1.01 V	317	25.20	13.61
2	118.00	35.0 QP	43.5	-8.5	1.01 V	5	22.89	12.08
3	191.00	32.2 QP	43.5	-11.3	1.25 V	0	20.27	11.89
4	625.02	41.3 QP	46.0	-4.7	1.01 V	72	19.59	21.73
5	743.00	34.0 QP	46.0	-12.0	1.24 V	183	10.90	23.11
6	874.00	32.9 QP	46.0	-13.1	1.01 V	359	7.42	25.45

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

ABOVE 1GHz WORST-CASE DATA

802.11a OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	110.6 PK			1.33 H	355	67.90	42.70
2	*5745.00	101.2 AV			1.33 H	355	58.50	42.70
3	11490.00	57.3 PK	74.0	-16.7	1.54 H	321	7.99	49.31
4	11490.00	46.9 AV	54.0	-7.1	1.54 H	321	-2.41	49.31
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	115.4 PK			1.34 V	273	72.70	42.70
2	*5745.00	109.3 AV			1.34 V	273	66.60	42.70
3	11490.00	57.3 PK	74.0	-16.7	1.31 V	261	7.99	49.31
4	11490.00	47.4 AV	54.0	-6.6	1.31 V	261	-1.91	49.31

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.
 6. The limit value is defined as per 15.247.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	110.3 PK			1.33 H	243	67.54	42.76
2	*5785.00	101.5 AV			1.33 H	243	58.74	42.76
3	11570.00	57.2 PK	74.0	-16.8	1.56 H	341	7.82	49.38
4	11570.00	46.3 AV	54.0	-7.7	1.56 H	341	-3.08	49.38
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	120.3 PK			1.35 V	241	77.54	42.76
2	*5785.00	110.6 AV			1.35 V	241	67.84	42.76
3	11570.00	57.3 PK	74.0	-16.7	1.29 V	269	7.92	49.38
4	11570.00	47.2 AV	54.0	-6.8	1.29 V	269	-2.18	49.38

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	110.6 PK			1.34 H	242	67.78	42.82
2	*5825.00	101.7 AV			1.34 H	242	58.88	42.82
3	11650.00	58.3 PK	74.0	-15.7	1.53 H	331	8.95	49.35
4	11650.00	46.2 AV	54.0	-7.8	1.53 H	331	-3.15	49.35
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	118.4 PK			1.31 V	284	75.58	42.82
2	*5825.00	108.6 AV			1.31 V	284	65.78	42.82
3	11650.00	57.6 PK	74.0	-16.4	1.34 V	346	8.25	49.35
4	11650.00	47.5 AV	54.0	-6.5	1.34 V	346	-1.85	49.35

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. The limit value is defined as per 15.247.

802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 149	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	112.6 PK			1.41 H	213	69.90	42.70
2	*5745.00	101.7 AV			1.41 H	213	59.00	42.70
3	11490.00	57.4 PK	74.0	-16.6	1.42 H	309	8.09	49.31
4	11490.00	46.3 AV	54.0	-7.7	1.42 H	309	-3.01	49.31
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	119.3 PK			1.36 V	321	76.60	42.70
2	*5745.00	109.6 AV			1.36 V	321	66.90	42.70
3	11490.00	58.4 PK	74.0	-15.6	1.31 V	324	9.09	49.31
4	11490.00	48.6 AV	54.0	-5.4	1.31 V	324	-0.71	49.31

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.
 6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 157	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	111.7 PK			1.40 H	263	68.94	42.76
2	*5785.00	101.2 AV			1.40 H	263	58.44	42.76
3	11570.00	58.4 PK	74.0	-15.6	1.43 H	254	9.02	49.38
4	11570.00	46.4 AV	54.0	-7.6	1.43 H	254	-2.98	49.38
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	119.4 PK			1.34 V	306	76.64	42.76
2	*5785.00	109.3 AV			1.34 V	306	66.54	42.76
3	11570.00	57.2 PK	74.0	-16.8	1.30 V	312	7.82	49.38
4	11570.00	47.1 AV	54.0	-6.9	1.30 V	312	-2.28	49.38

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 165	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	110.9 PK			1.33 H	265	68.08	42.82
2	*5825.00	101.6 AV			1.33 H	265	58.78	42.82
3	11650.00	57.6 PK	74.0	-16.4	1.40 H	241	8.25	49.35
4	11650.00	46.2 AV	54.0	-7.8	1.40 H	241	-3.15	49.35
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	119.3 PK			1.39 V	254	76.48	42.82
2	*5825.00	109.4 AV			1.39 V	254	66.58	42.82
3	11650.00	57.4 PK	74.0	-16.6	1.36 V	351	8.05	49.35
4	11650.00	47.3 AV	54.0	-6.7	1.36 V	351	-2.05	49.35

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. The limit value is defined as per 15.247.

802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 151	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	106.4 PK			1.35 H	288	63.68	42.72
2	*5755.00	98.1 AV			1.35 H	288	55.38	42.72
3	11510.00	58.2 PK	74.0	-15.8	1.54 H	263	8.87	49.33
4	11510.00	47.1 AV	54.0	-6.9	1.54 H	263	-2.23	49.33
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	115.4 PK			1.34 V	257	72.68	42.72
2	*5755.00	105.2 AV			1.34 V	257	62.48	42.72
3	11510.00	57.3 PK	74.0	-16.7	1.31 V	263	7.97	49.33
4	11510.00	47.6 AV	54.0	-6.4	1.31 V	263	-1.73	49.33

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ”: Fundamental frequency.
 6. The limit value is defined as per 15.247.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 159	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	107.3 PK			1.31 H	284	64.53	42.77
2	*5795.00	98.4 AV			1.31 H	284	55.63	42.77
3	11590.00	57.1 PK	74.0	-16.9	1.49 H	350	7.71	49.39
4	11590.00	46.9 AV	54.0	-7.1	1.49 H	350	-2.49	49.39
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	115.3 PK			1.36 V	263	72.53	42.77
2	*5795.00	105.4 AV			1.36 V	263	62.63	42.77
3	11590.00	57.3 PK	74.0	-16.7	1.40 V	351	7.91	49.39
4	11590.00	47.7 AV	54.0	-6.3	1.40 V	351	-1.69	49.39

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ”: Fundamental frequency.
6. The limit value is defined as per 15.247.

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.3.4 DEVIATION FROM TEST STANDARD

No deviation

5.3.5 TEST SETUP



5.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.3.7 TEST RESULTS

802.11a OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
149	5745	16.12	16.36	16.12	0.5	PASS
157	5785	16.09	15.96	16.39	0.5	PASS
165	5825	15.78	16.11	15.79	0.5	PASS


For CHAIN(2)
CH157



802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
149	5745	16.10	15.75	16.97	0.5	PASS
157	5785	16.29	16.66	17.40	0.5	PASS
165	5825	16.78	16.67	17.39	0.5	PASS


For CHAIN(2)
CH157



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)		
151	5755	35.78	35.27	35.37	0.5	PASS
159	5795	35.82	36.16	35.85	0.5	PASS

For CHAIN(1)
CH159



5.4 MAXIMUM PEAK OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

5.4.2 INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Peak Power Meter	ML2495A	0824006	May 04, 2011	May 03, 2012
Power Sensor	MA2411B	0738172	May 03, 2011	May 02, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

5.4.7 TEST RESULTS

802.11a OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
149	5745	21.2	20.7	21.7	397.2	26.0	28.6	PASS
157	5785	21.0	20.9	21.7	396.8	26.0	28.6	PASS
165	5825	21.4	20.6	22.4	426.6	26.3	28.6	PASS

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.4

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
149	5745	21.9	21.2	22.9	481.7	26.8	30	PASS
157	5785	21.7	21.6	22.5	470.3	26.7	30	PASS
165	5825	22.0	21.6	22.8	493.6	26.9	30	PASS

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)			TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)				
151	5755	21.6	21.3	22.6	461.4	26.6	30	PASS
159	5795	22.2	22.0	22.7	510.7	27.1	30	PASS

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.5.7 TEST RESULTS

802.11a OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
149	5745	-14.4	-15.0	-12.5	-9.1	6.6	PASS
157	5785	-13.7	-16.4	-13.0	-9.4	6.6	PASS
165	5825	-12.4	-16.4	-11.9	-8.4	6.6	PASS


Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.4

The effective legacy gain is 7.4dBi, therefore the limit needs to reduce.

For CHAIN(2)

CH165




802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
149	5745	-15.1	-16.3	-12.2	-9.4	8	PASS
157	5785	-12.2	-16.2	-14.4	-9.2	8	PASS
165	5825	-13.0	-15.8	-13.4	-9.1	8	PASS

For CHAIN(2)

CH149




802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)			TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)	CHAIN(2)			
151	5755	-16.1	-18.4	-15.4	-11.7	8	PASS
159	5795	-16.4	-17.8	-16.0	-11.9	8	PASS

For CHAIN(2)

CH151



5.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST INSTRUMENTS

Test date: Oct. 07, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100MHz or 200MHz bandwidth from band edge. The band edges was measured and recorded.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



5.6.6 TEST RESULTS

The spectrum plots are attached on the following pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).



Performing measurements: Measure and add 10 log(N) dB

802.11a OFDM modulation

CH149





CH165





802.11n (20MHz) OFDM MODULATION:

CH149





CH165



CH151



CH159



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5.phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Email: service.adt@tw.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also



A D T

7.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---