

FCC PART 15 Subpart C
EMI MEASUREMENT AND TEST REPORT
For
Rock Industries USA INC

105-10 Northern Blvd. Corona. NY 11368

FCC ID: QXE 268A9

April 9, 2003

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: Wireless Handsfree Car Kit (Headset)
Test Engineer: Philo Zhong	
Report No.: RSZ03030306	
Test Date: March 3, 2003	
Reviewed By: _____	
Prepared By: Bay Area Compliance Lab Corp. ShenZhen Suite C, 41-D Electronics Science & Technology Building, No. 2070 Shennanzhong Rd ShenZhen, Guandong 518031, P.R. China Tel: (755) 83296449 Fax: (755) 83273756	

Note: This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 OBJECTIVE	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY	3
1.5 TEST FACILITY	3
1.6 TEST EQUIPMENT LIST	4
1.7 SUPPORT EQUIPMENT LIST AND DETAILS.....	4
2 - SYSTEM TEST CONFIGURATION	5
2.1 DESCRIPTION OF TEST CONFIGURATION.....	5
2.2 TEST SETUP BLOCK DIAGRAM	5
2.3 EQUIPMENT MODIFICATIONS.....	5
3 - CONDUCTED EMISSIONS TEST DATA	6
4 - RADIATED EMISSION DATA	7
4.1 MEASUREMENT UNCERTAINTY	7
4.2 EUT SETUP	7
4.3 SPECTRUM ANALYZER SETUP	7
4.4 TEST PROCEDURE	7
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	8
4.6 SUMMARY OF TEST RESULTS.....	8
4.7 RADIATED EMISSIONS TEST RESULT DATA	8
5 – 10K BAND EDGES TESTING	9
5.1 TEST RESULTS PASS.....	9

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *Rock Industries USA INC*'s product, model name: T268A or the "EUT" as referred to in this report is a Wireless Handsfree Car Kit.

** The test data was good for test sample only. It may have deviation for other product samples.*

1.2 Objective

This document is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 2000.

The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to, as EUT hereafter, are within the specification limits defined by FCC Title 47, Part 15, Subpart C, and 15.235.

1.3 Related Submittal(s)/Grant(s)

No Related Submittals

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 - 2000, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.5 Test Facility

The open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated electromagnetic disturbance and disturbance voltage measurement data is located in the No. 3 building JingHua Courtyard, Shennanzhong Rd ShenZhen, Guandong 518031, P.R. C, Xinmiao District, Wuhou Avenue, Chengdu City, Sichuan Province, P. R. C, and 230 Commercial St. Ste. 2, Sunnyvale, CA 94085 USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2000.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22:1997 and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
R/S	Spectrum Analyzer	FSEM	849720/019	08/05/2003
R/S	Receiver	ESCS30	828304/014	09/05/2003
HP	Amplifier	8447D	2944A09795	08/05/2003
ETS	Log Periodic Antenna	3146	9603-4421	09/05/2003
ETS	Biconical Antenna	3110B	3360	08/05/2003
Solar Electronics	LISN	TYPE 8012-50-R-24-BNC	21162	09/05/2003
Solar Electronics	LISN	TYPE 8012-50-R-25-BNC	21163	10/05/2003

***Statement of Traceability: Bay Area Compliance Laboratory Corp.** Certifies that all calibration has been performed using suitable standards traceable to the NATIONAL INSTITUTE of STANDARDS and TECHNOLOGY.

1.7 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number	FCC ID
Shenzhen Nanyan Electronic Equipment Co.,LTD	Audio Generator	NY2201	N/A	N/A

2 - SYSTEM TEST CONFIGURATION

2.1 Description of Test Configuration

The EUT was configured for testing in a typical fashion (as normally used by a typical user). The EUT was powered by interior battery; the voltage of battery is 3.6V.

2.2 Test Setup Block Diagram



2.3 Equipment Modifications

No modification(s) to the EUT were made by BACL to comply with the applicable limits.

3 - CONDUCTED EMISSIONS TEST DATA

The EUT did not have AC power source, therefore conducted emissions test was not needed.

4 - RADIATED EMISSION DATA

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

4.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup accordance with the ANSI C63.4 - 2000. The specification used was the FCC Subpart C limits.

The EUT was placed center and the back edge of the test table and connected with the Generator, which was on the left side of the EUT.

The spacing between the peripherals was 10 centimeters.

The I/O cables were draped over edge of the test table and bundle when necessary.

The audio generator output is 1KHz, 100-dB SPL, and 10cm from the microphone.

4.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR, Section 15.33, the system was tested to 1000 MHz.

The spectrum analyzer was set with the following configurations during the radiated emission test:

Start Frequency30 MHz
Stop Frequency1000 MHz
Sweep SpeedAuto
IF Bandwidth100 KHz
Video Bandwidth1 MHz
Quasi-Peak Adapter Bandwidth120 kHz
Quasi-Peak Adapter ModeNormal
Resolution Bandwidth1MHz

4.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "Qp" in the data table.

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for applicable limits. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Applicable Limit}$$

4.6 Summary of Test Results

According to the data in section 4.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, and 15.235 had the worst margin of:

-5.3 dB μ V at 99.722 MHz in the Vertical polarization, 30 – 1000MHz, 3 meters.

4.7 Radiated Emissions Test Result Data

Indicated			Table	Antenna		Correction Factor			FCC 15 Subpart C		
Frequency MHz	Ampl. dB μ V/m	Direction Degree		Height Meter	Polar H/V	Antenna dB μ V/m	Cable Loss dB μ V/m	Amp. dB	Corr. Ampl. dB μ V/m	Limit dB μ V/m	Margin dB
99.722	44.09	45	1.1	v	10.4	8.7	25	38.2	43.5	-5.3	QP
199.441	37.61	0	2.0	v	14.4	9.8	25	36.8	43.5	-6.7	QP
99.722	39.06	270	1.8	h	10.4	8.7	25	33.2	40	-6.8	QP
149.58	38.71	300	1.8	h	13.4	9.2	25	36.3	43.5	-7.2	QP
149.58	35.1	45	1.0	v	13.4	9.2	25	32.7	40	-7.3	QP
199.441	36.23	180	1.9	h	14.4	9.8	25	35.4	43.5	-8.1	QP
49.864	71.72	0	1.1	v	11.3	8.1	25	66.1	80	-13.9	Fundamental
49.864	59.68	45	1.9	h	11.3	8.1	25	54.1	80	-25.9	Fundamental

5 – 10K BAND EDGES TESTING

Requirements: Only for 49.86MHz EUT, FCC 15.235 (b), The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the 26 dB below the level of the unmodulated carrier or to the general limits in FCC 15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in FCC 15.209.

5.1 Test Results: Pass

From the point 1 and 2 of the plot, we can see the emission level is lower than the general radiated emission limits in FCC 15.209.

Refer to the attached plots.

