

# Radio Exposure Evaluation Report

**FCC ID** : QXO-AP4020  
**Equipment** : Access Point  
**Brand Name** : Extreme Networks  
**Model Name** : AP4020  
**Applicant** : Extreme Networks, Inc.  
2121 RDU Center Drive Morrisville North Carolina  
United States 27560  
**Manufacturer** : Extreme Networks, Inc.  
2121 RDU Center Drive Morrisville North Carolina  
United States 27560  
**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Jun. 27, 2024, and testing was started from Oct. 13, 2024 and completed on Dec. 06, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

  
Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



## Table of Contents

|                                                 |          |
|-------------------------------------------------|----------|
| <b>HISTORY OF THIS TEST REPORT .....</b>        | <b>3</b> |
| <b>SUMMARY OF TEST RESULT .....</b>             | <b>4</b> |
| <b>1 GENERAL DESCRIPTION .....</b>              | <b>5</b> |
| 1.1 Information.....                            | 5        |
| 1.2 Applicable Standards .....                  | 8        |
| 1.3 Testing Location .....                      | 8        |
| <b>2 MAXIMUM PERMISSIBLE EXPOSURE .....</b>     | <b>9</b> |
| 2.1 Limit of Maximum Permissible Exposure ..... | 9        |
| 2.2 RF Exposure Exempt Measurement .....        | 10       |
| 2.3 Multiple RF Sources Exposure.....           | 11       |
| 2.4 MPE Calculation Method .....                | 12       |
| 2.5 Calculated Result and Limit.....            | 13       |
| <b>Photographs of EUT V01</b>                   |          |

## History of this test report

[illegible]



## Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items          | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2             | -               | Exposure evaluation | PASS               | -      |

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

None

**Reviewed by:** Barry Hsiao

**Report Producer:** Michelle Tsai

# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

| RF General Information |                                                  |                                                  |                                                                                                                                                                                                                                                                        |
|------------------------|--------------------------------------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode        | Frequency Range (MHz)                            | Operating Frequency (MHz)                        | Modulation Type                                                                                                                                                                                                                                                        |
| 2.4GHz WLAN            | 2400-2483.5                                      | 2412-2462                                        | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM) |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5470-5725<br>5725-5850 | 5180-5240<br>5260-5320<br>5500-5720<br>5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)                        |
| 6GHz WLAN              | 5925-6425<br>6525-6875                           | 5955-6415<br>6535-6855                           | 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)                                                                                        |
| Bluetooth              | 2400-2483.5                                      | 2402-2480                                        | LE: DSSS (GFSK)                                                                                                                                                                                                                                                        |

**1.1.2 Antenna Information**

| Ant. | Brand   | Model Name   | Antenna Type | Connector | Support    | Radio         |
|------|---------|--------------|--------------|-----------|------------|---------------|
| 1    | Sercomm | 6172005QWA01 | PIFA         | I-Pex     | 2.4G+5G    | Radio 1_2.4G  |
|      |         |              |              |           |            | Radio 2_5G    |
| 2    | Sercomm | 6172005QWA02 | PIFA         | I-Pex     | 2.4G+5G    | Radio 1_2.4G  |
|      |         |              |              |           |            | Radio 2_5G    |
| 3    | Sercomm | 6172005QWA04 | PIFA         | I-Pex     | 5G         | Radio 3_5G    |
| 4    | Sercomm | 6172005QWA05 | PIFA         | I-Pex     | 5G         | Radio 3_5G    |
| 5    | Sercomm | 6172005QWA06 | PIFA         | I-Pex     | 6G         | Radio 3_6G    |
| 6    | Sercomm | 6172005QWA07 | PIFA         | I-Pex     | 6G         | Radio 3_6G    |
| 7    | Sercomm | 6172005QWA03 | PIFA         | I-Pex     | 2.4G+5G+6G | Radio 1_Scan  |
| 8    | Sercomm | 6172005QWA08 | PIFA         | I-Pex     | BT         | BLE_chain 0   |
| 9    | Sercomm | 6172005QWA09 | PIFA         | I-Pex     | BT         | BLE_chain 1_H |
| 10   | Sercomm | 6172005QWA10 | PIFA         | I-Pex     | BT         | BLE_chain 1_V |
| 11   | Sercomm | 6172005QWA11 | PIFA         | I-Pex     | GPS        | N/A           |

| Ant. | Port | Gain (dBi) |        |         |         |        |        |        |        |        |               |                 |                 |
|------|------|------------|--------|---------|---------|--------|--------|--------|--------|--------|---------------|-----------------|-----------------|
|      |      | 2.4G       | 5G     |         |         |        | 6G     |        |        |        | BT<br>chain 0 | BT<br>chain 1_H | BT<br>chain 1_V |
|      |      |            | UNII-1 | UNII-2A | UNII-2C | UNII-3 | UNII-5 | UNII-6 | UNII-7 | UNII-8 |               |                 |                 |
| 1    | 1    | 1.53       | 2.94   | 3.56    | 4.68    | 5.34   | -      | -      | -      | -      | -             | -               | -               |
| 2    | 2    | 1.36       | 2.3    | 2.23    | 2.37    | 2.92   | -      | -      | -      | -      | -             | -               | -               |
| 3    | 1    | -          | 3.49   | 3.73    | -       | -      | -      | -      | -      | -      | -             | -               | -               |
| 4    | 2    | -          | 2.69   | 2.56    | -       | -      | -      | -      | -      | -      | -             | -               | -               |
| 5    | 1    | -          | -      | -       | -       | -      | 5.48   | 5.28   | 5.85   | 4.31   | -             | -               | -               |
| 6    | 2    | -          | -      | -       | -       | -      | 2.82   | 2.9    | 2.64   | 2.43   | -             | -               | -               |
| 7    | 1    | 2.22       | 3.14   | 3.33    | 3.41    | 4.5    | 5.35   | 4.73   | 4.59   | 4.69   | -             | -               | -               |
| 8    | 1    | -          | -      | -       | -       | -      | -      | -      | -      | -      | 1.58          | -               | -               |
| 9    | 1    | -          | -      | -       | -       | -      | -      | -      | -      | -      | -             | 2.24            | -               |
| 10   | 2    | -          | -      | -       | -       | -      | -      | -      | -      | -      | -             | -               | 1.8             |

| Composite Gain (dBi) |          |      |        |         |         |        |        |        |        |        |
|----------------------|----------|------|--------|---------|---------|--------|--------|--------|--------|--------|
| Ant.                 |          | 2.4G | UNII-1 | UNII-2A | UNII-2C | UNII-3 | UNII-5 | UNII-6 | UNII-7 | UNII-8 |
| 1~2                  | DG [1SS] | 1.55 | 3.19   | 4.6     | 5.41    | 5.34   | -      | -      | -      | -      |
|                      | DG [2SS] | 1.53 | 2.94   | 3.56    | 4.68    | 5.34   | -      | -      | -      | -      |
| 3~4                  | DG [1SS] | -    | 5.77   | 5.82    | -       | -      | -      | -      | -      | -      |
|                      | DG [2SS] | -    | 3.49   | 3.73    | -       | -      | -      | -      | -      | -      |
| 5~6                  | DG [1SS] | -    | -      | -       | -       | -      | 5.58   | 5.33   | 5.93   | 5.02   |
|                      | DG [2SS] | -    | -      | -       | -       | -      | 5.48   | 5.28   | 5.85   | 4.31   |

Note 1: The EUT has eleven antennas.

Note 2: The composite gain is derived as KDB 662911 D03 v01 which was used as directional gain. For more detail information, please refer to the Antenna Pattern Report AP462705.

**For 2.4GHz function:**

For IEEE 802.11 b/g/n/VHT/ax/be mode (1TX/2RX) (Radio 1)

Ant. 1 (port 1) could transmit/receive.

For IEEE 802.11 b/g/n/VHT/ax/be mode (2TX/2RX) (Radio 1)

Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

For b20, g20 mode (1TX/1RX) (Radio 1\_Scan)

Ant. 7 (port 1) could transmit/receive.

**For 5GHz function:**

For IEEE 802.11 a/n/ac/ax/be mode (1TX/2RX) (Radio 2)

Ant. 1 (port 1) could transmit/receive.

For IEEE 802.11 a/n/ac/ax/be mode (2TX/2RX) (Radio 2)

Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac/ax/be mode (1TX/2RX) (Radio 3)

Ant. 3 (port 1) could transmit/receive.

For IEEE 802.11 a/n/ac/ax/be mode (2TX/2RX) (Radio 3)

Ant. 3 (port 1) and Ant. 4 (port 2) could transmit/receive simultaneously.

For a20, a40, a80, a160 (1TX/1RX) (Radio 1\_Scan)

Ant. 7 (port 1) could transmit/receive.

**For BT function:**

For IEEE 802.15.1 Bluetooth mode (1TX/1RX) (Chain 0)

Ant. 8 (port 1) could transmit/receive.

For IEEE 802.15.1 Bluetooth mode (1TX/2RX) (Chain 1)

Ant. 9 (port 1) or Ant. 10 (port 2) could transmit/receive

Support diversity function and pre-tested on each single chain, the worst case was Ant. 10 (port 2) and it was recorded in this test report.

**For 6GHz function:**

For IEEE 802.11 a/ax/be mode (1TX/2RX) (Radio3)

Ant. 5 (port 1) could transmit/receive.

For IEEE 802.11 a/ax/be mode (2TX/2RX) (Radio 3)

Ant. 5 (port 1) and Ant. 6 (port 2) could transmit/receive simultaneously.

For 11a20, 11a40, 11a80, 11a160 (1RX) (Radio 1\_Scan)

Ant. 7 (port 1) could receive.

## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

## 1.3 Testing Location

| Test Lab. : Sporton International Inc. Hsinhua Laboratory |                             |                                                                                         |                     |
|-----------------------------------------------------------|-----------------------------|-----------------------------------------------------------------------------------------|---------------------|
| <input checked="" type="checkbox"/>                       | Hsinhua<br>(TAF: 3785)      | ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)          |                     |
|                                                           |                             | TEL: 886-3-327-3456                                                                     | FAX: 886-3-327-0973 |
| Test site Designation No. TW3785 with FCC.                |                             |                                                                                         |                     |
| <input type="checkbox"/>                                  | Wen 33rd.St.<br>(TAF: 3785) | ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) |                     |
|                                                           |                             | TEL: 886-3-318-0787                                                                     | FAX: 886-3-318-0287 |
| Test site Designation No. TW0008 with FCC.                |                             |                                                                                         |                     |

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f <sup>2</sup> )*                 | 6                                                                |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500              | -                                 | -                                 | F/300                                    | 6                                                                |
| 1500-100,000          | -                                 | -                                 | 5                                        | 6                                                                |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30                                                               |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                   | 30                                                               |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30                                                               |
| 300-1500              | -                                 | -                                 | F/1500                                   | 30                                                               |
| 1500-100,000          | -                                 | -                                 | 1.0                                      | 30                                                               |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

#### Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode:

1. Radio 1:2.4G+Radio 2:5G Full+Radio 3:6G Full+Bluetooth(chain0)
2. Radio 1:2.4G+Radio 2:5G High(Band3/4)+Radio 3:5G Low(Band1/2)+Bluetooth(chain0)
3. Radio 1:2.4G+Radio 2:5G Full+Radio 3:6G Full+Bluetooth(chain1)
4. Radio 1:2.4G+Radio 2:5G High(Band3/4)+Radio 3:5G Low(Band1/2)+Bluetooth(chain1)

## 2.2 RF Exposure Exempt Measurement

| Option | Refer Std.          | Exemption Exposure Thresholds (TL)                                                                                                                                                                                                                                                                                                                                                       |
|--------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A      | §1.1307(b)(3)(i)(A) | Available maximum time-averaged power is no more than 1 mW                                                                                                                                                                                                                                                                                                                               |
| B      | §1.1307(b)(3)(i)(B) | $P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$ |
| C      | §1.1307(b)(3)(i)(C) | $\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; <math>R &gt; \lambda / 2\pi</math></p>                                |

## 2.3 Multiple RF Sources Exposure

| Refer Std.           | Exemption Exposure Thresholds (TL)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| §1.1307(b)(3)(ii)(A) | The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| §1.1307(b)(3)(ii)(B) | $\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P<sub>th,i</sub> = the exemption threshold power ( P<sub>th</sub> ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p> |



## 2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.  
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

## 2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Non-Beamforming

2.4GHz WLAN\_Radio 1\_1T1S

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;G1D | 1.53        | 20.57          | 19.95        | 0.50              | 110.917                | 20               | B      | 3060.0         | 0.0363   |
| 2.4G;D1D | 1.53        | 19.62          | 19.00        | 0.50              | 89.125                 | 20               | B      | 3060.0         | 0.0291   |

2.4GHz WLAN\_Radio 1\_2T1S

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;G1D | 1.53        | 23.59          | 22.97        | 0.50              | 222.331                | 20               | B      | 3060.0         | 0.0727   |
| 2.4G;D1D | 1.53        | 23.18          | 22.56        | 0.50              | 202.302                | 20               | B      | 3060.0         | 0.0661   |

2.4GHz WLAN\_Radio 1\_2T2S

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;D1D | 1.53        | 23.13          | 22.51        | 0.50              | 199.986                | 20               | B      | 3060.0         | 0.0654   |

5GHz WLAN\_Radio 2\_1T1S

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 2.94        | 18.84          | 19.63        | 0.50              | 103.039                | 20               | B      | 3060.0         | 0.0337   |
| 5.3G;D1D | 3.56        | 19.07          | 20.48        | 0.50              | 125.314                | 20               | B      | 3060.0         | 0.0410   |
| 5.6G;D1D | 4.68        | 19.60          | 22.13        | 0.50              | 183.231                | 20               | B      | 3060.0         | 0.0599   |
| 5.8G;D1D | 5.34        | 19.88          | 23.07        | 0.50              | 227.510                | 20               | B      | 3060.0         | 0.0744   |

5GHz WLAN\_Radio 2\_2T1S

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 2.94        | 22.26          | 23.05        | 0.50              | 226.464                | 20               | B      | 3060.0         | 0.0740   |
| 5.3G;D1D | 3.56        | 22.36          | 23.77        | 0.50              | 267.301                | 20               | B      | 3060.0         | 0.0874   |
| 5.6G;D1D | 4.68        | 22.55          | 25.08        | 0.50              | 361.410                | 20               | B      | 3060.0         | 0.1182   |
| 5.8G;D1D | 5.34        | 22.99          | 26.18        | 0.50              | 465.586                | 20               | B      | 3060.0         | 0.1522   |

**5GHz WLAN\_Radio 2\_2T2S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 2.94        | 22.24          | 23.03        | 0.50              | 225.424                | 20               | B      | 3060.0         | 0.0737   |
| 5.3G;D1D | 3.56        | 22.34          | 23.75        | 0.50              | 266.073                | 20               | B      | 3060.0         | 0.0870   |
| 5.6G;D1D | 4.68        | 22.49          | 25.02        | 0.50              | 356.451                | 20               | B      | 3060.0         | 0.1165   |
| 5.8G;D1D | 5.34        | 23.09          | 26.28        | 0.50              | 476.431                | 20               | B      | 3060.0         | 0.1558   |

**5GHz WLAN\_Radio 3\_1T1S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 3.49        | 19.50          | 20.84        | 0.50              | 136.144                | 20               | B      | 3060.0         | 0.0445   |
| 5.3G;D1D | 3.73        | 20.42          | 22.00        | 0.50              | 177.828                | 20               | B      | 3060.0         | 0.0581   |

**5GHz WLAN\_Radio 3\_2T1S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 3.49        | 22.51          | 23.85        | 0.50              | 272.270                | 20               | B      | 3060.0         | 0.0890   |
| 5.3G;D1D | 3.73        | 23.23          | 24.81        | 0.50              | 339.625                | 20               | B      | 3060.0         | 0.1110   |

**5GHz WLAN\_Radio 3\_2T2S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 3.49        | 22.60          | 23.94        | 0.50              | 277.971                | 20               | B      | 3060.0         | 0.0909   |
| 5.3G;D1D | 3.73        | 23.27          | 24.85        | 0.50              | 342.768                | 20               | B      | 3060.0         | 0.1121   |

**6GHz WLAN\_Radio 3\_1T1S\_SPAP**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 6.2G;D1D | 5.48        | 18.22          | 21.55        | 0.50              | 160.325                | 20               | C      | 768.007        | 0.2088   |
| 6.7G;D1D | 5.85        | 17.54          | 21.24        | 0.50              | 149.279                | 20               | C      | 768.007        | 0.1944   |

**6GHz WLAN\_Radio 3\_2T1S\_SPAP**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 6.2G;D1D | 5.48        | 19.18          | 22.51        | 0.50              | 199.986                | 20               | C      | 768.007        | 0.2605   |
| 6.7G;D1D | 5.85        | 18.69          | 22.39        | 0.50              | 194.536                | 20               | C      | 768.007        | 0.2534   |

**6GHz WLAN\_Radio 3\_2T2S\_SPAP**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 6.2G;D1D | 4.35        | 20.46          | 22.66        | 0.50              | 207.014                | 20               | C      | 768.007        | 0.2696   |
| 6.7G;D1D | 4.54        | 20.34          | 22.73        | 0.50              | 210.378                | 20               | C      | 768.007        | 0.2740   |

**Bluetooth\_chain 0**

| Mode       | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|------------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;BT-LE | 1.58        | 11.92          | 11.35        | 0.50              | 15.311                 | 20               | B      | 3060.0         | 0.0050   |

**Bluetooth\_chain 1**

| Mode       | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|------------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;BT-LE | 1.80        | 11.69          | 11.34        | 0.50              | 15.276                 | 20               | B      | 3060.0         | 0.0050   |

**Beamforming****2.4GHz WLAN\_Radio 1\_2T1S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 2.4G;D1D | 1.55        | 22.76          | 22.16        | 0.50              | 184.502                | 20               | B      | 3060.0         | 0.0603   |

**5GHz WLAN\_Radio 2\_2T1S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 3.19        | 22.26          | 23.30        | 0.50              | 239.883                | 20               | B      | 3060.0         | 0.0784   |
| 5.3G;D1D | 4.60        | 22.36          | 24.81        | 0.50              | 339.625                | 20               | B      | 3060.0         | 0.1110   |
| 5.6G;D1D | 5.41        | 22.55          | 25.81        | 0.50              | 427.563                | 20               | B      | 3060.0         | 0.1398   |
| 5.8G;D1D | 5.34        | 22.99          | 26.18        | 0.50              | 465.586                | 20               | B      | 3060.0         | 0.1522   |

**5GHz WLAN\_Radio 3\_2T1S**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 5.2G;D1D | 5.77        | 22.51          | 26.13        | 0.50              | 460.257                | 20               | B      | 3060.0         | 0.1505   |
| 5.3G;D1D | 5.82        | 23.23          | 26.90        | 0.50              | 549.541                | 20               | B      | 3060.0         | 0.1797   |

**6GHz WLAN\_Radio 3\_2T1S\_SPAP**

| Mode     | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up<br>ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------|-------------|----------------|--------------|-------------------|------------------------|------------------|--------|----------------|----------|
| 6.2G;D1D | 8.59        | 19.71          | 26.15        | 0.50              | 462.381                | 20               | C      | 768.007        | 0.6023   |
| 6.7G;D1D | 8.94        | 20.39          | 27.18        | 0.50              | 586.138                | 20               | C      | 768.007        | 0.7635   |

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

**Simultaneous Transmission Analysis Mode:****Radio 1:2.4G+Radio 2:5G Full+Radio 3:6G Full+Bluetooth(chain0)**

| Mode           | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------------|-------------|----------------|--------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 2.4G;G1D       | 1.53        | 23.59          | 22.97        | 0.50              | 222.331             | 20               | B      | 3060.0         | 0.0727   |
| 5.8G;D1D       | 5.34        | 23.09          | 26.28        | 0.50              | 476.431             | 20               | B      | 3060.0         | 0.1558   |
| 6.7G;D1D       | -           | -              | 27.18        | 0.50              | 586.138             | 20               | C      | 768.007        | 0.7635   |
| 2.4G;BT-LE     | 1.58        | 11.92          | 11.35        | 0.50              | 15.311              | 20               | B      | 3060.0         | 0.0050   |
| Sum TL Ratio_B | 0.2335      |                |              |                   |                     |                  |        |                |          |
| Sum TL Ratio_C | 0.7635      |                |              |                   |                     |                  |        |                |          |
| Sum Ratio      | 0.9970      |                |              |                   |                     |                  |        |                |          |
| Ratio Limit    | 1           |                |              |                   |                     |                  |        |                |          |

**Radio 1:2.4G+Radio 2:5G High(Band3/4)+Radio 3:5G Low(Band1/2)+Bluetooth(chain0)**

| Mode           | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------------|-------------|----------------|--------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 2.4G;G1D       | 1.53        | 23.59          | 22.97        | 0.50              | 222.331             | 20               | B      | 3060.0         | 0.0727   |
| 5.8G;D1D       | 5.34        | 23.09          | 26.28        | 0.50              | 476.431             | 20               | B      | 3060.0         | 0.1558   |
| 5.3G;D1D       | 5.82        | 23.23          | 26.90        | 0.50              | 549.541             | 20               | B      | 3060.0         | 0.1797   |
| 2.4G;BT-LE     | 1.58        | 11.92          | 11.35        | 0.50              | 15.311              | 20               | B      | 3060.0         | 0.0050   |
| Sum TL Ratio_B | 0.4132      |                |              |                   |                     |                  |        |                |          |
| Ratio Limit    | 1           |                |              |                   |                     |                  |        |                |          |

**Radio 1:2.4G+Radio 2:5G Full+Radio 3:6G Full+Bluetooth(chain1)**

| Mode           | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------------|-------------|----------------|--------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 2.4G;G1D       | 1.53        | 23.59          | 22.97        | 0.50              | 222.331             | 20               | B      | 3060.0         | 0.0727   |
| 5.8G;D1D       | 5.34        | 23.09          | 26.28        | 0.50              | 476.431             | 20               | B      | 3060.0         | 0.1558   |
| 6.7G;D1D       | -           | -              | 27.18        | 0.50              | 586.138             | 20               | C      | 768.007        | 0.7635   |
| 2.4G;BT-LE     | 1.80        | 11.69          | 11.34        | 0.50              | 15.276              | 20               | B      | 3060.0         | 0.0050   |
| Sum TL Ratio_B | 0.2335      |                |              |                   |                     |                  |        |                |          |
| Sum TL Ratio_C | 0.7635      |                |              |                   |                     |                  |        |                |          |
| Sum Ratio      | 0.9970      |                |              |                   |                     |                  |        |                |          |
| Ratio Limit    | 1           |                |              |                   |                     |                  |        |                |          |



Radio 1:2.4G+Radio 2:5G High(Band3/4)+Radio 3:5G Low(Band1/2)+Bluetooth(chain1)

| Mode           | DG<br>(dBi) | Power<br>(dBm) | ERP<br>(dBm) | Tolerance<br>(dB) | Tune-up ERP<br>(mW) | Distance<br>(cm) | Option | TL ERP<br>(mW) | TL Ratio |
|----------------|-------------|----------------|--------------|-------------------|---------------------|------------------|--------|----------------|----------|
| 2.4G;G1D       | 1.53        | 23.59          | 22.97        | 0.50              | 222.331             | 20               | B      | 3060.0         | 0.0727   |
| 5.8G;D1D       | 5.34        | 23.09          | 26.28        | 0.50              | 476.431             | 20               | B      | 3060.0         | 0.1558   |
| 5.3G;D1D       | 5.82        | 23.23          | 26.90        | 0.50              | 549.541             | 20               | B      | 3060.0         | 0.1797   |
| 2.4G;BT-LE     | 1.80        | 11.69          | 11.34        | 0.50              | 15.276              | 20               | B      | 3060.0         | 0.0050   |
| Sum TL Ratio_B | 0.4132      |                |              |                   |                     |                  |        |                |          |
| Ratio Limit    | 1           |                |              |                   |                     |                  |        |                |          |

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

| Option | Sum TL Ratio_B                      | Option | Sum TL Ratio_C                          | Option | Sum TL Ratio_E                                     |
|--------|-------------------------------------|--------|-----------------------------------------|--------|----------------------------------------------------|
| B      | $\sum_{i=1}^a \frac{P_i}{P_{th,i}}$ | C      | $\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$ | E      | $\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$ |

Note: The above antenna gain was declared by manufacturer.

————THE END————