



This device complies with part 15 of FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause un-desired operation.

 **CAUTION:**
This surface is hot, avoid continuous body contact and do not place this notebook on your lap while it is operating.

S/N:

REF

MADE IN CHINA
P/N:242831700004

NOTE:

- 1.Material:PC KLX 1860 T 0.254mm,
it must be approved by UL & CSA standard
- 2.Adhesive:3M467
- 3.Follow RD approval sample as standard
- 4.Color:TEXT Foreground: Pantone Cool Gray 3C
Background: Pantone Black
- 5.Label should have pressure sensitive adhesive
with protective release liner on the back side.
- 6.Label manufacturer must use a process & materials
those which have been approved by UL & CSA
- 7.Sample must approve GP standard
- 8.黏性:黏著力為2.3 以上
- 9.表面:粗糙面
- 10.貼附位置:D件
- 11.環測項目及條件.(判定標準follow "QAP-4-75-A 系統表面處理的測試規範")

A technical drawing of a rectangular structure. The top horizontal side is labeled with a length of 59.0. The left vertical side is labeled with a height of 79.0. The right vertical side has a thickness of 4.7 indicated by a dimension line. The top-left and bottom-left corners are rounded with a radius of R4.5. The top-right and bottom-right corners are also rounded with a radius of R4.5. Three '+' symbols are placed on the top and bottom horizontal segments. A red rectangular stamp is located in the bottom right corner of the drawing area.

新圖發行
舊圖作廢
R01

NOV/03/2010

8

B

8

D

E

SHEET No. 1 of 1