



FCC Part 1 Subpart I
FCC Part 2 Subpart J

RF EXPOSURE EXCLUSION REPORT

WIRELESS TRANSMITTER

MODEL NUMBER: RFMD

FCC ID: QZC-RFMD-01

REPORT NUMBER: 10583303D

ISSUE DATE: April 26, 2016

Prepared for
Elster American Meter Co LLC
2221 Industrial Rd
Nebraska City
NE, 68410-6886, USA

Prepared by
UL LLC
333 Pfingsten Rd.
Northbrook, IL 60062
TEL: (847) 272-8800



NVLAP Lab code: 100414-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	2016-04-26	Initial Issue	VS

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION.....	5
5. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	6
5.1. FCC	6

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Elster American Meter Co LLC
2221 Industrial Rd
Nebraska City, NE, 68410-6886, USA

EUT DESCRIPTION: 902-928MHz transceiver

MODEL: RFMD

SERIAL NUMBER: None

DATE TESTED: September 10, 2015 to April 5, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL LLC By:



Vincent Sabalvaro
EMC Engineer
UL LLC

Tested By:



Bart Mucha
Staff Engineer
UL LLC

2. TEST METHODOLOGY

All calculations were made in accordance with FCC KDB "447498 D01 General RF Exposure Guidance v06".

3. REFERENCES

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 333 Pfingsten Road, Northbrook, IL 60062 USA.

UL NBK is accredited by NVLAP, Laboratory Code 100414-0. The full scope of accreditation can be viewed at <http://ts.nist.gov>

5. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

5.1. FCC

SAR test exclusion in accordance with KDB 447498.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

SAR Exclusion Calculations Table for Portable Devices (separation distance < 20 cm)

Antenna	Tx	Frequency (MHz)	Average Output power		Separation distances (mm)	Calculated Threshold Value
			dBm	mW		
*Main	FHSS	902	1.16	1.31	5	0.25
**Main	FHSS	902	1.56	1.43	5	0.27

* Initial power measured during EMC testing where settings adjusted to put out maximum power.

** Accounting for additional +0.4dB based on power tolerance reported by the manufacturer.

Conclusion:

The computed value is < 3 ; therefore, this device qualifies for Standalone SAR test exclusion

END OF REPORT