

Appendix C. Maximum Permissible Exposure

1. Maximum Permissible Exposure

1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.4 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.4m, as well as the gain of the used antenna, the RF power density can be obtained.

1.3. Calculated Result and Limit

For 5GHz Band:

<For Antenna 1>:

Antenna Type : Omni Antenna

Max Conducted Power for 802.11a Ant. 1-1 + Ant. 1-2 + Ant. 1-3 : 19.66 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8	6.3096	19.6608	92.4872	0.029038	1	Complies

<For Antenna 2>:

Antenna Type : Panel Antenna

Max Conducted Power for 802.11a Draft n 20MHz Ant. 2-1 + Ant. 2-2 + Ant. 2-3 : 19.66 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
13.5	22.3872	19.6608	92.4872	0.103032	1	Complies

<For Antenna 3>:

Antenna Type : Panel Antenna

Max Conducted Power for 802.11a Draft n 20MHz Ant. 3-1 + Ant. 3-2 + Ant. 3-3 : 19.66 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
10.7	11.7490	19.6608	92.4872	0.054072	1	Complies

<For Antenna 4>:

Antenna Type : Panel Antenna

Max Conducted Power for 802.11a Draft n 20MHz Ant. 4-1 + Ant. 4-2 + Ant. 4-3 : 18.09 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
23.5	223.8721	18.0867	64.3682	0.717070	1	Complies

For 2.4GHz Band:

<For Antenna 1>:

Antenna Type : Omni Antenna

Max Conducted Power for 802.11g Ant. 1-1 + Ant. 1-2 + Ant. 1-3 : 23.64 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
6	3.9811	23.6420	231.3155	0.045824	1	Complies

<For Antenna 2>:

Antenna Type : Panel Antenna

Max Conducted Power for 802.11g Ant. 2-1 + Ant. 2-2 + Ant. 2-3 : 23.64 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
10.9	12.3027	23.6420	231.3155	0.141610	1	Complies

<For Antenna 3>:

Antenna Type : Panel Antenna

Max Conducted Power for IEEE 802.11 Draft n 20MHz Ant. 3-1 + Ant. 3-2 + Ant. 3-3 : 24.78 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8	6.3096	24.7835	300.8508	0.094459	1	Complies