

Certification of Compliance

CFR 47 Part 15 Subpart B

Test Report File No. :	05-IST-0215	Date of Issue :	June 29, 2005
Model	L750		
FCC ID	QZFCML750		
Kind of Product	LCD Monitor		
Applicant	DAEWOO Lucoms co., ltd.		
Address	Gaya-Venture B/D, 28-130, Yeongdeungpo-Dong, Yeondeungpo-Gu, Seoul, Korea		
Manufacturer	DAEWOO Lucoms co., ltd.		
Address	Gaya-Venture B/D, 28-130, Yeongdeungpo-Dong, Yeondeungpo-Gu, Seoul, Korea		

Test Result

Positive

Negative

Reviewed By



S. J. Cho / EMC Group Manager

Approved By



Joon H. Lee / Chief

Comment(s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.
- The test report with appendix consists of 16 pages.
- The test result only responds to the tested sample.
- It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.
- This equipment as for has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2003.



TABLE OF CONTENTS

Table of contents	2
Information of test laboratory, Environmental conditions, Power used, Product information	3
Descriptions of test	
Conducted Emission	4
Radiated Emission	5
Equipment Under Test	6
Summary	7

■ Test Conditions and Data - Emissions

◆ Conducted Emissions	0.15MHz - 30MHz	Applicable
Test Conditions / Data and Plots		8-10
◆ Radiated Emissions	30MHz - 1GHz	Applicable
Test Conditions / Data and Plots		11-12

Appendix	A. The Photos of Test Setup	13-14
	B. The Photos of Equipment Under Test	15-16

Note:

INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. (*FCC Filing Lab.*)

San 21-8, Goan-Ri, Baekam-Myun, Yongin-City

Kyonggi-Do, 449-860, Korea

TEL : +82 31 333 4093 FAX : +82 31 333 4094

ENVIRONMENTAL CONDITIONS

Temperature 22.3 °C

51 10/10

Atmospheric pressure 1012 mbar

POWER SUPPLY SYSTEM USED

Power supply system AC 120Vac, 60Hz

(Refer to the product information)

PRODUCT INFORMATION

FCC ID :	QZFCML750
Panel :	Size 17inch diagonal Pixel Pitch 0.264 x 0.264mm Viewing Angle 70°(Right/Left), 60°(up), 60°(down) Contrast Ratio 500:1 contrast ratio(typ) Brightness 270cd/m² brightness(typ) Color Filter RGB vertical stripe LCD Panel (Samsung) LTM170EU-L11 (6E4B24610D)
Synchronization :	Horizontal 30 - 80kHz Vertical 56 - 77Hz
Video Bandwidth :	140MHz
Max Resolution :	1280 x 1024, 75Hz
Colors :	16M Colors
Display Area :	337.9mm x 270.4mm
PC Input Signal :	Sync H/V separate (TTL) Video 15pin mini D-sub (Analog RGB) DVI-D (Digital Visual Interface-Digital)
Power Source :	IN-AC100~240Vac, 50/60Hz 1A, OUT-DC12V, 3.33A (Li Shin International Enterprise Corp)
Power Consumption :	35W
Dimension W x H x D :	386 x 398 x 190mm (with stand)

- EMC suppression device is not used during the test.
 - Please refer to user's manual


DESCRIPTIONS OF TEST

Conducted Emissions:


The measurement were performed over the frequency range of 0.15MHz to 30MHz using a $50\Omega/50\mu\text{H}$ LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" & "Average" within a bandwidth of 9KHz.

-Procedure of Test

The line-conducted facility is located inside a shielded room No.1. A 1m X 1.5m wooden table 80cm height is placed 40cm away from the vertical wall and 1.5m away from the other wall of the shielded room. The LISN are bonded to bottom of the shielded room. The EUT is located on the wooden table with distance more than 80cm from the LISN and powered from the LISN. The peripheral equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to a 1m length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating conditions. The RF output of the LISN was connected to the R/S receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using Quasi-Peak mode by manual measurement, after scanned by automatic Peak mode for frequency range from 0.15 to 30MHz. The bandwidth of the receiver was set to 10kHz. The EUT, peripheral equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.



< Side View >



< Concept Drawing >


DESCRIPTION OF TEST

Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

-Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 300MHz using S/B bi-conical antenna and 300 to 1000MHz using S/B log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made at open site with 3-meters test distance using S/B bi-log antenna or horn antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.



Equipment Under Test

EUT Type :

- Table-Top.
- Floor-Standing.
- Table-Top and Floor-Standing(Combination).

Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- Standby Mode
- Operational Condition :
 - 640x480, 75Hz
 - 800x600, 75Hz
 - 1024x768, 75Hz
 - 1280x1024, 75Hz

The test results of followings are the representative of worst case emissions for the available resolution con be adjusted.

Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Type	Brand	Serial No.
PC	T328k	HP	KRJ33800KY
Keyboard	5219	HP	BN32402948
PS/2 Mouse	MO42KO	HP	030330777
Serial Mouse	M-M28	Logitech	811308-00
Printer	A0302380	Northern Telecom	2516S60951

Connecting Interface Cables :

- Unshielded AC power cable : 1.7 m
- Unshielded AC/DC Adapter's DC line cable (with one ferrite core) : 1.5 m
- Shielded monitor's signal cable (with two ferrite core) : 1.5 m
- Unshielded PC Stereo In cable : 1.0 m
- Shielded Printer's signal cable : 1.8 m

Note :

SUMMARY

Emissions

■ Conducted Emission

The requirements are

MET

Not MET

Minimum limit margin

16.5 dB at 1.891 MHz

Maximum limit exceeding

Remarks : Limits are kept with more 3dB margin.

Find the test data in following pages 9 to 10.

■ Radiated Emission

The requirements are

MET

Not MET

Minimum limit margin

7.0 dB at 540.0 MHz

Maximum limit exceeding

Remarks : Limits are kept with more 3dB margin.

Test Mode at 1280x1024, 75Hz.

Find the test data in following page 12.

test Date

Begin of testing : June 20, 2005.

End of testing : June 25, 2005.

Prepared By

Note :

- means the test is applicable,
- is not applicable.


S.J.OH / Senior Engineer

TEST CONDITIONS AND DATA

Conducted Emissions

[Applicable]

◆ Test Equipment Used

Model Name	Description	Manufacture	Calibration Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 15, 2004	861742/018
3725/2	LISN	EMCO	Jul. 15, 2004	9101-2068
KNW-407	LISN	Hyup-Rip	Jul. 15, 2004	8-883-10
ESH 3-Z2	Pulse Limiter	Rohde & Schwarz	Jul. 15, 2004	357.8810.52

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato


◆ Test Program Scrolling "H" Characters Mode

◆ Test Date June 21, 2005

◆ Test Area Shielded room No.1

Note : *The equipment used is calibrated in regular for every year.*


Conducted Emissions



Freq. [MHz]	Measurement [dB μ V]		Limit [dB μ V]		Insertion Loss	Cable Loss	Result [dB μ V]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.189	43.2	35.5	64.1	54.1	0.2	0.5	43.9	36.2	20.2	17.9
0.252	38.4	33.0	61.7	51.7	0.2	0.5	39.1	33.7	22.6	18.0
1.891	31.5	28.9	56.0	46.0	0.1	0.5	32.1	29.5	23.9	16.5
13.473	32.7	23.6	60.0	50.0	0.1	0.7	33.5	24.4	26.5	25.6

Note :

Conducted Emissions



Freq. [MHz]	Measurement [dB μ V]		Limit [dB μ V]		Insertion Loss [dB]	Cable Loss [dB μ V]	Result [dB μ V]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.189	41.8	34.2	64.1	54.1	0.1	0.5	42.4	34.8	21.7	19.3
4.411	33.4	19.1	56.0	46.0	0.1	0.4	34.0	19.7	22.0	26.3
13.570	35.0	27.0	60.0	50.0	0.2	0.7	35.9	27.9	24.1	22.1

Note :

TEST CONDITIONS AND DATA

Radiated Emission

[Applicable]

◆ Test Equipment Used

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESVS10	Test Receiver	Rohde & Schwarz	Aug. 17, 2004	839049/004
VULB 9160	Antenna	Schwarzbeck	Jul. 10, 2004	3047

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

◆ Test Program Scrolling "H" characters Mode

◆ Test Date June 24, 2005

◆ Test Area Open site No.2


Note : The equipment used is calibrated in regular for every year.

Radiated Emissions


Mode	Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]
640x480, 75Hz	52.1	11.1	11.4	1.6	V	24.1	40.0	15.9
	541.2	13.4	17.4	6.2	H	37.0	46.0	9.0
800x600, 75Hz	51.9	14.3	11.4	1.6	V	27.3	40.0	12.7
	541.2	14.9	17.4	6.2	H	38.5	46.0	7.5
1024x768, 75Hz	51.9	15.2	11.4	1.6	V	28.2	40.0	11.8
	540.0	15.2	17.4	6.2	H	38.8	46.0	7.2
1280x1024, 75Hz	51.9	15.4	11.4	1.6	V	28.4	40.0	11.6
	68.1	11.4	9.9	1.8	V	23.1	40.0	16.9
	153.9	11.6	12.8	2.9	H	27.3	43.5	16.2
	168.5	11.7	12.3	3.0	H	27.0	43.5	16.5
	432.0	5.4	15.5	5.4	H	26.3	46.0	19.7
	540.0	15.4	17.4	6.2	H	39.0	46.0	7.0

Note:

Appendix A. The Photos of Test Setup



Conducted Emissions - Front View



Conducted Emissions - Rear View

Appendix A. The Photos of Test Setup



Radiated Emissions – Front View



Radiated Emissions – Rear View

Appendix B. The Photos of Equipment Under Test



Front View




Rear View

Appendix B. The Photos of Equipment Under Test



LCD Panel Label



EUT Label