

FCC ID PER PART 18

MEASUREMENT AND TEST REPORT

FOR

THE DESIGNERS EDGE INC.

11730 N.E. 12th Street
Bellevue, WA 98005
USA

FCC ID: QZOL2300

March 12, 2003

| | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| This Report Concerns: <input checked="" type="checkbox"/> Original Report | Equipment Type: Indoor RLF |
| Test Engineer: <u>Jerry Wang</u> | |
| Report Number: <u>R0302244</u> | |
| Test Date: <u>March 7, 2003</u> | |
| Reviewed By: <u>Hans Mellberg</u> | |
| Prepared By: Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164 | |

Note: The test report is specially limited to the use of the above client company and the product model. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government

TABLE OF CONTENTS

| | |
|-------------------------------------------------------------|----------|
| 1 - GENERAL INFORMATION | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| 1.2 OBJECTIVE | 3 |
| 1.3 RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| 1.4 TEST METHODOLOGY | 3 |
| 1.5 TEST FACILITY | 3 |
| 1.6 TEST EQUIPMENT LIST AND DETAILS..... | 4 |
| 1.7 LOCAL SUPPORT EQUIPMENT | 4 |
| 1.8 INTERFACE PORTS AND CABLING..... | 4 |
| 2 - SYSTEM TEST CONFIGURATION | 5 |
| 2.1 JUSTIFICATION | 5 |
| 2.2 EUT EXERCISE PROGRAM..... | 5 |
| 2.3 SCHEMATICS/BLOCK DIAGRAM | 5 |
| 2.4 EQUIPMENT MODIFICATIONS..... | 5 |
| 2.5 CONFIGURATION OF TEST SYSTEM..... | 6 |
| 2.6 TEST SETUP BLOCK DIAGRAM | 6 |
| 3 - CONDUCTED EMISSIONS TEST DATA | 7 |
| 3.1 MEASUREMENT UNCERTAINTY | 7 |
| 3.2 EUT SETUP | 7 |
| 3.3 EMI RECEIVER SETUP | 7 |
| 3.4 TEST PROCEDURE | 7 |
| 3.5 SUMMARY OF TEST RESULTS..... | 8 |
| 3.6 CONDUCTED EMISSIONS TEST DATA..... | 8 |

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *THE DESIGNERS EDGE INC., Model: L2300 65W* or the "EUT" as referred to in this report is an indoor light, which measures 6.5" L x 3.75" W x 3.00" H.

Note: The test data collected are from a representative production sample provided by the manufacturer.

1.2 Objective

This Following test report is prepared on behalf of *THE DESIGNERS EDGE INC.* in accordance with Part 2, Subpart J, and Part 18, Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to demonstrate compliance with FCC Part 18 limit requirements for Industrial, Scientific, and Medical Equipment.

1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

1.4 Test Methodology

All measurements contained in this report were conducted in accordance with MP-5, FCC Methods of Measurements of Radio Noise Emissions from Industrial, Scientific, and Medical Equipment. All radiated and conducted emission measurements were performed at Bay Area Compliance Laboratory Corp. (BACL). The radiated testing was performed at an antenna-to-EUT distance of 3 Meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2000 and FCC MP-5.

The Federal Communications Commission and Voluntary Control Council for Interference have the reports on file and listed under FCC as Test Firm Registration Number: 800513. The test site has been approved by the FCC and VCCI for public use and listed in the FCC Public Access Link (PAL) database.

Additionally Bay Area Compliance Laboratory Corporation (USA) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Cal. Due Date |
|-------------------|----------------------|-----------------------|---------------|---------------|
| R/S | Spectrum Analyzer | FSEM | 849720/019 | 08/05/2003 |
| HP | Receiver | PH8546A | A9704039 | 08/05/2003 |
| HP | Amplifier | 8447D | 2944A09795 | 08/05/2003 |
| ETS | Log Periodic Antenna | 3146 | 9603-4421 | 09/05/2003 |
| ETS | Biconical Antenna | 3110B | 3360 | 08/05/2003 |
| Solar Electronics | LISN | TYPE 8012-50-R-24-BNC | 21162 | 09/05/2003 |
| Solar Electronics | LISN | TYPE 8012-50-R-25-BNC | 21163 | 10/05/2003 |

1.7 Local Support Equipment

| Manufacturer | Description | Model | Serial Number | FCC ID |
|---------------------|-------------|-------|---------------|--------|
| Commercial Electric | Light | 6400K | N/A | DoC |

1.8 Interface Ports and Cabling

| Cable Description | Length (M) | From/Port | To |
|------------------------------------------|------------|-----------|----------------------|
| None-Shielded Power Cord Extension Cable | 1.6 | AC Output | WALL Light / Adapter |

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The EUT is configured for testing in a typical fashion (as normally used by a typical user).

2.2 EUT Exercise Program

The sequence used is as follows:

The EUT was switched on after being connected to the mains power supply.


2.3 Schematics/Block Diagram

The EUT's block diagram is presented in Appendix D.


2.4 Equipment Modifications

The EUT was a typical representative production sample with no modifications.

2.5 Configuration of Test System



2.6 Test Setup Block Diagram



3 - CONDUCTED EMISSIONS TEST DATA

3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties. The factors contributing to uncertainties are spectrum analyzer, amplifier, and calibration procedures, LISN etc.

Based on NIS 81, The Treatment of Uncertainty in EMI Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

3.2 EUT Setup

The measurement is performed at the **Open Area Test Site**, using the same setup per FCC MP-5 measurement procedure. The specification used was the FCC Part Subpart C 18 limits.

The EUT was placed on the center of the back edge on the test table.

The power cord extension of the EUT was connected with 120 Vac/60 Hz power source.

3.3 EMI Receiver Setup

The EMI receiver is configured during the conduction test is as follows:

| | |
|-----------------------------------|---------|
| Start Frequency | 450 kHz |
| Stop Frequency | 30 MHz |
| Sweep Speed | Auto |
| IF Bandwidth..... | 10 kHz |
| Video Bandwidth | 10 kHz |
| Quasi-Peak Adapter Bandwidth..... | 9 kHz |
| Quasi-Peak Adapter Mode | Normal |

3.4 Test Procedure

During the conducted emissions test, the power cord of the power cord extension was connected to the auxiliary outlet of the first LISN.

The six highest emissions were maximized to ensure the EUT is in compliance in all possible installation configurations.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB μ V of the specification limits). Quasi-peak readings are distinguished with a "Qp".

The EUT was tested under the normal modes during the final qualification test to represent the worst case results.

3.5 Summary of Test Results

According to the data in section 3.6, the EUT, was found to be in compliance with the FCC 18 Conducted margin for industry, scientific and medical devices, and with the worst margin reading of:

-1.9 dB μ V at 0.45 MHz at the Line mode, 0.45-30MHz

3.6 Conducted Emissions Test Data

3.6.1 Conducted Test, 0.45-30MHz.

| LINE CONDUCTED EMISSIONS | | | | FCC PART 18 | |
|--------------------------|------------|-------------|--------------|-------------|--------|
| Frequency | Amplitude | Detector | Phase | Limit | Margin |
| MHz | dB μ V | Qp/Ave/Peak | Line/Neutral | dB μ V | dB |
| 0.45 | 46.1 | QP | Line | 48 | -1.9 |
| 0.45 | 45.4 | QP | Neutral | 48 | -2.6 |
| 3.23 | 26.0 | QP | Line | 48 | -22.0 |
| 3.23 | 25.9 | QP | Neutral | 48 | -22.1 |
| 5.98 | 20.4 | QP | Line | 48 | -27.6 |
| 6.06 | 20.4 | QP | Neutral | 48 | -27.6 |

3.6.2 Plot of Conducted Emissions Test Data

The plot(s) of conducted emission test is presented in the following page as reference.

