



## Test Report

Prepared for: MICRORISC s.r.o.

Model: TR-82G

Serial Number:

Project No: p2420010

Test Results: Compliant

To

FCC Part 1.1310 / 2.1093  
and  
RSS-102: Issue 5 (March 2015)

Date of Issue: July 11, 2024

On the behalf of the applicant:

MICRORISC s.r.o.  
Prumyslova 1275  
Valdicke Predmesti  
506 01 Czech Republic

Attention of:

Martin Spiller  
Ph: +420 774 570 657  
E-Mail: spiller@microrisc.com

Prepared By:

Compliance Testing, LLC  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
ANAB Cert#: AT-2901  
FCC Site Reg. #US2901  
ISED Site Reg. #2044A-2

Reviewed / Authorized By:

John Michalowicz, Test Engineer

*This report may not be reproduced, except in full, without written permission from Compliance Testing. All results contained herein relate only to the sample tested. All samples were selected by the customer.*



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	July 11, 2024	John Michalowicz	Original Document
2.0	August 20, 2024	John Michalowicz	Updated 1mw exemption reference

*Current revision of the test report replaces any prior versions. Only the current version of the test report is valid.*

### EUT Description

<b>Model Tested:</b>	TR-82G
<b>Models Covered:</b>	TR-82GA, TR-85GA, TR-86GA, TR-86G
<b>Serial:</b>	NA
<b>Firmware:</b>	
<b>Software:</b>	4.1
<b>Description:</b>	<b>900 MHz radio module</b>
<b>Additional Information:</b>	Calculations in this report are based on measured values from the respective FCC 15.249 and RSS-210 Reports.  <b>Radio Frequency Range and Operational Info:</b> 902-928MHz <b>EUT is a module and operates off 3.3 V DC sourced from an evaluation board</b> <b>Usage: Portable</b>

**MPE Evaluation (FCC)**

This is a mobile device used in Uncontrolled Exposure environment.

**Limits Controlled Exposure**
**47 CFR 1.1310**
**Table 1, (A)**

0.3-3.0 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
3.0-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (900/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 1.0
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/300
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 5

**Limits Uncontrolled Exposure**
**47 CFR 1.1310**
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

**Test Data**

Test Frequency, MHz	902 - 928
Peak Power, Conducted, mW (P)	0.009
Antenna Gain Isotropic	2.15 dBi
Antenna Gain Numeric (G)	1.64
Antenna Type	External Omni
Distance (R)	0.5cm

The exemption limit for routine evaluation is set at 1 mW. For KDB 447498 D04  
 The EUT transmits at a level below 1 mw

**MPE Evaluation (RSS 102)**  
**EIRP Calculations**

Frequency (MHz)	Output Power (dBm)	Duty Cycle (%)	Time Averaged Power (dBm)	Antenna Gain (dB)	EIRP (dBm)	EIRP (mW)	Exemption Limit (mW)
902.24	-20.36	100	-20.36	2.15	-18.21	0.015	1.0

**6.3 SAR exemption limits**

Devices operating at or below the applicable output power levels (adjusted for tune-up tolerance) specified in table 11, based on the separation distance, are exempt from SAR evaluation. The separation distance, defined as the distance between the user and/or bystander and the antenna and/or radiating element of the device or the outer surface of the device, shall be less than or equal to 20 cm for these exemption limits to apply.

Table 11: Power limits for exemption from routine SAR evaluation based on the separation distance

Frequency (MHz)	≤ 5 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	> 50 mm (mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296
835	21	32	41	54	72	96	129	172	228	298
1900	6	10	18	33	57	92	138	194	257	323
2450	3	7	16	32	56	89	128	170	209	245
3500	2	6	15	29	50	72	94	114	134	158
5800	1	5	13	23	32	41	54	74	102	128

The exemption limit for routine evaluation is set at 1 mW.

The EUT transmits at a level below 1 mw

**The SAR measurement is not necessary.**

RSS 102 Annex C has been submitted with this Technical Brief, which shows compliance to the RF Exposure Limits in RSS 102.

**END OF TEST REPORT**