



MPE Calculations

FCC ID: R33D2
IC ID: 7848A-D2

1.0	SCOPE_____	3
2.0	REVISION LEVEL_____	3
3.0	REFERENCE DOCUMENTS_____	3
4.0	CALCULATIONS_____	4
5.0	CONCLUSION_____	4

1.0 SCOPE:

This Report Demonstrates Evaluation and Compliance to the following standards:

- 1. Code of Federal Regulations Title 47, Volume 1, Section 1.1310.**
- 2. Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) - RSS-102 Issue 3**

2.0 REVISION LEVEL:

DATE	COMMENTS	REVISION
10/10/08	Created.	1.0
08/16/10	Added RSS-102 references	2.0

3.0 REFERENCE DOCUMENTS:

- (A) Limits for Maximum Permissible Exposure (MPE). Code of Federal Regulations Title 47, Volume 1, Section 1.1310.**
- (B) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. OET Bulletin 67 Edition 97-01.**
- (C) Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) - RSS-102 Issue 3**

4.0 CALCULATIONS:

The following worst case emissions was calculated by using Method 2 below

Method 1: Based on a PPt (Peak Power Total) measurement of the total power into the antenna and the worst case antenna gain.

Effective/Equivalent Isotropic Radiated Power [EIRP] dBm = Total power into the antenna [dBm] + antenna gain [dBi]

To convert the values from dBm to mW

$$\text{mW} = 10^{\text{dBm}/10}$$

Method 2: Based on the radiated field strength measurement at 3 meters [at a calibrated OATS site, maximizing the antenna polarity and height]

The worst case radiated field Strength when measured at 3 meters at the CCL Wanship facility, was 103.1 dBμV/m, peak detection vertical polarity while in the Wi-Fi “G” mode – power level at 14

Converting the 103.1 dBμV/m at 3 meters to EIRP = 6.12 mW or 0.00612 W

After obtaining the EIRP, the Power density is calculated and compared against the FCC and IC limits.

S_{FCC} = Power density in **mW/cm²** for FCC

$$S_{\text{FCC}} = \text{EIRP}/4\pi \cdot R^2$$

EIRP = Equivalent isotropically radiated power (**mW**)

R = Distance to the center of radiation of the antenna (**20 cm**)

$$S_{\text{FCC}} = 0.0012 \text{ mW/cm}^2$$

S_{IC} = Power density in **W/m²** for IC

$$S_{\text{IC}} = \text{EIRP}/4\pi \cdot R^2$$

EIRP = Equivalent isotropically radiated power in watts (**W**)

R = Distance to the center of radiation of the antenna (**0.2 m**)

$$S_{\text{IC}} = 0.012 \text{ W/m}^2$$

5.0 CONCLUSION:

1. Based upon the limits for Maximum Permissible Exposure (MPE) given in Table 1 of reference document (A) as 1mW/cm², this device falls under the required limits.
2. Based upon the limits given in section 4.2 of the reference document (C) as 10W/m², this device falls under the required limits.