



FCC RF Test Report

APPLICANT : Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
EQUIPMENT : Smartphone
BRAND NAME : Coolpad
MODEL NAME : Coolpad 3623A
MARKETING NAME : Coolpad Tattoo
FCC ID : R38YL3623A
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 26, 2015 and testing was completed on Mar. 11, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Andy Yeh / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant.....	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test	5
1.4	Product Specification of Equipment Under Test	6
1.5	Modification of EUT	7
1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7	Testing Location	7
1.8	Applicable Standards	8
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1	Test Mode.....	9
2.2	Connection Diagram of Test System	10
2.3	Support Unit used in test configuration	10
2.4	Measurement Results Explanation Example	10
3	CONDUCTED TEST RESULT	12
3.1	Measuring Instruments.....	12
3.2	Test Setup	12
3.3	Test Result of Conducted Test.....	12
3.4	Conducted Output Power	13
3.5	Peak-to-Average Ratio	14
3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.7	Conducted Band Edge	16
3.8	Conducted Spurious Emission	17
3.9	Frequency Stability	18
4	RADIATED TEST ITEMS	19
4.1	Measuring Instruments.....	19
4.2	Test Setup	19
4.3	Test Result of Radiated Test.....	19
4.4	Effective Radiated Power and Effective Isotropic Radiated Power Measurement	20
4.5	Field Strength of Spurious Radiation Measurement	22
5	LIST OF MEASURING EQUIPMENT	23
6	UNCERTAINTY OF EVALUATION	24

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG5D2601A	Rev. 01	Initial issue of report	Mar. 22, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 37.33 dB at 7520.000 MHz



1 General Description

1.1 Applicant

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Coolpad Information Harbor, 2nd Mengxi Road, Hi-Tech Industrial Park(North), Nanshan district, Shenzhen, P.R.C

1.2 Manufacturer

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Coolpad Information Harbor, 2nd Mengxi Road, Hi-Tech Industrial Park(North), Nanshan district, Shenzhen, P.R.C

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	Coolpad
Model Name	Coolpad 3623A
Marketing Name	Coolpad Tattoo
FCC ID	R38YL3623A
EUT supports Radios application	CDMA/EV-DO/WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v2.1 + EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 99000773338079 Radiation: 99000773338062 ERP&EIRP: 99000773338059
HW Version	P1
SW Version	051.00.160215
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	CDMA2000: BC0: 824.70 MHz ~ 848.31 MHz BC1: 1851.25 MHz ~ 1908.75 MHz
Rx Frequency	CDMA2000: BC0: 869.70 MHz ~ 893.31 MHz BC1: 1931.25 MHz ~ 1988.75 MHz
Maximum Output Power to Antenna	CDMA2000: BC0: 23.80 dBm BC1: 21.87 dBm
Antenna Type	PIFA Antenna
Type of Modulation	CDMA2000 1xRTT: QPSK CDMA2000 1xEV-DO: QPSK/8PSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	CDMA2000 BC0 1xRTT	QPSK	0.1242	0.0167 ppm	1M27F9W
Part 24	CDMA2000 BC1 1xRTT	QPSK	0.3296	0.0138 ppm	1M28F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-SZ	831040

Note: The test site complies with ANSI C63.4 2009 requirement.



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.


Radiated emissions were investigated from 30 MHz to 10th harmonic.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
CDMA BC0	■ 1xRTT Link	■ 1xRTT Link
CDMA BC1	■ 1xRTT Link	■ 1xRTT Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
3.	iPod Earphone	Apple	MC690ZP/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.



Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.5 + 10 = 14.5 (dB)

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~40GHz	Jan. 12, 2016	Mar. 01, 2016~ Mar. 11, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Mar. 01, 2016~ Mar. 11, 2016	Aug. 06, 2016	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May. 26, 2015	Mar. 05, 2016	May.25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz;Max 30dBm	Jun. 07, 2015	Mar. 05, 2016	Jun. 06, 2016	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz-2GHz	Oct. 17, 2015	Mar. 05, 2016	Oct. 16, 2016	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 17, 2015	Mar. 05, 2016	Oct. 16, 2016	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2015	Mar. 05, 2016	Jul. 17, 2016	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Aug.19, 2015	Mar. 05, 2016	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	HP	8447F	3113A04622	9kHz ~1300MHz / 30 dB	Aug. 07, 2015	Mar. 05, 2016	Aug. 06, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 12, 2016	Mar. 05, 2016	Jan. 11, 2017	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Mar. 05, 2016	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 05, 2016	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 05, 2016	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8dB
---	-------



Appendix A. Test Results of Conducted Test







Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	CDMA2000 BC0			CDMA2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	23.67	23.53	23.71	21.75	21.86	21.76
1xRTT RC3 SO55	23.69	23.64	23.80	21.79	21.87	21.78
1xRTT RC3 SO32(+ F-SCH)	23.68	23.54	23.75	21.75	21.86	21.76
1xRTT RC3 SO32(+SCH)	23.66	23.53	23.74	21.64	21.71	21.67
1xEVDO RTAP 153.6Kbps	23.65	23.62	23.78	21.71	21.83	21.74
1xEVDO RETAP 4096Bits	23.61	23.60	23.75	21.67	21.81	21.73

**Peak-to-Average Ratio**

Mode	CDMA BC0	CDMA BC1	Limit: 13dB
Mod.	1xRTT	1xRTT	Result
Lowest CH	3.76	4.52	PASS
Middle CH	3.96	4.68	
Highest CH	4.00	4.20	




CDMA BC0 (1xRTT)	CDMA BC1 (1xRTT)																												
Lowest Channel	Lowest Channel																												
 Center 824.7 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>23.66 dBm</td></tr><tr><td>Peak</td><td>27.97 dBm</td></tr><tr><td>Crest</td><td>4.30 dB</td></tr></table> <table><tr><td>10 %</td><td>1.96 dB</td></tr><tr><td>1 %</td><td>3.20 dB</td></tr><tr><td>.1 %</td><td>3.76 dB</td></tr><tr><td>.01 %</td><td>4.08 dB</td></tr></table> Date: 1.MAR.2016 10:18:35	Mean	23.66 dBm	Peak	27.97 dBm	Crest	4.30 dB	10 %	1.96 dB	1 %	3.20 dB	.1 %	3.76 dB	.01 %	4.08 dB	 Center 1.85125 GHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>22.96 dBm</td></tr><tr><td>Peak</td><td>27.76 dBm</td></tr><tr><td>Crest</td><td>4.80 dB</td></tr></table> <table><tr><td>10 %</td><td>2.56 dB</td></tr><tr><td>1 %</td><td>3.96 dB</td></tr><tr><td>.1 %</td><td>4.52 dB</td></tr><tr><td>.01 %</td><td>4.72 dB</td></tr></table> Date: 1.MAR.2016 12:21:36	Mean	22.96 dBm	Peak	27.76 dBm	Crest	4.80 dB	10 %	2.56 dB	1 %	3.96 dB	.1 %	4.52 dB	.01 %	4.72 dB
Mean	23.66 dBm																												
Peak	27.97 dBm																												
Crest	4.30 dB																												
10 %	1.96 dB																												
1 %	3.20 dB																												
.1 %	3.76 dB																												
.01 %	4.08 dB																												
Mean	22.96 dBm																												
Peak	27.76 dBm																												
Crest	4.80 dB																												
10 %	2.56 dB																												
1 %	3.96 dB																												
.1 %	4.52 dB																												
.01 %	4.72 dB																												
Middle Channel	Middle Channel																												
 Center 836.52 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>23.59 dBm</td></tr><tr><td>Peak</td><td>28.11 dBm</td></tr><tr><td>Crest</td><td>4.51 dB</td></tr></table> <table><tr><td>10 %</td><td>2.04 dB</td></tr><tr><td>1 %</td><td>3.36 dB</td></tr><tr><td>.1 %</td><td>3.96 dB</td></tr><tr><td>.01 %</td><td>4.32 dB</td></tr></table> Date: 1.MAR.2016 10:18:51	Mean	23.59 dBm	Peak	28.11 dBm	Crest	4.51 dB	10 %	2.04 dB	1 %	3.36 dB	.1 %	3.96 dB	.01 %	4.32 dB	 Center 1.85 GHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>22.91 dBm</td></tr><tr><td>Peak</td><td>27.97 dBm</td></tr><tr><td>Crest</td><td>5.06 dB</td></tr></table> <table><tr><td>10 %</td><td>2.60 dB</td></tr><tr><td>1 %</td><td>4.04 dB</td></tr><tr><td>.1 %</td><td>4.68 dB</td></tr><tr><td>.01 %</td><td>4.96 dB</td></tr></table> Date: 1.MAR.2016 12:21:50	Mean	22.91 dBm	Peak	27.97 dBm	Crest	5.06 dB	10 %	2.60 dB	1 %	4.04 dB	.1 %	4.68 dB	.01 %	4.96 dB
Mean	23.59 dBm																												
Peak	28.11 dBm																												
Crest	4.51 dB																												
10 %	2.04 dB																												
1 %	3.36 dB																												
.1 %	3.96 dB																												
.01 %	4.32 dB																												
Mean	22.91 dBm																												
Peak	27.97 dBm																												
Crest	5.06 dB																												
10 %	2.60 dB																												
1 %	4.04 dB																												
.1 %	4.68 dB																												
.01 %	4.96 dB																												
Highest Channel	Highest Channel																												
 Center 848.31 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>23.45 dBm</td></tr><tr><td>Peak</td><td>27.76 dBm</td></tr><tr><td>Crest</td><td>4.30 dB</td></tr></table> <table><tr><td>10 %</td><td>2.00 dB</td></tr><tr><td>1 %</td><td>3.32 dB</td></tr><tr><td>.1 %</td><td>4.00 dB</td></tr><tr><td>.01 %</td><td>4.20 dB</td></tr></table> Date: 1.MAR.2016 10:19:06	Mean	23.45 dBm	Peak	27.76 dBm	Crest	4.30 dB	10 %	2.00 dB	1 %	3.32 dB	.1 %	4.00 dB	.01 %	4.20 dB	 Center 1.90875 GHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 <table><tr><td>Mean</td><td>22.67 dBm</td></tr><tr><td>Peak</td><td>27.19 dBm</td></tr><tr><td>Crest</td><td>4.52 dB</td></tr></table> <table><tr><td>10 %</td><td>2.56 dB</td></tr><tr><td>1 %</td><td>3.80 dB</td></tr><tr><td>.1 %</td><td>4.20 dB</td></tr><tr><td>.01 %</td><td>4.40 dB</td></tr></table> Date: 1.MAR.2016 12:22:08	Mean	22.67 dBm	Peak	27.19 dBm	Crest	4.52 dB	10 %	2.56 dB	1 %	3.80 dB	.1 %	4.20 dB	.01 %	4.40 dB
Mean	23.45 dBm																												
Peak	27.76 dBm																												
Crest	4.30 dB																												
10 %	2.00 dB																												
1 %	3.32 dB																												
.1 %	4.00 dB																												
.01 %	4.20 dB																												
Mean	22.67 dBm																												
Peak	27.19 dBm																												
Crest	4.52 dB																												
10 %	2.56 dB																												
1 %	3.80 dB																												
.1 %	4.20 dB																												
.01 %	4.40 dB																												

**26dB Bandwidth**

Mode	CDMA BC0	CDMA BC1
Mod.	1xRTT	1xRTT
Lowest CH	1.422	1.432
Middle CH	1.418	1.420
Highest CH	1.416	1.432

CDMA BC0 (1xRTT)


Lowest Channel



Date: 1.MAR.2016 09:40:10


CDMA BC1 (1xRTT)

Lowest Channel




Date: 1.MAR.2016 11:23:50

Middle Channel




Date: 1.MAR.2016 09:41:11

Middle Channel




Date: 1.MAR.2016 11:25:07

Highest Channel



Date: 11.MAR.2016 10:41:33


Highest Channel



Date: 1.MAR.2016 11:27:22

**Occupied Bandwidth**

Mode	CDMA BC0	CDMA BC1
Mod.	1xRTT	1xRTT
Lowest CH	1.272	1.276
Middle CH	1.272	1.276
Highest CH	1.270	1.276






Conducted Band Edge




CDMA BC0 (1xRTT)

Lowest Band Edge



Date: 2.MAR.2016 10:12:37


Highest Band Edge



Date: 1.MAR.2016 09:54:16


CDMA BC1 (1xRTT)

Lowest Band Edge



Date: 1.MAR.2016 11:52:09

Highest Band Edge



Date: 1.MAR.2016 11:54:58




Conducted Spurious Emission



CDMA BC0 (1xRTT)


Lowest Channel



Date: 1.MAR.2016 10:04:05


CDMA BC1 (1xRTT)

Lowest Channel




Date: 1.MAR.2016 11:57:02

Middle Channel




Date: 1.MAR.2016 10:06:15

Middle Channel




Date: 1.MAR.2016 11:59:01

Highest Channel



Date: 1.MAR.2016 10:08:14

Highest Channel



Date: 1.MAR.2016 12:00:23

**Frequency Stability**

Test Conditions	Middle Channel	CDMA BC0 (1xRTT)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0143	PASS
40	Normal Voltage	0.0131	
30	Normal Voltage	0.0120	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0096	
0	Normal Voltage	0.0120	
-10	Normal Voltage	0.0143	
-20	Normal Voltage	0.0155	
-30	Normal Voltage	0.0167	
20	Maximum Voltage	0.0060	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0024	



Test Conditions	Middle Channel	CDMA BC1 (1xRTT)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0138	PASS
40	Normal Voltage	0.0128	
30	Normal Voltage	0.0133	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0080	
0	Normal Voltage	0.0112	
-10	Normal Voltage	0.0117	
-20	Normal Voltage	0.0128	
-30	Normal Voltage	0.0138	
20	Maximum Voltage	0.0027	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0016	

Note:

1. Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	CDMA BC0 1xRTT	20.94	0.1242	9.24	0.0084
Middle		20.26	0.1063	8.02	0.0063
Highest		19.96	0.0992	7.76	0.0060
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	CDMA BC1 1xRTT	24.68	0.2939	25.02	0.3180
Middle		24.63	0.2905	25.18	0.3296
Highest		24.83	0.3043	24.98	0.3145
Limit	EIRP < 2W	Result		PASS	

**Radiated Spurious Emission**

CDMA BC0(1xRTT)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1673.04	-62.29	-13	-49.29	-63.90	-68.98	0.56	9.40	H
	2509.56	-61.16	-13	-48.16	-65.06	-68.86	0.75	10.60	H
	3346.08	-57.40	-13	-44.40	-66.70	-67.00	0.85	12.60	H
	1673.04	-61.30	-13	-48.30	-63.75	-67.99	0.56	9.40	V
	2509.56	-61.36	-13	-48.36	-65.74	-69.06	0.75	10.60	V
	3346.08	-59.91	-13	-46.91	-66.77	-69.51	0.85	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

CDMA BC1(1xRTT)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-55.00	-13	-42.00	-66.25	-66.73	0.87	12.60	H
	5640	-52.87	-13	-39.87	-68.75	-64.90	1.07	13.10	H
	7520	-50.33	-13	-37.33	-68.65	-59.94	1.69	11.30	H
	3760	-53.91	-13	-40.91	-66.38	-65.64	0.87	12.6	V
	5640	-52.37	-13	-39.37	-68.69	-64.40	1.07	13.1	V
	7520	-50.68	-13	-37.68	-68.9	-60.29	1.69	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.