



EMC TEST REPORT

Product Name: Smart Phone

Model Name: CP36t

FCC ID: R38YLCP36T

Issued For : Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Floor 21, Block A, Coolpad Building, Nanshan District, Shenzhen, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT24G115EM01

Sample Received Date: Jul. 17, 2024

Date of Test: Jul. 17, 2024 – Aug. 13, 2024

Date of Issue: Aug. 13, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address: Floor 21, Block A, Coolpad Building, Nanshan District, Shenzhen, China
Manufacturer: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address: Floor 21, Block A, Coolpad Building, Nanshan District, Shenzhen, China
Product Name: Smart Phone
Trademark: coolpad
Model Name: CP36t
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR Part 15 Subpart B ANSI C63.4-2014	PASS

Prepared by:

Terry Zhao

Terry Zhao
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents

1. TEST SUMMARY	5
1.1 TEST LABORATORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	8
2.3 DESCRIPTION OF THE SUPPORT UNITS	8
2.4 MEASUREMENT INSTRUMENTS LIST	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14
APPENDIX I - TEST SETUP	22
APPENDIX II - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	24



Revision History

Rev.	Issue Date	Revisions
00	Aug. 13, 2024	Initial Issue



1. TEST SUMMARY

EMC Emission				
Standard	Test Item	Limit	Judgement	Remark
FCC 47 CFR Part 15 Subpart B ANSI C63.4-2014	Conducted Emissions	Class B	PASS	
	Radiated Emissions Below 1GHz	Class B	PASS	
	Radiated Emissions Above 1GHz	Class B	PASS	Note 2

Note:

- 1 "N/A" denotes test is not applicable in this Test Report
- 2 If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.



1.1 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

Test Item	Measurement Frequency Range MHz	Uncertainty dB
Conducted Emissions at AC mains power port	0.009 ~ 30	2.80
Radiated Emissions	0.009 ~ 30	2.16
Radiated Emissions	30 ~ 1000	4.40
Radiated Emissions	1000 ~ 18000	5.49
Note: 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. 2. The measurement uncertainty is not included in the test result.		



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Smart Phone
Trademark:	coolpad
Model Name:	CP36t
Series Model:	N/A
Model Difference:	N/A
Adapter:	Input: 100-240V, 50/60Hz, 0.8A Output: 5.0V 3A, 9V 3A, 12V 2.5A, 33W Max
Battery:	Rated Capacity: 4900mAh Rated Voltage: 3.87V
Test Voltage:	AC 120V/60Hz Battery: 3.87V
Hardware Version:	H895_MB_V2
Software Version:	N/A

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operating mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Mode	Description
Mode 1	Charging+GSM link+BT+Wi-Fi+GPS+Camera recording
Mode 2	Charging+WCDMA link+BT+Wi-Fi+GPS+Camera recording
Mode 3	Charging+LTE link+BT+Wi-Fi+GPS+Camera recording
Mode 4	USB Data Transmission
Mode 5	NFC

Note: Only the data of worst-case mode 1 was recorded in this report.

2.3 DESCRIPTION OF THE SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	Shenzhen Yichengxin Electronic Technology Co., LTD	YCX-33W	N/A	Input: 100-240V, 50/60Hz, 0.8A Output: 5.0V 3A, 9V 3A, 12V 2.5A

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	HKF-16	N/A	N/A
USB-A to Micro-USB Cable	UGREEN	10848	N/A	1m, shielded, without ferrite core

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.4 MEASUREMENT INSTRUMENTS LIST

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
LISN	COM-POWER	LI-115	02032	2024.03.09	2025.03.08
LISN	SCHWARZBECK	NNLK 8122	00160	2024.03.09	2025.03.08
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2024.03.09	2025.03.08
Temperature & Humidity	KTJ	TA218B	N.A	2024.03.09	2025.03.08
Testing Software	EMC-I_V1.4.0.3_SKET				
Radiated Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
Spectrum Analyzer	Keysight	N9020A	MY50530994	2024.03.09	2025.03.08
Spectrum Analyzer	Keysight	N9010B	MY60242508	2024.08.05	2025.08.04
Active loop Antenna	ETS	6502	00049544	2023.10.13	2025.10.12
Bilog Antenna	SCHWARZBECK	VULB 9168	01447	2022.12.12	2025.12.11
Horn Antenna	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Pre-amplifier (9kHz-1GHz)	EMtrace	RP01A	02017	2024.03.09	2025.03.08
Pre-amplifier (1-26.5G)	Agilent	8449B	3008A4722	2024.03.09	2025.03.08
Antenna Tower	SAEMC	BK-4AT-BS-D	SK2021093008	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2024.03.11	2025.03.10
Testing Software	EMC-I_V1.4.0.3_SKET				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS

FREQUENCY (MHz)	Conducted Emission Limits (dBuV)			
	Class A		Class B	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.5 ~ 5	73.00	60.00	56.00	46.00
5 ~ 30	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
- (3) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor
Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item - EUT Test Photos.




3.1.3 TEST SETUP





3.1.4 TEST RESULTS


Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 26.8°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-18
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1	0.154	48.05	10.60	58.65	65.78	-7.13	QP	L1
2	0.190	46.26	10.60	56.86	64.04	-7.18	QP	L1
3	0.230	42.51	10.60	53.11	62.45	-9.34	QP	L1
4	0.290	38.82	10.60	49.42	60.52	-11.10	QP	L1
5	0.354	33.99	10.60	44.59	58.87	-14.28	QP	L1
6*	0.742	34.87	10.58	45.45	56.00	-10.55	QP	L1
7*	0.486	27.22	10.57	37.79	46.24	-8.45	AV	L1
8*	0.726	22.88	10.58	33.46	46.00	-12.54	AV	L1
9*	1.034	20.89	10.70	31.59	46.00	-14.41	AV	L1
10*	1.554	22.80	10.86	33.66	46.00	-12.34	AV	L1
11*	4.062	21.42	11.13	32.55	46.00	-13.45	AV	L1
12*	11.290	21.87	11.12	32.99	50.00	-17.01	AV	L1



Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 26.8°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-18
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1	0.190	50.30	10.60	60.90	64.04	-3.14	QP	N
2	0.230	47.84	10.60	58.44	62.45	-4.01	QP	N
3*	0.278	46.83	10.58	57.41	60.88	-3.46	QP	N
4*	0.350	44.38	10.59	54.97	58.96	-3.99	QP	N
5*	0.478	41.11	10.55	51.66	56.37	-4.72	QP	N
6	4.370	32.63	10.80	43.43	56.00	-12.57	QP	N
7*	0.214	23.20	10.57	33.77	53.05	-19.28	AV	N
8*	0.474	20.45	10.55	31.00	46.44	-15.45	AV	N
9*	0.694	20.60	10.56	31.16	46.00	-14.84	AV	N
10*	1.562	18.21	10.66	28.87	46.00	-17.13	AV	N
11*	4.470	24.62	10.82	35.44	46.00	-10.56	AV	N
12*	17.090	25.10	11.48	36.58	50.00	-13.42	AV	N



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS

Below 1 GHz

Frequency (MHz)	Class A	Class B
	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 - 88	49.5	40
88 - 216	53.9	43.5
216 - 960	56.9	46
Above 960	60	54

Above 1 GHz

Frequency (MHz)	Class A		Class B	
	Field strength (dBuV/m) (at 3m)		Field strength (dBuV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54

Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 - 108	1000
108 - 500	2000
500 - 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Note:

- (1) The limit for radiated test was performed according to FCC Part 15, Subpart B;
- (2) The tighter limit applies at the band edges;
- (3) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor,
Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use),
Margin Level = Measurement Value - Limit Value.

3.2.2 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. EUT as the center to the edge of the auxiliary device, the distance from the maximum edge to the center of the antenna is 3 meter.
- c. The height of antenna is varied from 1 meter to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meter and the rotatable table was turned from 0 degrees to 360 degree to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.



The diagram illustrates the experimental setup for measuring the radiation pattern of an Electromagnetic Under Test (EUT) in a semi-anechoic chamber. The chamber is lined with pyramidal absorbers. The EUT is placed on a turntable at a height of 0.8m, which can rotate 360°. The distance between the turntable and the antenna is 3m. The antenna is mounted on a tower and can move vertically within a range of 1m to 4m. The antenna is connected to a receiver system housed in a cabinet, which includes a Receiver, Position Controller, and Preamplifier. A computer is connected to the system for data acquisition.


The diagram illustrates a measurement setup within a Semi Anechoic Chamber. The chamber's interior walls, floor, and ceiling are lined with black pyramidal electromagnetic absorbers to eliminate reflections. A horizontal table on the left holds the Equipment Under Test (EUT) at a height of 0.8m. A vertical antenna mount on the right holds a horn antenna at a height of 1m to 4m. The horizontal distance between the EUT and the antenna is 3m. A dashed line indicates the line of sight between the EUT and the antenna, with a 360-degree rotation symbol around the EUT indicating full coverage. A computer system at the bottom center is connected to the antenna mount. To the right, a separate cabinet contains the Receiver, Position Controller, and Preamplifier, which are interconnected and connected to the antenna mount and the computer.




3.2.4 TEST RESULTS

BELOW 1GHZ

Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-19
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note: 6+128G	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	54.250	5.84	19.05	24.89	40.00	-15.11	QP	Hor
2*	91.231	14.80	15.13	29.93	43.50	-13.57	QP	Hor
3*	98.143	13.42	15.52	28.94	43.50	-14.56	QP	Hor
4*	196.113	7.87	17.34	25.21	43.50	-18.29	QP	Hor
5*	647.526	7.09	29.18	36.27	46.00	-9.73	QP	Hor
6*	990.058	5.36	34.53	39.89	54.00	-14.11	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	37.881	10.87	19.02	29.89	40.00	-10.11	QP	Ver
2*	57.039	10.22	18.85	29.07	40.00	-10.93	QP	Ver
3*	88.079	19.12	15.09	34.21	43.50	-9.29	QP	Ver
4*	196.840	14.28	17.30	31.58	43.50	-11.92	QP	Ver
5*	770.231	6.19	30.79	36.98	46.00	-9.02	QP	Ver
6*	986.784	5.55	34.51	40.06	54.00	-13.94	QP	Ver



Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-19
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note: 8+256G	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	46.975	5.48	19.28	24.76	40.00	-15.24	QP	Hor
2*	91.474	16.89	15.14	32.03	43.50	-11.47	QP	Hor
3*	97.900	15.30	15.50	30.80	43.50	-12.70	QP	Hor
4*	200.235	9.36	17.12	26.48	43.50	-17.02	QP	Hor
5*	671.291	6.13	29.47	35.60	46.00	-10.40	QP	Hor
6*	985.329	5.44	34.50	39.94	54.00	-14.06	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	47.339	11.14	19.29	30.43	40.00	-9.57	QP	Ver
2*	57.403	11.99	18.83	30.82	40.00	-9.18	QP	Ver
3*	87.715	21.39	15.09	36.48	40.00	-3.52	QP	Ver
4*	98.143	17.70	15.52	33.22	43.50	-10.28	QP	Ver
5*	199.629	14.93	17.14	32.07	43.50	-11.43	QP	Ver
6*	977.084	5.62	34.46	40.08	54.00	-13.92	QP	Ver



Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: Battery	Test Data: 2024-08-08
Test Mode: USB Data Transmission	
Note: 6+128G	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	42.853	3.48	19.29	22.77	40.00	-17.20	QP	Hor
2*	61.768	4.22	18.53	22.75	40.00	-17.20	QP	Hor
3*	153.190	3.87	19.94	23.81	43.50	-19.70	QP	Hor
4*	398.479	4.17	22.80	26.97	46.00	-19.00	QP	Hor
5*	672.625	5.34	29.48	34.82	46.00	-11.20	QP	Hor
6*	975.508	4.52	34.45	38.97	54.00	-15.00	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	59.828	5.97	18.65	24.62	40.00	-15.40	QP	Ver
2*	142.641	15.77	19.30	35.07	43.50	-8.40	QP	Ver
3*	169.680	8.95	19.79	28.74	43.50	-14.80	QP	Ver
4*	240.005	18.23	17.68	35.91	46.00	-10.10	QP	Ver
5*	463.711	6.66	24.17	30.83	46.00	-15.20	QP	Ver
6*	687.539	6.71	29.69	36.40	46.00	-9.60	QP	Ver



Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: Battery	Test Data: 2024-07-19
Test Mode: USB Data Transmission	
Note: 8+256G	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	69.528	15.87	18.05	33.92	40.00	-6.08	QP	Hor
2*	156.464	20.39	19.89	40.28	43.50	-3.22	QP	Hor
3*	228.971	25.14	17.06	42.20	46.00	-3.80	QP	Hor
4*	269.226	22.94	19.15	42.09	46.00	-3.91	QP	Hor
5*	326.941	19.45	20.74	40.19	46.00	-5.81	QP	Hor
6*	724.156	12.06	30.05	42.11	46.00	-3.89	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	71.104	14.88	17.71	32.59	40.00	-7.40	QP	Ver
2*	169.438	18.15	19.79	37.94	43.50	-5.60	QP	Ver
3*	246.674	16.10	18.05	34.15	46.00	-11.90	QP	Ver
4*	286.808	16.14	19.65	35.79	46.00	-10.20	QP	Ver
5*	299.175	15.09	19.90	34.99	46.00	-11.00	QP	Ver
6*	956.835	6.17	34.09	40.26	46.00	-5.70	QP	Ver




ABOVE 1GHZ

Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-19
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note: 6+128G	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1044.6000	62.15	-24.36	37.79	74.00	-36.21	PK	Hor
2*	1369.7000	60.85	-21.70	39.15	74.00	-34.85	PK	Hor
3*	3020.9000	53.68	-8.78	44.90	74.00	-29.10	PK	Hor
4*	5131.0000	54.17	-7.44	46.73	74.00	-27.27	PK	Hor
5*	8917.7000	54.44	-3.82	50.62	74.00	-23.38	PK	Hor
6*	14364.1000	50.52	0.72	51.24	74.00	-22.76	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1182.7000	61.34	-23.16	38.18	74.00	-35.82	PK	Ver
2*	1382.5000	61.60	-21.60	40.00	74.00	-34.00	PK	Ver
3*	2853.0000	54.28	-9.51	44.77	74.00	-29.23	PK	Ver
4*	4648.6000	54.71	-6.65	48.06	74.00	-25.94	PK	Ver
5*	8023.1000	55.92	-5.46	50.46	74.00	-23.54	PK	Ver
6*	14702.0000	50.86	0.58	51.44	74.00	-22.56	PK	Ver



Project: LGT24G115	Test Engineer: LiuH
EUT: Smart Phone	Temperature: 25.1°C
M/N: CP36t	Humidity: 50%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-07-19
Test Mode: Charging+GSM link+BT+Wi-Fi+GPS+Camera recording	
Note: 8+256G	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1093.5000	61.83	-23.94	37.89	74.00	-36.11	PK	Hor
2*	1550.4000	59.66	-20.62	39.04	74.00	-34.96	PK	Hor
3*	2931.6000	53.51	-9.12	44.39	74.00	-29.61	PK	Hor
4*	5205.4000	53.95	-7.70	46.25	74.00	-27.75	PK	Hor
5*	8922.0000	54.08	-3.81	50.27	74.00	-23.73	PK	Hor
6*	14702.0000	49.76	0.58	50.34	74.00	-23.66	PK	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1180.6000	61.38	-23.18	38.20	74.00	-35.80	PK	Ver
2*	1718.2000	59.65	-19.19	40.46	74.00	-33.54	PK	Ver
3*	2479.0000	56.09	-11.52	44.57	74.00	-29.43	PK	Ver
4*	4912.1000	53.78	-6.91	46.87	74.00	-27.13	PK	Ver
5*	8930.5000	54.33	-3.80	50.53	74.00	-23.47	PK	Ver
6*	17955.4000	49.49	2.00	51.49	74.00	-22.51	PK	Ver




APPENDIX I - TEST SETUP

Set-up for Conducted Emission on AC Mains (CE)




Set-up for Radiated Emission (RE), Below 1GHz





Set-up for Radiated Emission (RE), Above 1GHz





APPENDIX II - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please see the attached CP36t_EUT Photos.

*****END OF THE REPORT*****