

Maximum Permissible Exposure (MPE) Evaluation Report

Report No. : EME-040629
**Model No. : GateOne 500A,
GateOne 240G**
Issued Date : June 28, 2004

**Applicant : ZyGATE Communications Inc.
2F, No. 48, Lung-Chin Road, Lung-Tan, Taoyuan,
Taiwan**

**Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan**

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of ITS Laboratory. The test result in this report only applies to the tested sample.

Project Engineer

Jackey Chiu

Jackey Chiu

Reviewed By

Jerry Liu

Jerry Liu

Table of Contents

Summary of Tests	3
1. Introduction	4
2. RF Exposure Limit	4
3. RF Exposure calculations.....	5
4. Test results.....	5
4.1 GateOne 500A	5
4.2 GateOne 240G	6

Summary of Tests**MPE Evaluation meet FCC OET No. 65: 1997/ IEEE C95.1-1999**

**High Speed, Long Range-Ethernet Wireless Bridge:
GateOne 500A, GateOne 240G
FCC ID: R3N-GATEONE50A24G**

Test	Reference	Results
MPE Evaluation	FCC Guidelines for Human Exposure IEEE C95.1	Complies

1. Introduction

The EUT operates in the 5.8GHz UNII band or 2.4GHz ISM band. Due to the EUT (include antenna) at its normal operation distance is at least 20 cm from the human body, the EUT was defined as a fixed, point-to-point device.

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited Power density (S) at 20cm distance for 2.4GHz or the acceptable distance for 5GHz away from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

F= Frequency in MHz

3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is 1mW/(cm²)
Power density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.1416$

Example:

Assume a mobile device operates at 2412MHz and its maximum output power is 50mW, and the maximum gain of antenna is 1 (numeric) /0dBi.

then the power density (S) = $(50 * 1) / 4 * \pi * 20^2 = 0.00995$ (mW/cm²)

4. Test results

4.1 GateOne 500A

Test Mode: Normal mode

Channel Frequency (MHz)	Maximum antenna gain (numeric)	Output power to antenna (mW)	Calculated RF Exposure Allowable Minimum Separation Distance(cm)	Limit of power density (mW/cm ²)
5745	158.49	126.77	39.99	1.0
5785	158.49	97.27	35	1.0
5825	158.49	98.63	35.3	1.0

Test Mode: Turbo mode

Channel Frequency (MHz)	Maximum antenna gain (numeric)	Output power to antenna (mW)	Calculated RF Exposure Allowable Minimum Separation Distance(cm)	Limit of power density (mW/cm ²)
5760	158.49	99.31	35.4	1.0
5800	158.49	100.69	35.64	1.0

The Notice in Installation Manual has been stated as below:

The Flat panel antenna of EUT is fixed exclusively, point-to-point operation and is professionally installed.

4.2 GateOne 240G

Test Mode: 802.11g OFDM Modulation

Channel	Channel Frequency (MHz)	Maximum antenna gain (numeric)	Output power to antenna (mW)	Power density (mW/cm ²)	Limit of power density (mW/cm ²)
1	2412	33.19	24.21	0.159854525	1.0
6	2437	33.19	32.73	0.21611064	1.0
11	2462	33.19	29.72	0.196236121	1.0

Test Mode: 802.11g Turbo mode

Channel	Channel Frequency (MHz)	Maximum antenna gain (numeric)	Output power to antenna (mW)	Power density (mW/cm ²)	Limit of power density (mW/cm ²)
6	2437	33.19	32.73	0.21611064	1.0