

## FCC §15.247 (i), §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Standard Applicable

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Test Data

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally **numeric** gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Maximum peak output power at antenna input terminal: 15.92 (dBm)

Maximum peak output power at antenna input terminal: 39.084 (mW)

Predication distance: 20 (cm)

Predication frequency: 2449.440 (MHz)

Antenna Gain (typical): 3 (dBi)

Maximum Antenna Gain: 1.995 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0155 (mW/cm<sup>2</sup>)

MPE limit for general population exposure at predication frequency: 1.0 (mW/cm<sup>2</sup>)

### Result:

The predicted power density level at 20 cm is 0.0155 mw/cm<sup>2</sup> which is below the uncontrolled exposure limit of 1.0 mw/cm<sup>2</sup>, The EUT is used at least 20 cm away from user's body. It is determined as mobile equipment and complies with the MPE limit.