



Report No.: RZA1104-0483RF01R2



Part 22

TEST REPORT

Product Name	CDMA 1X digital mobile phone
Model Name	OT-208C
FCC ID	R5C208C
Client	Huizhou TCL Mobile Communication Co.,Ltd

TA Technology (Shanghai) Co., Ltd.



GENERAL SUMMARY

Product Name	CDMA 1X digital mobile phone	Model Name	OT-208C
FCC ID	R5C208C		
Report No.	RZA1104-0483RF01R2		
Client	Huizhou TCL Mobile Communication Co.,Ltd		
Manufacturer	Huizhou TCL Mobile Communication Co.,Ltd		
Reference Standard(s)	FCC CFR47 Part 2 (2010-12) Frequency Allocations And Radio Treaty Matters; General Rules And Regulations FCC CFR 47 Part 22H (2010-12) Public Mobile Services(850MHz) ANSI/TIA-603-C(2004) Land mobile FM or PM Communications Equipment Measurements and Performance Standards.		
Conclusion	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 2 of this test report are below limits specified in the relevant standards. General Judgment: Pass  (Stamp) Date of issue: May 3rd, 2011		
Comment	The test result only responds to the measured sample.		

Approved by 杨伟中
Yang Weizhong

Revised by 徐凯
Xu Kai

Performed by 康玲玲
Kang Lingling

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 3 of 36

TABLE OF CONTENT

1. General Information	4
1.1. Notes of the test report	4
1.2. Testing laboratory	4
1.3. Applicant Information	5
1.4. Manufacturer Information	5
1.5. Information of EUT	6
1.6. Test Date	7
2. Test Information	8
2.1. Summary of test results	8
2.2. RF Power Output	9
2.3. Effective Radiated Power	11
2.4. Occupied Bandwidth	13
2.5. Band Edge Compliance	16
2.6. Frequency Stability	19
2.7. Spurious Emissions at Antenna Terminals	21
2.8. Radiates Spurious Emission	28
3. Main Test Instruments	33
ANNEX A: EUT Appearance and Test Setup	34
A.1 EUT Appearance	34
A.2 Test Setup	36

1. General Information

1.1. Notes of the test report

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. This report only refers to the item that has undergone the test.

This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electrical report is inconsistent with the printed one, it should be subject to the latter.

1.2. Testing laboratory

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Yang Weizhong
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	yangweizhong@ta-shanghai.com

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 5 of 36

1.3. Applicant Information

Company: Huizhou TCL Mobile Communication Co.,Ltd
Address: NO.23 Zone, ZhongKai High-Technology Development Zone
City: /
Postal Code: /
Country: P.R.China
Contact: Ji Jianjun
Telephone: 86-755-33035352
Fax: 86-755-33313007

1.4. Manufacturer Information

Company: Huizhou TCL Mobile Communication Co.,Ltd
Address: NO.23 Zone, ZhongKai High-Technology Development Zone
City: /
Postal Code: /
Country: P.R.China
Telephone: 86-755-33035352
Fax: 86-755-33313007

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 6 of 36

1.5. Information of EUT

General information

Name of EUT:	CDMA 1X digital mobile phone		
MEID:	/		
Hardware Version:	SATURN-V1.1		
Software Version:	SATURN_BASE_V1.8		
Antenna Type:	Internal Antenna		
Device Operating Configurations:			
Operating Mode(s):	CDMA Cellular;(tested)		
Test Modulation:	QPSK		
Maximum E.R.P.	21.93 dBm		
Power Supply:	Battery or Charger (AC adaptor)		
Rated Power Supply Voltage:	3.7 V		
Extreme Voltage:	Minimum: 3.4 V Maximum: 4.2 V		
Extreme Temperature:	Lowest: -30°C Highest: +50°C		
Test Channel: (Low - Middle - High)	1013 - 384 - 777 (CDMA Cellular) (tested)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	CDMA Cellular	824.7 ~ 848.31	869.7 ~ 893.31

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 7 of 36

Auxiliary Equipment Details

AE1: Battery

Model:	CAB21EC000C1
Manufacture:	BYD COMPANY LIMITED
S/N:	/

Equipment Under Test (EUT) is CDMA 1X digital mobile phone with internal antenna. The EUT is tested CDMA Cellular in this report.

The sample under test was selected by the Client.

Components list please refer to documents of the manufacturer.

1.6. Test Date

The test is performed from March 31, 2011 to April 19, 2011 and April 25, 2011.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 8 of 36

2. Test Information

2.1. Summary of test results

Number	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	22.917	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 9 of 36

2.2. RF Power Output


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation (RBW=3MHz, VBW=3MHz). These measurements have been tested at following

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 0.4$ dB.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 10 of 36

Test Results

CDMA Cellular	Conducted Power(dBm)		
	Channel 1013	Channel 384	Channel 777
	824.7(MHz)	836.52(MHz)	848.31(MHz)
RC1/SO2	23.28	23.56	23.60
RC1/SO55	23.29	23.57	23.61
RC3/SO2	23.36	23.63	23.67
RC3/SO55	23.37	23.65	23.68

Note:

- 1) The maximum RF Output Power numbers are marks in bold.
- 2) The following testing are set to RC3/SO55 based on the maximum RF Output Power.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 11 of 36

2.3. Effective Radiated Power

Ambient condition


Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

The measurement procedures in TIA- 603C are used.

Step 1:

The measurement is carried out in the semi-anechoic chamber. EUT was placed on a 0.8 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations. The test setup refers to figure below.




Step 2:

A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a adjustable S.G. applied through a 30dB amplifier and a Tx cable. Then the Analyzer reading which is equal to LVL is recorded while the antenna was moving up and down. The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, Tx cable loss and the gain of the substitution antenna. The test setup refers to figure below.

TA Technology (Shanghai) Co., Ltd. Test Report

Report No.: RZA1104-0483RF01R2

Page 12 of 36



$$\text{E.R.P} = \text{S.G} + 30. - \text{Tx Cable loss} + \text{Substitution antenna gain} - 2.15.$$

$$\text{EIRP} = \text{E.R.P} + 2.15$$

Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 1.19 \text{ dB}$

Test Results: Pass

	Channel	Polarization	LVL (dBm)	SG+30 (dBm)	Gain (dBi)	Cable Loss (dBm)	E.R.P. (dBm)
CDMA Cellular	1013	Vertical	-16.38	33.91	1.06	15.17	19.83
	384	Vertical	-17.09	35.86	1.24	15.20	19.75
	777	Vertical	-15.33	37.97	1.38	15.24	21.93

Note: 1. $\text{E.R.P} = \text{S.G} + 30. - \text{Tx Cable loss} + \text{Substitution antenna gain} - 2.15.$

2. $\text{EIRP} = \text{E.R.P} + 2.15$

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 13 of 36

2.4. Occupied Bandwidth


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 30kHz, VBW is set to 300kHz in spectrum analyzer. 99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. $U = 624\text{Hz}$.

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1104-0483RF01R2

Page 14 of 36

Test Result

	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
CDMA Cellular	1013	824.7	1.3175	1.491
	384	836.52	1.3246	2.106
	777	848.31	1.3223	1.952




CDMA Cellular CH1013 Occupied Bandwidth

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1104-0483RF01R2

Page 15 of 36



CDMA Cellular CH384 Occupied Bandwidth



CDMA Cellular CH777 Occupied Bandwidth

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 16 of 36

2.5. Band Edge Compliance


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to 15kHz,VBW is set to 15kHz in spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U=0.684$ dB.

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1104-0483RF01R2

Page 17 of 36

Test Result:

	Frequency (MHz)	Reference value (dBm)	Limit	Conclusion
CDMA Cellular	824	-14.953	-13	PASS
	849	-13.952	-13	PASS



CDMA Cellular 1013 Channel

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 18 of 36



CDMA Cellular 777 Channel

2.6. Frequency Stability

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.4 V and 4.2 V, with a nominal voltage of 3.7 V.

Test setup



TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 20 of 36

Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency from the base station.

Limits	$\leq 2.5 \text{ ppm}$
--------	------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$. $U = 0.01 \text{ ppm}$.

Test Result

Temperature (°C)	Test Results (ppm) / 3.7 V Power supply
	Channel 384
-30	0.00454
-20	0.00323
-10	0.00179
0	0.00036
10	0.00120
20	0.00227
30	0.00323
40	0.00359
50	0.00383

Voltage (V)	Test Results(ppm) / 20°C
	Channel 384
3.4	0.00215
3.7	0.00227
4.2	0.00251

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 21 of 36

2.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. RBW and VBW are set to 100 kHz for the carrier frequency, or RBW and VBW are set to 1MHz (other frequency), Sweep is set to ATUO.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75 % confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB


TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 22 of 36

Test Result: PASS

CDMA Cellular CH1013




Note: The signal beyond the limit is carrier.
CDMA Cellular 1013 Channel 30MHz~1.5GHz

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 23 of 36



CDMA Cellular 1013 Channel 1.5GHz~9GHz

Harmonic	TX ch.1013 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1649.6	-50.43	-13	37.43
3	2474.1	Nf	-13	/
4	3298.8	Nf	-13	/
5	4123.5	Nf	-13	
6	4948.2	Nf	-13	/
7	5772.9	Nf	-13	/
8	6597.8	-49.60	-13	36.60
9	7422.3	Nf	-13	/
10	8247	Nf	-13	/
Nf: noise floor				


Note: The other Spurious RF conducted emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 24 of 36

CDMA Cellular CH384




Note: The signal beyond the limit is carrier.
CDMA Cellular 384 Channel 30MHz~1.5GHz

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 25 of 36



CDMA Cellular 384 Channel 1.5GHz~9GHz

Harmonic	TX ch.384 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1673.6	-50.94	-13	37.94
3	2509.56	Nf	-13	
4	3346.08	Nf	-13	/
5	4182.6	Nf	-13	/
6	5019.12	Nf	-13	/
7	5855.64	Nf	-13	/
8	6691.5	-50.13	-13	37.13
9	7528.68	Nf	-13	/
10	8365.2	Nf	-13	/

Nf: noise floor


Note: The other Spurious RF conducted emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 26 of 36

CDMA Cellular CH777




Note: The signal beyond the limit is carrier.
CDMA Cellular 777 Channel 30MHz~1.5GHz

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 27 of 36



CDMA Cellular 777 Channel 1.5GHz~9GHz

Harmonic	TX ch.777 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1697.3	-54.22	-13	41.22
3	2544.93	Nf	-13	/
4	3393.24	Nf	-13	/
5	4241.55	Nf	-13	/
6	5089.86	Nf	-13	/
7	5938.17	Nf	-13	/
8	6786.0	-50.60	-13	37.60
9	7634.79	Nf	-13	/
10	8483.1	Nf	-13	/
Nf: noise floor				

Note: The other Spurious RF conducted emissions level is no more than noise floor.

2.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement


The measurements procedures in TIA -603C are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment.

The procedure of Radiates Spurious Emission is as follows:

Step 1:

The measurement is carried out in the full-anechoic chamber.. EUT was placed on a 0.8 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations. The test setup refers to figure below.



Step 2:


A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a adjustable S.G. applied through a Tx cable. Adjust the level of the signal generator output until the value of the receiver reach the previously recorded analyzer power level (LVL). Then The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, Tx cable loss and the gain of the substitution antenna. The test setup refers to figure below.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1104-0483RF01R2

Page 29 of 36



$E.R.P \text{ (peak power)} = S.G. - Tx \text{ Cable loss} + \text{Substitution antenna gain} - 2.15.$

$EIRP = E.R.P + 2.15$

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the antenna is vertical.

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 3.16$ dB.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 30 of 36

Test Result : PASS

CDMA Cellular CH1013

Harmonic	TX ch.1013 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1649.4	/	10.15	16.1	Nf	-13	/	/
3	2474.1	/	10.25	16.5	Nf	-13	/	/
4	3300	-27.99	10.75	16.8	-34.04	-13	21.04	0
5	4123.5	/	11.35	17.2	Nf	-13	/	/
6	4948.2	/	11.95	17.4	Nf	-13	/	/
7	5772.9	/	13.55	17.6	Nf	-13	/	/
8	6597.8	-39.12	14.1	17.8	-42.82	-13	29.82	0
9	7422.3	/	14.2	18	Nf	-13	/	/
10	8247	/	14.5	18.1	Nf	-13	/	/

Note: The other Spurious RF Radiated emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 31 of 36

CDMA Cellular CH384

Harmonic	TX ch.384 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.04	/	10.15	16.1	Nf	-13	/	/
3	2509.56	/	10.25	16.5	Nf	-13	/	/
4	3345	-30.3	10.75	16.8	-36.35	-13	23.35	0
5	4182.6	/	11.35	17.2	Nf	-13	/	/
6	5019.12	/	11.95	17.4	Nf	-13	/	/
7	5855.64	/	13.55	17.6	Nf	-13	/	/
8	6692.16	/	14.1	17.8	Nf	-13	/	/
9	7528.68	/	14.2	18	Nf	-13	/	/
10	8365.2	/	14.5	18.1	Nf	-13	/	/

Note: The other Spurious RF Radiated emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 32 of 36

CDMA Cellular CH777

Harmonic	TX ch.777 Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1696.62	/	10.15	16.1	Nf	-13	/	/
3	2544.93	/	10.25	16.5	Nf	-13	/	/
4	3391.5	-22.33	10.75	16.8	-28.38	-13	15.38	0
5	4242	-39.27	11.35	17.2	-45.12	-13	32.12	135
6	5089.86	/	11.95	17.4	Nf	-13	/	/
7	5938.17	/	13.55	17.6	Nf	-13	/	/
8	6787.9	-39.2	14.1	17.8	-42.9	-13	29.86	135
9	7634.79	/	14.2	18	Nf	-13	/	/
10	8483.1	/	14.5	18.1	Nf	-13	/	/

Note: The other Spurious RF Radiated emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 33 of 36

3. Main Test Instruments

No.	Name	Type	Manufacturer	Serial Number	Calibration Date	Valid Period
01	Base Station Simulator	CMU200	R&S	118133	2010-05-27	One year
02	Signal Analyzer	FSV	R&S	100815	2010-06-28	One year
03	Signal generator	SMR27	R&S	1606.6000.02	2010-06-28	One year
04	EMI Test Receiver	ESCI	R&S	100948	2010-07-01	One year
05	Trilog Antenna	VUBL 9163	SCHWARZB ECK	9163-201	2010-06-29	Two years
06	Horn Antenna	HF907	R&S	100126	2009-07-02	Two years
07	Power Splitter	11667A	Agilent	52960	NA	NA
08	DC Power Supply	GPS-3030D	GM	E877677	NA	NA
09	Climatic Chamber	ESS-SDH401	YIN HE	2006001	NA	NA
10	Semi-Anechoic Chamber	9.6*6.7*6.6m	ETS-Lindgren	NA	NA	NA
11	EMI test software	ES-K1	R&S	NA	NA	NA

*******END OF REPORT BODY*******

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance



a: EUT

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1104-0483RF01R2

Page 35 of 36



b: Charger

Picture 1 EUT and Auxiliary

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup