



Part 22

TEST REPORT

Product Name	cdma2000 digital mobile phone
Model Name	one touch 710C
FCC ID	R5C710C
Client	Huizhou TCL Mobile Communication Co.,Ltd

TA Technology (Shanghai) Co., Ltd.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 2of 34

GENERAL SUMMARY

Product Name	cdma2000 digital mobile phone	Model Name	one touch 710C
FCC ID	R5C710C		
Report No.	RZA1110-1746RF02R2		
Client	Huizhou TCL Mobile Communication Co.,Ltd		
Manufacturer	Huizhou TCL Mobile Communication Co.,Ltd		
Reference Standard(s)	FCC CFR47 Part 2 (2010-12) Frequency Allocations And Radio Treaty Matters; General Rules And Regulations FCC CFR 47 Part 22H (2010-12) Public Mobile Services(850MHz) ANSI/TIA-603-C(2004) Land mobile FM or PM Communications Equipment Measurements and Performance Standards.		
Conclusion	This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 2 of this test report are below limits specified in the relevant standards. General Judgment: Pass (Stamp) Date of issue: November 4th,2011		
Comment	The test result only responds to the measured sample.		

Approved by 杨伟中
Director

Revised by 徐凯
RF Manager

Performed by 王峰
RF Engineer

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 3 of 34

TABLE OF CONTENT

1. General Information	4
1.1. Notes of the test report	4
1.2. Testing laboratory	4
1.3. Applicant Information	5
1.4. Manufacturer Information	5
1.5. Information of EUT	6
1.6. Test Date	7
2. Test Information	8
2.1. Summary of test results	8
2.2. RF Power Output	9
2.3. Effective Radiated Power	11
2.4. Occupied Bandwidth	14
2.5. Band Edge Compliance	17
2.6. Frequency Stability	18
2.7. Spurious Emissions at Antenna Terminals	18
2.8. Radiates Spurious Emission	18
3. Main Test Instruments	18
ANNEX A: EUT Appearance and Test Setup	18
A.1 EUT Appearance	18
A.2 Test Setup	18

1. General Information

1.1. Notes of the test report

TA Technology (Shanghai) Co., Ltd. guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at TA Technology (Shanghai) Co., Ltd. at the time of execution of the test.

TA Technology (Shanghai) Co., Ltd. is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test. This report only refers to the item that has undergone the test.

This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of **TA Technology (Shanghai) Co., Ltd.** and the Accreditation Bodies, if it applies.

If the electrical report is inconsistent with the printed one, it should be subject to the latter.

1.2. Testing laboratory

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Yang Weizhong
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	yangweizhong@ta-shanghai.com

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 5 of 34

1.3. Applicant Information

Company: Huizhou TCL Mobile Communication Co.,Ltd
Address: NO.23 Zone, ZhongKai High-Technology Development Zone
City: /
Postal Code: /
Country: P.R. China
Contact: Jianjun Ji
Telephone: 86-755-33035352
Fax: 86-755-33313007

1.4. Manufacturer Information

Company: Huizhou TCL Mobile Communication Co.,Ltd
Address: NO.23 Zone, ZhongKai High-Technology Development Zone
City: /
Postal Code: /
Country: P.R. China
Telephone: 86-755-33035352
Fax: 86-755-33313007

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 6 of 34

1.5. Information of EUT

General information

Name of EUT:	cdma2000 digital mobile phone		
MEID :	A100000864E0D4		
Hardware Version:	V1.2		
Software Version:	710C_OMH_V1.5_5		
Emission Designator	1M29F9W		
Antenna Type:	Internal Antenna		
Device Operating Configurations:			
Operating Mode(s):	CDMA Cellular; (tested)		
Test Modulation:	(CDMA)QPSK		
Maximum E.R.P.	CDMA Cellular: 20.03 dBm		
Power Supply:	Battery or Charger (AC adaptor)		
Rated Power Supply Voltage:	3.7V		
Extreme Voltage:	Minimum: 3.4V Maximum: 4.2V		
Extreme Temperature:	Lowest: -10°C Highest: +55°C		
Test Channel: (Low - Middle - High)	1013 - 384 - 777 (CDMA Cellular) (tested)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	CDMA Cellular	824.7 ~ 848.31	869.7 ~ 893.31

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 7 of 34

Auxiliary Equipment Details

AE1: Battery

Model: /
Manufacture: BYD
S/N: CAB3120000C1

AE1: Charger

Model: WIN350mA5V00_00
Manufacture: BYD
S/N: /

Equipment Under Test (EUT) is cdma2000 digital mobile phone. The EUT is tested CDMA Cellular band in this report.

The sample under test was selected by the Client.

Components list please refer to documents of the manufacturer.

1.6. Test Date

The test is performed from October 25, 2011 to October 30, 2011.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 8 of 34

2. Test Information

2.1. Summary of test results

Number	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	22.917	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

2.2. RF Power Output


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 10 of 34

Test Results

CDMA Cellular	Conducted Power(dBm)		
	Channel 1013	Channel 384	Channel 777
	824.7 (MHz)	836.52 (MHz)	848.31 (MHz)
RC1 S02	23.27	23.15	23.02
RC1 S055	23.30	23.20	23.05
RC3 S02	23.29	23.18	23.11
RC3 S055	23.30	23.04	23.15

Note:

- 1) The maximum RF Output Power numbers are marks in bold.
- 2) The following testing based on the maximum RF Output Power(RC3 S055).

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 11 of 34

2.3. Effective Radiated Power

Ambient condition


Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

The measurement procedures in TIA- 603C are used.

Step 1:

The measurement is carried out in the semi-anechoic chamber. EUT was placed on a 0.8 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations. The test setup refers to figure below.




Step 2:

A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a adjustable S.G. applied through a 30dB amplifier and a Tx cable. Then the Analyzer reading which is equal to LVL is recorded while the antenna was moving up and down. The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, Tx cable loss and the gain of the substitution antenna. The test setup refers to figure below.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 12 of 34



$E.R.P = S.G + 30 - Tx \text{ Cable loss} + \text{Substitution antenna gain} - 2.15$.

$EIRP = E.R.P + 2.15$

Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 13 of 34

Test Results: Pass

	Channel	Polarization	LVL(dBm)	SG+30 (dBm)	Gain(dBi)	Cable Loss(dBm)	E.R.P. (dBm)
CDMA Cellular	1013	Vertical	-27.79	36.29	1.06	15.17	20.03
	384	Vertical	-24.44	35.57	1.24	15.2	19.46
	777	Vertical	-25.46	35.61	1.38	15.24	19.60

Note: 1. E.R.P = S.G+30. - Tx Cable loss + Substitution antenna gain – 2.15.

2. EIRP= E.R.P+2.15

2.4. Occupied Bandwidth


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 30kHz, VBW is set to 300kHz. 99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1110-1746RF02R2

Page 15 of 34

Test Result

	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
CDMA Cellular	1013	824.7	1.2801	1.433
	384	836.52	1.2858	1.440
	777	848.31	1.2831	1.427




CDMA Cellular CH1013 Occupied Bandwidth


TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 16 of 34



CDMA Cellular CH384 Occupied Bandwidth



CDMA Cellular CH777 Occupied Bandwidth

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 17 of 34

2.5. Band Edge Compliance


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to 30kHz, VBW is set to 300kHz. Sweep is set to 6.52ms. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1110-1746RF02R2

Page 18 of 34

Test Result:

	Carrier frequency (MHz)	Reference value (dBm)	Limit	Conclusion
CDMA Cellular	824	-19.42	-13	PASS
	849	-15.04	-13	PASS




CDMA Cellular 1013 Channel

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 19 of 34



CDMA Cellular 777 Channel

2.6. Frequency Stability

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a "call mode". These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.4 V and 4.2 V, with a nominal voltage of 3.7V.

Test setup



TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 21 of 34

Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency from the base station.

Limits	$\leq 2.5 \text{ ppm}$
--------	------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3, U = 0.01 \text{ ppm}$.

Test Result

Temperature (°C)	Test Results (ppm) / 3.7 V Power supply
	Channel 384
-30	0.011532
-20	0.009536
-10	0.007564
0	0.003541
10	0.002556
20	0.005284
30	0.005895
40	0.006214
50	0.006541

Voltage (V)	Test Results(ppm) / 20°C
	Channel 384
3.4	0.005892
3.7	0.005284
4.2	0.006845

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 22 of 34

2.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. VBW are set to 100 kHz, Sweep is set to ATUO.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75 % confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB

TA Technology (Shanghai) Co., Ltd.


Test Report

Report No.: RZA1110-1746RF02R2

Page 23 of 34

Test Result

CDMA Cellular CH1013



Note: The signal beyond the limit is carrier
CDMA Cellular 1013 Channel 30MHz~9GHz

Harmonic	TX ch.1013 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1649.4	Nf	-13	/
3	2474.625	-57.5	-13	44.5
4	3298.8	Nf	-13	/
5	4123.5	Nf	-13	/
6	4948.2	Nf	-13	/
7	5772.9	Nf	-13	/
8	6597.6	Nf	-13	/
9	7422.3	Nf	-13	/
10	8247	Nf	-13	/

Nf: noise floor

Note: The other Spurious RF conducted emissions level is no more than noise floor.


TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 24 of 34

CDMA Cellular CH384



Note: The signal beyond the limit is carrier
CDMA Cellular 384 Channel 30MHz~9GHz

Harmonic	TX ch.384 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1673.04	Nf	-13	/
3	2511.00	-59.393	-13	46.393
4	3346.08	Nf	-13	/
5	4182.6	Nf	-13	/
6	5019.12	Nf	-13	/
7	5855.64	Nf	-13	/
8	6692.16	Nf	-13	/
9	7528.68	Nf	-13	/
10	8365.2	Nf	-13	/
Nf: noise floor				

Note: The other Spurious RF conducted emissions level is no more than noise floor.

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 25 of 34


TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 26 of 34

CDMA Cellular CH777



Note: The signal beyond the limit is carrier
CDMA Cellular 777 Channel 30MHz~9GHz

Harmonic	TX ch.777 Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)
2	1696.62	Nf	-13	/
3	2544.93	Nf	-13	/
4	3393.24	Nf	-13	/
5	4241.55	Nf	-13	/
6	5089.86	Nf	-13	/
7	5938.17	Nf	-13	/
8	6786.48	Nf	-13	/
9	7634.79	Nf	-13	/
10	8483.1	Nf	-13	/
Nf: noise floor				

Note: The other Spurious RF conducted emissions level is no more than noise floor.

2.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement


The measurements procedures in TIA -603C are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment.

The procedure of Radiates Spurious Emission is as follows:

Step 1:

The measurement is carried out in the semi-anechoic chamber. EUT was placed on a 0.8 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used while RBW and VBW are both set to 3MHz. During the measurement, the highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna moved up and down over a range from 1 to 4 meters in both horizontally and vertically polarized orientations. The test setup refers to figure below.



Step 2:


A dipole antenna shall be substituted in place of the EUT. The antenna will be driven by a signal generator with a adjustable S.G. applied through a Tx cable. Adjust the level of the signal generator output until the value of the receiver reach the previously recorded analyzer power level (LVL). Then The E.R.P. /E.I.R.P. of the EUT can be calculated through the level of the signal generator, Tx cable loss and the gain of the substitution antenna. The test setup refers to figure below.

TA Technology (Shanghai) Co., Ltd.

Test Report

Report No.: RZA1110-1746RF02R2

Page 28 of 34



$E.R.P \text{ (peak power)} = S.G. - Tx \text{ Cable loss} + \text{Substitution antenna gain} - 2.15.$

$EIRP = E.R.P + 2.15$

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the antenna is vertical.

Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB."

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

Page 29 of 34

CDMA Cellular CH1013

[illegible]

Page 30 of 34

[illegible]

Page 31 of 34

[illegible]

TA Technology (Shanghai) Co., Ltd.
Test Report

Report No.: RZA1110-1746RF02R2

Page 32 of 34

3. Main Test Instruments

No.	Name	Type	Manufacturer	Serial Number	Calibration Date	Valid Period
01	Base Station Simulator	CMU200	R&S	118133	2011-05-26	One year
02	Power Splitter	SHX-GF2-2-13	Hua Xiang	10120101	NA	NA
03	Spectrum Analyzer	E4445A	Agilent	MY46181146	2011-06-07	One year
04	Universal Radio Communication Tester	E5515C	Agilent	MY48367192	2011-06-03	One year
05	Signal Analyzer	FSV	R&S	100815	2011-06-27	One year
06	Signal generator	SMR27	R&S	1606.6000.02	2011-06-27	One year
07	EMI Test Receiver	ESCI	R&S	100948	2011-06-30	One year
08	Trilog Antenna	VUBL 9163	SCHWARZB ECK	9163-201	2010-06-29	Two years
09	Horn Antenna	HF907	R&S	100126	2011-07-01	Two years
10	Climatic Chamber	PT-30B	Re Ce	20101891	2010-09-10	Three years
11	Semi-Anechoic Chamber	9.6*6.7*6.6m	ETS-Lindgren	NA	NA	NA
12	EMI test software	ES-K1	R&S	NA	NA	NA

*****END OF REPORT BODY*****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance



a: EUT



b: Battery

Picture 1 EUT and Auxiliary

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup