

Radiated Emission Measurement above 1000MHz

Test Mode : Channel 1, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1010	60.98	*	-8.04	52.94	*	74	54	21.06	*
1122	55.40	*	-7.67	47.73	*	74	54	26.27	*
1562	53.39	*	-6.23	47.16	*	74	54	26.84	*
1614	54.11	*	-6.06	48.05	*	74	54	25.95	*
1686	50.68	*	-5.82	44.86	*	74	54	29.14	*
1704	67.25	52.26	-5.76	61.49	46.50	74	54	12.51	7.50
1798	57.19	*	-5.44	51.75	*	74	54	22.25	*
1880	71.49	55.26	-5.16	66.33	50.1	74	54	7.67	3.90
2020	53.20	*	-4.68	48.52	*	74	54	25.48	*
2216	54.49	*	-3.90	50.59	*	74	54	23.41	*
2508	52.61	*	-2.75	49.86	*	74	54	24.14	*
2686	61.30	46.18	-2.29	59.01	43.89	74	54	14.99	10.11
2696	70.85	54.66	-2.26	68.59	52.40	74	54	5.41	1.60
2820	49.92	*	-1.93	47.99	*	74	54	26.01	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1048	60.40	*	-7.92	52.48	*	74	54	21.52	*
1164	52.18	*	-7.54	44.64	*	74	54	29.36	*
1658	52.13	*	-5.91	46.22	*	74	54	27.78	*
1746	55.91	*	-5.61	50.30	*	74	54	23.70	*
1918	70.29	54.14	-5.04	65.25	49.1	74	54	8.75	4.9
2098	53.16	*	-4.37	48.79	*	74	54	25.21	*
2266	52.85	*	-3.7	49.15	*	74	54	24.85	*
2786	51.28	*	-2.02	49.26	*	74	54	24.74	*
2796	49.26	*	-1.99	47.27	*	74	54	26.73	*
2808	48.93	*	-1.96	46.97	*	74	54	27.03	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1086	56.06	*	-7.79	48.27	*	74	54	25.73	*
1702	47.51	*	-5.76	41.75	*	74	54	32.25	*
1788	62.08	47.99	-5.47	56.61	42.52	74	54	17.39	11.48
1956	69.67	56.81	-4.91	64.76	51.90	74	54	9.24	2.1
2172	51.80	*	-4.07	47.73	*	74	54	26.27	*
2608	47.65	*	-2.49	45.16	*	74	54	28.84	*
2896	43.64	*	-1.73	41.91	*	74	54	32.09	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1010	59.88	*	-8.04	51.84	*	74	54	22.16	*
1122	54.95	*	-7.67	47.28	*	74	54	26.72	*
1562	52.82	*	-6.23	46.59	*	74	54	27.41	*
1614	53.81	*	-6.06	47.75	*	74	54	26.25	*
1704	57.25	*	-5.76	51.49	*	74	54	22.51	*
1798	56.24	*	-5.44	50.80	*	74	54	23.20	*
1880	71.02	55.14	-5.16	65.86	49.98	74	54	8.14	4.02
2022	54.57	*	-4.67	49.90	*	74	54	24.10	*
2218	54.07	*	-3.89	50.18	*	74	54	23.82	*
2507	50.16	*	-2.75	47.41	*	74	54	26.59	*
2695	59.77	45.15	-2.26	57.51	42.89	74	54	16.49	11.11
2889	44.84	*	-1.75	43.09	*	74	54	30.91	*
4822	41.97	*	2.49	44.46	*	74	54	29.54	*
14472	33.36	*	13.84	47.20	*	74	54	26.80	*
16886	46.60	32.23	14.92	61.52	47.15	74	54	12.48	6.85

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1048	65.22	54.07	-7.92	57.30	46.15	74	54	16.70	7.85
1118	51.59	*	-7.68	43.91	*	74	54	30.09	*
1164	56.61	*	-7.54	49.07	*	74	54	24.93	*
1198	51.25	*	-7.43	43.82	*	74	54	30.18	*
1606	51.33	*	-6.08	45.25	*	74	54	28.75	*
1658	55.04	*	-5.91	49.13	*	74	54	24.87	*
1746	47.73	*	-5.61	42.12	*	74	54	31.88	*
1864	57.33	*	-5.22	52.11	*	74	54	21.89	*
1918	72.32	56.34	-5.04	67.28	51.30	74	54	6.72	2.70
2096	50.73	*	-4.38	46.35	*	74	54	27.65	*
2266	55.43	*	-3.7	51.73	*	74	54	22.27	*
2556	54.90	*	-2.62	52.28	*	74	54	21.72	*
2796	51.52	*	-1.99	49.53	*	74	54	24.47	*
2878	43.71	*	-1.78	41.93	*	74	54	32.07	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1086	62.32	49.78	-7.79	54.53	41.69	74	54	19.47	12.31
1110	58.50	*	-7.71	50.79	*	74	54	23.21	*
1206	55.70	*	-7.40	48.30	*	74	54	25.70	*
1702	52.30	*	-5.76	46.54	*	74	54	27.46	*
1738	47.35	*	-5.64	41.71	*	74	54	32.29	*
1788	54.17	*	-5.47	48.70	*	74	54	25.30	*
1812	48.68	*	-5.39	43.29	*	74	54	30.71	*
1956	70.03	55.08	-4.91	65.12	50.17	74	54	8.88	3.83
2172	54.05	*	-4.07	49.98	*	74	54	24.02	*
2896	49.11	*	-1.73	47.38	*	74	54	26.62	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Transmitter with FLAT-PATCH-ANTENNA

Tester : Alex Temperature : 19°C

Humidity : 53%RH Frequency Range : 1GHz~25GHz

RBW : 1MHz VBW : 1MHz (peak)

Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1880	47.12	*	-5.16	41.96	*	74	54	32.04	*
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Transmitter with FLAT-PATCH-ANTENNA

Tester : Alex Temperature : 19°C

Humidity : 53%RH Frequency Range : 1GHz~25GHz

RBW : 1MHz VBW : 1MHz (peak)

Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1010	60.69	*	-8.04	52.65	*	74	54	21.35	*
1080	52.38	*	-7.81	44.57	*	74	54	29.43	*
1170	51.94	*	-7.52	44.42	*	74	54	29.58	*
1616	54.28	*	-6.05	48.23	*	74	54	25.77	*
1704	58.00	*	-5.76	52.24	*	74	54	21.76	*
1798	57.52	*	-5.44	52.08	*	74	54	21.92	*
1880	73.12	56.26	-5.16	67.96	51.1	74	54	6.04	2.9
2022	48.94	*	-4.67	44.27	*	74	54	29.73	*
2216	50.71	*	-3.90	46.81	*	74	54	27.19	*
2508	47.47	*	-2.75	44.72	*	74	54	29.28	*
2686	46.10	*	-2.29	43.81	*	74	54	30.19	*
2696	42.62	*	-2.26	40.36	*	74	54	33.64	*
2820	48.79	*	-1.93	46.86	*	74	54	27.14	*
2892	42.35	*	-1.74	40.61	*	74	54	33.39	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with FLAT-PATCH-ANTENNA

Tester : Alex Temperature : 19°C

Humidity : 53%RH Frequency Range : 1GHz~25GHz

RBW : 1MHz VBW : 1MHz (peak)

Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1918	47.94	*	-5.04	42.90	*	74	54	31.10	*
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Transmitter with FLAT-PATCH-ANTENNA

Tester : Alex Temperature : 19°C

Humidity : 53%RH Frequency Range : 1GHz~25GHz

RBW : 1MHz VBW : 1MHz (peak)

Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1048	63.01	50.43	-7.92	55.09	42.51	74	54	18.91	11.49
1118	56.53	*	-7.68	48.85	*	74	54	25.15	*
1138	60.65	*	-7.62	53.03	*	74	54	20.97	*
1606	53.98	*	-6.08	47.90	*	74	54	26.10	*
1658	55.80	*	-5.91	49.89	*	74	54	24.11	*
1746	67.43	54.58	-5.61	61.82	48.97	74	54	12.18	5.03
1864	58.53	*	-5.22	53.31	*	74	54	20.69	*
1918	75.83	55.85	-5.04	70.79	50.81	74	54	3.21	3.19
2098	49.59	*	-4.37	45.22	*	74	54	28.78	*
2266	48.82	*	-3.70	45.12	*	74	54	28.88	*
2556	50.47	*	-2.62	47.85	*	74	54	26.15	*
2796	56.87	49.14	-1.99	54.88	47.15	74	54	39.12	6.85
2878	50.12	*	-1.78	48.34	*	74	54	25.66	*
2968	42.00	*	-1.54	40.46	*	74	54	33.54	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1956	46.82	*	-4.91	41.91	*	74	54	32.09	*
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Transmitter with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
1086	59.52	*	-7.79	51.73	*	74	54	22.27	*
1110	59.65	*	-7.71	51.94	*	74	54	22.06	*
1158	53.12	*	-7.55	45.57	*	74	54	28.43	*
1194	56.83	*	-7.44	49.39	*	74	54	24.61	*
1702	58.58	*	-5.76	52.82	*	74	54	21.18	*
1788	58.20	*	-5.47	52.73	*	74	54	21.27	*
1812	54.04	*	-5.39	48.65	*	74	54	25.35	*
1956	75.29	55.09	-4.91	70.38	50.18	74	54	3.62	3.82
2028	50.52	*	-4.65	45.87	*	74	54	28.13	*
2172	55.22	*	-4.07	51.15	*	74	54	22.85	*
2608	53.01	*	-2.49	50.52	*	74	54	23.48	*
2752	50.66	*	-2.1	48.56	*	74	54	25.44	*
2896	48.03	*	-1.73	46.30	*	74	54	27.70	*
2934	51.98	*	-1.63	50.35	*	74	54	23.65	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with ANT-OMNI-8
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with ANT-OMNI-12
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 1, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4824	*	*	*	*	*	74	54	*	*
7236	*	*	*	*	*	74	54	*	*
9648	*	*	*	*	*	74	54	*	*
12060	*	*	*	*	*	74	54	*	*
14472	*	*	*	*	*	74	54	*	*
16884	*	*	*	*	*	74	54	*	*
19296	*	*	*	*	*	74	54	*	*
21708	*	*	*	*	*	74	54	*	*
24120	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 6, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4874	*	*	*	*	*	74	54	*	*
7311	*	*	*	*	*	74	54	*	*
9748	*	*	*	*	*	74	54	*	*
12185	*	*	*	*	*	74	54	*	*
14622	*	*	*	*	*	74	54	*	*
17059	*	*	*	*	*	74	54	*	*
19496	*	*	*	*	*	74	54	*	*
21933	*	*	*	*	*	74	54	*	*
24370	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Horizontal 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.

Test Mode : Channel 11, Receiver with FLAT-PATCH-ANTENNA
Tester : Alex **Temperature** : 19°C
Humidity : 53%RH **Frequency Range** : 1GHz~25GHz
RBW : 1MHz **VBW** : 1MHz (peak)
Polarization : Vertical 10Hz (Average)

Frequency (MHz)	Reading Data (dBuV)		Correction Factor (dB1/m)	Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
	PK	AV		PK	AV	PK	AV	PK	AV
4924	*	*	*	*	*	74	54	*	*
7386	*	*	*	*	*	74	54	*	*
9848	*	*	*	*	*	74	54	*	*
12310	*	*	*	*	*	74	54	*	*
14772	*	*	*	*	*	74	54	*	*
17234	*	*	*	*	*	74	54	*	*
19696	*	*	*	*	*	74	54	*	*
22158	*	*	*	*	*	74	54	*	*
24620	*	*	*	*	*	74	54	*	*

Note:

1. Emission Level (dBuV/m) = Reading Value + Correction Factor.
2. Correction Factor (dB1/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Margin (dB) = Limit–Emission Level.
4. PK. and AV. are abbreviation of peak and average respectively.
5. “*”: The emission is too low to be measured.