

TEST REPORT



Testing Certification # 1367-01

Laboratory ID

PRODUCT SAFETY ENGINEERING, INC.
12955 Bellamy Brothers Boulevard
Dade City, Florida 33525 USA
PH (352) 588-2209 FX (352) 588-2544

Submitter ID

Microsemi Corp. - RFIS
1064 Greenwood Blvd
Suite 124
Lake Mary, FL 32746

Report Issue Date: 28 Aug 2013

Sample S/N: P7 #4

Sample Receipt Date: 07 Nov 2012

Test Report Number: 12F323B

Model Designation: All Clear

Product Description: Handheld Metal
Detector

Sample Test Date: see data sheets

Description of non-standard test method or test practice: *None*

Estimated Measurement Uncertainty: *See page 9. This uncertainty represents and expanded uncertainty expressed at approximately 95% confidence level using a coverage factor of k=2.*

Special limitations of use: *None*

Traceability: *reference standards of measurement have been calibrated by a competent body using standards traceable to the NIST.*

According to testing performed at Product Safety Engineering, Inc., the above-mentioned unit is in compliance with the electromagnetic compatibility requirements defined in regulations indicated on page (3) of the test report. The test results contained herein relate only to the item identified above. It is the manufacturer's responsibility to assure that additional production units are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Project Engineer, I hereby declare that the equipment tested as specified above conforms to the requirements indicated on page (3) of the test report.

Signature

A handwritten signature in dark ink, appearing to read 'David Foerstner', written over a horizontal line.

Name David Foerstner

Title Engineering Group Leader

Date 28 Aug 2013

Reviewed by:

Approved Signatory

A handwritten signature in dark ink, appearing to read 'Steve Hoke', written over a horizontal line.

Date 28 Aug 2013

Steve Hoke (EMC Site Manager)

This report shall not be reproduced except in full, without written approval from Product Safety Engineering, Inc

Test Report Number 12F323B

Product Safety Engineering, Inc. 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

DIRECTORY - EMISSIONS

		Page(s)
A) Documentation		
Test report		1 - 10
Directory		2
Test Regulations		3
General Remarks		10
Test-setups (Photos)		11 - 12
B) Test data		
Conducted emissions	10/150 kHz - 30 MHz	5, 9
Radiated emissions	10 kHz - 30 MHz	5, 9
Radiated emissions	30 MHz - 1000 MHz	6, 9
Disturbance power	30 MHz - 300 MHz	6, 9
Equivalent Radiated emissions	1 GHz - 18 GHz	7, 9
Antenna Disturbance Voltage	30 MHz - 1,000 MHz	7,9
C) Appendix A		
Test Data Sheets		A2 - A 3

Test Report Number 12F323B

EMISSIONS TEST REGULATIONS :

The emissions tests were performed according to following regulations:

☐ - EN 61000-6-3:2007

☐ - EN 61000-6-4:2007

☐ - EN 55011 : 2009/A1:2010

☐ - Group 1

☐ - Group 2

☐ - Class A

☐ - Class B

☐ - EN 55013 : 2001 /A1:2003 /A2:2006

☐ - EN 55014 -1: 2006/A2:2011

☐ - Household appliances and similar

☐ - Portable tools

☐ - Semiconductor devices

☐ - EN 55022:2010/AC:2011

☐ - Class A

☐ - Class B

☐ - CISPR 22:2008

☐ - Class A

☐ - Class B

☐ -AS/NZS CISPR 22:2009

☐ - Class A

☐ - Class B

☐ - ICES-003

☐ - Class A

☐ - Class B

☐ - CNS 13438

☐ - Class A

☐ - Class B

☐ - VCCI V-3/2010.4

☐ - Class A

☐ - Class B

■ - FCC Part 15 (per ANSI C63.4)
(per 15.209)

☐ - Class A

☐ - Class B

■ - Certification

☐ - Verification

☐ - Declaration of Conformity

☐ - FCC Part 18

Test Report Number 12F323B

Environmental conditions during testing:

	LAB	OATS
Temperature: *	_____	: _____
Relative Humidity: **	_____	: _____

* The ambient temperature during the testing was within the range of (50° - 104° F) unless indicted above.
** The humidity levels during the testing was within the range of (10% - 90%) relative humidity unless indicated above.

Power supply system : _____ Volts _____ Hz SINGLE phase
Battery operated

Sign Explanations:

- ☐ - not applicable
- ☒ - applicable

Test Report Number 12F323B

Emissions Test Conditions: CONDUCTED EMISSIONS (Interference Voltage)

The *CONDUCTED EMISSIONS (INTERFERENCE VOLTAGE)* measurements were performed at the following test location:

☒ - Test not applicable

- ☐ - Darby Test Site (Open Area Test Site)
☐ - Darby Laboratory

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - 8028-50	Solar	50 Ω LISN	829012, 829022
☐ - 8012	Solar	50 Ω LISN	924840
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - 85662A	Hewlett Packard	Analyzer Display	2403A07352
☐ - 8028-50	Solar	50 Ω LISN	903725, 903726
☐ - FCC-TLISN-T4-02	Fisher Custom Com.	Telecom ISN	20454
☐ - FCC-TLISN-T8-02	Fisher Custom Com.	Telecom ISN	20452
☐ - LI-125	Com-Power	50 Ω LISN	191080/191081

Emissions Test Conditions: RADIATED EMISSIONS (Magnetic Field)

The *RADIATED EMISSIONS (MAGNETIC FIELD)* measurements were performed at the following test location:

- ☒ - Darby Test Site (Open Area Test Site)
☐ -
☐ -

at a test distance of :

- ☒ - 3 meters
☐ - 30 meters

☐ - Test not applicable

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - 3148	EMCO	Log Periodic Antenna	00044783
☐ - BIA-25	Electro-Metrics	Biconical Antenna	4283
☒ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☒ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☒ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☒ - ALR-30M	Electro-Metrics	Loop Antenna	824
☒ - 8447D	Hewlett Packard	Preamplifier	2944A06832
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - ALA-130/A	Antenna Research	Loop Antenna	106

Test Report Number 12F323B

Emissions Test Conditions: RADIATED EMISSIONS (Electric Field)

The *RADIATED EMISSIONS (ELECTRIC FIELD)* measurements, in the frequency range of 30 MHz-1000 MHz, were tested in a horizontal and vertical polarization at the following test location :

■ - Test not applicable

- ☐ - Darby Site (Open Area Test Site)
- ☐ - Darby Lab
- ☐ -

at a test distance of :

- ☐ - 3 meters
- ☐ - 10 meters
- ☐ - 30 meters

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - HLP 3003C	EMC Automation	Hybrid Periodic Antenna	017501
☐ - 8447D	Hewlett-Packard	Preamplifier (26dB)	1937A03247
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - BIA 25	Electro-Metrics	Biconical Antenna	4283
☐ - EMC-30	Electro-Metrics	EMI Receiver	191
☐ - 8566B	Hewlett Packard	Spectrum Analyzer	2532A02418
☐ - 85650A	Hewlett Packard	Quasi-Peak Adapter	2043A00358
☐ - 85662A	Hewlett Packard	Analyzer Display	2403A06604
☐ - LPA30	Electro-Metrics	Log Periodic	2280
☐ - 3104C	Emco	Biconical Antenna	00075927
☐ - 9005	Eaton	Log Periodic Antenna	1099

Emissions Test Conditions): DISTURBANCE POWER

The *DISTURBANCE POWER* measurements were performed by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz at the following test location :

■ - Test not applicable

- ☐ - Darby Lab
- ☐ -

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - MDS-21	Rhode&Schwarz	Absorbing Clamp	8608447020
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - 8447D	Hewlett-Packard	Amplifier (26 dB)	2944A06832
☐ - EMC-30	Electro-Metrics	EMI Receiver	191

Test Report Number 12F323B

The *EQUIVALENT RADIATED EMISSIONS* measurements in the frequency range GHz - GHz were performed in a horizontal and vertical polarization at the following test location :

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ -
- ☐ -
- ☐ -

at a test distance of:

- ☐ - 1 meters
- ☐ - 3 meters
- ☐ - 10 meters

■ - Test not applicable

Test equipment used :

Model Number	Manufacturer	Description	Serial Number
☐ - 8566B	Hewlett-Packard	Spectrum Analyzer	2421A00526
☐ - 85662A	Hewlett-Packard	Analyzer Display	2403A07352
☐ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2043A00209
☐ - 8449B	Hewlett-Packard	Preamplifier	3008A00320
☐ - 3115	Electro-Mechanics	Double Ridge Guide Horn	3810

The *ANTENNA TERMINAL DISTURBANCE VOLTAGE* in the frequency range 30 MHz - 1,000 MHz were performed.

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ - Laboratory
- ☐ -
- ☐ -

■ - Test not applicable

Model Number	Manufacturer	Description	Serial Number
☐ - 2F9-3C4-3C5	Wavecom	UHF PAL TV Modulator	185879
☐ - 2F1-3C4-3C5	Wavecom	VHF PAL TV Modulator	157728
☐ - A-8000	IFR	Spectrum Analyzer	1306
☐ - 8648B	Hewlett-Packard	Signal Generator	3623A01433
☐ - 8648B	Hewlett-Packard	Signal Generator	3623A01477
☐ - LMV-182A	Leader	RMS Milli-Voltmeter	8010091
☐ - 3202	Krhon-Hite	Active filter	5899
☐ - FMT115	Leaming	FM Modulator	NONE
☐ - 371	UDT	Optical power meter	06657
☐ - TSG95	Tektronix	PAL video / Audio gen	B028883

Test Report Number 12F323B

Equipment Under Test (EUT) Test Operation Mode - Emission tests :

The device under test was operated under the following conditions during emissions testing:

- ☐ - Standby
- ☐ - Test program (H - Pattern)
- ☐ - Test program (color bar)
- ☐ - Test program (customer specific)
- ☐ - Practice operation
- ☒ - Normal Operating Mode
- ☐ -

Configuration of the device under test:

- ☐ - See System Under Test Information in Appendix B
- ☒ - EUT tested as a stand-alone device

Rationale for EUT setup / configuration:

ANSI C63.4:2003

Emission Test Results:

Conducted emissions 150 kHz - 30 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
MU: 5.3 dB

Radiated emissions (magnetic field) 10 kHz - 30 MHz

The requirements are ☒ - MET ☐ - NOT MET
Minimum limit margin 21.7 dB at 0.125 MHz
MU: NA

Radiated emissions (electric field) 30 MHz - 1000 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
MU: 5.2 dB

Interference Power at the mains and interface cables 30 MHz - 300 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
MU: NA

Radiated emissions GHz - GHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at GHz
MU: 4.9 dB

Antenna Terminal Disturbance Voltage 30 MHz - 1,000 MHz

The requirements are ☐ - MET ☐ - NOT MET
Minimum limit margin dB at MHz
MU: NA

MU = Measurement Uncertainty

Test Report Number 12F323B

GENERAL REMARKS:

Radiated emissions - The equipment under test examined in (3) orthogonal orientations. The highest orientation was used to collect the final data.

SUMMARY:

The requirements according to the technical regulations are

■ - met

□ - **not** met.

The device under test does

■ - fulfill the general approval requirements mentioned on page 3.

□ - **not** fulfill the general approval requirements mentioned on page 3.

Testing Start Date 07 Nov 2012

Testing End Date: 07 Nov 2012

- PRODUCT SAFETY ENGINEERING INC -

Test Report Number 12F323B

Test-setup photo(s):
Conducted emission 150 kHz - 30 MHz

NA

Test Report Number 12F323B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

Test-setup photo(s):

Radiated emission 30 MHz - 1000 MHz



Test Report Number 12F323B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525
Tel (352) 588-2209 Fax (352) 588-2544

APPENDIX

A

Test Equipment Calibration Information & Test Data Sheets

Test Report Number 12F323B

	TEST EQUIPMENT CALIBRATION INFORMATION			
Manufacturer	Model	Description	Serial Number	Cal Due *
Hewlett Packard	8566B	Spectrum Analyzer	2421A00526	11/4/2013
Hewlett Packard	85662A	Display	2403A07352	11/4/2013
Hewlett Packard	85650A	Quasi-peak Adapter	2043A00209	11/4/2013
Hewlett Packard	8566B	Spectrum Analyzer	2532A02418	
Hewlett Packard	85662A	Display	2403A06604	
Hewlett Packard	85650A	Quasi-peak Adapter	2043A00358	
Hewlett Packard	8447D	Preamp 0.1 - 1,000 MHz	2944A06832	2/17/2014
Hewlett Packard	8447D	Preamp 0.1 - 1,000 MHz	2944A06901	
Hewlett Packard	8447D	Preamp 0.1 - 1,000 MHz	1937A03247	
Hewlett Packard	8449B	Preamp 1 - 26.5 GHz	3008A00320	
Hewlett Packard	E7402A	Portable Spectrum Analyzer	US40240204	
Eaton	96005	Log Periodic Antenna	1099	
Electro-Metrics	BIA-30	Biconical Antenna	3852	
EMCO	3104C	Biconical Antenna	75927	
Electro-Metrics	ALR30M	Magnetic Loop Antenna	824	11/9/2013
Electro-Metrics	EMC-30	EMI Receiver	191	
Electro-Metrics	3115	Double Ridge Guide Antenna	3810	
Solar	8028	LISN	829012/809022	
Com-Power	LI-125	LISN	191180/191181	
EMCO	3148	Log Periodic Antenna	44783	
Schwartzbeck	MDS-21	Absorbing Clamp	2581	
Fisher Custom	FCC-TLISN-T4-02	T LISN	20454	
Fisher Custom	FCC-TLISN-T8-02	Fisher Custom	20452	
ATM	42-441-6	Stanard Gain Horn Antenna	E531612-01	
Electro-Metrics	3117	Double Ridge Guide Antenna	109296	
		* Cal Due Date Format = MM/DD/YY		
All equipment was calibrated one year prior to the cal due date listed unless otherwise indicated				

Freq	Measured	ACF	CL	PA Gain	Adj FS		Limit	Margin
kHz	FS	dB/m	dB	dB	dBuV/m		dBuV/m	dB
124.8	56.3	53.5	0.2	26	84		105.7	21.7