



## **Gimbal™ U-Series 5 Proximity Beacon**

*Model 900-0004-000*

*Frequency and Voltage Stability Declaration*

358-0096-000 Revision A

Gimbal, Inc. Confidential and Proprietary

**NO PUBLIC DISCLOSURE PERMITTED:** Please report postings of this document on public servers or websites to: [legal@gimbal.com](mailto:legal@gimbal.com)

**Restricted Distribution:** Not to be distributed to anyone who is not an employee of either Gimbal, Inc. or its subsidiaries without the express approval by Gimbal, Inc.

Not to be used, copied, reproduced, or modified in whole or in part, nor its contents revealed in any manner to others without the express written permission of Gimbal, Inc.

This technical data may be subject to U.S. and international export, re-export or transfer ("export") laws. Diversion contrary to U.S. and international law is strictly prohibited.

Gimbal, Inc.  
San Diego, California  
U.S.A.

© 2015 Gimbal, Inc. All Rights Reserved.

Gimbal™ is a trademark of Gimbal, Inc. registered in the United States and other countries.

# Revision History

Revision	Date	Description
A	28 March, 2015	Initial Release

# Frequency and Voltage Stability Declaration

This product was designed to maintain FR characteristics over voltage and temperature.

Gimbal, Inc. declares that the Gimbal U-Series 5 Proximity Beacon (Model 900-0004-000) has stable RF output power and clock stability of 20ppm given a stable 5V power source and temperature range of – 20C to + 55C.