

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Portable Netbook

MODEL No.: UMPC9901

FCC ID: R6LUMPC9901

REPORT NO: E0908123F

ISSUE DATE: October 11, 2009

Prepared for

SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD.

**Shuoying Road, Hebei Industrial Area, Dalang, Long Hua Town, Baoan, Shenzhen,
China**

Prepared by

SHENZHEN EMTEK CO., LTD

**Bldg 69, Majialong Industry Zone, Nan0shan District,
Shenzhen, Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE

Applicant:	SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD. Shuoying Road, Hebei Industrial Area, Dalang, Long Hua Town, Baoan, Shenzhen, China
Manufacturer:	SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD. Shuoying Road, Hebei Industrial Area, Dalang, Long Hua Town, Baoan, Shenzhen, China
Product Description:	Portable Netbook
Brand Name:	N/A
Model Number:	UMPC9901
Serial Number:	N/A
File Number:	E0908123F
Date of Test:	September 01, 2009 to October 11, 2009

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Approved By



David Lee / Q.A. Manager
SHENZHEN EMTEK CO., LTD.

Table of Contents

1.	GENERAL INFORMATION	5
1.1	PRODUCT DESCRIPTION.....	5
1.2	RELATED SUBMITTAL(S) / GRANT (S)	5
1.3	TEST METHODOLOGY	5
1.4	SPECIAL ACCESSORIES	6
1.5	EQUIPMENT MODIFICATIONS	6
1.6	TEST FACILITY	6
2.	SYSTEM TEST CONFIGURATION	7
2.1	EUT CONFIGURATION.....	7
2.2	EUT EXERCISE	7
2.3	TEST PROCEDURE	7
2.4	CONFIGURATION OF TESTED SYSTEM	7
3.	DESCRIPTION OF TEST MODES	9
4.	CONDUCTED EMISSIONS TEST	10
4.1	MEASUREMENT PROCEDURE:.....	10
4.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	10
4.3	MEASUREMENT EQUIPMENT USED:	10
4.4	CONDUCTED EMISSION LIMIT	10
4.5	MEASUREMENT RESULT:.....	11
4.6	CONDUCTED MEASUREMENT PHOTOS:	12
5.	RADIATED EMISSION TEST	13
5.1	MEASUREMENT PROCEDURE.....	13
5.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
5.3	MEASUREMENT EQUIPMENT USED:	14
5.4	RADIATED EMISSION LIMIT	14
5.5	MEASUREMENT RESULT	15
5.6	RADIATED MEASUREMENT PHOTOS:	27
6.	OCCUPIED BANDWIDTH TEST.....	28
6.1	MEASUREMENT PROCEDURE.....	28
6.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	28
6.3	MEASUREMENT EQUIPMENT USED:	28
6.4	LIMIT	28
6.5	MEASUREMENT RESULTS:.....	28
7.	MAX IMUM PEAK OUTPUT POWER TEST	33
7.1	MEASUREMENT PROCEDURE.....	33
7.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	33
7.3	MEASUREMENT EQUIPMENT USED:	33

7.4	PEAK POWER OUTPUT LIMIT.....	33
7.5	MEASUREMENT RESULTS:.....	33
8.	BAND EDGE TEST.....	35
8.1	MEASUREMENT PROCEDURE.....	35
8.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	35
8.3	MEASUREMENT EQUIPMENT USED:	36
8.4	MEASUREMENT RESULTS:.....	36
9.	POWER DENSITY.....	40
9.1	TEST EQUIPMENT	40
9.2	MEASURING INSTRUMENTS AND SETTING	40
9.3	TEST PROCEDURES	40
9.4	BLOCK DIAGRAM OF TEST SETUP	40
9.5	LIMIT	40
9.6	TEST RESULT	41
10.	ANTENNA APPLICATION.....	45
10.1	ANTENNA REQUIREMENT	45
10.2	RESULT	45

1. GENERAL INFORMATION

1.1 Product Description

A major technical descriptions of EUT is described as following:

- A). Standards: IEEE802.11b/g
- B). Operation Frequency: 2412-2462MHz
- C). Modulation: OFDM with BPSK, QPSK, 16QAM, 64QAM(11g), BPSK, QPSK, CCK (11b)
- D). Number of Channel: 11
- E). Max Data Rate: 11Mbps(802.11b), 54Mbps(802.11g)
- F). Transmit Power: 13.25dBm(802.11b), 12.24dBm(802.11g)
- G). Conducted power: 11.25dBm(802.11b), 10.24dBm(802.11g)
- H). Antenna GAIN: 2dBi
- I). Antenna Type: PCB trace Antenna
- J). Power Supply: DC5V with external adapter or battery

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is a 2.4GHz Portable Netbook included 802.11b and 802.11g 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in highest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: R6LUMPC9901 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description
EMC Lab. : Accredited by CNAS, 2005.11.02
The certificate is valid until 2010.11
The Laboratory has been assessed and proved to be in compliance
with CNAS/CL01:2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2008.3
The Laboratory has been assessed according to the requirements
ISO/IEC 17025

Accredited by FCC, March 18, 2008
The Certificate Registration Number is 709623.

Accredited by Industry Canada, May 24, 2008
The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Portable Netbook	Shuoying	UMPC9901	R6LUMPC9901	N/A	EUT
2.	Mouse	HP	M-S48a	DOC	LZE14823966A W	
3.	Keyboard	HP	SK-2502C	DOC	C0111141546	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

3. Description of test modes

The Transmitter of EUT is a Portable Netbook and powered by host equipment. This is Digital Transmission system(DTS) and have four type of modulation DBPSK DQPSK CCK&OFDM. The data rates are 54Mbps.

The equipment enables high-speed access without wires to network assets. This adapter uses the IEEE 802.11b/g protocol to enable wireless communications between the host computer and computers, in the same way that the computer would use an Ethernet adapter.

1. For lowest channel : 2412MHz(Channel 1)
2. For middle channel : 2437MHz(Channel 6)
3. For highest channel: 2462MHz(Channel 11)

EUT operating conditions:

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to typical use, The exercise sequence is listed as below:


1. Setup the EUT and simulators as shown on 2.4.
2. Turn on the power of all equipments.
3. The EUT Ping with the wireless router.
4. Repeat the above steps.

4. Conducted Emissions Test

4.1 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

4.2 Test SET-UP (Block Diagram of Configuration)



4.3 Measurement Equipment Used:

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2009	05/29/2010
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2009	05/29/2010
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2009	05/29/2010
50ΩCoaxial Switch	Anritsu	MP59B	M20531	005/29/2009	05/29/2010

4.4 Conducted Emission Limit (7) Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.5 Measurement Result:

Date of Test:	<u>September 08, 2009</u>	Temperature:	<u>22°C</u>
Frequency Detector:	<u>0.15~30MHz</u>	Humidity:	<u>50%</u>
Test Result:	<u>PASS</u>	Test Mode:	<u>WIFI Mode</u>

Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Margin QP dB(μV)	Margin AV dB(μV)
0.170	52.08	50.17	64.96	54.96	-12.88	-4.79
0.220	51.96	49.20	62.82	52.82	-10.86	-3.62
0.350	48.53	46.34	58.96	48.96	-10.43	-2.62
0.420	45.02	43.52	57.45	47.45	-12.43	-3.93
0.665	44.13	42.67	56.00	46.00	-11.87	-3.33
28.351	36.27	33.73	60.00	50.00	-23.73	-16.27
0.175	53.21	51.09	64.72	54.72	-11.51	-3.63
0.225	51.04	48.76	62.63	52.63	-11.59	-3.87
0.345	47.66	46.00	59.08	49.08	-11.42	-3.08
0.425	46.53	44.51	57.35	47.35	-10.82	-2.84
0.680	44.28	43.15	56.00	46.00	-11.72	-2.85
28.366	38.26	36.42	60.00	50.00	-21.74	-13.58

4.6 Conducted Measurement Photos:




5. Radiated Emission Test

5.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



5.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSP7	839511/010	05/29/2009	05/29/2010
Spectrum Analyzer	HP	E4407B	839840481	05/29/2009	05/29/2010
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2009	05/29/2010
Pre-Amplifier	HP	8447D	2944A07999	05/29/2009	05/29/2010
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2009	05/29/2010
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2009	05/29/2010
Horn Antenna	Electro-Metrics	EM-6961	103314	05/29/2009	05/29/2010
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2009	05/29/2010

5.4 Radiated emission limit

FCC Class B Limit at 3m

Frequency MHz	Distance Meter	Field Strength uV/m	Field Strength dBuV/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
Above 960	3	500	54.0

Note: The frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above maximum permitted average limit.

5.5 Measurement Result

Operation Mode: 802.11b TX Channel 1 Test Date : 09/08/2009
Frequency Range: 30~1000MHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
31.03	V	36.83	40.00	-3.17	PK
58.91	V	34.26	40.00	-5.74	PK
168.94	V	37.97	43.5	-5.53	PK
216.31	V	41.18	46.00	-4.82	PK
382.50	V	40.95	46.00	-5.05	PK
453.27	V	41.27	46.00	-4.73	PK
125.69	H	36.50	43.5	-7.0	PK
155.36	H	36.86	43.5	-6.64	PK
162.84	H	35.64	43.5	-7.86	PK
248.65	H	37.73	46.00	-8.27	PK
277.00	H	42.19	46.00	-3.81	PK
456.29	H	40.07	46.00	-5.93	PK

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 6 Test Date : 09/08/2009
Frequency Range: 30~1000MHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBUV)	Limit 3m (dBUV/m)	Margin (dB)	Note
32.95	V	35.96	40.00	-4.04	PK
53.21	V	35.05	40.00	-4.95	PK
176.37	V	34.24	43.5	-9.26	PK
227.65	V	42.61	46.00	-3.39	PK
383.07	V	42.08	46.00	-3.92	PK
491.61	V	40.55	46.00	-5.45	PK
116.05	H	36.63	43.5	-6.87	PK
134.20	H	35.57	43.5	-7.93	PK
171.73	H	36.14	43.5	-7.36	PK
248.65	H	39.09	46.00	-6.91	PK
265.49	H	41.25	46.00	-4.75	PK
460.53	H	41.95	46.00	-4.05	PK

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 11 Test Date : 09/08/2009
Frequency Range: 30~1000MHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBUV)	Limit 3m (dBUV/m)	Margin (dB)	Note
50.26	V	36.04	40.00	-3.96	PK
103.57	V	34.53	43.5	-8.97	PK
175.32	V	35.05	43.5	-8.45	PK
220.61	V	37.58	46.00	-8.42	PK
379.46	V	42.27	46.00	-3.73	PK
500.32	V	38.69	46.00	-7.31	PK
68.27	H	34.22	43.5	-9.28	PK
130.42	H	33.91	43.5	-9.59	PK
171.60	H	35.64	43.5	-7.86	PK
253.06	H	36.36	46.00	-9.64	PK
288.63	H	39.52	46.00	-6.48	PK
503.71	H	40.00	46.00	-6.00	PK

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 1 Test Date : 09/08/2009
 Frequency Range: 30~1000MHz Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBUV)	Limit 3m (dBUV/m)	Margin (dB)	Note
36.74	V	34.24	40.00	-5.76	PK
85.36	V	33.06	40.00	-6.94	PK
175.28	V	35.81	43.5	-7.69	PK
219.62	V	37.52	46.00	-8.48	PK
375.90	V	39.50	46.00	-6.5	PK
563.37	V	39.98	53.90	-13.92	PK
39.27	H	31.64	40.00	-8.36	PK
165.18	H	34.71	43.5	-8.79	PK
219.50	H	37.06	46.00	-8.94	PK
375.92	H	40.20	46.00	-5.8	PK
406.15	H	39.53	46.00	-6.47	PK
559.61	H	41.09	46.00	-4.91	PK

Note: (1) All Readings are Peak Value.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 6 Test Date : 09/08/2009
 Frequency Range: 30~1000MHz Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
35.74	V	32.30	40.00	-7.7	PK
93.60	V	34.81	43.5	-8.69	PK
178.72	V	33.85	43.5	-9.65	PK
220.67	V	37.61	46.00	-8.39	PK
430.59	V	42.04	46.00	-3.96	PK
600.11	V	43.13	53.90	-10.77	PK
43.57	H	34.16	40.00	-5.84	PK
100.34	H	33.94	43.5	-9.56	PK
177.29	H	35.78	43.5	-7.72	PK
220.46	H	40.26	46.00	-5.74	PK
432.20	H	41.37	46.00	-4.63	PK
586.75	H	41.81	46.00	-4.19	PK

Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 11 Test Date : 09/08/2009
Frequency Range: 30~1000MHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Zone

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
40.33	V	35.59	40.00	-4.41	PK
89.61	V	37.18	43.5	-6.32	PK
177.29	V	37.22	43.5	-6.28	PK
223.37	V	38.75	46.00	-7.25	PK
400.63	V	42.08	46.00	-3.92	PK
592.87	V	41.36	53.90	-12.54	PK
50.29	H	35.27	40.00	-4.73	PK
100.34	H	35.96	43.5	-7.54	PK
177.29	H	39.37	43.5	-4.13	PK
220.46	H	39.18	46.00	-6.82	PK
432.20	H	42.61	46.00	-3.39	PK
586.75	H	40.80	46.00	-5.2	PK

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11b TX Channel 1	Test Date :	09/08/2009
Frequency Range:	Above 1GHz	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
7239.82	V	53.29	38.64	74	54	-20.71	-15.36
14294.10	V	53.25	42.15	74	54	-20.75	-11.85
16853.00	V	58.72	48.52	74	54	-15.28	-5.48
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4824.60	H	44.68	35.78	74	54	-29.32	-18.22
7241.20	H	62.91	51.61	74	54	-11.09	-2.39
9648.60	H	44.35	34.95	74	54	-29.65	-19.05
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level+Probe Factor +Cable Loss
- (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11b Channel 6	Test Date :	09/08/2009
Frequency Range:	Above 1GHz	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
9746.50	V	56.36	40.66	74	54	-17.64	-13.34
14649.00	V	60.82	46.62	74	54	-13.18	-7.38
17266.00	V	64.28	47.92	74	54	-9.72	-6.08
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4875.00	H	51.95	40.15	74	54	-22.05	-13.85
7311.70	H	64.29	51.49	74	54	-9.71	-2.51
9748.50	H	56.42	44.72	74	54	-17.58	-9.28
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11b (Channel 11)	Test Date :	09/08/2009
Frequency Range:	Above 1GHz	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
9849.30	V	55.26	52.56	74	54	-18.74	-1.44
14322.10	V	60.48	45.98	74	54	-13.52	-8.02
17972.70	V	64.48	47.28	74	54	-9.52	-6.72
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4925.40	H	50.62	41.02	74	54	-23.38	-12.98
7383.80	H	62.17	51.67	74	54	-11.83	-2.33
9852.70	H	53.77	43.92	74	54	-20.23	-10.08
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11g TX Channel 1	Test Date :	09/08/2009
Frequency Range:	Above 1GHz	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
9650.20	V	52.36	38.46	74	54	-21.64	-15.54
14349.30	V	61.02	46.02	74	54	-12.98	-7.98
16892.50	V	62.54	48.44	74	54	-11.46	-5.56
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4826.50	H	45.18	34.48	74	54	-28.82	-19.52
7237.90	H	57.91	45.51	74	54	-16.09	-8.49
9648.50	H	57.48	44.98	74	54	-16.52	-9.02
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g(Channel 6)
 Frequency Range: Above 1GHz
 Test Result: PASS
 Measured Distance: 3m

Test Date : 09/08/2009
 Temperature : 28 °C
 Humidity : 65 %
 Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
9745.10	V	56.22	42.82	74	54	-17.78	-11.18
14458.30	V	62.23	47.03	74	54	-11.77	-6.97
17153.50	V	58.66	45.26	74	54	-15.34	-8.74
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4868.50	H	49.25	36.75	74	54	-24.75	-17.25
7320.50	H	60.78	49.08	74	54	-13.22	-4.92
9745.10	H	53.37	42.31	74	54	-20.63	-11.69
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11g(Channel 11)	Test Date :	09/08/2009
Frequency Range:	Above 1GHz	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
9850.60	V	52.27	41.57	74	54	-21.73	-12.43
15030.40	V	60.18	44.68	74	54	-13.82	-9.32
17830.80	V	58.63	43.23	74	54	-15.37	-10.77
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4928.80	H	48.02	35.72	74	54	-25.98	-18.28
7384.20	H	58.16	46.86	74	54	-15.84	-7.14
9854.10	H	52.07	41.38	74	54	-21.93	-12.62
17750.70	H	58.32	51.72	74	54	-15.68	-2.28
--	H	--	--	--	--	--	--
--	H	--	--	--	--	--	--

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

5.6 Radiated Measurement Photos:




6. Occupied Bandwidth test

6.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.

6.4 Limit



The minimum 6dB bandwidth shall be at least 500kHz.


6.5 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	09/10/2009
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11b		

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)
1	2412	11.25	>500
6	2437	11.25	>500
11	2462	11.40	>500








Spectrum Detector: PK
 Test By: Andy
 Test Result: PASS
 Operation Mode: 802.11 g

Test Date : 09/10/2009
 Temperature : 28 °C
 Humidity : 65 %

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)
1	2412	16.58	>500
6	2437	16.58	>500
11	2462	16.58	>500






7. MAXIMUM PEAK OUTPUT POWER TEST

7.1 Measurement Procedure

- The Transmitter output (antenna port) was connected to the power meter.
- Turn on the EUT and power meter and then record the peak power value.
- Repeat above procedures on all channels needed to be tested.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	Boonton	4232A	29001	05/29/2009	05/29/2010
Power sensor	Boonton	51011-EMC	31184	05/29/2009	05/29/2010

7.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

7.5 Measurement Results:

Spectrum Detector: PK Test Date : 09/10/2009
Test By: Andy Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11b

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	10.98	1W(30dBm)	PASS
6	2437.00	11.16	1W(30dBm)	PASS
11	2462.00	11.25	1W(30dBm)	PASS

Spectrum Detector: PK Test Date : 079/10/2009
Test By: Andy Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Operation Mode: 802.11g


Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	9.80	1W(30dBm)	PASS
6	2437.00	10.05	1W(30dBm)	PASS
11	2462.00	10.24	1W(30dBm)	PASS

8. Band EDGE test

8.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.

8.4 Measurement Results:

Refer to attached data chart.



Spectrum Detector: PK Test Date : 09/10/2009
 Test By: Andy Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11b

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
<2400	-12.84	-56.76	43.92	>20dBc
>2483.5	-13.10	-60.18	47.08	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PK	AV	PK	AV
<2400	V	47.00	35.52	74.00	54.00
>2483.5	V	45.32	30.67	74.00	54.00





Spectrum Detector: PK Test Date : 09/10/2009
 Test By: Andy Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11g

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
<2400	-14.96	-52.37	37.41	>20dBc
>2483.5	-14.50	-60.11	45.61	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		PK	AV	PK	AV
<2400	V	46.28	32.55	74.00	54.00
>2483.5	V	43.69	31.57	74.00	54.00



9. Power density

9.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2009	05/29/2010

9.2 Measuring Instruments and setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	300kHz
RB	3kHz
VB	30kHz
Detector	Peak
Trace	Max hold
Sweep Time	100s

9.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz, Set Detector to Peak, Trace to Max Hold.
- Mark the frequency with maximum peak power as the center of the display of the spectrum.
- Set the span to 300kHz and the sweep time to 100s and record the maximum peak value.

9.4 Block Diagram of Test setup




9.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3KHz bandwidth.

9.6. Test Result

Spectrum Detector:	PK	Test Date :	09/10/2009
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11 b		


Frequency (MHz)	Measurement Level (dBm)	Required limit (dBm)	Result
2412.00	-35.60	<8dBm	PASS
2437.00	-34.19	<8dBm	PASS
2462.00	-35.25	<8dBm	PASS







Spectrum Detector: PK Test Date : 09/10/2009
 Test By: Andy Temperature : 28 °C
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11 g

Frequency (MHz)	Measurement Level (dBm)	Required limit (dBm)	Result
2412.00	-38.66	<8dBm	PASS
2437.00	-37.55	<8dBm	PASS
2462.00	-39.40	<8dBm	PASS





10. Antenna Application

10.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

10.2 Result

The EUT'S antenna is PCB trace antenna. The antenna's gain is 2dBi and meets the requirement.